

Markdown file - a basic example

Insert your name here

2019-05-16

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see <http://rmarkdown.rstudio.com>.

When you *click* the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:

```
summary(mtcars)
```

```
##           mpg           cyl           disp           hp
##  Min.      :10.40   Min.      :4.000   Min.      : 71.1   Min.      : 52.0
## 1st Qu.:15.43   1st Qu.:4.000   1st Qu.:120.8   1st Qu.: 96.5
## Median :19.20   Median :6.000   Median :196.3   Median :123.0
## Mean   :20.09   Mean   :6.188   Mean   :230.7   Mean   :146.7
## 3rd Qu.:22.80   3rd Qu.:8.000   3rd Qu.:326.0   3rd Qu.:180.0
## Max.    :33.90   Max.    :8.000   Max.    :472.0   Max.    :335.0
##           drat           wt           qsec           vs
##  Min.      :2.760   Min.      :1.513   Min.      :14.50   Min.      :0.0000
## 1st Qu.:3.080   1st Qu.:2.581   1st Qu.:16.89   1st Qu.:0.0000
## Median :3.695   Median :3.325   Median :17.71   Median :0.0000
## Mean   :3.597   Mean   :3.217   Mean   :17.85   Mean   :0.4375
## 3rd Qu.:3.920   3rd Qu.:3.610   3rd Qu.:18.90   3rd Qu.:1.0000
## Max.    :4.930   Max.    :5.424   Max.    :22.90   Max.    :1.0000
##           am           gear           carb
##  Min.      :0.0000   Min.      :3.000   Min.      :1.000
## 1st Qu.:0.0000   1st Qu.:3.000   1st Qu.:2.000
## Median :0.0000   Median :4.000   Median :2.000
## Mean   :0.4062   Mean   :3.688   Mean   :2.812
## 3rd Qu.:1.0000   3rd Qu.:4.000   3rd Qu.:4.000
## Max.    :1.0000   Max.    :5.000   Max.    :8.000
```

You can hide the `summary(mtcars)` R code from the knitted output: (this is done using the `echo=FALSE` parameter)

Note: two empty spaces at the end of a line force a line return

- Lists are insterted using *
- Horizontal lines ---
- Headings are produced using #, ##, etc.
- Math expression are inserted through LaTeX syntax: $\hat{\beta}_1$, σ_i^2

Heading 1

Heading 2

Heading 3

Another R code & output goes here:

```
summary(cars)
```

```
##      speed      dist
##  Min.   : 4.0    Min.    : 2.00
## 1st Qu.:12.0    1st Qu.: 26.00
##  Median :15.0    Median : 36.00
##   Mean  :15.4    Mean    : 42.98
## 3rd Qu.:19.0    3rd Qu.: 56.00
##   Max.  :25.0    Max.    :120.00
```


Additional information on the data:

```
str(mtcars)
```

```
## 'data.frame':   32 obs. of  11 variables:
## $ mpg : num  21 21 22.8 21.4 18.7 18.1 14.3 24.4 22.8 19.2 ...
## $ cyl : num   6 6 4 6 8 6 8 4 4 6 ...
## $ disp: num  160 160 108 258 360 ...
## $ hp  : num  110 110 93 110 175 105 245 62 95 123 ...
## $ drat: num   3.9 3.9 3.85 3.08 3.15 2.76 3.21 3.69 3.92 3.92 ...
## $ wt  : num   2.62 2.88 2.32 3.21 3.44 ...
## $ qsec: num  16.5 17 18.6 19.4 17 ...
## $ vs  : num   0 0 1 1 0 1 0 1 1 1 ...
## $ am  : num   1 1 1 0 0 0 0 0 0 0 ...
## $ gear: num   4 4 4 3 3 3 3 4 4 4 ...
## $ carb: num   4 4 1 1 2 1 4 2 2 4 ...
```

You can also embed plots, for example:

```
plot(mtcars)
```



Linear regression models (LRMs) in R - example

- Using the `mtcars` dataset, we may perform LRM estimation
- For example, we may estimate a model:

$$\text{MPG}_i = \beta_0 + \beta_1 \text{HP}_i + \beta_2 \text{WT}_i + \varepsilon_i$$

- In R, we use a general syntax `y ~ x1 + x2` to cast the regression equation (the intercept is included by default).

```
lrm1 <- lm(mpg~hp+wt, data=mtcars)
summary(lrm1)
```

```
##
## Call:
## lm(formula = mpg ~ hp + wt, data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -3.941  -1.600  -0.182   1.050   5.854
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  37.22727    1.59879   23.285  < 2e-16 ***
```

```
## hp          -0.03177    0.00903   -3.519   0.00145 **
## wt          -3.87783    0.63273   -6.129   1.12e-06 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.593 on 29 degrees of freedom
## Multiple R-squared:  0.8268, Adjusted R-squared:  0.8148
## F-statistic: 69.21 on 2 and 29 DF,  p-value: 9.109e-12
```

```
#
# Fitted values
head(cbind(mtcars$mpg, predict(lrm1)))
```

```
##           [,1]      [,2]
## Mazda RX4      21.0 23.57233
## Mazda RX4 Wag  21.0 22.58348
## Datsun 710      22.8 25.27582
## Hornet 4 Drive  21.4 21.26502
## Hornet Sportabout 18.7 18.32727
## Valiant        18.1 20.47382
```

- The above code is just a basic example of LRM estimation & output syntax.
- Additional (introductory-level) LRM topics are discussed in `R03_LRM_self_study_material.R`