



Jasmin: high-assurance high-speed cryptography

Miguel Quaresma Santiago Arranz Olmos

September 4, 2024

Max Planck Institute for Security and Privacy

Efficient, correct, safe, and secure

```
fn memeq(reg u64 p q n) -> reg u64 {  
    reg u64 r one i;  
    r = 0;  
    one = 1;  
    i = 0;  
    while (i < n) {  
        if (r != 0) {  
            reg u64 a b;  
            a = [p];  
            b = [q];  
            r = a != b ? one : r;  
            p += 8;  
            q += 8;  
        }  
        i = #INC(i);  
    }  
    return r;  
}
```

Efficient, correct, safe, and secure

```
fn memeq(reg u64 p q n) -> reg u64 {  
  reg u64 r one i;  
  r = 0;  
  one = 1;  
  i = 0;  
  while (i < n) {  
    if (r != 0) {  
      reg u64 a b;  
      a = [p];  
      b = [q];  
      r = a != b ? one : r;  
      p += 8;  
      q += 8;  
    }  
    i = #INC(i);  
  }  
  return r;  
}  
  
memeq:  
  movq $0, %rax  
  movq $1, %rcx  
  movq $0, %r8  
  jmp Lmemeq$1  
Lmemeq$2:  
  cmpq $0, %rax  
  je Lmemeq$3  
  movq (%rdi), %r9  
  movq (%rsi), %r10  
  cmpq %r10, %r9  
  cmovne %rcx, %rax  
  addq $8, %rdi  
  addq $8, %rsi  
Lmemeq$3:  
  incq %r8  
Lmemeq$1:  
  cmpq %rdx, %r8  
  jnb Lmemeq$2  
  ret
```

Efficient, correct, safe, and secure

```
fn memeq(reg u64 p q n) -> reg u64 {  
  reg u64 r one i;  
  r = 0;  
  one = 1;  
  i = 0;  
  while (i < n) {  
    if (r != 0) {  
      reg u64 a b;  
      a = [p];  
      b = [q];  
      r = a != b ? one : r;  
      p += 8;  
      q += 8;  
    }  
    i = #INC(i);  
  }  
  return r;  
}  
  
memeq:  
  movq $0, %rax  
  movq $1, %rcx  
  movq $0, %r8  
  jmp Lmemeq$1  
Lmemeq$2:  
  cmpq $0, %rax  
  je Lmemeq$3  
  movq (%rdi), %r9  
  movq (%rsi), %r10  
  cmpq %r10, %r9  
  cmovne %rcx, %rax  
  addq $8, %rdi  
  addq $8, %rsi  
Lmemeq$3:  
  incq %r8  
Lmemeq$1:  
  cmpq %rdx, %r8  
  jnb Lmemeq$2  
  ret
```

Efficient, correct, safe, and secure

```
fn memeq(reg u64 p q n) -> reg u64 {  
  reg u64 r one i;  
  r = 0;  
  one = 1;  
  i = 0;  
  while (i < n) {  
    if (r != 0) {  
      reg u64 a b;  
      a = [p];  
      b = [q];  
      r = a != b ? one : r;  
      p += 8;  
      q += 8;  
    }  
    i = #INC(i);  
  }  
  return r;  
}  
  
memeq:  
  movq $0, %rax  
  movq $1, %rcx  
  movq $0, %r8  
  jmp Lmemeq$1  
Lmemeq$2:  
  cmpq $0, %rax  
  je Lmemeq$3  
  movq (%rdi), %r9  
  movq (%rsi), %r10  
  cmpq %r10, %r9  
  cmovne %rcx, %rax  
  addq $8, %rdi  
  addq $8, %rsi  
Lmemeq$3:  
  incq %r8  
Lmemeq$1:  
  cmpq %rdx, %r8  
  jnb Lmemeq$2  
  ret
```

Correctness

Use EasyCrypt to ensure:

- Implementation matches specification
- Specification is secure

Correctness

Use EasyCrypt to ensure:

- Implementation matches specification
- Specification is secure

Safety

- Termination
- Array accesses in bounds
- Arithmetic errors

Correctness

Use EasyCrypt to ensure:

- Implementation matches specification
- Specification is secure

Safety

- Termination
- Array accesses in bounds
- Arithmetic errors

Constant time

Runtime does not depend on secrets

- Control flow
- Memory accesses

Correctness

Use EasyCrypt to ensure:

- Implementation matches specification
- Specification is secure

Constant time

Runtime does not depend on secrets

- Control flow
- Memory accesses

Safety

- Termination
- Array accesses in bounds
- Arithmetic errors

Speculative constant time

CT even under speculative execution

Safety - uninitialized values

```
export
fn uninitialized() -> reg u64 {
    reg u64 x;
    x = x + 1; // Uninitialized read from x.
    return x;
}
```

Safety - division by zero

```
export
fn arithmetic(reg u64 x y) -> reg u64 {
  x = x / y; // y could be zero.
  return x;
}
```

Safety - out of bounds access

```
export
fn index(reg u64 x) -> reg u64 {
  stack u64[1] s;
  s[x] = 0; // x could be out of bounds.
  x = s[0]; // s[0] could be uninitialized
  return x;
}
```

```
export
fn termination(reg u64 n) -> reg u64 {
  reg u64 i;
  i = 0;
  while (i <= n) { // n could be 2^64-1
    i += 1;
  }
  return i;
}
```

Safety - memory accesses

```
export
fn alignment(reg u64 p) {
  [#aligned p] = 0; // p needs to be 64bit-aligned.
}
```

```
export
fn memset(reg u64 p, reg u8 c, reg u64 n) {
  reg u64 i;
  i = 0;
  while (i < n) {
    (u8)[p + i] = c;
    i += 1;
  }
}
```

Side-channel - memeq 1/2

```
export
fn memeq(#public reg u64 p q n) -> #public reg u64 {
  reg u64 r one i;
  r = 0; one = 1; i = 0;
  while (i < n) {
    reg u64 a b;
    a = [p + i * 8];
    b = [q + i * 8];
    r = one if a != b;
    i += 1;
  }
  #declassify r = r;
  return r;
}
```

Side-channel - memeq 2/2

```
fn memeq_early_abort(#public reg u64 p q n) -> #public reg u64 {  
  reg u64 i x  
  reg u8 r;  
  i = 0;  
  while (i < n) {  
    reg u64 a b;  
    a = [p + i * 8];  
    b = [q + i * 8];  
    i = n if a != b;  
    i += 1;  
  }  
  r = #SETcc(i == n);  
  #declassify x = (64u)r;  
  return x;  
}
```



```
fn strlen(#public reg u64 s) -> #public reg u64 {  
    reg u64 i;  
    i = 0;  
  
    reg u8 c;  
    while {  
        c = (u8)[s + i];  
    } (c != 0) {  
        i += 1;  
    }  
  
    return i;  
}
```

```
fn strlen_ct(#public reg u64 s) -> #public reg u64 {  
    reg u64 i;  
    i = 0;  
  
    reg bool is_null;  
    while {  
        reg u8 c;  
        c = (u8)[s + i];  
        #declassify is_null = c != 0;  
    } (is_null) {  
        i += 1;  
    }  
  
    return i;  
}
```

```
fn strlen_sct(#transient reg u64 s) -> #public reg u64 {  
  reg u64 msf i;  
  msf = #init_msf(); i = 0;  
  reg u8 is_null c;  
  while {  
    c = (u8)[s + i];  
    #declassify is_null = #SETcc(c != 0);  
    is_null = #protect_8(is_null, msf);  
  } (is_null == 1) {  
    msf = #update_msf(is_null == 1, msf);  
    i += 1;  
  }  
  return i;  
}
```



Jasmin: `github.com/jasmin-lang/jasmin`

EasyCrypt specifications: `github.com/formosa-crypto/crypto-specs`

Libjade: `github.com/formosa-crypto/libjade`