

بسم الله الرحمن الرحيم

نظريه علوم كامپيوتر

نظريه علوم كامپيوتر - بهار ۱۴۰۰-۱۴۰۱ - جلسه شانزدهم: سلسله مراتب زمان

Theory of computation - 002 - S16 - Time hierarchy

Contents

2

Last time:

- Log-space reducibility
- $L = NL$? question
- *PATH* is NL-complete
- $\overline{2SAT}$ is NL-complete
- $NL = coNL$

Today: (Sipser §9.1)

- Time and Space Hierarchy Theorems

Review: Major Complexity Classes

3

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$

Review: Major Complexity Classes

3

$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$

\neq
Today

Review: Major Complexity Classes

3

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$


Today

The time and space hierarchy theorems show that
if a TM is given more time (or space) then it can do more.*

* certain restrictions apply.

Review: Major Complexity Classes

3

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$


Today

The time and space hierarchy theorems show that
if a TM is given more time (or space) then it can do more.*

* certain restrictions apply.


For example:

$$\text{TIME}(n^2) \subsetneq \text{TIME}(n^3) \quad [\subsetneq \text{ means proper subset }]$$

Review: Major Complexity Classes

3

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$



The time and space hierarchy theorems show that
if a TM is given more time (or space) then it can do more.*

* certain restrictions apply.


For example:

$$\text{TIME}(n^2) \subsetneq \text{TIME}(n^3) \quad [\subsetneq \text{ means proper subset }]$$

$$\text{SPACE}(n^2) \subsetneq \text{SPACE}(n^3)$$

Review: Major Complexity Classes

3

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$


Today

The time and space hierarchy theorems show that
if a TM is given more time (or space) then it can do more.*

* certain restrictions apply.

For example:

$$\text{TIME}(n^2) \subsetneq \text{TIME}(n^3) \quad [\subsetneq \text{ means proper subset }]$$

$$\text{SPACE}(n^2) \subsetneq \text{SPACE}(n^3)$$

Space Hierarchy Theorem (1/2)

4

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)
there is a language A where A requires $O(f(n))$ space, i.e,

Space Hierarchy Theorem (1/2)

4

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

1) A is decidable in $O(f(n))$ space, and

Space Hierarchy Theorem (1/2)

4

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

Space Hierarchy Theorem (1/2)

4

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e.,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$

Space Hierarchy Theorem (1/2)


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Space Hierarchy Theorem (1/2)

4

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,


- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$

Proof outline: (Diagonalization)

Give TM D where



Space Hierarchy Theorem (1/2)

4


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Proof outline: (Diagonalization)

Give TM D where

- 1) D runs in $O(f(n))$ space

Space Hierarchy Theorem (1/2)

4


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Proof outline: (Diagonalization)

Give TM D where

- 1) D runs in $O(f(n))$ space
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n))$ space.

Space Hierarchy Theorem (1/2)

4


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Proof outline: (Diagonalization)

Give TM D where

- 1) D runs in $O(f(n))$ space
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n))$ space.

Let $A = L(D)$.

Space Hierarchy Theorem (1/2)


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Proof outline: (Diagonalization)

Give TM D where

- 1) D runs in $O(f(n))$ space
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n))$ space.

Let $A = L(D)$.

Space Hierarchy Theorem (1/2)


Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ (where f satisfies a technical condition)

there is a language A where A requires $O(f(n))$ space, i.e,

- 1) A is decidable in $O(f(n))$ space, and
- 2) A is not decidable in $o(f(n))$ space

On other words, $\text{SPACE}(o(f(n))) \subsetneq \text{SPACE}(f(n))$

Notation: $\text{SPACE}(o(f(n))) = \{B \mid \text{some TM } M \text{ decides } B \text{ in space } o(f(n))\}$



Proof outline: (Diagonalization)

Give TM D where

- 1) D runs in $O(f(n))$ space
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n))$ space.

Let $A = L(D)$.

Time Hierarchy Theorem (1/2)

5

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ where f is time constructible
there is a language A where A requires $O(f(n))$ time, i.e,

Time Hierarchy Theorem (1/2)

5

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ where f is time constructible
there is a language A where A requires $O(f(n))$ time, i.e.,

- 1) A is decidable in $O(f(n))$ time, and
- 2) A is not decidable in $o(f(n)/\log(f(n)))$ time

Time Hierarchy Theorem (1/2)

5

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ where f is time constructible
there is a language A where A requires $O(f(n))$ time, i.e,

- 1) A is decidable in $O(f(n))$ time, and
- 2) A is not decidable in $o(f(n)/\log(f(n)))$ time

On other words, $\text{TIME}\left(o\left(\frac{f(n)}{\log(f(n))}\right)\right) \subsetneq \text{TIME}(f(n))$

Time Hierarchy Theorem (1/2)

5

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ where f is time constructible
there is a language A where A requires $O(f(n))$ time, i.e,

- 1) A is decidable in $O(f(n))$ time, and
- 2) A is not decidable in $o(f(n)/\log(f(n)))$ time

On other words, $\text{TIME}\left(o\left(\frac{f(n)}{\log(f(n))}\right)\right) \subsetneq \text{TIME}(f(n))$

Proof outline: Give TM D where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n)/\log(f(n)))$ time .

Let $A = L(D)$.

Time Hierarchy Theorem (1/2)

5

Theorem: For any $f: \mathbb{N} \rightarrow \mathbb{N}$ where f is time constructible
there is a language A where A requires $O(f(n))$ time, i.e.,

- 1) A is decidable in $O(f(n))$ time, and
- 2) A is not decidable in $o(f(n)/\log(f(n)))$ time

On other words, $\text{TIME}\left(o\left(\frac{f(n)}{\log(f(n))}\right)\right) \subsetneq \text{TIME}(f(n))$

Proof outline: Give TM D where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o(f(n)/\log(f(n)))$ time .

Let $A = L(D)$.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

To do so, D counts the number of steps it uses and stops if the limit is exceeded. The counter has size $\log(f(n))$ and is stored on the tape.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

To do so, D counts the number of steps it uses and stops if the limit is exceeded. The counter has size $\log(f(n))$ and is stored on the tape. It must be kept near the current head location.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ “On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted.”

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

To do so, D counts the number of steps it uses and stops if the limit is exceeded. The counter has size $\log(f(n))$ and is stored on the tape.

It must be kept near the current head location.

Cost of moving it adds a $O(\log(f(n)))$ overhead factor. So to halt within $O(f(n))$ time, D stops when the counter reaches $f(n)/\log(f(n))$.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ "On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted."

*Note: D can simulate M with a log factor time overhead due to the step counter.

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

To do so, D counts the number of steps it uses and stops if the limit is exceeded. The counter has size $\log(f(n))$ and is stored on the tape.

It must be kept near the current head location.

Cost of moving it adds a $O(\log(f(n)))$ overhead

factor. So to halt within $O(f(n))$ time, D stops when the counter reaches $f(n)/\log(f(n))$.

Time Hierarchy Theorem (2/2)

6

Goal: Exhibit $A \in \text{TIME}(f(n))$ but $A \notin \text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$

$A = L(D)$ where

- 1) D runs in $O(f(n))$ time
- 2) D ensures that $L(D) \neq L(M)$ for every TM M that runs in $o\left(f(n)/\log(f(n))\right)$ time.

$D =$ "On input w

1. Compute $f(n)$.
2. If $w \neq \langle M \rangle 10^*$ for some TM M , *reject*.
3. Simulate* M on w for $f(n)/\log(f(n))$ steps.

Accept if M rejects,

Reject if M accepts or hasn't halted."

*Note: D can simulate M with a log factor time overhead due to the step counter.

For no M in $\text{TIME}\left(o\left(f(n)/\log(f(n))\right)\right)$, $L(M) \neq L(D)$

Contradiction, $M(\langle M \rangle 10^k)$ runs in $o(f/\log f)$
 $D(\langle M \rangle 1)$ rejects iff $M(\langle M \rangle 10^k)$ accepts

Why do we lose a factor of $\log(f(n))$?

D must halt within $O(f(n))$ time.

To do so, D counts the number of steps it uses and stops if the limit is exceeded. The counter has size $\log(f(n))$ and is stored on the tape.

It must be kept near the current head location.

Cost of moving it adds a $O(\log(f(n)))$ overhead

factor. So to halt within $O(f(n))$ time, D stops when the counter reaches $f(n)/\log(f(n))$.

Recap: Separating Complexity Classes

7

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$


Space Hierarchy Theorem

$$NL \subseteq \text{SPACE}(\log^2 n) \subsetneq \text{SPACE}(n) \subseteq PSPACE$$

Recap: Separating Complexity Classes

7

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$

$\uparrow \quad \quad \quad \neq \quad \quad \quad \uparrow$
Space Hierarchy Theorem

$$NL \subseteq SPACE(\log^2 n) \subsetneq SPACE(n) \subseteq PSPACE$$

Recap: Separating Complexity Classes

7

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE$$

$\uparrow \quad \quad \quad \neq \quad \quad \quad \uparrow$
Space Hierarchy Theorem

$$NL \subseteq SPACE(\log^2 n) \subsetneq SPACE(n) \subseteq PSPACE$$

Check-in 21.3

Consider these two famous unsolved questions:

1. Does $L = P$?
2. Does $P = PSPACE$?

What do the hierarchy theorems tell us about these questions?

- a) Nothing
- b) At least one of these has answer “NO”
- c) At least one of these has answer “YES”

Exponential Complexity Classes

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$$

Exponential Complexity Classes

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$$

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE \subseteq \text{EXPTIME} \subseteq \text{EXPSPACE}$$


Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem




Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}(2^{(n^k)})$

$$\text{EXPSPACE} = \bigcup_k \text{SPACE}(2^{(n^k)})$$



Defn: B is EXPTIME-complete if


- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_p B$

Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}(2^{(n^k)})$

$$\text{EXPSPACE} = \bigcup_k \text{SPACE}(2^{(n^k)})$$



Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_p B$

Same for EXPSPACE-complete


Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem



Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_p B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$


Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem



Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_p B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)


Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}(2^{(n^k)})$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}(2^{(n^k)})$

Time Hierarchy Theorem



Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_p B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)


} intractable

Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}(2^{(n^k)})$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}(2^{(n^k)})$



Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_P B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)

} intractable

Defn: $EQ_{\text{REX}} \uparrow = \{ \langle R_1, R_2 \rangle \mid R_1 \text{ and } R_2 \text{ are equivalent regular expressions with exponentiation} \}$

Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem \neq

$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE \subseteq \text{EXPTIME} \subseteq \text{EXPSPACE}$

Space Hierarchy Theorem \neq

Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_P B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)

} intractable

Defn: $EQ_{\text{REX}} \uparrow = \{ \langle R_1, R_2 \rangle \mid R_1 \text{ and } R_2 \text{ are equivalent regular expressions with exponentiation} \}$

Notation: If R is a regular expression write R^k to mean $\overbrace{RR \cdots R}^k$ (exponent is written in binary).

Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem \neq

$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE \subseteq \text{EXPTIME} \subseteq \text{EXPSPACE}$

Space Hierarchy Theorem \neq

Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_P B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)

} intractable

Defn: $EQ_{\text{REX}} \uparrow = \{ \langle R_1, R_2 \rangle \mid R_1 \text{ and } R_2 \text{ are equivalent regular expressions with exponentiation} \}$

Notation: If R is a regular expression write R^k to mean $\overbrace{RR \cdots R}^k$ (exponent is written in binary).

Exponential Complexity Classes

8

Defn: $\text{EXPTIME} = \bigcup_k \text{TIME}\left(2^{(n^k)}\right)$

$\text{EXPSPACE} = \bigcup_k \text{SPACE}\left(2^{(n^k)}\right)$

Time Hierarchy Theorem \neq

$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE \subseteq \text{EXPTIME} \subseteq \text{EXPSPACE}$

Space Hierarchy Theorem \neq

Defn: B is EXPTIME-complete if

- 1) $B \in \text{EXPTIME}$
- 2) For all $A \in \text{EXPTIME}$, $A \leq_P B$

Same for EXPSPACE-complete

Theorem: If B is EXPTIME-complete then $B \notin P$

Theorem: If B is EXPSPACE-complete then $B \notin PSPACE$ (and $B \notin P$)

} intractable

Defn: $EQ_{\text{REX}} \uparrow = \{ \langle R_1, R_2 \rangle \mid R_1 \text{ and } R_2 \text{ are equivalent regular expressions with exponentiation} \}$

Notation: If R is a regular expression write R^k to mean $\overbrace{RR \cdots R}^k$ (exponent is written in binary).

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{B \mid B \text{ is decidable in polynomial time with an oracle for } A\}$

Thus $NP \subseteq P^{SAT}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{B \mid B \text{ is decidable in polynomial time with an oracle for } A\}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{B \mid B \text{ is decidable in polynomial time with an oracle for } A\}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A\}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{B \mid B \text{ is decidable in polynomial time with an oracle for } A\}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A\}$

Recall $MIN-FORMULA = \{\langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula}\}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{ B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A \}$

Recall $MIN-FORMULA = \{ \langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula} \}$

Example: $\overline{MIN-FORMULA} \in NP^{SAT}$

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{ B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A \}$

Recall $MIN\text{-}FORMULA = \{ \langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula} \}$

Example: $\overline{MIN\text{-}FORMULA} \in NP^{SAT}$

“On input $\langle \phi \rangle$

1. Guess shorter formula ψ

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{ B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A \}$

Recall $MIN-FORMULA = \{ \langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula} \}$

Example: $\overline{MIN-FORMULA} \in NP^{SAT}$

“On input $\langle \phi \rangle$

1. Guess shorter formula ψ
2. Use SAT oracle to solve the coNP problem: ϕ and ψ are equivalent

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{ B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A \}$

Recall $MIN-FORMULA = \{ \langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula} \}$

Example: $\overline{MIN-FORMULA} \in NP^{SAT}$

“On input $\langle \phi \rangle$

1. Guess shorter formula ψ
2. Use SAT oracle to solve the coNP problem: ϕ and ψ are equivalent
3. *Accept* if ϕ and ψ are equivalent. *Reject* if not.”

Computation with Oracles

9

Let A be any language.

Defn: A TM M with oracle for A , written M^A , is a TM equipped with a “black box” that can answer queries “is $x \in A$?” for free.

Example: A TM with an oracle for SAT can decide all $B \in NP$ in polynomial time.

Defn: $P^A = \{ B \mid B \text{ is decidable in polynomial time with an oracle for } A \}$

Thus $NP \subseteq P^{SAT}$

$NP = P^{SAT}$? Probably No because $coNP \subseteq P^{SAT}$

Defn: $NP^A = \{ B \mid B \text{ is decidable in nondeterministic polynomial time with an oracle for } A \}$

Recall $MIN-FORMULA = \{ \langle \phi \rangle \mid \phi \text{ is a minimal Boolean formula} \}$

Example: $\overline{MIN-FORMULA} \in NP^{SAT}$

“On input $\langle \phi \rangle$

1. Guess shorter formula ψ
2. Use SAT oracle to solve the coNP problem: ϕ and ψ are equivalent
3. *Accept* if ϕ and ψ are equivalent. *Reject* if not.”

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? $\wedge \wedge \wedge$.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSPACE = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

If both TMs were oracle TMs D^A and M^A with the same oracle A , the simulation and the diagonalization would still work.

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

If both TMs were oracle TMs D^A and M^A with the same oracle A , the simulation and the diagonalization would still work.

Therefore, if we could prove $P \neq NP$ by a diagonalization, we would also prove that $P^A \neq NP^A$ for every oracle A .

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

If both TMs were oracle TMs D^A and M^A with the same oracle A , the simulation and the diagonalization would still work.

Therefore, if we could prove $P \neq NP$ by a diagonalization, we would also prove that $P^A \neq NP^A$ for every oracle A .

But that is false!

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSpace = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

If both TMs were oracle TMs D^A and M^A with the same oracle A , the simulation and the diagonalization would still work.

Therefore, if we could prove $P \neq NP$ by a diagonalization, we would also prove that $P^A \neq NP^A$ for every oracle A .

But that is false!

Oracles and P versus NP

10

Theorem: There is an oracle A where $P^A = NP^A$

Proof: Let $A = TQBF$

$$NP^{TQBF} \subseteq NPSPACE = PSPACE \subseteq P^{TQBF}$$

Relevance to the P versus NP question

Recall: We showed $EQ_{\text{REX}} \uparrow \notin PSPACE$.

Could we show $SAT \notin P$ using a similar method? NO.

Reason: Suppose YES.

The Hierarchy Theorems are proved by a diagonalization.

In this diagonalization, the TM D simulates some TM M .

If both TMs were oracle TMs D^A and M^A with the same oracle A , the simulation and the diagonalization would still work.

Therefore, if we could prove $P \neq NP$ by a diagonalization, we would also prove that $P^A \neq NP^A$ for every oracle A .

But that is false!

Check-in 22.3

Which of these are known to be true?
Check all that apply.

- (a) $P^{SAT} = P^{\overline{SAT}}$
- (b) $NP^{SAT} = coNP^{SAT}$
- (c) $MIN-FORMULA \in P^{TQBF}$
- (d) $NP^{TQBF} = coNP^{TQBF}$

Check-in 22.3