

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 源代码鉴别材料

软件名称: EQT Easy QR Transfer 局域网文件传输系统 软件版本: V1.0.0 著作权人: 李跃龙

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 1 页

```
package main

import (
    "os"

    "eqrcp/cmd"
)

func main() {
    if err := cmd.Execute(); err != nil {
        os.Exit(1)
    }
}

package application

type Flags struct {
    Quiet          bool
    KeepAlive      bool
    ListAllInterfaces bool
    Port           int
    Path           string
    Interface      string
    Bind           string
    FQDN           string
    Zip            bool
    Config         string
    Browser        bool
    Secure        bool
    TlsCert        string
    TlsKey         string
    Output         string
    Reversed       bool
}

type App struct {
    Flags Flags
    Name  string
}

func New() App {
    return App{
```

```
        Name: "eqrcp",
        Flags: Flags{},
    }
}
package cmd

import (
    "eqrcp/application"
    "github.com/spf13/cobra"
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 2 页

```
)

var app application.App

func init() {
    app = application.New()
    rootCmd.AddCommand(sendCmd)
    rootCmd.AddCommand(receiveCmd)
    rootCmd.AddCommand(chatCmd)
    rootCmd.AddCommand(configCmd)
    rootCmd.AddCommand(versionCmd)
    rootCmd.AddCommand(completionCmd)
    rootCmd.AddCommand(desktopCmd)
    desktopCmd.AddCommand(desktopShareCmd)
    desktopCmd.AddCommand(desktopReceiveCmd)
    desktopCmd.AddCommand(desktopChatCmd)
    desktopCmd.AddCommand(desktopInstallCmd)
    desktopCmd.AddCommand(desktopStatusCmd)
    desktopCmd.AddCommand(desktopStartupEnableCmd)
    desktopCmd.AddCommand(desktopStartupDisableCmd)
    desktopCmd.AddCommand(desktopStartupStatusCmd)
    desktopCmd.AddCommand(desktopUninstallCmd)
    desktopCmd.AddCommand(desktopAgentCmd)
    desktopCmd.AddCommand(desktopAgentStartCmd)
    desktopCmd.AddCommand(desktopAgentRestartHelperCmd)
    desktopCmd.AddCommand(desktopAgentHistoryClearCmd)
    desktopCmd.AddCommand(desktopAgentStopCmd)
    desktopCmd.AddCommand(desktopAgentStopCurrentCmd)
    desktopCmd.AddCommand(desktopAgentStatusCmd)
    desktopCmd.AddCommand(desktopAgentOpenCmd)
    desktopCmd.AddCommand(desktopAgentOpenCurrentCmd)
    configCmd.AddCommand(migrateCmd)
    desktopAgentCmd.Flags().BoolP("background", "B", false, "start the desktop
agent in the background")
    desktopAgentStartCmd.Flags().BoolP("background", "B", false, "start the
desktop agent in the background")
    // Global command flags
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.Quiet, "quiet", "q", false,
"only print errors")
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.KeepAlive, "keep-alive", "k",
false, "keep server alive after transferring")
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.ListAllInterfaces, "list-all-
interfaces", "l", false, "list all available interfaces when choosing the one to
use")
    rootCmd.PersistentFlags().IntVarP(&app.Flags.Port, "port", "p", 0, "port to
use for the server")
    rootCmd.PersistentFlags().StringVar(&app.Flags.Path, "path", "", "path to use.
Defaults to a random string")
    rootCmd.PersistentFlags().StringVarP(&app.Flags.Interface, "interface", "i",
"", "network interface to use for the server")
}
```

```
    rootCmd.PersistentFlags().StringVar(&app.Flags.Bind, "bind", "", "address to  
bind the web server to")  
    rootCmd.PersistentFlags().StringVarP(&app.Flags.FQDN, "fqdn", "d", "", "fully-  
qualified domain name to use for the resulting URLs")  
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.Zip, "zip", "z", false, "zip  
content before transferring")  
    rootCmd.PersistentFlags().StringVarP(&app.Flags.Config, "config", "c", "",  
"path to the config file, defaults to $XDG_CONFIG_HOME/eqrcp/config.yml")  
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.Browser, "browser", "b", false,  
"display the QR code in a browser window")  
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.Secure, "secure", "s", false,  
"use https connection")  
    rootCmd.PersistentFlags().StringVar(&app.Flags.TlsCert, "tls-cert", "", "path  
to TLS certificate to use with HTTPS")  
    rootCmd.PersistentFlags().StringVar(&app.Flags.TlsKey, "tls-key", "", "path to  
TLS private key to use with HTTPS")  
    rootCmd.PersistentFlags().BoolVarP(&app.Flags.Reversed, "reversed", "r",  
false, "Reverse QR code (black text on white background)")
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 3 页

```
// Receive command flags
receiveCmd.PersistentFlags().StringVarP(&app.Flags.Output, "output", "o", "",
"output directory for receiving files")
}

// The root command (`eqrcp`) is like a shortcut of the `send` command
var rootCmd = &cobra.Command{
    Use:           "eqrcp",
    Args:          cobra.MinimumNArgs(1),
    RunE:          sendCmdFunc,
    SilenceErrors: true,
    SilenceUsage:  true,
}

// Execute the root command
func Execute() error {
    if err := rootCmd.Execute(); err != nil {
        rootCmd.PrintErrf("Error: %v\nRun `eqrcp help` for help.\n", err)
        return err
    }
    return nil
}

package cmd

import (
    "fmt"

    "eqrcp/body"
    "eqrcp/config"
    "eqrcp/logger"
    "eqrcp/qr"
    "github.com/eiannone/keyboard"

    "eqrcp/server"
    "github.com/spf13/cobra"
)

func sendCmdFunc(command *cobra.Command, args []string) error {
    log := logger.New(app.Flags.Quiet)
    body, err := body.FromArgs(args, app.Flags.Zip)
    if err != nil {
        return err
    }
    cfg, err := config.New(app)
    if err != nil {
        return err
    }
    srv, err := server.New(&cfg)
    if err != nil {
```

```
    return err  
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 4 页

```

    // Sets the body
    srv.Send(body)
    log.Print(`Scan the following URL with a QR reader to start the file transfer,
    press CTRL+C or "q" to exit:`)
    log.Print(srv.SendURL)
    if err := qr.RenderString(srv.SendURL, cfg.Reversed); err != nil {
        return err
    }
    if app.Flags.Browser {
        if err := srv.DisplayQR(srv.SendURL); err != nil {
            return err
        }
    }
    if err := keyboard.Open(); err == nil {
        defer func() {
            keyboard.Close()
        }()
        go func() {
            for {
                char, key, _ := keyboard.GetKey()
                if string(char) == "q" || key == keyboard.KeyCtrlC {
                    srv.Shutdown()
                }
            }
        }()
    } else {
        log.Print(fmt.Sprintf("Warning: keyboard not detected: %v", err))
    }
    if err := srv.Wait(); err != nil {
        return err
    }
    return nil
}

var sendCmd = &cobra.Command{
    Use:     "send",
    Short:   "Send a file(s) or directories from this host",
    Long:    "Send a file(s) or directories from this host",
    Aliases: []string{"s"},
    Example: `# Send /path/file.gif. Webserver listens on a random port
eqrcp send /path/file.gif
# Shorter version:
eqrcp /path/file.gif
# Zip file1.gif and file2.gif, then send the zip package
eqrcp /path/file1.gif /path/file2.gif
# Zip the content of directory, then send the zip package
eqrcp /path/directory
# Send file.gif by creating a webserver on port 8080
eqrcp --port 8080 /path/file.gif`
}

```

```
,  
    Args: cobra.MinimumNArgs(1),
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 5 页

```
    RunE: sendCmdFunc,
}
package cmd

import (
    "fmt"

    "eqrcp/config"
    "eqrcp/logger"
    "eqrcp/qr"
    "eqrcp/server"
    "github.com/eiannone/keyboard"
    "github.com/spf13/cobra"
)

func receiveCmdFunc(command *cobra.Command, args []string) error {
    log := logger.New(app.Flags.Quiet)
    // Load configuration
    cfg, err := config.New(app)
    if err != nil {
        return err
    }
    // Create the server
    srv, err := server.New(&cfg)
    if err != nil {
        return err
    }
    // Sets the output directory
    if err := srv.ReceiveTo(cfg.Output); err != nil {
        return err
    }
    // Prints the URL to scan to screen
    log.Print(`Scan the following URL with a QR reader to start the file transfer,
press CTRL+C or "q" to exit:`)
    log.Print(srv.ReceiveURL)
    // Renders the QR
    if err := qr.RenderString(srv.ReceiveURL, cfg.Reversed); err != nil {
        return err
    }
    if app.Flags.Browser {
        if err := srv.DisplayQR(srv.ReceiveURL); err != nil {
            return err
        }
    }
    if err := keyboard.Open(); err == nil {
        defer func() {
            keyboard.Close()
        }()
        go func() {
```

```
for {  
    char, key, _ := keyboard.GetKey()
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 6 页

```

        if string(char) == "q" || key == keyboard.KeyCtrlC {
            srv.Shutdown()
        }
    }
}()
} else {
    log.Print(fmt.Sprintf("Warning: keyboard not detected: %v", err))
}
if err := srv.Wait(); err != nil {
    return err
}
return nil
}

var receiveCmd = &cobra.Command{
    Use:      "receive",
    Aliases: []string{"r"},
    Short:    "Receive one or more files",
    Long:     "Receive one or more files. The destination directory can be set with
the config wizard, or by passing the --output flag. If none of the above are set,
the current working directory will be used as a destination directory.",
    Example: `# Receive files in the current directory
eqrcp receive
# Receive files in a specific directory
eqrcp receive --output /tmp
`,
    RunE: receiveCmdFunc,
}

package cmd

import (
    "fmt"

    "eqrcp/config"
    "eqrcp/logger"
    "eqrcp/qr"
    "eqrcp/server"
    "github.com/eiannone/keyboard"
    "github.com/spf13/cobra"
)

func chatCmdFunc(command *cobra.Command, args []string) error {
    log := logger.New(app.Flags.Quiet)
    cfg, err := config.New(app)
    if err != nil {
        return err
    }
    srv, err := server.New(&cfg)
    if err != nil {
        return err
    }

```

```
}  
log.Print(`Scan the following URL with a QR reader to join the chat session,  
press CTRL+C or "q" to exit:`)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 7 页

```

log.Print(srv.ChatJoinURL())
if err := qr.RenderString(srv.ChatJoinURL(), cfg.Reversed); err != nil {
    return err
}
if app.Flags.Browser {
    if err := srv.DisplayChat(); err != nil {
        return err
    }
} else {
    if err := srv.Chat(); err != nil {
        return err
    }
}
if err := keyboard.Open(); err == nil {
    defer func() {
        keyboard.Close()
    }()
    go func() {
        for {
            char, key, _ := keyboard.GetKey()
            if string(char) == "q" || key == keyboard.KeyCtrlC {
                srv.Shutdown()
            }
        }
    }()
} else {
    log.Print(fmt.Sprintf("Warning: keyboard not detected: %v", err))
}
return srv.Wait()
}

var chatCmd = &cobra.Command{
    Use:     "chat",
    Short:   "Start a browser chat session with another device",
    Long:    "Start a browser chat session where this host and a scanned mobile
device can exchange text and attachments.",
    Aliases: []string{"c"},
    Example: `# Start a chat session and print a QR code
eqrcp chat
# Start a chat session and open the desktop browser interface
eqrcp chat --browser`,
    Args: cobra.NoArgs,
    RunE: chatCmdFunc,
}

package cmd

import (
    "fmt"

```

```
"eqrcp/config"  
"github.com/spf13/cobra"
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 8 页

```

)

func configCmdFunc(command *cobra.Command, args []string) error {
    return config.Wizard(app)
}

var configCmd = &cobra.Command{
    Use:     "config",
    Short:   "Configure eqrcp",
    Long:    "Run an interactive configuration wizard for eqrcp. With this command
you can configure which network interface and port should be used to create the
file server.",
    Aliases: []string{"c", "cfg"},
    RunE:    configCmdFunc,
}

var migrateCmd = &cobra.Command{
    Use:     "migrate",
    Short:   "Migrate the legacy configuration file",
    Long:    "Migrate the legacy JSON configuration file to the new YAML format",
    Run: func(cmd *cobra.Command, args []string) {
        ok, err := config.Migrate(app)
        if err != nil {
            fmt.Println("error while migrating the legacy JSON configuration
file:", err)
        }
        if ok {
            fmt.Println("Legacy JSON configuration file has been successfully
deleted")
        }
    },
}

package cmd

import (
    "fmt"

    "eqrcp/version"
    "github.com/spf13/cobra"
)

var versionCmd = &cobra.Command{
    Use:     "version",
    Short:   "Print version number and build information.",
    Run: func(c *cobra.Command, args []string) {
        fmt.Println(version.String())
    },
}

package cmd

```

```
import (  
    "os"  
  
    "github.com/spf13/cobra"
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 9 页

```

)

// completionCmd represents the completion command
var completionCmd = &cobra.Command{
    Use:     "completion [bash|zsh|fish|powershell]",
    Short:   "Generate completion script",
    Long:    `To load completions:

Bash:

$ source <(eqrcp completion bash)

# To load completions for each session, execute once:
Linux:
    $ eqrcp completion bash > /etc/bash_completion.d/eqrcp
MacOS:
    $ eqrcp completion bash > /usr/local/etc/bash_completion.d/eqrcp

Zsh:

# If shell completion is not already enabled in your environment you will need
# to enable it. You can execute the following once:

$ echo "autoload -U compinit; compinit" >> ~/.zshrc

# To load completions for each session, execute once:
$ eqrcp completion zsh > "${fpath[1]}/_eqrcp"

# You will need to start a new shell for this setup to take effect.

Fish:

$ eqrcp completion fish | source

# To load completions for each session, execute once:
$ eqrcp completion fish > ~/.config/fish/completions/eqrcp.fish
`,
    DisableFlagsInUseLine: true,
    ValidArgs:             []string{"bash", "zsh", "fish", "powershell"},
    Args:                  cobra.MatchAll(cobra.ExactArgs(1),
cobra.OnlyValidArgs),
    RunE: func(cmd *cobra.Command, args []string) error {
        switch args[0] {
        case "bash":
            if err := cmd.Root().GenBashCompletion(os.Stdout); err != nil {
                return err
            }
        case "zsh":
            if err := cmd.Root().GenZshCompletion(os.Stdout); err != nil {

```

```
        return err  
    }
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 10 页

```

        case "fish":
            if err := cmd.Root().GenFishCompletion(os.Stdout, true); err != nil {
                return err
            }
        case "powershell":
            if err := cmd.Root().GenPowerShellCompletion(os.Stdout); err != nil {
                return err
            }
        }
        return nil
    },
}

package cmd

import (
    "fmt"

    "eqrcp/application"
    "eqrcp/config"
    "eqrcp/version"
    "github.com/spf13/cobra"
)

var desktopCmd = &cobra.Command{
    Use:   "desktop",
    Short: "Desktop integration helpers",
    Long:  "Desktop integration helpers for file manager context menus and other non-terminal launchers.",
}

var desktopShareCmd = &cobra.Command{
    Use:   "share <file-or-directory> [file-or-directory...]",
    Short: "Share selected files or directories from a desktop launcher",
    Long:  "Share selected files or directories from a desktop launcher. This command opens the QR code in a browser by default.",
    Example: `# Share one file from a desktop launcher
eqrcp desktop share /path/file.txt
# Share multiple selected paths
eqrcp desktop share /path/file.txt /path/photo.jpg
# Share a directory
eqrcp desktop share /path/directory`,
    Args: cobra.MinimumNArgs(1),
    RunE: func(command *cobra.Command, args []string) error {
        app.Flags.Browser = desktopBrowserPreference(app.Flags, true)
        return sendCmdFunc(command, args)
    },
}

var desktopReceiveCmd = &cobra.Command{
    Use:   "receive [directory]",

```

Short: "Receive files into a directory from a desktop launcher",

Long: "Receive files into a directory from a desktop launcher. This command opens the QR code in a browser by default. When no directory is passed, the configured output directory or current working directory is used.",

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 11 页

```

Example: `# Receive files into a selected directory
eqrcp desktop receive /path/directory
# Receive files into the configured output directory or current directory
eqrcp desktop receive`,
  Args: cobra.RangeArgs(0, 1),
  RunE: func(command *cobra.Command, args []string) error {
    app.Flags.Browser = desktopBrowserPreference(app.Flags, true)
    if output, ok := desktopReceiveOutput(args); ok {
      app.Flags.Output = output
    } else if app.Flags.Output == "" {
      app.Flags.Output = desktopOutputPreference(app.Flags)
    }
    return receiveCmdFunc(command, args)
  },
}

var desktopChatCmd = &cobra.Command{
  Use:   "chat",
  Short: "Start a chat session from a desktop launcher",
  Long:  "Start a browser-based chat session from a desktop launcher. This
command opens the chat interface in a browser by default.",
  Example: `# Start a chat session
eqrcp desktop chat`,
  Args: cobra.NoArgs,
  RunE: func(command *cobra.Command, args []string) error {
    app.Flags.Browser = desktopBrowserPreference(app.Flags, true)
    return chatCmdFunc(command, args)
  },
}

func desktopReceiveOutput(args []string) (string, bool) {
  if len(args) == 0 {
    return "", false
  }
  return args[0], true
}

func desktopBrowserPreference(flags application.Flags, fallback bool) bool {
  settingsApp := application.New()
  settingsApp.Flags = flags
  settings, err := config.ReadDesktopSettings(settingsApp)
  if err != nil {
    return fallback
  }
  return settings.Browser
}

func desktopOutputPreference(flags application.Flags) string {
  settingsApp := application.New()

```

```
settingsApp.Flags = flags  
settings, err := config.ReadDesktopSettings(settingsApp)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 12 页

```
    if err != nil || settings.Output == "" {
        return config.DefaultDesktopOutputDirectory()
    }
    return settings.Output
}

var desktopInstallCmd = &cobra.Command{
    Use: "install",
    Short: "Install desktop context menu entries",
    Long: "Install desktop context menu entries for the current user.",
    RunE: func(command *cobra.Command, args []string) error {
        if err := installDesktopIntegration(); err != nil {
            return err
        }
        fmt.Fprintln(command.OutOrStdout(), "Desktop context menu entries
installed.")
        return nil
    },
}

var desktopStatusCmd = &cobra.Command{
    Use: "status",
    Short: "Show desktop context menu integration status",
    Long: "Show desktop context menu integration status for the current user.",
    RunE: func(command *cobra.Command, args []string) error {
        status, err := desktopIntegrationStatus()
        if err != nil {
            return err
        }
        fmt.Fprintf(command.OutOrStdout(), "%s\n%s", version.String(), status)
        return nil
    },
}

var desktopStartupEnableCmd = &cobra.Command{
    Use: "startup-enable",
    Short: "Start the desktop agent at login",
    Long: "Register the desktop integration agent to start when the current user
logs in.",
    RunE: func(command *cobra.Command, args []string) error {
        if err := installDesktopStartup(); err != nil {
            return err
        }
        fmt.Fprintln(command.OutOrStdout(), "Desktop agent startup enabled.")
        return nil
    },
}

var desktopStartupDisableCmd = &cobra.Command{
    Use: "startup-disable",
```

```
Short: "Stop starting the desktop agent at login",  
Long: "Remove the current-user login startup registration for the desktop  
integration agent.",
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 13 页

```

    RunE: func(command *cobra.Command, args []string) error {
        if err := uninstallDesktopStartup(); err != nil {
            return err
        }
        fmt.Fprintln(command.OutOrStdout(), "Desktop agent startup disabled.")
        return nil
    },
}

var desktopStartupStatusCmd = &cobra.Command{
    Use:   "startup-status",
    Short: "Show desktop agent startup status",
    Long:  "Show whether the desktop integration agent is registered to start when
the current user logs in.",
    RunE: func(command *cobra.Command, args []string) error {
        status, err := desktopStartupStatus()
        if err != nil {
            return err
        }
        fmt.Fprintf(command.OutOrStdout(), "%s\n%s", version.String(), status)
        return nil
    },
}

var desktopUninstallCmd = &cobra.Command{
    Use:   "uninstall",
    Short: "Uninstall desktop context menu entries",
    Long:  "Uninstall desktop context menu entries created by eqrcp.",
    RunE: func(command *cobra.Command, args []string) error {
        if err := uninstallDesktopIntegration(); err != nil {
            return err
        }
        fmt.Fprintln(command.OutOrStdout(), "Desktop context menu entries
uninstalled.")
        return nil
    },
}

package cmd

import (
    "context"
    "encoding/json"
    "fmt"
    "html/template"
    "io"
    "net"
    "net/http"
    "net/url"
    "os"
    "os/exec"

```

```
"path/filepath"  
"runtime"
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 14 页

```

    "strconv"
    "strings"
    "sync"
    "time"

    "eqrcp/application"
    "eqrcp/body"
    "eqrcp/config"
    "eqrcp/server"
    "eqrcp/version"
    "github.com/spf13/cobra"
)

const desktopAgentAddress = "127.0.0.1:48176"
const desktopAgentMaxQueue = 16
const desktopAgentMaxHistory = 20
const desktopAgentHistoryFilename = "desktop-agent-history.json"

var openDesktopAgentPage = openDesktopAgentPageURL
var desktopAgentBaseURL = "http://" + desktopAgentAddress
var desktopAgentExecutable = os.Executable
var desktopAgentBackgroundStarter = startDesktopAgentBackgroundProcess
var desktopAgentReadyWaiter = waitForDesktopAgentReady

type desktopAgentTask struct {
    Action string `json:"action"`
    Paths []string `json:"paths"`
}

type desktopAgentTaskRecord struct {
    ID int `json:"id"`
    Action string `json:"action"`
    Paths []string `json:"paths"`
    State string `json:"state"`
    TransferState string `json:"transferState,omitempty"`
    TransferMessage string `json:"transferMessage,omitempty"`
    TransferMode string `json:"transferMode,omitempty"`
    TransferTarget string `json:"transferTarget,omitempty"`
    TransferArchive bool `json:"transferArchive,omitempty"`
    TransferArchiveName string `json:"transferArchiveName,omitempty"`
    TransferItems []string `json:"transferItems,omitempty"`
    TransferCurrent string `json:"transferCurrent,omitempty"`
    TransferPercent int `json:"transferPercent,omitempty"`
    BytesDone int64 `json:"bytesDone,omitempty"`
    BytesTotal int64 `json:"bytesTotal,omitempty"`
    SavedFiles []string `json:"savedFiles,omitempty"`
    ChatState string `json:"chatState,omitempty"`
    ChatMessageCount int `json:"chatMessageCount,omitempty"`
}

```

ChatDeviceCount	int	`json:"chatDeviceCount,omitempty"`
ChatLastActivity	string	`json:"chatLastActivity,omitempty"`

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 15 页

```

    PageURL      string    `json:"pageUrl,omitempty"`
    Error         string    `json:"error,omitempty"`
    StartedAt     time.Time `json:"startedAt"`
    FinishedAt    *time.Time `json:"finishedAt,omitempty"`
}

type desktopAgentResponse struct {
    State      string    `json:"state"`
    Current    *desktopAgentTaskRecord `json:"current,omitempty"`
    Chat       *desktopAgentTaskRecord `json:"chat,omitempty"`
    Queued     int       `json:"queued"`
    History    []desktopAgentTaskRecord `json:"history,omitempty"`
    LastError  string    `json:"lastError,omitempty"`
    Version    string    `json:"version"`
    AgentStartedAt time.Time `json:"agentStartedAt"`
}

type desktopAgentHistoryStore struct {
    History []desktopAgentTaskRecord `json:"history"`
}

type desktopAgentNotifier func(title string, message string) error

type desktopAgent struct {
    mu          sync.Mutex
    baseFlags   application.Flags
    startedAt   time.Time
    busy        bool
    current     *desktopAgentTaskRecord
    chat        *desktopAgentTaskRecord
    queue       []desktopAgentTask
    history     []desktopAgentTaskRecord
    nextID      int
    activeStop  func(string)
    chatStop    func(string)
    shutdown    func()
    lastError   string
    runner      func(desktopAgentTask) error
    notifier    desktopAgentNotifier
    historyPath string
    notified    map[int]map[string]bool
    revision    int64
    subscribers map[chan struct{}]struct{}
}

func newDesktopAgent(baseFlags application.Flags) *desktopAgent {
    agent := &desktopAgent{
        baseFlags: baseFlags,

```

```
startedAt:    time.Now(),  
notifier:    notifyDesktop,
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 16 页

```
        historyPath: defaultDesktopAgentHistoryPath(),
        notified:    map[int]map[string]bool{},
        subscribers: map[chan struct{}]struct{}{},
    }
    agent.runner = agent.runTask
    return agent
}

func defaultDesktopAgentHistoryPath() string {
    return filepath.Join(config.DefaultConfigDir(), desktopAgentHistoryFilename)
}

func (agent *desktopAgent) routes() http.Handler {
    mux := http.NewServeMux()
    mux.HandleFunc("/", agent.handlePage)
    mux.HandleFunc("/health", agent.handleHealth)
    mux.HandleFunc("/status", agent.handleStatus)
    mux.HandleFunc("/events", agent.handleEvents)
    mux.HandleFunc("/settings", agent.handleSettings)
    mux.HandleFunc("/restart", agent.handleRestart)
    mux.HandleFunc("/tasks", agent.handleTasks)
    mux.HandleFunc("/tasks/", agent.handleTaskAction)
    mux.HandleFunc("/history", agent.handleHistory)
    mux.HandleFunc("/stop-current", agent.handleStopCurrent)
    mux.HandleFunc("/stop-chat", agent.handleStopChat)
    mux.HandleFunc("/shutdown", agent.handleShutdown)
    return mux
}

func (agent *desktopAgent) handlePage(w http.ResponseWriter, r *http.Request) {
    if r.URL.Path != "/" {
        http.NotFound(w, r)
        return
    }
    if r.Method != http.MethodGet {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    status := agent.snapshot()
    w.Header().Set("Content-Type", "text/html; charset=utf-8")
    _ = desktopAgentPageTemplate.Execute(w, status)
}

func (agent *desktopAgent) handleHealth(w http.ResponseWriter, r *http.Request) {
    if handleDesktopAgentCORS(w, r, http.MethodGet) {
        w.WriteHeader(http.StatusNoContent)
        return
    }
}
```

```
if rejectCrossOriginDesktopAgent(w, r) {  
    return
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 17 页

```
}
if r.Method != http.MethodGet {
    http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
    return
}
w.WriteHeader(http.StatusNoContent)
}

func (agent *desktopAgent) handleStatus(w http.ResponseWriter, r *http.Request) {
    if handleDesktopAgentCORS(w, r, http.MethodGet) {
        w.WriteHeader(http.StatusNoContent)
        return
    }
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodGet {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    agent.writeStatus(w)
}

func (agent *desktopAgent) handleEvents(w http.ResponseWriter, r *http.Request) {
    if handleDesktopAgentCORS(w, r, http.MethodGet) {
        w.WriteHeader(http.StatusNoContent)
        return
    }
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodGet {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    flusher, ok := w.(http.Flusher)
    if !ok {
        http.Error(w, "streaming unsupported", http.StatusInternalServerError)
        return
    }
    w.Header().Set("Content-Type", "text/event-stream")
    w.Header().Set("Cache-Control", "no-cache")
    w.Header().Set("Connection", "keep-alive")
    lastRevision := int64(-1)
    send := func() bool {
        status, revision := agent.snapshotWithRevision()
        if revision == lastRevision {
            return true
        }
    }
```

```
}  
lastRevision = revision
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 18 页

```
        if _, err := fmt.Fprint(w, "data: "); err != nil {
            return false
        }
        if err := json.NewEncoder(w).Encode(status); err != nil {
            return false
        }
        if _, err := fmt.Fprint(w, "\n"); err != nil {
            return false
        }
        flusher.Flush()
        return true
    }
    if !send() {
        return
    }
    events, unsubscribe := agent.subscribeEvents()
    defer unsubscribe()
    heartbeat := time.NewTicker(15 * time.Second)
    defer heartbeat.Stop()
    for {
        select {
        case <-r.Context().Done():
            return
        case <-events:
            if !send() {
                return
            }
        case <-heartbeat.C:
            if _, err := fmt.Fprint(w, ": keep-alive\n\n"); err != nil {
                return
            }
            flusher.Flush()
        }
    }
}

func (agent *desktopAgent) subscribeEvents() (<-chan struct{}, func()) {
    ch := make(chan struct{}, 1)
    agent.mu.Lock()
    if agent.subscribers == nil {
        agent.subscribers = map[chan struct{}]struct{}{}
    }
    agent.subscribers[ch] = struct{}{}
    agent.mu.Unlock()
    return ch, func() {
        agent.mu.Lock()
        delete(agent.subscribers, ch)
        close(ch)
    }
}
```

```
    agent.mu.Unlock()  
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 19 页

```
}

func (agent *desktopAgent) touchLocked() {
    agent.revision++
    for ch := range agent.subscribers {
        select {
        case ch <- struct{}{}:
        default:
        }
    }
}

func (agent *desktopAgent) handleRestart(w http.ResponseWriter, r *http.Request) {
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    logFile, logPath, err := createDesktopAgentBackgroundLog()
    if err != nil {
        http.Error(w, fmt.Sprintf("desktop agent restart failed: %v", err),
            http.StatusInternalServerError)
        return
    }
    exe, err := desktopAgentExecutable()
    if err != nil {
        _ = logFile.Close()
        http.Error(w, fmt.Sprintf("desktop agent restart failed: %v", err),
            http.StatusInternalServerError)
        return
    }
    cmd := exec.Command(exe, "desktop", "agent-restart-helper")
    configureDesktopAgentBackgroundCommand(cmd)
    cmd.Stdout = logFile
    cmd.Stderr = logFile
    if err := cmd.Start(); err != nil {
        _ = logFile.Close()
        http.Error(w, fmt.Sprintf("desktop agent restart failed: %v", err),
            http.StatusInternalServerError)
        return
    }
    if err := cmd.Process.Release(); err != nil {
        _ = logFile.Close()
        http.Error(w, fmt.Sprintf("desktop agent restart failed: %v", err),
            http.StatusInternalServerError)
        return
    }
    agent.mu.Lock()
}
```

```
agent.queue = nil
if agent.busy {
    agent.finalizeActiveLocked("replaced")
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 20 页

```
if agent.chat != nil {
    agent.finalizeChatLocked("replaced")
}
shutdown := agent.shutdown
agent.touchLocked()
agent.mu.Unlock()

w.WriteHeader(http.StatusAccepted)
fmt.Fprintf(w, "Desktop agent restarting.\nLog: %s\n", logPath)
go func() {
    defer logFile.Close()
    if shutdown != nil {
        shutdown()
    }
}()
}

func (agent *desktopAgent) handleSettings(w http.ResponseWriter, r *http.Request)
{
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    switch r.Method {
    case http.MethodGet:
        settings, err := agent.readSettings()
        if err != nil {
            http.Error(w, fmt.Sprintf("desktop agent settings unavailable: %v",
err), http.StatusInternalServerError)
            return
        }
        w.Header().Set("Content-Type", "application/json")
        _ = json.NewEncoder(w).Encode(settings)
    case http.MethodPost:
        var settings config.DesktopSettings
        if err := json.NewDecoder(r.Body).Decode(&settings); err != nil {
            http.Error(w, fmt.Sprintf("invalid settings: %v", err),
http.StatusBadRequest)
            return
        }
        saved, err := agent.writeSettings(settings)
        if err != nil {
            http.Error(w, fmt.Sprintf("save desktop agent settings failed: %v",
err), http.StatusBadRequest)
            return
        }
        w.Header().Set("Content-Type", "application/json")
        _ = json.NewEncoder(w).Encode(saved)
    default:
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
    }
}
```

```
}
```

```
func (agent *desktopAgent) settingsApp() application.App {  
    settingsApp := application.New()
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 21 页

```
    settingsApp.Flags = agent.baseFlags
    return settingsApp
}

func (agent *desktopAgent) readSettings() (config.DesktopSettings, error) {
    return config.ReadDesktopSettings(agent.settingsApp())
}

func (agent *desktopAgent) writeSettings(settings config.DesktopSettings)
(config.DesktopSettings, error) {
    return config.WriteDesktopSettings(agent.settingsApp(), settings)
}

func (agent *desktopAgent) handleTasks(w http.ResponseWriter, r *http.Request) {
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    var task desktopAgentTask
    if err := json.NewDecoder(r.Body).Decode(&task); err != nil {
        http.Error(w, fmt.Sprintf("invalid task: %v", err), http.StatusBadRequest)
        return
    }
    if err := validateDesktopAgentTask(task); err != nil {
        http.Error(w, err.Error(), http.StatusBadRequest)
        return
    }
    agent.mu.Lock()
    if task.Action == "chat" && agent.chat != nil && agent.chat.State == "running"
{
        agent.lastError = ""
        agent.touchLocked()
        agent.mu.Unlock()
        w.WriteHeader(http.StatusAccepted)
        agent.writeStatus(w)
        return
    }
    agent.lastError = ""
    if task.Action == "chat" {
        agent.startChatLocked(task)
    } else {
        if len(agent.queue) >= desktopAgentMaxQueue {
            agent.mu.Unlock()
            http.Error(w, "desktop agent queue is full",
http.StatusTooManyRequests)
            return
        }
    }
}
```

```
agent.queue = append(agent.queue, task)
if agent.busy {
    agent.replaceActiveLocked("replaced")
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 22 页

```
        }
        agent.startNextLocked()
    }
    agent.touchLocked()
    agent.mu.Unlock()

    w.WriteHeader(http.StatusAccepted)
    agent.writeStatus(w)
}

func (agent *desktopAgent) handleTaskAction(w http.ResponseWriter, r
*http.Request) {
    if handleDesktopAgentCORS(w, r, http.MethodPost) {
        w.WriteHeader(http.StatusNoContent)
        return
    }
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    taskID, action, ok := parseDesktopAgentTaskActionPath(r.URL.Path)
    if !ok || action != "repeat" {
        http.NotFound(w, r)
        return
    }
    if err := agent.repeatTask(taskID); err != nil {
        http.Error(w, err.Error(), http.StatusConflict)
        return
    }
    w.WriteHeader(http.StatusAccepted)
    agent.writeStatus(w)
}

func parseDesktopAgentTaskActionPath(path string) (int, string, bool) {
    parts := strings.Split(strings.Trim(path, "/"), "/")
    if len(parts) != 3 || parts[0] != "tasks" {
        return 0, "", false
    }
    id, err := strconv.Atoi(parts[1])
    if err != nil || id <= 0 {
        return 0, "", false
    }
    return id, parts[2], true
}

func handleDesktopAgentCORS(w http.ResponseWriter, r *http.Request, methods
...string) bool {
```

```
origin := r.Header.Get("Origin")
if origin != "" && trustedDesktopAgentOrigin(origin, r.Host) {
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 23 页

```
w.Header().Set("Access-Control-Allow-Origin", origin)
w.Header().Set("Vary", "Origin")
w.Header().Set("Access-Control-Allow-Headers", "Content-Type")
if len(methods) > 0 {
    allowed := append([]string(nil), methods...)
    allowed = append(allowed, http.MethodOptions)
    w.Header().Set("Access-Control-Allow-Methods", strings.Join(allowed,
", "))
}
}
return r.Method == http.MethodOptions
}

func rejectCrossOriginDesktopAgent(w http.ResponseWriter, r *http.Request) bool {
    origin := r.Header.Get("Origin")
    if origin == "" {
        return false
    }
    if trustedDesktopAgentOrigin(origin, r.Host) {
        return false
    }
    http.Error(w, "forbidden", http.StatusForbidden)
    return true
}

func trustedDesktopAgentOrigin(origin string, requestHost string) bool {
    parsed, err := url.Parse(origin)
    if err != nil {
        return false
    }
    if trustedDesktopAgentWailsOrigin(parsed) {
        return true
    }
    if strings.EqualFold(parsed.Host, requestHost) {
        return true
    }
    return trustedDesktopAgentLocalHost(parsed.Hostname())
}

func trustedDesktopAgentWailsOrigin(parsed *url.URL) bool {
    host := strings.ToLower(parsed.Hostname())
    return parsed.Scheme == "wails" || host == "wails.localhost"
}

func trustedDesktopAgentLocalHost(host string) bool {
    host = strings.Trim(strings.ToLower(host), "[ ]")
    if host == "localhost" {
        return true
    }
    ip := net.ParseIP(host)
```

```
return ip != nil && (ip.IsLoopback() || ip.IsPrivate() ||  
ip.IsLinkLocalUnicast())
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 24 页

```
}

func (agent *desktopAgent) handleHistory(w http.ResponseWriter, r *http.Request) {
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodDelete {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    if err := agent.clearHistory(); err != nil {
        http.Error(w, fmt.Sprintf("clear desktop agent history failed: %v", err),
            http.StatusInternalServerError)
        return
    }
    w.WriteHeader(http.StatusNoContent)
}

func (agent *desktopAgent) handleStopCurrent(w http.ResponseWriter, r
*http.Request) {
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    if !agent.stopCurrent("stopped") {
        http.Error(w, "desktop agent has no active task", http.StatusConflict)
        return
    }
    if strings.Contains(r.Header.Get("Accept"), "text/html") {
        http.Redirect(w, r, "/", http.StatusSeeOther)
        return
    }
    w.WriteHeader(http.StatusAccepted)
    fmt.Fprintln(w, "Current desktop agent task stopped.")
}

func (agent *desktopAgent) handleStopChat(w http.ResponseWriter, r *http.Request)
{
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    if !agent.stopChat("stopped") {
        http.Error(w, "desktop agent has no active chat", http.StatusConflict)
    }
}
```

```
        return  
    }  
    w.WriteHeader(http.StatusAccepted)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 25 页

```
    fmt.Fprintln(w, "Current desktop chat stopped.")
}

func (agent *desktopAgent) handleShutdown(w http.ResponseWriter, r *http.Request)
{
    if rejectCrossOriginDesktopAgent(w, r) {
        return
    }
    if r.Method != http.MethodPost {
        http.Error(w, "method not allowed", http.StatusMethodNotAllowed)
        return
    }
    agent.mu.Lock()
    agent.queue = nil
    if agent.busy {
        agent.finalizeActiveLocked("replaced")
    }
    shutdown := agent.shutdown
    agent.touchLocked()
    agent.mu.Unlock()

    w.WriteHeader(http.StatusAccepted)
    fmt.Fprintln(w, "Desktop agent stopping.")
    if shutdown != nil {
        go shutdown()
    }
}

func (agent *desktopAgent) execute(task desktopAgentTask, id int) {
    err := agent.runner(task)
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if agent.current != nil && agent.current.ID == id {
        finishedAt := time.Now()
        agent.current.FinishedAt = &finishedAt
        if agent.current.State == "running" {
            if err != nil {
                agent.current.State = "failed"
                agent.current.Error = err.Error()
                agent.lastError = err.Error()
            } else if isTerminalDesktopTransferState(agent.current.TransferState)
        {
            agent.current.State = agent.current.TransferState
        } else {
            agent.current.State = "completed"
        }
    }
    agent.addHistoryLocked(*agent.current)
    agent.notifyRecordLocked(*agent.current)
    delete(agent.notified, agent.current.ID)
```

```
agent.busy = false  
agent.current = nil
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 26 页

```
        agent.activeStop = nil
        agent.startNextLocked()
        agent.touchLocked()
    }
}

func (agent *desktopAgent) executeChat(task desktopAgentTask, id int) {
    err := agent.runner(task)
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if agent.chat != nil && agent.chat.ID == id {
        finishedAt := time.Now()
        agent.chat.FinishedAt = &finishedAt
        if agent.chat.State == "running" {
            if err != nil {
                agent.chat.State = "failed"
                agent.chat.Error = err.Error()
                agent.lastError = err.Error()
            } else {
                agent.chat.State = "completed"
            }
        }
        agent.addHistoryLocked(*agent.chat)
        agent.notifyRecordLocked(*agent.chat)
        delete(agent.notified, agent.chat.ID)
        agent.chat = nil
        agent.chatStop = nil
        agent.touchLocked()
    }
}

func (agent *desktopAgent) stopCurrent(state string) bool {
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if agent.busy {
        agent.replaceActiveLocked(state)
        agent.touchLocked()
        return true
    }
    if agent.chat == nil {
        return false
    }
    agent.replaceChatLocked(state)
    agent.touchLocked()
    return true
}

func (agent *desktopAgent) stopChat(state string) bool {
```

```
agent.mu.Lock()  
defer agent.mu.Unlock()
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 27 页

```

    if agent.chat == nil {
        return false
    }
    agent.replaceChatLocked(state)
    agent.touchLocked()
    return true
}

func (agent *desktopAgent) repeatTask(id int) error {
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if len(agent.queue) >= desktopAgentMaxQueue {
        return fmt.Errorf("desktop agent queue is full")
    }
    var repeated *desktopAgentTask
    if agent.current != nil && agent.current.ID == id {
        task := desktopAgentTask{Action: agent.current.Action, Paths:
append([]string(nil), agent.current.Paths...)}
        repeated = &task
    }
    if repeated == nil && agent.chat != nil && agent.chat.ID == id {
        task := desktopAgentTask{Action: agent.chat.Action, Paths:
append([]string(nil), agent.chat.Paths...)}
        repeated = &task
    }
    if repeated == nil {
        for _, record := range agent.history {
            if record.ID == id {
                task := desktopAgentTask{Action: record.Action, Paths:
append([]string(nil), record.Paths...)}
                repeated = &task
                break
            }
        }
    }
    if repeated == nil {
        return fmt.Errorf("desktop agent task #%d was not found", id)
    }
    if err := validateDesktopAgentTask(*repeated); err != nil {
        return err
    }
    agent.lastError = ""
    if repeated.Action == "chat" {
        if agent.chat != nil {
            agent.replaceChatLocked("replaced")
        }
        agent.startChatLocked(*repeated)
    } else {
        agent.queue = append(agent.queue, *repeated)
        if agent.busy {

```

```
        agent.replaceActiveLocked("replaced")
    }
    agent.startNextLocked()
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 28 页

```
    }
    agent.touchLocked()
    return nil
}

func isTerminalDesktopTransferState(state string) bool {
    return state == "completed" || state == "stopped" || state == "failed"
}

func isTerminalDesktopChatState(state string) bool {
    return state == "ended" || state == "stopped" || state == "failed" || state ==
"replaced"
}

func desktopTaskStateForChatState(state string) string {
    switch state {
    case "ended":
        return "completed"
    case "stopped", "failed", "replaced":
        return state
    default:
        return "running"
    }
}

func (agent *desktopAgent) replaceActiveLocked(state string) {
    if agent.current != nil && agent.current.State == "running" {
        agent.current.State = state
        finishedAt := time.Now()
        agent.current.FinishedAt = &finishedAt
    }
    if agent.activeStop == nil {
        return
    }
    stop := agent.activeStop
    go stop(state)
}

func (agent *desktopAgent) replaceChatLocked(state string) {
    if agent.chat != nil && agent.chat.State == "running" {
        agent.chat.State = state
        finishedAt := time.Now()
        agent.chat.FinishedAt = &finishedAt
    }
    if agent.chatStop == nil {
        return
    }
    stop := agent.chatStop
    go stop(state)
}
```

```
}

```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 29 页

```
func (agent *desktopAgent) finalizeActiveLocked(state string) {
    agent.replaceActiveLocked(state)
    if agent.current == nil {
        return
    }
    record := *agent.current
    agent.addHistoryLocked(record)
    agent.notifyRecordLocked(record)
    delete(agent.notified, record.ID)
    agent.busy = false
    agent.current = nil
    agent.activeStop = nil
}

func (agent *desktopAgent) finalizeChatLocked(state string) {
    agent.replaceChatLocked(state)
    if agent.chat == nil {
        return
    }
    record := *agent.chat
    agent.addHistoryLocked(record)
    agent.notifyRecordLocked(record)
    delete(agent.notified, record.ID)
    agent.chat = nil
    agent.chatStop = nil
}

func (agent *desktopAgent) startNextLocked() {
    if agent.busy || len(agent.queue) == 0 {
        return
    }
    task := agent.queue[0]
    agent.queue = agent.queue[1:]
    agent.nextID++
    record := desktopAgentTaskRecord{
        ID:      agent.nextID,
        Action:   task.Action,
        Paths:    append([]string(nil), task.Paths...),
        State:    "running",
        StartedAt: time.Now(),
    }
    agent.busy = true
    agent.current = &record
    agent.notifyRecordLocked(record)
    go agent.execute(task, record.ID)
}

func (agent *desktopAgent) startChatLocked(task desktopAgentTask) {
```

```
agent.nextID++  
record := desktopAgentTaskRecord{
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 30 页

```

        ID:      agent.nextID,
        Action:   task.Action,
        Paths:    append([]string(nil), task.Paths...),
        State:     "running",
        StartedAt: time.Now(),
    }
    agent.chat = &record
    agent.notifyRecordLocked(record)
    go agent.executeChat(task, record.ID)
}

func (agent *desktopAgent) taskIDForAction(action string) int {
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if action == "chat" {
        if agent.chat == nil {
            return 0
        }
        return agent.chat.ID
    }
    if agent.current == nil {
        return 0
    }
    return agent.current.ID
}

func (agent *desktopAgent) observeTransferStatus(taskID int, status
server.TransferStatusSnapshot) {
    agent.mu.Lock()
    defer agent.mu.Unlock()
    if agent.current == nil || agent.current.ID != taskID {
        return
    }
    agent.current.TransferState = status.State
    agent.current.TransferMessage = status.Message
    agent.current.TransferMode = status.Mode
    agent.current.TransferTarget = status.Target
    agent.current.TransferArchive = status.Archive
    agent.current.TransferArchiveName = status.ArchiveName
    agent.current.TransferItems = append([]string(nil), status.Items...)
    agent.current.TransferCurrent = status.Current
    agent.current.TransferPercent = status.Percent
    agent.current.BytesDone = status.BytesDone
    agent.current.BytesTotal = status.BytesTotal
    agent.current.SavedFiles = append([]string(nil), status.SavedFiles...)
    if isTerminalDesktopTransferState(status.State) && agent.current.State ==
"running" {
        agent.current.State = status.State
        finishedAt := time.Now()
        agent.current.FinishedAt = &finishedAt
    }
}

```

```
}  
agent.notifyTransferStatusLocked(*agent.current)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 31 页

```
if (typeof index !== 'number') return defaultValue
index = ~~index // Coerce to integer.
if (index >= len) return len
if (index >= 0) return index
index += len
if (index >= 0) return index
return 0
}

var toType = function (flag) {
  switch (flag) {
    case 0:
      return 'file'
    case 1:
      return 'link'
    case 2:
      return 'symlink'
    case 3:
      return 'character-device'
    case 4:
      return 'block-device'
    case 5:
      return 'directory'
    case 6:
      return 'fifo'
    case 7:
      return 'contiguous-file'
    case 72:
      return 'pax-header'
    case 55:
      return 'pax-global-header'
    case 27:
      return 'gnu-long-link-path'
    case 28:
    case 30:
      return 'gnu-long-path'
  }
}

return null
}

var toTypeflag = function (flag) {
  switch (flag) {
    case 'file':
      return 0
    case 'link':
      return 1
    case 'symlink':
```

```
    return 2  
    case 'character-device':
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 32 页

```
        return 3
      case 'block-device':
        return 4
      case 'directory':
        return 5
      case 'fifo':
        return 6
      case 'contiguous-file':
        return 7
      case 'pax-header':
        return 72
    }

    return 0
  }

  var indexOf = function (block, num, offset, end) {
    for (; offset < end; offset++) {
      if (block[offset] === num) return offset
    }
    return end
  }

  var cksum = function (block) {
    var sum = 8 * 32
    for (var i = 0; i < 148; i++) sum += block[i]
    for (var j = 156; j < 512; j++) sum += block[j]
    return sum
  }

  var encodeOct = function (val, n) {
    val = val.toString(8)
    if (val.length > n) return SEVENS.slice(0, n) + ' '
    else return ZEROS.slice(0, n - val.length) + val + ' '
  }

  /* Copied from the node-tar repo and modified to meet
   * tar-stream coding standard.
   *
   * Source: https://github.com/npm/node-
   tar/blob/51b6627a1f357d2eb433e7378e5f05e83b7aa6cd/lib/header.js#L349
   */
  function parse256 (buf) {
    // first byte MUST be either 80 or FF
    // 80 for positive, FF for 2's comp
    var positive
    if (buf[0] === 0x80) positive = true
    else if (buf[0] === 0xFF) positive = false
    else return null
  }
```

```
// build up a base-256 tuple from the least sig to the highest
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 33 页

```
var tuple = []
for (var i = buf.length - 1; i > 0; i--) {
  var byte = buf[i]
  if (positive) tuple.push(byte)
  else tuple.push(0xFF - byte)
}

var sum = 0
var l = tuple.length
for (i = 0; i < l; i++) {
  sum += tuple[i] * Math.pow(256, i)
}

return positive ? sum : -1 * sum
}

var decodeOct = function (val, offset, length) {
  val = val.slice(offset, offset + length)
  offset = 0

  // If prefixed with 0x80 then parse as a base-256 integer
  if (val[offset] & 0x80) {
    return parse256(val)
  } else {
    // Older versions of tar can prefix with spaces
    while (offset < val.length && val[offset] === 32) offset++
    var end = clamp(indexOf(val, 32, offset, val.length), val.length, val.length)
    while (offset < end && val[offset] === 0) offset++
    if (end === offset) return 0
    return parseInt(val.slice(offset, end).toString(), 8)
  }
}

var decodeStr = function (val, offset, length, encoding) {
  return val.slice(offset, indexOf(val, 0, offset, offset + length)).toString(encoding)
}

var addLength = function (str) {
  var len = Buffer.byteLength(str)
  var digits = Math.floor(Math.log(len) / Math.log(10)) + 1
  if (len + digits >= Math.pow(10, digits)) digits++

  return (len + digits) + str
}

exports.decodeLongPath = function (buf, encoding) {
  return decodeStr(buf, 0, buf.length, encoding)
}
```

```
exports.encodePax = function (opts) { // TODO: encode more stuff in pax
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 34 页

```
var result = ''
if (opts.name) result += addLength(' path=' + opts.name + '\n')
if (opts.linkname) result += addLength(' linkpath=' + opts.linkname + '\n')
var pax = opts.pax
if (pax) {
  for (var key in pax) {
    result += addLength(' ' + key + '=' + pax[key] + '\n')
  }
}
return Buffer.from(result)
}

exports.decodePax = function (buf) {
  var result = {}

  while (buf.length) {
    var i = 0
    while (i < buf.length && buf[i] !== 32) i++
    var len = parseInt(buf.slice(0, i).toString(), 10)
    if (!len) return result

    var b = buf.slice(i + 1, len - 1).toString()
    var keyIndex = b.indexOf('=')
    if (keyIndex === -1) return result
    result[b.slice(0, keyIndex)] = b.slice(keyIndex + 1)

    buf = buf.slice(len)
  }

  return result
}

exports.encode = function (opts) {
  var buf = alloc(512)
  var name = opts.name
  var prefix = ''

  if (opts.typeflag === 5 && name[name.length - 1] !== '/') name += '/'
  if (Buffer.byteLength(name) !== name.length) return null // utf-8

  while (Buffer.byteLength(name) > 100) {
    var i = name.indexOf('/')
    if (i === -1) return null
    prefix += prefix ? '/' + name.slice(0, i) : name.slice(0, i)
    name = name.slice(i + 1)
  }

  if (Buffer.byteLength(name) > 100 || Buffer.byteLength(prefix) > 155) return null
}
```

```
if (opts.linkname && Buffer.byteLength(opts.linkname) > 100) return null
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 35 页

```
buf.write(name)
buf.write(encodeOct(opts.mode & MASK, 6), 100)
buf.write(encodeOct(opts.uid, 6), 108)
buf.write(encodeOct(opts.gid, 6), 116)
buf.write(encodeOct(opts.size, 11), 124)
buf.write(encodeOct((opts.mtime.getTime() / 1000) | 0, 11), 136)

buf[156] = ZERO_OFFSET + toTypeflag(opts.type)

if (opts.linkname) buf.write(opts.linkname, 157)

USTAR_MAGIC.copy(buf, MAGIC_OFFSET)
USTAR_VER.copy(buf, VERSION_OFFSET)
if (opts.uname) buf.write(opts.uname, 265)
if (opts.gname) buf.write(opts.gname, 297)
buf.write(encodeOct(opts.devmajor || 0, 6), 329)
buf.write(encodeOct(opts.devminor || 0, 6), 337)

if (prefix) buf.write(prefix, 345)

buf.write(encodeOct(cksum(buf), 6), 148)

return buf
}

exports.decode = function (buf, filenameEncoding, allowUnknownFormat) {
  var typeflag = buf[156] === 0 ? 0 : buf[156] - ZERO_OFFSET

  var name = decodeStr(buf, 0, 100, filenameEncoding)
  var mode = decodeOct(buf, 100, 8)
  var uid = decodeOct(buf, 108, 8)
  var gid = decodeOct(buf, 116, 8)
  var size = decodeOct(buf, 124, 12)
  var mtime = decodeOct(buf, 136, 12)
  var type = toType(typeflag)
  var linkname = buf[157] === 0 ? null : decodeStr(buf, 157, 100,
filenameEncoding)
  var uname = decodeStr(buf, 265, 32)
  var gname = decodeStr(buf, 297, 32)
  var devmajor = decodeOct(buf, 329, 8)
  var devminor = decodeOct(buf, 337, 8)

  var c = cksum(buf)

  // checksum is still initial value if header was null.
  if (c === 8 * 32) return null

  // valid checksum
  if (c !== decodeOct(buf, 148, 8)) throw new Error('Invalid tar header. Maybe the
tar is corrupted or it needs to be gunzipped?')
```

```
if (USTAR_MAGIC.compare(buf, MAGIC_OFFSET, MAGIC_OFFSET + 6) === 0) {
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 36 页

```

    // ustar (posix) format.
    // prepend prefix, if present.
    if (buf[345]) name = decodeStr(buf, 345, 155, filenameEncoding) + '/' + name
  } else if (GNU_MAGIC.compare(buf, MAGIC_OFFSET, MAGIC_OFFSET + 6) === 0 &&
    GNU_VER.compare(buf, VERSION_OFFSET, VERSION_OFFSET + 2) === 0) {
    // 'gnu'/'oldgnu' format. Similar to ustar, but has support for incremental
and
    // multi-volume tarballs.
  } else {
    if (!allowUnknownFormat) {
      throw new Error('Invalid tar header: unknown format.')
    }
  }
}

// to support old tar versions that use trailing / to indicate dirs
if (typeflag === 0 && name && name[name.length - 1] === '/') typeflag = 5

return {
  name,
  mode,
  uid,
  gid,
  size,
  mtime: new Date(1000 * mtime),
  type,
  linkname,
  uname,
  gname,
  devmajor,
  devminor
}
}
exports.extract = require('./extract')
exports.pack = require('./pack')
var constants = require('fs-constants')
var eos = require('end-of-stream')
var inherits = require('inherits')
var alloc = Buffer.alloc

var Readable = require('readable-stream').Readable
var Writable = require('readable-stream').Writable
var StringDecoder = require('string_decoder').StringDecoder

var headers = require('./headers')

var DMODE = parseInt('755', 8)
var FMODE = parseInt('644', 8)

var END_OF_TAR = alloc(1024)

```

```
var noop = function () {}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 37 页

```
var overflow = function (self, size) {
  size &= 511
  if (size) self.push(END_OF_TAR.slice(0, 512 - size))
}

function modeToType (mode) {
  switch (mode & constants.S_IFMT) {
    case constants.S_IFBLK: return 'block-device'
    case constants.S_IFCHR: return 'character-device'
    case constants.S_IFDIR: return 'directory'
    case constants.S_IFIFO: return 'fifo'
    case constants.S_IFLNK: return 'symlink'
  }

  return 'file'
}

var Sink = function (to) {
  Writable.call(this)
  this.written = 0
  this._to = to
  this._destroyed = false
}

inherits(Sink, Writable)

Sink.prototype._write = function (data, enc, cb) {
  this.written += data.length
  if (this._to.push(data)) return cb()
  this._to._drain = cb
}

Sink.prototype.destroy = function () {
  if (this._destroyed) return
  this._destroyed = true
  this.emit('close')
}

var LinkSink = function () {
  Writable.call(this)
  this.linkname = ''
  this._decoder = new StringDecoder('utf-8')
  this._destroyed = false
}

inherits(LinkSink, Writable)
```

```
LinkSink.prototype._write = function (data, enc, cb) {  
  this.linkname += this._decoder.write(data)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 38 页

```
    cb()
  }

LinkSink.prototype.destroy = function () {
  if (this._destroyed) return
  this._destroyed = true
  this.emit('close')
}

var Void = function () {
  Writable.call(this)
  this._destroyed = false
}

inherits(Void, Writable)

Void.prototype._write = function (data, enc, cb) {
  cb(new Error('No body allowed for this entry'))
}

Void.prototype.destroy = function () {
  if (this._destroyed) return
  this._destroyed = true
  this.emit('close')
}

var Pack = function (opts) {
  if (!(this instanceof Pack)) return new Pack(opts)
  Readable.call(this, opts)

  this._drain = noop
  this._finalized = false
  this._finalizing = false
  this._destroyed = false
  this._stream = null
}

inherits(Pack, Readable)

Pack.prototype.entry = function (header, buffer, callback) {
  if (this._stream) throw new Error('already piping an entry')
  if (this._finalized || this._destroyed) return

  if (typeof buffer === 'function') {
    callback = buffer
    buffer = null
  }
}
```

```
if (!callback) callback = noop
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 39 页

```
var self = this

if (!header.size || header.type === 'symlink') header.size = 0
if (!header.type) header.type = modeToType(header.mode)
if (!header.mode) header.mode = header.type === 'directory' ? DMODE : FMODE
if (!header.uid) header.uid = 0
if (!header.gid) header.gid = 0
if (!header.mtime) header.mtime = new Date()

if (typeof buffer === 'string') buffer = Buffer.from(buffer)
if (Buffer.isBuffer(buffer)) {
  header.size = buffer.length
  this._encode(header)
  var ok = this.push(buffer)
  overflow(self, header.size)
  if (ok) process.nextTick(callback)
  else this._drain = callback
  return new Void()
}

if (header.type === 'symlink' && !header.linkname) {
  var linkSink = new LinkSink()
  eos(linkSink, function (err) {
    if (err) { // stream was closed
      self.destroy()
      return callback(err)
    }

    header.linkname = linkSink.linkname
    self._encode(header)
    callback()
  })

  return linkSink
}

this._encode(header)

if (header.type !== 'file' && header.type !== 'contiguous-file') {
  process.nextTick(callback)
  return new Void()
}

var sink = new Sink(this)

this._stream = sink

eos(sink, function (err) {
```

```
self._stream = null
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 40 页

```
    if (err) { // stream was closed
      self.destroy()
      return callback(err)
    }

    if (sink.written !== header.size) { // corrupting tar
      self.destroy()
      return callback(new Error('size mismatch'))
    }

    overflow(self, header.size)
    if (self._finalizing) self.finalize()
    callback()
  })

  return sink
}

Pack.prototype.finalize = function () {
  if (this._stream) {
    this._finalizing = true
    return
  }

  if (this._finalized) return
  this._finalized = true
  this.push(END_OF_TAR)
  this.push(null)
}

Pack.prototype.destroy = function (err) {
  if (this._destroyed) return
  this._destroyed = true

  if (err) this.emit('error', err)
  this.emit('close')
  if (this._stream && this._stream.destroy) this._stream.destroy()
}

Pack.prototype._encode = function (header) {
  if (!header.pax) {
    var buf = headers.encode(header)
    if (buf) {
      this.push(buf)
      return
    }
  }
}
this._encodePax(header)
```

```
}

```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 41 页

```
Pack.prototype._encodePax = function (header) {
  var paxHeader = headers.encodePax({
    name: header.name,
    linkname: header.linkname,
    pax: header.pax
  })

  var newHeader = {
    name: 'PaxHeader',
    mode: header.mode,
    uid: header.uid,
    gid: header.gid,
    size: paxHeader.length,
    mtime: header.mtime,
    type: 'pax-header',
    linkname: header.linkname && 'PaxHeader',
    uname: header.uname,
    gname: header.gname,
    devmajor: header.devmajor,
    devminor: header.devminor
  }

  this.push(headers.encode(newHeader))
  this.push(paxHeader)
  overflow(this, paxHeader.length)

  newHeader.size = header.size
  newHeader.type = header.type
  this.push(headers.encode(newHeader))
}

Pack.prototype._read = function (n) {
  var drain = this._drain
  this._drain = noop
  drain()
}

module.exports = Pack
const tar = require('tar-stream')
const fs = require('fs')
const path = require('path')
const pipeline = require('pump') // eequire('stream').pipeline

fs.createReadStream('test.tar')
  .pipe(tar.extract())
  .on('entry', function (header, stream, done) {
    console.log(header.name)
    pipeline(stream, fs.createWriteStream(path.join('/tmp', header.name)), done)
```

```
}  
'use strict'
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 42 页

```
var net = require('net')
  , tls = require('tls')
  , http = require('http')
  , https = require('https')
  , events = require('events')
  , assert = require('assert')
  , util = require('util')
  , Buffer = require('safe-buffer').Buffer
;

exports.httpOverHttp = httpOverHttp
exports.httpsOverHttp = httpsOverHttp
exports.httpOverHttps = httpOverHttps
exports.httpsOverHttps = httpsOverHttps

function httpOverHttp(options) {
  var agent = new TunnelingAgent(options)
  agent.request = http.request
  return agent
}

function httpsOverHttp(options) {
  var agent = new TunnelingAgent(options)
  agent.request = http.request
  agent.createSocket = createSecureSocket
  agent.defaultPort = 443
  return agent
}

function httpOverHttps(options) {
  var agent = new TunnelingAgent(options)
  agent.request = https.request
  return agent
}

function httpsOverHttps(options) {
  var agent = new TunnelingAgent(options)
  agent.request = https.request
  agent.createSocket = createSecureSocket
  agent.defaultPort = 443
  return agent
}

function TunnelingAgent(options) {
  var self = this
```

```
self.options = options || {}  
self.proxyOptions = self.options.proxy || {}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 43 页

```
self.maxSockets = self.options.maxSockets || http.Agent.defaultMaxSockets
self.requests = []
self.sockets = []

self.on('free', function onFree(socket, host, port) {
  for (var i = 0, len = self.requests.length; i < len; ++i) {
    var pending = self.requests[i]
    if (pending.host === host && pending.port === port) {
      // Detect the request to connect same origin server,
      // reuse the connection.
      self.requests.splice(i, 1)
      pending.request.onSocket(socket)
      return
    }
  }
  socket.destroy()
  self.removeSocket(socket)
})
}
util.inherits(TunnelingAgent, events.EventEmitter)

TunnelingAgent.prototype.addRequest = function addRequest(req, options) {
  var self = this

  // Legacy API: addRequest(req, host, port, path)
  if (typeof options === 'string') {
    options = {
      host: options,
      port: arguments[2],
      path: arguments[3]
    };
  }

  if (self.sockets.length >= this.maxSockets) {
    // We are over limit so we'll add it to the queue.
    self.requests.push({host: options.host, port: options.port, request: req})
    return
  }

  // If we are under maxSockets create a new one.
  self.createConnection({host: options.host, port: options.port, request: req})
}

TunnelingAgent.prototype.createConnection = function createConnection(pending) {
  var self = this

  self.createSocket(pending, function(socket) {
    socket.on('free', onFree)
```

```
socket.on('close', onCloseOrRemove)  
socket.on('agentRemove', onCloseOrRemove)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 44 页

```
    pending.request.onSocket(socket)

    function onFree() {
        self.emit('free', socket, pending.host, pending.port)
    }

    function onCloseOrRemove(err) {
        self.removeSocket(socket)
        socket.removeListener('free', onFree)
        socket.removeListener('close', onCloseOrRemove)
        socket.removeListener('agentRemove', onCloseOrRemove)
    }
  })
}

TunnelingAgent.prototype.createSocket = function createSocket(options, cb) {
  var self = this
  var placeholder = {}
  self.sockets.push(placeholder)

  var connectOptions = mergeOptions({}, self.proxyOptions,
    { method: 'CONNECT'
    , path: options.host + ':' + options.port
    , agent: false
    }
  )
  if (connectOptions.proxyAuth) {
    connectOptions.headers = connectOptions.headers || {}
    connectOptions.headers['Proxy-Authorization'] = 'Basic ' +
      Buffer.from(connectOptions.proxyAuth).toString('base64')
  }

  debug('making CONNECT request')
  var connectReq = self.request(connectOptions)
  connectReq.useChunkedEncodingByDefault = false // for v0.6
  connectReq.once('response', onResponse) // for v0.6
  connectReq.once('upgrade', onUpgrade)   // for v0.6
  connectReq.once('connect', onConnect)   // for v0.7 or later
  connectReq.once('error', onError)
  connectReq.end()

  function onResponse(res) {
    // Very hacky. This is necessary to avoid http-parser leaks.
    res.upgrade = true
  }

  function onUpgrade(res, socket, head) {
    // Hacky.
  }
}
```

```
process.nextTick(function() {  
  onConnect(res, socket, head)
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 45 页

```
    })
  }

function onConnect(res, socket, head) {
  connectReq.removeAllListeners()
  socket.removeAllListeners()

  if (res.statusCode === 200) {
    assert.equal(head.length, 0)
    debug('tunneling connection has established')
    self.sockets[self.sockets.indexOf(placeholder)] = socket
    cb(socket)
  } else {
    debug('tunneling socket could not be established, statusCode=%d',
res.statusCode)
    var error = new Error('tunneling socket could not be established, ' +
'statusCode=' + res.statusCode)
    error.code = 'ECONNRESET'
    options.request.emit('error', error)
    self.removeSocket(placeholder)
  }
}

function onError(cause) {
  connectReq.removeAllListeners()

  debug('tunneling socket could not be established, cause=%s\n', cause.message,
cause.stack)
  var error = new Error('tunneling socket could not be established, ' + 'cause='
+ cause.message)
  error.code = 'ECONNRESET'
  options.request.emit('error', error)
  self.removeSocket(placeholder)
}

TunnelingAgent.prototype.removeSocket = function removeSocket(socket) {
  var pos = this.sockets.indexOf(socket)
  if (pos === -1) return

  this.sockets.splice(pos, 1)

  var pending = this.requests.shift()
  if (pending) {
    // If we have pending requests and a socket gets closed a new one
    // needs to be created to take over in the pool for the one that closed.
    this.createConnection(pending)
  }
}
```

```
function createSecureSocket(options, cb) {  
  var self = this  
  TunnelingAgent.prototype.createSocket.call(self, options, function(socket) {  
    // 0 is dummy port for v0.6
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 46 页

```
var secureSocket = tls.connect(0, mergeOptions({}, self.options,
  { servername: options.host
    , socket: socket
  }
))
self.sockets[self.sockets.indexOf(socket)] = secureSocket
cb(secureSocket)
})
}

function mergeOptions(target) {
  for (var i = 1, len = arguments.length; i < len; ++i) {
    var overrides = arguments[i]
    if (typeof overrides === 'object') {
      var keys = Object.keys(overrides)
      for (var j = 0, keyLen = keys.length; j < keyLen; ++j) {
        var k = keys[j]
        if (overrides[k] !== undefined) {
          target[k] = overrides[k]
        }
      }
    }
  }
}

return target
}

var debug
if (process.env.NODE_DEBUG && /\btunnel\b/.test(process.env.NODE_DEBUG)) {
  debug = function() {
    var args = Array.prototype.slice.call(arguments)
    if (typeof args[0] === 'string') {
      args[0] = 'TUNNEL: ' + args[0]
    } else {
      args.unshift('TUNNEL:')
    }
    console.error.apply(console, args)
  }
} else {
  debug = function() {}
}
exports.debug = debug // for test

/**
 * Module exports.
 */
```

```
module.exports = deprecate;
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 47 页

```
/**
 * Mark that a method should not be used.
 * Returns a modified function which warns once by default.
 *
 * If `localStorage.noDeprecation = true` is set, then it is a no-op.
 *
 * If `localStorage.throwDeprecation = true` is set, then deprecated functions
 * will throw an Error when invoked.
 *
 * If `localStorage.traceDeprecation = true` is set, then deprecated functions
 * will invoke `console.trace()` instead of `console.error()`.
 *
 * @param {Function} fn - the function to deprecate
 * @param {String} msg - the string to print to the console when `fn` is invoked
 * @returns {Function} a new "deprecated" version of `fn`
 * @api public
 */

function deprecate (fn, msg) {
  if (config('noDeprecation')) {
    return fn;
  }

  var warned = false;
  function deprecated() {
    if (!warned) {
      if (config('throwDeprecation')) {
        throw new Error(msg);
      } else if (config('traceDeprecation')) {
        console.trace(msg);
      } else {
        console.warn(msg);
      }
      warned = true;
    }
    return fn.apply(this, arguments);
  }

  return deprecated;
}

/**
 * Checks `localStorage` for boolean values for the given `name`.
 *
 * @param {String} name
 * @returns {Boolean}
 * @api private
 */
```

```
function config (name) {
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 48 页

```
// accessing global.localStorage can trigger a DOMException in sandboxed iframes
try {
  if (!global.localStorage) return false;
} catch (_) {
  return false;
}
var val = global.localStorage[name];
if (null == val) return false;
return String(val).toLowerCase() === 'true';
}

/**
 * For Node.js, simply re-export the core `util.deprecate` function.
 */

module.exports = require('util').deprecate;
// Returns a wrapper function that returns a wrapped callback
// The wrapper function should do some stuff, and return a
// presumably different callback function.
// This makes sure that own properties are retained, so that
// decorations and such are not lost along the way.
module.exports = wrappy
function wrappy (fn, cb) {
  if (fn && cb) return wrappy(fn)(cb)

  if (typeof fn !== 'function')
    throw new TypeError('need wrapper function')

  Object.keys(fn).forEach(function (k) {
    wrapper[k] = fn[k]
  })

  return wrapper

  function wrapper() {
    var args = new Array(arguments.length)
    for (var i = 0; i < args.length; i++) {
      args[i] = arguments[i]
    }
    var ret = fn.apply(this, args)
    var cb = args[args.length-1]
    if (typeof ret === 'function' && ret !== cb) {
      Object.keys(cb).forEach(function (k) {
        ret[k] = cb[k]
      })
    }
    return ret
  }
}
```

```
}  
'use strict';
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 49 页

```
const fs = require('fs');
const path = require('path');
const { promisify } = require('util');
const { cppdb } = require('../util');
const fsAccess = promisify(fs.access);

module.exports = async function backup(filename, options) {
  if (options == null) options = {};

  // Validate arguments
  if (typeof filename !== 'string') throw new TypeError('Expected first argument to be a string');
  if (typeof options !== 'object') throw new TypeError('Expected second argument to be an options object');

  // Interpret options
  filename = filename.trim();
  const attachedName = 'attached' in options ? options.attached : 'main';
  const handler = 'progress' in options ? options.progress : null;

  // Validate interpreted options
  if (!filename) throw new TypeError('Backup filename cannot be an empty string');
  if (filename === ':memory:') throw new TypeError('Invalid backup filename ":memory:"');
  if (typeof attachedName !== 'string') throw new TypeError('Expected the "attached" option to be a string');
  if (!attachedName) throw new TypeError('The "attached" option cannot be an empty string');
  if (handler != null && typeof handler !== 'function') throw new TypeError('Expected the "progress" option to be a function');

  // Make sure the specified directory exists
  await fsAccess(path.dirname(filename)).catch(() => {
    throw new TypeError('Cannot save backup because the directory does not exist');
  });

  const isNewFile = await fsAccess(filename).then(() => false, () => true);
  return runBackup(this[cppdb].backup(this, attachedName, filename, isNewFile), handler || null);
};

const runBackup = (backup, handler) => {
  let rate = 0;
  let useDefault = true;

  return new Promise((resolve, reject) => {
    setImmediate(function step() {
      try {
```

```
const progress = backup.transfer(rate);
if (!progress.remainingPages) {
  backup.close();
  resolve(progress);
  return;
}
if (useDefault) {
  useDefault = false;
  rate = 100;
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 50 页

```

    }
    if (handler) {
      const ret = handler(progress);
      if (ret !== undefined) {
        if (typeof ret === 'number' && ret === ret) rate =
Math.max(0, Math.min(0x7fffffff, Math.round(ret)));
        else throw new TypeError('Expected progress callback to
return a number or undefined');
      }
    }
    setImmediate(step);
  } catch (err) {
    backup.close();
    reject(err);
  }
});
});
};

<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <link rel="icon" type="image/png" href="/favicon.png">
  <title>eqrcp</title>
  <style>
    :root {
      color-scheme: light;
      font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-
serif;
    }

    * {
      box-sizing: border-box;
    }

    body {
      margin: 0;
      min-height: 100vh;
      background: #f4f7f6;
      color: #15221f;
    }

    main {
      width: min(100%, 720px);
      margin: 0 auto;
      padding: 28px 18px 40px;
    }

```

```
.status {  
  display: inline-flex;  
  align-items: center;
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 51 页

```
        gap: 10px;
        margin-bottom: 18px;
        color: #0f6b55;
        font-size: 15px;
        font-weight: 700;
    }
    .brand-logo {
        display: block;
        height: 56px;
        margin-bottom: 14px;
        width: 56px;
    }

    .status-mark {
        display: inline-grid;
        place-items: center;
        width: 30px;
        height: 30px;
        border-radius: 8px;
        background: #0f8a68;
        color: #fff;
        font-size: 20px;
        line-height: 1;
    }

    h1 {
        margin: 0 0 10px;
        font-size: 32px;
        line-height: 1.15;
        letter-spacing: 0;
    }

    .summary {
        margin: 0 0 26px;
        color: #465653;
        font-size: 17px;
        line-height: 1.5;
    }

    .section-title {
        margin: 0 0 12px;
        color: #263532;
        font-size: 15px;
        font-weight: 700;
    }

    .file-list {
        display: grid;
```

```
gap: 10px;  
margin: 0 0 24px;
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 52 页

```

        padding: 0;
        list-style: none;
    }

    .file-list li,
    .file-fallback {
        overflow-wrap: anywhere;
        border: 1px solid #d8e2df;
        border-radius: 8px;
        background: #fff;
        padding: 13px 14px;
        color: #15221f;
        font-size: 15px;
        line-height: 1.45;
        box-shadow: 0 1px 2px rgba(21, 34, 31, 0.05);
    }

    .file-fallback {
        margin: 0 0 24px;
    }

    .hint {
        margin: 0;
        color: #647470;
        font-size: 15px;
        line-height: 1.5;
    }

    @media (max-width: 420px) {
        main {
            padding: 24px 14px 34px;
        }

        h1 {
            font-size: 28px;
        }
    }
</style>
</head>
<body>
    <main>
        
        <div class="status"><span class="status-mark">OK</span> Transfer
complete</div>
        <h1>Upload complete</h1>
        {{if eq .Count 1}}
        <p class="summary">1 file was sent to this device.</p>
        {{else}}
        <p class="summary">{{.Count}} files were sent to this device.</p>

```

{{end}}

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 53 页

```

    {{if .Files}}
    <p class="section-title">Saved files</p>
    <ul class="file-list">
        {{range .Files}}<li>{{.}}</li>{{end}}
    </ul>
    {{else if .File}}
    <p class="section-title">Saved file</p>
    <p class="file-fallback">{{.File}}</p>
    {{end}}

    <p class="hint">You can close this page now.</p>
</main>
</body>
</html>
'use strict';
const { getBooleanOption, cppdb } = require('../util');

module.exports = function defineAggregate(name, options) {
    // Validate arguments
    if (typeof name !== 'string') throw new TypeError('Expected first argument to
be a string');
    if (typeof options !== 'object' || options === null) throw new
TypeError('Expected second argument to be an options object');
    if (!name) throw new TypeError('User-defined function name cannot be an empty
string');

    // Interpret options
    const start = 'start' in options ? options.start : null;
    const step = getFunctionOption(options, 'step', true);
    const inverse = getFunctionOption(options, 'inverse', false);
    const result = getFunctionOption(options, 'result', false);
    const safeIntegers = 'safeIntegers' in options ? +getBooleanOption(options,
'safeIntegers') : 2;
    const deterministic = getBooleanOption(options, 'deterministic');
    const directOnly = getBooleanOption(options, 'directOnly');
    const varargs = getBooleanOption(options, 'varargs');
    let argCount = -1;

    // Determine argument count
    if (!varargs) {
        argCount = Math.max(getLength(step), inverse ? getLength(inverse) : 0);
        if (argCount > 0) argCount -= 1;
        if (argCount > 100) throw new RangeError('User-defined functions cannot
have more than 100 arguments');
    }

    this[cppdb].aggregate(start, step, inverse, result, name, argCount,
safeIntegers, deterministic, directOnly);
    return this;
};

```

```
const getFunctionOption = (options, key, required) => {  
  const value = key in options ? options[key] : null;  
  if (typeof value === 'function') return value;  
  if (value !== null) throw new TypeError(`Expected the "${key}" option to be a  
function`);  
  if (required) throw new TypeError(`Missing required option "${key}"`);  
}
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 54 页

```
    return null;
  };

  const getLength = ({ length }) => {
    if (Number.isInteger(length) && length >= 0) return length;
    throw new TypeError('Expected function.length to be a positive integer');
  };
  'use strict';
  module.exports = require('./database');
  module.exports.SqliteError = require('./sqlite-error');
  'use strict';
  const fs = require('fs');
  const path = require('path');
  const util = require('./util');
  const SqliteError = require('./sqlite-error');

  let DEFAULT_ADDON;

  function Database(filenameGiven, options) {
    if (new.target == null) {
      return new Database(filenameGiven, options);
    }

    // Apply defaults
    let buffer;
    if (Buffer.isBuffer(filenameGiven)) {
      buffer = filenameGiven;
      filenameGiven = ':memory:';
    }
    if (filenameGiven == null) filenameGiven = '';
    if (options == null) options = {};

    // Validate arguments
    if (typeof filenameGiven !== 'string') throw new TypeError('Expected first argument to be a string');
    if (typeof options !== 'object') throw new TypeError('Expected second argument to be an options object');
    if ('readOnly' in options) throw new TypeError('Misspelled option "readOnly" should be "readonly"');
    if ('memory' in options) throw new TypeError('Option "memory" was removed in v7.0.0 (use ":memory:" filename instead)');

    // Interpret options
    const filename = filenameGiven.trim();
    const anonymous = filename === '' || filename === ':memory:';
    const readonly = util.getBooleanOption(options, 'readonly');
    const fileMustExist = util.getBooleanOption(options, 'fileMustExist');
    const timeout = 'timeout' in options ? options.timeout : 5000;
    const verbose = 'verbose' in options ? options.verbose : null;
    const nativeBinding = 'nativeBinding' in options ? options.nativeBinding :
```

```
    null;

    // Validate interpreted options
    if (readonly && anonymous && !buffer) throw new TypeError('In-memory/temporary
databases cannot be readonly');
    if (!Number.isInteger(timeout) || timeout < 0) throw new TypeError('Expected
the "timeout" option to be a positive integer');
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 55 页

```

    if (timeout > 0x7fffffff) throw new RangeError('Option "timeout" cannot be
greater than 2147483647');
    if (verbose != null && typeof verbose !== 'function') throw new
TypeError('Expected the "verbose" option to be a function');
    if (nativeBinding != null && typeof nativeBinding !== 'string' && typeof
nativeBinding !== 'object') throw new TypeError('Expected the "nativeBinding"
option to be a string or addon object');

    // Load the native addon
    let addon;
    if (nativeBinding == null) {
        addon = DEFAULT_ADDON || (DEFAULT_ADDON = require('bindings')
('better_sqlite3.node'));
    } else if (typeof nativeBinding === 'string') {
        // See <https://webpack.js.org/api/module-
variables/#__non_webpack_require__-webpack-specific>
        const requireFunc = typeof __non_webpack_require__ === 'function' ?
__non_webpack_require__ : require;
        addon = requireFunc(path.resolve(nativeBinding).replace(/(\.node)?$/,
'.node'));
    } else {
        // See <https://github.com/WiseLibs/better-sqlite3/issues/972>
        addon = nativeBinding;
    }

    if (!addon.isInitialized) {
        addon.setErrorConstructor(SqliteError);
        addon.isInitialized = true;
    }

    // Make sure the specified directory exists
    if (!anonymous && !filename.startsWith('file:') &&
!fs.existsSync(path.dirname(filename))) {
        throw new TypeError('Cannot open database because the directory does not
exist');
    }

    Object.defineProperties(this, {
        [util.cppdb]: { value: new addon.Database(filename, filenameGiven,
anonymous, readonly, fileMustExist, timeout, verbose || null, buffer || null) },
        ...wrappers.getters,
    });
}

const wrappers = require('./methods/wrappers');
Database.prototype.prepare = wrappers.prepare;
Database.prototype.transaction = require('./methods/transaction');
Database.prototype.pragma = require('./methods/pragma');
Database.prototype.backup = require('./methods/backup');
Database.prototype.serialize = require('./methods/serialize');

```

```
Database.prototype.function = require('./methods/function');
Database.prototype.aggregate = require('./methods/aggregate');
Database.prototype.table = require('./methods/table');
Database.prototype.loadExtension = wrappers.loadExtension;
Database.prototype.exec = wrappers.exec;
Database.prototype.close = wrappers.close;
Database.prototype.defaultSafeIntegers = wrappers.defaultSafeIntegers;
Database.prototype.unsafeMode = wrappers.unsafeMode;
Database.prototype[util.inspect] = require('./methods/inspect');

module.exports = Database;
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 56 页

```
'use strict';
const path = require('path');
const fs = require('fs');

const dest = process.argv[2];
const source = path.resolve(path.sep, process.argv[3] || path.join(__dirname,
'sqlite3'));
const files = [
  { filename: 'sqlite3.c', optional: false },
  { filename: 'sqlite3.h', optional: false },
];

if (process.argv[3]) {
  // Support "_HAVE_SQLITE_CONFIG_H" in custom builds.
  files.push({ filename: 'config.h', optional: true });
} else {
  // Required for some tests.
  files.push({ filename: 'sqlite3ext.h', optional: false });
}

for (const { filename, optional } of files) {
  const sourceFilepath = path.join(source, filename);
  const destFilepath = path.join(dest, filename);

  if (optional && !fs.existsSync(sourceFilepath)) {
    continue;
  }

  fs.accessSync(sourceFilepath);
  fs.mkdirSync(path.dirname(destFilepath), { recursive: true });
  fs.copyFileSync(sourceFilepath, destFilepath);
}
'use strict'

exports.byteLength = byteLength
exports.toByteArray = toByteArray
exports.fromByteArray = fromByteArray

var lookup = []
var revLookup = []
var Arr = typeof Uint8Array !== 'undefined' ? Uint8Array : Array

var code = 'ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789+/'
for (var i = 0, len = code.length; i < len; ++i) {
  lookup[i] = code[i]
  revLookup[code.charCodeAt(i)] = i
}

// Support decoding URL-safe base64 strings, as Node.js does.
```

```
// See: https://en.wikipedia.org/wiki/Base64#URL\_applications  
revLookup['-'.charAt(0)] = 62
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 57 页

```
revLookup['_'].charCodeAt(0)] = 63

function getLens (b64) {
  var len = b64.length

  if (len % 4 > 0) {
    throw new Error('Invalid string. Length must be a multiple of 4')
  }

  // Trim off extra bytes after placeholder bytes are found
  // See: https://github.com/beatgammit/base64-js/issues/42
  var validLen = b64.indexOf('=')
  if (validLen === -1) validLen = len

  var placeholdersLen = validLen === len
    ? 0
    : 4 - (validLen % 4)

  return [validLen, placeholdersLen]
}

// base64 is 4/3 + up to two characters of the original data
function byteLength (b64) {
  var lens = getLens(b64)
  var validLen = lens[0]
  var placeholdersLen = lens[1]
  return ((validLen + placeholdersLen) * 3 / 4) - placeholdersLen
}

function _byteLength (b64, validLen, placeholdersLen) {
  return ((validLen + placeholdersLen) * 3 / 4) - placeholdersLen
}

function toByteArray (b64) {
  var tmp
  var lens = getLens(b64)
  var validLen = lens[0]
  var placeholdersLen = lens[1]

  var arr = new Arr(_byteLength(b64, validLen, placeholdersLen))

  var curByte = 0

  // if there are placeholders, only get up to the last complete 4 chars
  var len = placeholdersLen > 0
    ? validLen - 4
    : validLen
```

```
var i
for (i = 0; i < len; i += 4) {
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 58 页

```
    tmp =
      (revLookup[b64.charCodeAt(i)] << 18) |
      (revLookup[b64.charCodeAt(i + 1)] << 12) |
      (revLookup[b64.charCodeAt(i + 2)] << 6) |
      revLookup[b64.charCodeAt(i + 3)]
    arr[curByte++] = (tmp >> 16) & 0xFF
    arr[curByte++] = (tmp >> 8) & 0xFF
    arr[curByte++] = tmp & 0xFF
  }

  if (placeholdersLen === 2) {
    tmp =
      (revLookup[b64.charCodeAt(i)] << 2) |
      (revLookup[b64.charCodeAt(i + 1)] >> 4)
    arr[curByte++] = tmp & 0xFF
  }

  if (placeholdersLen === 1) {
    tmp =
      (revLookup[b64.charCodeAt(i)] << 10) |
      (revLookup[b64.charCodeAt(i + 1)] << 4) |
      (revLookup[b64.charCodeAt(i + 2)] >> 2)
    arr[curByte++] = (tmp >> 8) & 0xFF
    arr[curByte++] = tmp & 0xFF
  }

  return arr
}

function tripletToBase64 (num) {
  return lookup[num >> 18 & 0x3F] +
    lookup[num >> 12 & 0x3F] +
    lookup[num >> 6 & 0x3F] +
    lookup[num & 0x3F]
}

function encodeChunk (uint8, start, end) {
  var tmp
  var output = []
  for (var i = start; i < end; i += 3) {
    tmp =
      ((uint8[i] << 16) & 0xFF0000) +
      ((uint8[i + 1] << 8) & 0xFF00) +
      (uint8[i + 2] & 0xFF)
    output.push(tripletToBase64(tmp))
  }
  return output.join('')
}
```

```
function fromByteArray (uint8) {
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 59 页

```

var tmp
var len = uint8.length
var extraBytes = len % 3 // if we have 1 byte left, pad 2 bytes
var parts = []
var maxChunkLength = 16383 // must be multiple of 3

// go through the array every three bytes, we'll deal with trailing stuff later
for (var i = 0, len2 = len - extraBytes; i < len2; i += maxChunkLength) {
  parts.push(encodeChunk(uint8, i, (i + maxChunkLength) > len2 ? len2 : (i +
maxChunkLength)))
}

// pad the end with zeros, but make sure to not forget the extra bytes
if (extraBytes === 1) {
  tmp = uint8[len - 1]
  parts.push(
    lookup[tmp >> 2] +
    lookup[(tmp << 4) & 0x3F] +
    '=='
  )
} else if (extraBytes === 2) {
  tmp = (uint8[len - 2] << 8) + uint8[len - 1]
  parts.push(
    lookup[tmp >> 10] +
    lookup[(tmp >> 4) & 0x3F] +
    lookup[(tmp << 2) & 0x3F] +
    '='
  )
}

return parts.join('')
}

(function(a){if("object"==typeof exports&&"undefined"!=typeof
module)module.exports=a();else if("function"==typeof
define&&define.amd)define([],a);else{var b;b="undefined"==typeof
window?"undefined"==typeof global?"undefined"==typeof self?
this:self:global>window,b.base64js=a()}})(function(){return function(){function
b(d,e,g){function a(j,i){if(!e[j]){if(!d[j]){var f="function"==typeof
require&&require;if(!i&&f)return f(j,!0);if(h)return h(j,!0);var c=new
Error("Cannot find module '"+j+"'");throw c.code="MODULE_NOT_FOUND",c}var k=e[j]=
{exports:{}};d[j][0].call(k.exports,function(b){var c=d[j][1][b];return
a(c||b)},k,k.exports,b,d,e,g)}return e[j].exports}for(var h="function"==typeof
require&&require,c=0;c<g.length;c++)a(g[c]);return a}return b}()({"/" :
[function(a,b,c){'use strict';function d(a){var b=a.length;if(0<b%4)throw new
Error("Invalid string. Length must be a multiple of 4");var
c=a.indexOf("=");-1===c&&(c=b);var d=c===b?0:4-c%4;return[c,d]}function e(a,b,c)
{return 3*(b+c)/4-c}function f(a){var b,c,f=d(a),g=f[0],h=f[1],j=new
m(e(a,g,h)),k=0,n=0<h?g-4:g;for(c=0;c<n;c+=4)b=l[a.charCodeAt(c)]
<<18|l[a.charCodeAt(c+1)]<<12|l[a.charCodeAt(c+2)]
<<6|l[a.charCodeAt(c+3)],j[k++]=255&b>>16,j[k++]=255&b>>8,j[k++]=255&b;return

```

```

2==h&&(b=l[a.charCodeAt(c)]<<2|l[a.charCodeAt(c+1)]>>4,j[k++]=255&b),1==h&&
(b=l[a.charCodeAt(c)]<<10|l[a.charCodeAt(c+1)]
<<4|l[a.charCodeAt(c+2)]>>2,j[k++]=255&b>>8,j[k++]=255&b),j}function g(a){return
k[63&a>>18]+k[63&a>>12]+k[63&a>>6]+k[63&a]}function h(a,b,c){for(var d,e=
[],f=b;f<c;f+=3)d=(16711680&a[f]<<16)+(65280&a[f+1]<<8)+
(255&a[f+2]),e.push(g(d));return e.join("")}function j(a){for(var
b,c=a.length,d=c%3,e=[],f=16383,g=0,j=c-d;g<j;g+=f)e.push(h(a,g,g+f>j?
j:g+f));return 1===d?(b=a[c-1],e.push(k[b>>2]+k[63&b<<4]+"==")):2===d&&(b=(a[c-2]
<<8)+a[c-
1],e.push(k[b>>10]+k[63&b>>4]+k[63&b<<2]+"=")),e.join(""))c.byteLength=function(a)
{var b=d(a),c=b[0],e=b[1];return 3*(c+e)/4-
e},c.toByteArray=f,c.fromByteArray=j;for(var k=[],l=[],m="undefined"==typeof
Uint8Array?
Array:Uint8Array,n="ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789
+/",o=0,p=n.length;o<p;++o)k[o]=n[o],l[n.charCodeAt(o)]=o;l[45]=62,l[95]=63},{}}},
{}),[])(("/")});
//go:build windows

```

```
package main
```

```
import (
    "os/exec"
    "syscall"
)
```

```
func configureHiddenCommand(cmd *exec.Cmd) {
    cmd.SysProcAttr = &syscall.SysProcAttr{HideWindow: true}
}
//go:build !windows

```

```
package main
```

```
import "os/exec"
```

EQT Easy QR Transfer 局域网文件传输系统 V1.0.0 | 第 60 页

```

func configureHiddenCommand(cmd *exec.Cmd) {}
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8"/>
    <meta content="width=device-width, initial-scale=1.0" name="viewport"/>
    <title>eqrcp-desktop</title>
</head>
<body>
<div id="app"></div>
<script src="./src/main.js" type="module"></script>
</body>
</html>
//go:build windows

package cmd

import (
    "os"

    toast "git.sr.ht/~jackmordaunt/go-toast/v2"
)

const eqtToastAppID = "EQT Easy QR Transfer"

func notifyDesktopWindows(title string, message string) error {
    exe, _ := os.Executable()
    _ = toast.SetAppData(toast.AppData{
        AppID:      eqtToastAppID,
        GUID:       "{7F4E6F7D-4E10-49A1-A80D-93F1B9B89B7C}",
        ActivationExe: exe,
    })
    notification := toast.Notification{
        AppID:      eqtToastAppID,
        Title:      title,
        Body:       message,
        Duration:   toast.Short,
    }
    if err := notification.Push(); err == nil {
        return nil
    }
    return notifyDesktopWindowsBalloon(title, message)
}
//go:build !windows

package cmd

func notifyDesktopWindows(title string, message string) error {

```

```
    return nil  
}
```