

Backup and Restore Configuration

Document field	Value
Document owner	FortVault
Intended audience	FortVault's ISO 27001 implementation partner
Classification	Confidential
Evidence basis	Management-provided current-state description
Verification status	Not independently verified; restore test not performed
Version	0.1
Date	August 28, 2026

1. Current Backup Configuration

Data set	Method	Schedule	Retention / location
AWS application PostgreSQL databases	Native Amazon RDS automated backup	Daily	7 days in AWS region us-east-1
AWS MPC node 1 PostgreSQL database	Native Amazon RDS automated backup	Daily	7 days in AWS region us-east-1
GCP MPC node 2 PostgreSQL database	Native Cloud SQL automated backup	Daily	7 days in a United States multi-region location, as reported
Backend, Custody Processing, and Listener databases	Additional scheduled export from an AWS virtual machine	Daily	Password-protected archive uploaded to customer-controlled Azure storage

The supplied note also referred to a Frontend database. The Frontend is not expected to own durable business data, so FortVault should confirm whether this means the server hosting the backup script rather than a separate Frontend database. Exchange Processing is not listed in the supplied backup scope and must be added if that service is deployed with durable state.

2. Backup Administration

The current administrator role can create, modify, delete, restore, and otherwise manage backups. This is operationally convenient but creates a concentration-of-privilege risk. A compromised or mistaken administrator could alter or remove both production data and its recoverable copies.

Recommended improvement: separate backup policy administration, backup deletion, and restore execution; require MFA and approval for destructive changes; restrict routine service identities; and review privileged access periodically.

3. Backup Protection Status

Control	Current status
Daily managed database backups	Reported as enabled
Seven-day retention	Reported as enabled
Additional customer-controlled copy	Reported for Backend, Processing, and Listener exports
Cross-region copy	Not enabled
Cross-account protection	Not enabled
Immutable or vault-lock protection	Not enabled
Deletion protection for backups	Not enabled
Approved recovery point objective (RPO)	Not defined
Approved recovery time objective (RTO)	Not defined
Recorded successful restore test	Not available

4. Encryption and Transfer Evidence

The additional archive is described as password protected, but the supplied information does not identify the archive encryption algorithm, password storage and rotation process, transfer protocol, Azure storage encryption, retention policy, or access controls. Password protection alone is not sufficient evidence of an approved encryption-at-rest control.

Required evidence:

- RDS and Cloud SQL backup encryption settings and key ownership;
- encryption settings for the customer-controlled Azure storage;
- archive encryption algorithm and approved key/password handling process;
- secure transfer mechanism and service identity used for upload;
- backup-script source revision, execution logs, failure alerting, and ownership; and
- assurance that credentials and backup passwords are never written to source control or logs.

5. Recovery Objectives and Restore Testing

RPO and RTO have not been defined, and no successful restore-test result has been supplied. Therefore, daily execution and seven-day retention cannot yet demonstrate that FortVault can recover within an approved business timeframe.

Priority remediation:

- complete a business-impact review and approve RPO/RTO for each data owner;
- perform a controlled restore into an isolated non-production environment;
- verify integrity, application compatibility, access controls, and reconciliation;
- record start/end times, recovered backup age, result, exceptions, and corrective actions; and
- repeat restore testing on an approved schedule and after material backup changes.

6. Resilience and Immutability

Recommended improvement: protect at least one backup copy using an isolated account or customer-controlled boundary, immutable retention or vault lock, restricted deletion privileges, and a separate encryption key. Review whether cross-region recovery is required by the approved availability and data-residency objectives.

The customer-controlled Azure copy can contribute to separation, but its current access, immutability, retention, and restore behavior have not been evidenced.

7. MPC Recovery Boundary

Database backups are not a substitute for MPC cryptographic recovery. MPC shares and recovery material require a separate controlled process, secure storage boundary, authorization procedure, and tested recovery plan. No MPC share or recovery material should be placed in this evidence package.

8. Evidence to Attach

- Sanitized RDS and Cloud SQL backup-policy exports showing schedule, retention, encryption, and status.
- Sanitized Azure storage policy showing encryption, access, retention, and immutability settings.
- Backup job success/failure evidence with identifiers and customer data removed.
- Approved RPO/RTO register.
- Latest restore-test record and corrective actions.
- Privileged backup-role inventory and access-review evidence.
- Backup and restore operating procedure with named control owners.

9. Conclusion

FortVault currently has daily managed database backups and an additional off-cloud export for selected application databases. The backup control is only partially evidenced and is not yet operationally validated because recovery objectives, immutable protection, least-privilege administration, and restore testing are missing.