```
\ 6809 assembler: utilities
                               (c) 14 11 85 BJR
VOCABULARY ASSEMBLER IMMEDIATE ASSEMBLER DEFINITIONS HEX
: WITHIN ROT SWAP OVER \ n lo hi -- f | test within limits
 < ROT ROT > OR 0= ;
: 8BIT? -80 7F WITHIN;
: 5BIT? -10 OF WITHIN ;
: (,) ,;
\ : ALIGN ; ( for byte-addressing hosts)
\ Buffoonery to allow byte-oriented assembly on word machines.
\ Assembler does ALIGNing, thus always knows when to de-ALIGN!
\ Include if host is word-aligned.
0 VARIABLE ALIGNED \ flag indicating HERE was adjusted
: ALIGN HERE 1 AND DUP ALLOT ALIGNED ! ; \ align HERE
: DEALIGN ALIGNED @ MINUS ALLOT 0 ALIGNED ! ; \setminus cancel ALIGN
\ -----
  6809 assembler: addressing modes (c) 03 06 85 BJR
: W, DUP >< C, C, ;
                      \ store word as hibyte, lobyte
: OPCODE,
                      \ store opcode with prefix (if any)
  DUP FF00 AND IF W, ELSE C, THEN ;
30 VARIABLE MODE \ 0=immed,10=direct,20=indexed,30=extended
: # 0 MODE ! ;
: <> 10 MODE ! ;
: INDEXREG 20 MODE ! \ rval postbyte -- postbyte |
  SWAP 1- DUP 0 3 WITHIN 0= 3 ?ERROR \ must be x,y,u, or s
  20 * OR ;
                               \ put reg # in postbyte
: XMODE \ <BUILDS (,) \ \ postbyte -- \ | Simple Indexed Modes
  DOES> @ INDEXREG ; \ rval -- postbyte
                                  8B XMODE D,
84 XMODE 0, 86 XMODE A, 85 XMODE B,
80 XMODE ,+
          81 XMODE ,++ 82 XMODE -, 83 XMODE --,
\ -----
 6809 assembler: addressing modes (c) 04 06 85 BJR
      SWAP 89 INDEXREG ; \ rval n -- n postbyte |
: ,PCR 20 MODE ! 8D ; \ n -- n postbyte |
IF DUP 9D AND 80 = 3 ?ERROR 10 + \ Indexed Indirect
ELSE 20 MODE ! 9F THEN; \ Extended Indirect
: RESET 30 MODE ! ;
\ register definitions
0 CONSTANT D 1 CONSTANT X 2 CONSTANT Y 3 CONSTANT U 4 CONSTANT S 5 CONSTANT PC 8 CONSTANT A 9 CONSTANT B
OA CONSTANT CCR OB CONSTANT DPR
Y CONSTANT IP U CONSTANT SP S CONSTANT RP X CONSTANT W
\ -----
\ 6809 assembler: inherent instruction(c) 03 06 85 BJR
```

```
: INHOP <BUILDS (,) \ opcode -- | Inherent Addressing
  DOES> @ OPCODE, RESET; \ -- | lay one or two bytes
3A INHOP ABX, 48 INHOP ASLA, 58 INHOP ASLB, 47 INHOP ASRA,
57 INHOP ASRB, 4F INHOP CLRA, 5F INHOP CLRB, 43 INHOP COMA,
53 INHOP COMB, 19 INHOP DAA, 4A INHOP DECA, 5A INHOP DECB,
4C INHOP INCA, 5C INHOP INCB, 48 INHOP LSLA, 58 INHOP LSLB,
44 INHOP LSRA, 54 INHOP LSRB, 3D INHOP MUL, 40 INHOP NEGA,
50 INHOP NEGB, 12 INHOP NOP, 49 INHOP ROLA, 59 INHOP ROLB, 46 INHOP RORA, 56 INHOP RORB, 3B INHOP RTI, 39 INHOP RTS,
1D INHOP SEX, 3F INHOP SWI, 103F INHOP SWI2, 113F INHOP SWI3,
13 INHOP SYNC, 4D INHOP TSTA, 5D INHOP TSTB,
  6809 assembler: immediate instructio(c) 03 06 85 BJR
: IMMOP <BUILDS (,) \ opcode -- | Immediate Only (8-bit)
  DOES> MODE @ 3 ?ERROR @ C, C, RESET; \ operand --
3C IMMOP CWAI, 34 IMMOP PSHS, 36 IMMOP PSHU, 35 IMMOP PULS, 37 IMMOP PULU, 1C IMMOP ANDCC, 1A IMMOP ORCC,
: RROP <BUILDS (,) \ opcode -- | Register-Register
   DOES> @ C, SWAP 10 * + C, RESET; \ srcrval dstrval --
1E RROP EXG, 1F RROP TFR,
  6809 assembler: +mode
                                         (c) 03 06 85 BJR
: +MODE \ operand -- operand | modify operand per mode
  MODE @ + DUP 0F0 AND 50 = IF 0F AND THEN; \setminus chng 5x to 0x
  6809 assembler: pcrel, cofset (c) 29 03 85 BJR
: PCREL \ operand postbyte -- | lay PC relative
  SWAP HERE 2+ - DUP 8BIT? \ try 8 bit relative offset
IF SWAP OFE AND C, C, \ it fits...lay postbyte,offset
ELSE 1- SWAP C, W, THEN; \ no good...use 16 bit relative
: NOTINDIR? 10 AND 0=; \ postbyte -- f | test for indirect
: COFSET \ operand postbyte -- | lay constant offset
   OVER 0= IF 0F0 AND 4 OR C, DROP \ no offset
   ELSE OVER 5BIT? OVER NOTINDIR? AND IF
  60 AND SWAP 1F AND OR C, \ 5 bit offset ELSE OVER 8BIT? IF 0FE AND C, C, \ 8 bit offset ELSE C, W, THEN THEN THEN; \ 16 bit offset
\ -----
  6809 assembler: indexed, immed (c) 03 06 85 BJR
: EXTIND \ operand postbyte -- | lay extended indirect
                \ lay postbyte and operand
: INDEXED \ operand? postbyte -- | lay indexed poststuff
   DUP 8F AND CASE \ check postbyte for modes w/ operands
      89 OF COFSET ENDOF \ const.offset
      8D OF PCREL ENDOF \ PC relative
8F OF EXTIND ENDOF \ extended indir
            SWAP C, ENDCASE; \ simple modes, postbyte only
: IMMED \ operand opcode-pfa -- | lay immediate poststuff
```

```
2+ @ DUP 0= 3 ?ERROR \ test immedsize
    1- IF W, ELSE C, THEN ; \ lay immed. operand in reqd.size
  ______
   6809 assembler: general addr instr (c) 03 06 85 BJR
: GENOP <BUILDS (,) (,) \ immedsize opcode -- | Gen'l Addr
    DOES> DUP @ +MODE OPCODE, \ [see below] | lay opcode MODE @ CASE 0 OF IMMED ENDOF \ immediate 10 OF DROP C, ENDOF \ direct
                       20 OF DROP INDEXED ENDOF \ indexed
                       30 OF DROP W, ENDOF \ extended
        ENDCASE RESET ;
: INXOP <BUILDS (,) \ opcode -- | Indexed Only
    DOES> MODE @ 20 - 3 ?ERROR @ OPCODE, INDEXED RESET;
\ Stack action of general addressing instructions
\ (1) immediate, direct, extended:
                                                                   operand --
\ (2) all indexed except (3):
                                                                  postbyte --
\ (3) const.offset, PCR, extended indir: operand postbyte --
\ -----
    6809 assembler: general addr instr (c) 29 03 85 BJR
1 89 GENOP ADCA, 1 C9 GENOP ADCB, 1 88 GENOP ADDA,
1 CB GENOP ADDB, 2 C3 GENOP ADDD, 1 84 GENOP ANDA,
1 C4 GENOP ANDB, 1 85 GENOP BITA, 1 C5 GENOP BITB,
0 48 GENOP ASL, 0 47 GENOP ASR, 0 4F GENOP CLR,
1 81 GENOP CMPA, 1 C1 GENOP CMPB, 2 1083 GENOP CMPD,
2 118C GENOP CMPS, 2 1183 GENOP CMPU, 2 8C GENOP CMPX,
2 108C GENOP CMPY, 1 88 GENOP EORA, 1 C8 GENOP EORB,
0 43 GENOP COM, 0 4A GENOP DEC, 0 4C GENOP INC,
1 86 GENOP LDA, 1 C6 GENOP LDB, 2 CC GENOP LDD,
2 10CE GENOP LDS, 2 CE GENOP LDU, 2 8E GENOP LDX,
2 108E GENOP LDY, 0 4E GENOP JMP, 0 8D GENOP JSR,
0 48 GENOP LSL, 0 44 GENOP LSR, 0 40 GENOP NEG,
1 8A GENOP ORA, 1 CA GENOP ORB, 0 49 GENOP ROL,
\ -----
   6809 assembler: general addr instr (c) 29 03 85 BJR
\
0 46 GENOP ROR, 1 82 GENOP SBCA, 1 C2 GENOP SBCB,
0 87 GENOP STA, 0 C7 GENOP STB, 0 CD GENOP STD, 0 10CF GENOP STS, 0 CF GENOP STU, 0 8F GENOP STX, 0 108F GENOP STY, 1 80 GENOP SUBA, 1 C0 GENOP SUBB, 2 83 GENOP SUBD, 0 4D GENOP TST,
32 INXOP LEAS, 33 INXOP LEAU, 30 INXOP LEAX, 31 INXOP LEAY,
\ -----
\ 6809 assembler: branches
                                         (c) 03 06 85 BJR
CONDBR <BUILDS (,) \ opcode -- | Conditional Branch
    DOES> @ SWAP HERE 2+ - \ addr -- DUP 8BIT? IF SWAP C, C,
                                                             \ 8 bit
    ELSE 10 C, SWAP C, 2- W, THEN RESET;
: UNCBR <BUILDS (,) \ short:long -- | Uncondit'l Bran
    DOES> @ SWAP HERE 2+ - \ addr --
DUP 8BIT? IF SWAP >< C, C, \ 8 bit: use short opcod
    ELSE SWAP C, 1- W, THEN RESET; \ 16 bit: use long opcod
```

```
6809 assembler: branch instructions (c) 29 03 85 BJR
24 CONDBR BCC, 25 CONDBR BCS, 27 CONDBR BEQ, 2C CONDBR BGE,
2E CONDBR BGT, 22 CONDBR BHI, 24 CONDBR BHS, 2F CONDBR BLE,
25 CONDBR BLO, 23 CONDBR BLS, 2D CONDBR BLT, 2B CONDBR BMI,
26 CONDBR BNE, 2A CONDBR BPL, 21 CONDBR BRN, 28 CONDBR BVC,
29 CONDBR BVS, 2016 UNCBR BRA, 8D17 UNCBR BSR,
6809 assembler: conditions
                                 (c) 03 06 85 BJR
24 CONSTANT CS 25 CONSTANT CC 27 CONSTANT NE 2C CONSTANT LT
2E CONSTANT LE 22 CONSTANT LS 24 CONSTANT LO 2F CONSTANT GT
25 CONSTANT HS 23 CONSTANT HI 2D CONSTANT GE 2B CONSTANT PL
26 CONSTANT EQ 2A CONSTANT MI 21 CONSTANT ALW 28 CONSTANT VS
29 CONSTANT VC 20 CONSTANT NVR
  6809 assembler: structured cond'ls (c) 03 06 85 BJR
: IF, \ br.opcode -- adr.next.instr 2 | reserve space
  C, 0 C, HERE 2;
: ENDIF, \ adr.instr.after.br 2 -- | patch the forward ref.
  2 ?PAIRS HERE OVER - DUP 8BIT? 0= 3 ?ERROR SWAP 1- C!;
: ELSE, \ adr.after.br 2 -- adr.after.this.br 2
  2 ?PAIRS NVR C, 0 C, HERE SWAP 2 ENDIF, 2;
: BEGIN, \ -- dest.adr 1 HERE 1;
: UNTIL, \ dest.adr 1 br.opcode --
  SWAP 1 ?PAIRS C, HERE 1+ - DUP 8BIT? 0= 3 ?ERROR C, ;
: WHILE, \ dest.adr 1 br.opcod -- adr.after.this 2 dest.adr 1
  IF, 2SWAP;
: REPEAT, \ adr.after.while 2 dest.adr.of.begin 1 --
  NVR UNTIL, ENDIF, ;
: THEN, ENDIF, ;
: END, UNTIL, ;
\ -----
  6809 assembler: code, ;code, ;c (c) 14 11 85 BJR
\
FORTH DEFINITIONS ASSEMBLER
: ENTERCODE [COMPILE] ASSEMBLER ASSEMBLER ALIGN !CSP ;
: CODE CREATE ENTERCODE ;
: ; CODE ? CSP COMPILE (; CODE) [COMPILE] [ ENTERCODE ;
  IMMEDIATE
ASSEMBLER DEFINITIONS
: ;C CURRENT @ CONTEXT ! ?CSP SMUDGE ;
: NEXT, Y ,++ LDX, X 0, [] JMP, ;
: NEXT
       NEXT, ;
FORTH DEFINITIONS DECIMAL
```