

[\(/developers/#\)](#)

# API

Changelog (<https://www.discogs.com/forum/thread/521520689469733cfcfd2089>)

API (<https://www.discogs.com/forum/topic/1082>)

Create an App (<https://www.discogs.com/settings/developers>)

API Terms (<https://support.discogs.com/hc/articles/360009334593-API-Terms-of-L>)

|                                 |
|---------------------------------|
| Home                            |
| ≡ Quickstart                    |
| ≡ General Information           |
| ≡ Rate Limiting                 |
| ≡ Pagination                    |
| ≡ Versioning and Media Types    |
| ≡ FAQ                           |
| Authentication                  |
| ≡ Discogs Auth Flow             |
| ≡ OAuth Flow                    |
| 🔑 Request Token URL             |
| 🔑 Access Token URL              |
| Database                        |
| 🔑 Release                       |
| ≡ Release Rating By User        |
| 🔑 Get Release Rating By User    |
| ✎ Update Release Rating By User |
| ⚠ Delete Release Rating By User |
| 🔑 Community Release Rating      |
| 🔑 Release Stats                 |
| 🔑 Master Release                |
| 🔑 Master Release Versions       |
| 🔑 Artist                        |
| 🔑 Artist Releases               |
| 🔑 Label                         |
| 🔑 All Label Releases            |
| 🔑 Search                        |
| ≡ Videos                        |
| Images                          |

## User Collection

### Collection

The Collection resource allows you to view and manage a user's collection. A collection is arranged into folders. Every user has two permanent folders already:

ID 0 , the "All" folder, which cannot have releases added to it, and  
ID 1 , the "Uncategorized" folder.

Because it's possible to own more than one copy of a release, each with its own notes, grading, and so on, each instance of a release in a folder has an instance ID.

Through the Discogs website, users can create custom notes fields. There is not yet an API method for creating and deleting th fields, but they can be listed, and the values of the fields on any instance can be modified.

GET /users/{username}/collection/folders

Retrieve a list of folders in a user's collection. If the collection has been made private by its owner, [authentication](#) as the collection owner is required. If you are not authenticated as the collection owner, only folder ID 0 (the "All" folder) will be visible (if the requested user's collection is public).

Parameters

username

string (required) **Example:** rodneyfool

The username of the collection you are trying to retrieve.

Response 200 

Toggle

POST /users/{username}/collection/folders

Create a new folder in a user's collection. [Authentication](#) as the collection owner is required.

Parameters

username

string (required) **Example:** rodneyfool

The username of the collection you are trying to retrieve.

name

string (optional) **Example:** My favorites

The name of the newly-created folder.

Response 201 

Toggle

### Collection Folder

GET /users/{username}/collection/folders/{folder\_id}

Retrieve metadata about a folder in a user's collection.  
If folder\_id is not 0 , [authentication](#) as the collection owner is required.

Parameters

|                       |
|-----------------------|
| Marketplace           |
| ➦ Inventory           |
| ☰ Listing             |
| ➦ Get listing         |
| ➦ Edit A Listing      |
| ⚠ Delete A Listing    |
| ➦ New Listing         |
| ☰ Order               |
| ➦ Get Order           |
| ➦ Edit An Order       |
| ➦ List Orders         |
| ☰ List Order Messages |
| ➦ List Order Messages |
| ➦ Add New Message     |
| ➦ Fee                 |
| ➦ Fee with currency   |
| ➦ Price Suggestions   |
| ➦ Release Statistics  |

|                         |
|-------------------------|
| Inventory Export        |
| ➦ Export your inventory |
| ➦ Get recent exports    |
| ➦ Get an export         |
| ➦ Download an export    |

|                      |
|----------------------|
| Inventory Upload     |
| ➦ Add inventory      |
| ➦ Change inventory   |
| ➦ Delete inventory   |
| ➦ Get recent uploads |
| ➦ Get an upload      |

|                |
|----------------|
| User Identity  |
| ➦ Identity     |
| ☰ Profile      |
| ➦ Get Profile  |
| ➦ Edit Profile |

username

string (required) **Example:** rodneyfool

The username of the collection you are trying to request.

folder\_id

number (required) **Example:** 3

The ID of the folder to request.

Response 200

Toggle

POST /users/{username}/collection/folders/{folder\_id}

Edit a folder's metadata. Folders 0 and 1 cannot be renamed.

[Authentication](#) as the collection owner is required.

Parameters

username

string (required) **Example:** rodneyfool

The username of the collection you are trying to modify.

folder\_id

number (required) **Example:** 3

The ID of the folder to modify.

Response 200

Toggle

DELETE /users/{username}/collection/folders/{folder\_id}

Delete a folder from a user's collection. A folder must be empty before it can be deleted.

[Authentication](#) as the collection owner is required.

Parameters

username

string (required) **Example:** rodneyfool

The username of the collection you are trying to modify.

folder\_id

number (required) **Example:** 3

The ID of the folder to delete.

Response 204

## Collection Items By Release

GET /users/{username}/collection/releases/{release\_id}

View the user's collection folders which contain a specified release. This will also show information about each release instance.

The `release_id` must be non-zero.

[Authentication](#) as the collection owner is required if the owner's collection is private.

Parameters

username

string (required) **Example:** susan.salkeld

The username of the collection you are trying to view.

release\_id

number (required) **Example:** 7781525

The ID of the release to request.

Response 200

Toggle

## Collection Items By Folder

GET /users/{username}/collection/folders/{folder\_id}/releases

|                               |
|-------------------------------|
| 🕒 User Submissions            |
| 🕒 User Contributions          |
| User Collection               |
| ☰ Collection                  |
| 🕒 Get Collection Folders      |
| ➕ Create Folder               |
| ☰ Collection Folder           |
| 🕒 Get Folders                 |
| ➕ Edit Folder                 |
| ⚠ Delete Folder               |
| 🕒 Collection Items By Release |
| 🕒 Collection Items By Folder  |
| ➕ Add To Collection Folder    |
| ➕ Change Rating Of Release    |
| ⚠ Delete Instance From Folder |
| 🕒 List Custom Fields          |
| ➕ Edit Fields Instance        |
| 🕒 Collection Value            |

|                                |
|--------------------------------|
| User Wantlist                  |
| 🕒 Wantlist                     |
| ☰ Add To Wantlist              |
| ✎ Add To Wantlist              |
| ➕ Edit Release In Wantlist     |
| ⚠ Delete Release From Wantlist |

|              |
|--------------|
| User Lists   |
| 🕒 User Lists |
| 🕒 List       |

<https://api.discogs.com>  
(<https://api.discogs.com>).

Returns the list of item in a folder in a user's collection. Accepts [Pagination](#) parameters.

Basic information about each release is provided, suitable for display in a list. For detailed information, make another API call to fetch the corresponding release.

If `folder_id` is not `0`, or the collection has been made private by its owner, [authentication](#) as the collection owner is required.

If you are not authenticated as the collection owner, only public notes fields will be visible.

Valid `sort` keys are:

- label
- artist
- title
- catno
- format
- rating
- added
- year

Parameters

|                   |                                                                                                                        |
|-------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>username</b>   | string (required) <b>Example:</b> rodneyfool<br>The username of the collection you are trying to request.              |
| <b>folder_id</b>  | number (required) <b>Example:</b> 3<br>The ID of the folder to request.                                                |
| <b>sort</b>       | string (optional) <b>Example:</b> artist<br>Sort items by this field (see below for all valid <code>sort</code> keys). |
| <b>sort_order</b> | string (optional) <b>Example:</b> desc<br>Sort items in a particular order ( <code>asc</code> or <code>desc</code> )   |

Response 200

Toggle

## Add To Collection Folder

`POST` `/users/{username}/collection/folders/{folder_id}/releases/{release_id}`

Add a release to a folder in a user's collection.

The `folder_id` must be non-zero – you can use `1` for “Uncategorized”.

[Authentication](#) as the collection owner is required.

Parameters

|                   |                                                                                                          |
|-------------------|----------------------------------------------------------------------------------------------------------|
| <b>username</b>   | string (required) <b>Example:</b> rodneyfool<br>The username of the collection you are trying to modify. |
| <b>folder_id</b>  | number (required) <b>Example:</b> 3<br>The ID of the folder to modify.                                   |
| <b>release_id</b> | number (required) <b>Example:</b> 130076<br>The ID of the release you are adding.                        |

Response 201

Toggle

## Change Rating Of Release

`POST` `/users/{username}/collection/folders/{folder_id}/releases/{release_id}/instances/{instance_id}`

Change the rating on a release and/or move the instance to another folder.

This endpoint potentially takes 2 `folder_id` parameters: one in the URL (which is the folder you are requesting, and is required), and one in the request body (representing the folder you want to move the instance to, which is optional)

[Authentication](#) as the collection owner is required.

Parameters

|                    |                                                                                                                                                                               |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>username</b>    | string (required) <b>Example:</b> rodneyfool<br>The username of the collection you are trying to modify.                                                                      |
| <b>folder_id</b>   | number (optional) <b>Example:</b> 4<br>The ID of the folder to modify (this parameter is set in the request body and is set if you want to move the instance to this folder). |
| <b>release_id</b>  | number (required) <b>Example:</b> 130076<br>The ID of the release you are modifying.                                                                                          |
| <b>instance_id</b> | number (required) <b>Example:</b> 1<br>The ID of the instance.                                                                                                                |
| <b>rating</b>      | number (optional) <b>Example:</b> 5<br>The rating of the instance you are supplying.                                                                                          |

Response 204

## Delete Instance From Folder

**DELETE** /users/{username}/collection/folders/{folder\_id}/releases/{release\_id}/instances/{instance\_id}

Remove an instance of a release from a user's collection folder.  
To move the release to the "Uncategorized" folder instead, use the `POST` method.  
[Authentication](#) as the collection owner is required.

### Parameters

|                    |                                                                                                          |
|--------------------|----------------------------------------------------------------------------------------------------------|
| <b>username</b>    | string (required) <b>Example:</b> rodneyfool<br>The username of the collection you are trying to modify. |
| <b>folder_id</b>   | number (required) <b>Example:</b> 3<br>The ID of the folder to modify.                                   |
| <b>release_id</b>  | number (required) <b>Example:</b> 130076<br>The ID of the release you are modifying.                     |
| <b>instance_id</b> | number (required) <b>Example:</b> 1<br>The ID of the instance.                                           |

Response 204

Response 403

[Toggle](#)

## List Custom Fields

**GET** /users/{username}/collection/fields

Retrieve a list of user-defined collection notes fields. These fields are available on every release in the collection.  
If the collection has been made private by its owner, [authentication](#) as the collection owner is required.  
If you are not authenticated as the collection owner, only fields with public set to true will be visible.

### Parameters

|                 |                                                                                                          |
|-----------------|----------------------------------------------------------------------------------------------------------|
| <b>username</b> | string (required) <b>Example:</b> rodneyfool<br>The username of the collection you are trying to modify. |
|-----------------|----------------------------------------------------------------------------------------------------------|

Response 200

[Toggle](#)

## Edit Fields Instance

**POST** /users/{username}/collection/folders/{folder\_id}/releases/{release\_id}/instances/{instance\_id}/fields/{field\_id}/{?value}

Change the value of a notes field on a particular instance.

Parameters

|             |                                                                                                                                      |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------|
| username    | string (required) <b>Example:</b> rodneyfool                                                                                         |
|             | The username of the collection you are trying to modify.                                                                             |
| value       | string (required) <b>Example:</b> foo                                                                                                |
|             | The new value of the field. If the field's type is dropdown , the value must match one of the values in the field's list of options. |
| folder_id   | number (required) <b>Example:</b> 3                                                                                                  |
|             | The ID of the folder to modify.                                                                                                      |
| release_id  | number (required) <b>Example:</b> 130076                                                                                             |
|             | The ID of the release you are modifying.                                                                                             |
| instance_id | number (required) <b>Example:</b> 1                                                                                                  |
|             | The ID of the instance.                                                                                                              |
| field_id    | number (required) <b>Example:</b> 8                                                                                                  |
|             | The ID of the field.                                                                                                                 |

Response 204

Collection Value

GET /users/{username}/collection/value

Returns the minimum, median, and maximum value of a user's collection.  
Authentication as the collection owner is required.

Parameters

|          |                                                          |
|----------|----------------------------------------------------------|
| username | string (required) <b>Example:</b> rodneyfool             |
|          | The username of the collection you are trying to modify. |

Response 200

[Toggle](#)

[Previous](#)

[Ne](#)