

빅 데이터 혁신 공유 대학

# 파이썬으로 배우는 데이터 구조

---

한동대학교 전산전자공학부

김영섭 교수



교육부




한국연구재단



# Data Structures in Python

## Chapter 4

- Recursion Concepts
- Recursion Stack and Memoization
- Recursive Algorithms
- Recursive Graphics
- Exercise - Stacking boxes



# Agenda

---

- Recursion Definition
  - Definitions and Programming
  - Why recursion?
  - Concept Example
  - More Examples

# Recursion Definition

- See Recursion

**TOP DEFINITION**

**recursion**

See recursion.


by **Anonymous** December 05, 2002

 916  42


Very descriptive definition

# Recursion Definition


- See Recursion
- Recursion is when a function calls itself
- Recursion simplifies program structure at a cost of function calls



<https://www.xkcd.com/1739/>




Recursion — Image from AlgoDaily



The **Sierpinski triangle**  
a confined recursion of triangles that form a fractal

# Recursion Definition

- See Recursion
- Recursion is when a function calls itself
- Recursion simplifies program structure at a cost of function calls
- Recursion vs. Leap of faith



***recursion is  
when a function calls  
itself***


# Why recursion?

---

- A new "cultural experience"
  - A different way of thinking of problems or creative thinking
- It can solve some kinds of problems better than iteration.
- It leads to elegant, simplistic, and short code (when used well).
- Believe it or not, there are some programming languages ("functional" languages such as Scheme, ML, and Haskell) use recursion exclusively (no loops)
- This skill is a key component of the rest of our course.

# Recursion

- Recursion is a method where the solution to a problem depends on solutions to smaller instances of the same problem (as opposed to iteration).
- Recursive algorithm is expressed in terms of
  1. **base case(s)** for which the solution can be stated non-recursively,
  2. **recursive case(s)** for which the solution can be expressed in terms of **a smaller version of itself**.



Four stages in the construction of a **Koch snowflake**. The stages are obtained via a recursive definition.



## Concept Example

- Pick one of students in the row and ask:  
How many students total are next you in your "row"?
  - You have poor vision, so you can see only the people next to you. So, you can't just look the sides and count.
  - But you are allowed to ask questions of two persons next to you.
  - How can we solve this problem, recursively?



## Concept Example: pass the buck

- Number of people on the both sides of me:
  - If there is someone to the left side of me, ask him/her how many people are to the left size of him/her.
  - Do the same to the right side of me.
  - When they respond with a value  $L$  from the left and  $R$  from the right, then I will answer  $L + R + 1$ .
- If there is nobody both side of me, I will answer 1.



# Recursion and cases

- Every recursive algorithm involves at least 2 cases:
  - **base case:** A simple occurrence that can be answered directly.
  - **recursive case:** A more complex occurrence of the problem that cannot be directly answered but can instead be described in terms of smaller occurrences of the same problem.
- Some recursive algorithms have more than one base or recursive case, but all have at least one of each.
- A crucial part of recursive programming is identifying these cases.



## Example 1: Factorial

- Recurrence relation: A mathematical formula that generates the terms in a sequence from previous terms.
  - $\text{factorial}(n) = n * [(n-1) * (n-2) * \dots * 1]$
  - $\text{factorial}(n) = n * \text{factorial}(n-1)$
- Recursive definition of  $\text{factorial}(n)$ :
  - $$\text{factorial}(n) = \begin{cases} 1, & \text{if } n = 0 \\ n * \text{factorial}(n - 1), & \text{if } n > 0 \end{cases}$$
- Examples:
  - $4! = 4 * 3 * 2 * 1 = 24$
  - $7! = 7 * 6 * 5 * 4 * 3 * 2 * 1 = 5040$

## Example 1: Factorial

- Recursive definition of factorial( $n$ )

- $$factorial(n) = \begin{cases} 1, & \text{if } n = 0 \\ n * factorial(n - 1), & \text{if } n > 0 \end{cases}$$

### factorial( $n$ )

```
function factorial
input: integer  $n$  such that  $n \geq 0$ 
output:  $[n \times (n-1) \times (n-2) \times \dots \times 1]$ 
  1. if  $n$  is 0, return 1
  2. otherwise, return  $[n \times factorial(n-1)]$ 
end factorial
```

### factorial( $n = 4$ )

```
f4 = 4 * f3
     = 4 * (3 * f2)
     = 4 * (3 * (2 * f1))
     = 4 * (3 * (2 * (1 * f0)))
     = 4 * (3 * (2 * (1 * 1)))
     = 4 * (3 * (2 * 1))
     = 4 * (3 * 2)
     = 4 * 6
     = 24
```

**Exercise:** With four students, compute  $4!$  using recursion.


# Example 1: Factorial

- Recursive definition of factorial(*n*)

$$\text{factorial}(n) = \begin{cases} 1, & \text{if } n = 0 \\ n * \text{factorial}(n - 1), & \text{if } n > 0 \end{cases}$$

**factorial(*n*)**

```
function factorial
input: integer n such that n >= 0
output: [n × (n-1) × (n-2) × ... × 1]
  1. if n is 0, return 1
  2. otherwise, return [ n × factorial(n-1) ]
end factorial
```



**Exercise:** With four students, compute 4! using recursion.

## Example 2: print\_starts()

- Consider the following function to print a line of \* characters:

```
def print_starts(n):  
    """prints a line containing the given number of stars.  
    precondition: n >= 0 """  
    for i in range(n):  
        print('*', end='')  
    print()
```

- Write a recursive version of this method (that calls itself).
  - Solve the problem **without using any loops**.
  - Hint: Your solution should print just one star at a time.

## Example 2: print\_starts()

---

- What are the cases to consider?
  - What is a very easy number of stars to print without a loop?

```
def print_stars(n):  
    if n == 1:  
        print('*')  
    else:  
        ...  
    print()
```



## Example 2: print\_starts()

- Handling additional cases, with no loops (**in a wrong way**):

```
def print_starts(n):  
    if n == 1:  
        print('*')  
    elif n == 2:  
        print '**'  
    elif n == 3:  
        print '***'  
    ...  
    else:  
        ...  
    print()
```

## Example 2: print\_starts()

- Taking advantage of the repeated pattern (**somewhat better**):

```
def print_starts(n):  
    if n == 1:  
        print('*')  
    elif n == 2:  
        print_starts(2)  
    elif n == 3:  
        print_starts(3)  
    ...  
    else:  
        ...  
    print()
```

## Example 2: Using recursion properly

- Condensing the recursive cases into a single case:

```
def print_stars(n):  
    if n == 1:                # base case:  
        print('*')           # print one star  
    else:                     # recursive case:  
        print('*', end='')    # print one and more stars  
        print_stars(n - 1)
```

## Example 2: Using recursion properly

- The real, even simpler base case is **an n of 0, not 1**:

```
def print_stars(n):  
    if n == 0:                # base case:  
        print()              # end the output  
    else:                     # recursive case:  
        print('*', end='')   # print one and more stars  
        print_stars(n - 1)
```

# Bad Recursion Example 1

---

- Problem:
  - Compute the sum of all integers from 1 to n

```
def bad_sum(n):  
    return n + bad_sum(n-1)
```

No base case!!!

## Bad Recursion Example 2

- Problem:
  - If  $n$  is odd, compute the sum of all odd integers from 1 to  $n$ ; and if it is even compute sum of all even integers.

```
def bad_sum(n):  
    if n == 0:  
        return 0  
    return n + bad_sum(n-2)
```

Base case cannot be reached!!!

## Recursion Exercise 1

- What is the result of the following call `mystery(648)`?  
Do it by hands, not running the code, and draw a diagram for the function calls.
- How many kinds of the results will you get if you give many different `n`?

```
def mystery(n):  
    if n < 10:  
        return n  
    else:  
        a = n // 10  
        b = n % 10  
        return mystery(a + b)
```

# Recursion Exercise 1

- What is the result of the following call `mystery(648)`?  
Do it by hands, not running the code.
- How many kinds of the results will you get if you give many different `n`?

```
def mystery(n):  
    if n < 10:  
        return n  
    else:  
        a = n // 10  
        b = n % 10  
        return mystery(a + b)
```

```
mystery(648):  
    a = 648 // 10      # 64  
    b = 648 % 10      # 8  
    return mystery(72) # mystery(72)
```



# Recursion Exercise 1

- What is the result of the following call `mystery(648)`?  
Do it by hands, not running the code.
- How many kinds of the results will you get if you give many different `n`?

```
def mystery(n):  
    if n < 10:  
        return n  
    else:  
        a = n // 10  
        b = n % 10  
        return mystery(a + b)
```

```
mystery(648):  
    a = 648 // 10      # 64  
    b = 648 % 10      # 8  
    return mystery(72) # mystery(72)
```

```
mystery(72):  
    a = 72 // 10      # 7  
    b = 72 % 10       # 2  
    return mystery(9) # mystery(9)
```

# Recursion Exercise 1

- What is the result of the following call `mystery(648)`?  
Do it by hands, not running the code.
- How many kinds of the results will you get if you give many different `n`?

```
def mystery(n):  
    if n < 10:  
        return n  
    else:  
        a = n // 10  
        b = n % 10  
        return mystery(a + b)
```

```
mystery(648):  
    a = 648 // 10      # 64  
    b = 648 % 10      # 8  
    return mystery(72) # mystery(72)
```

```
mystery(72):  
    a = 72 // 10      # 7  
    b = 72 % 10      # 2  
    return mystery(9) # mystery(9)
```

```
mystery(9):  
    return 9
```

## Recursion Exercise 2

- What is result of the following call, `mystery(234)` and `mystery(5067)`, respectively? Do it by hands and draw the function call diagrams like the previous example.

```
def mystery(n):  
    if n < 10:  
        return 10 * n + n  
    else:  
        a = mystery(n // 10)  
        b = mystery(n % 10)  
        return a * 100 + b
```

## Recursion Exercise 2

- What is result of the following call, `mystery(234)` and `mystery(5067)`, respectively? Do it by hands and draw the function call diagrams like the previous example.

```
def mystery(n):  
    if n < 10:  
        return 10 * n + n  
    else:  
        a = mystery(n // 10)  
        b = mystery(n % 10)  
        return a * 100 + b
```

```
mystery(234):
```

a = ...


$$b = \dots$$

```
return ...
```

# Summary

---

- **Recursion:** *see Recursion*
- Recursion is when a function calls itself
  - It can be used to simplify complex solutions to difficult problems.
- A recursive algorithm **passes the buck** repeatedly to the same function.



# Data Structures in Python

## Chapter 4

- Recursion Concepts
- Recursion Stack and Memoization
- Recursive Algorithms
- Recursive Graphics
- Exercise - Stacking boxes

