1 Type inference

For each of the terms below, specify its principal type scheme in the Hindley-Milner system (if it has one) for STLC with booleans, or otherwise say that the term cannot be typed.

As a reminder, the principal type scheme for a term is the most general type scheme that can be used as this term's type. For example, the principal type scheme of the identity function $\lambda x.x$ is $\forall a.a \rightarrow a$.

- 1. λp . λq . p
- $2. \lambda p.$ (p true)
- $3. \lambda p. \lambda q. pq$
- $4. \lambda p. p p$
- $5. \lambda p. p (p true)$
- $6. \lambda p. \lambda q. \lambda r. p q true$
- 7. λp . λq . $p(q(\lambda r. r))$
- 8. λp . λq . p (q true) (q (λr . r))

2 Subtyping

In this problem, we study some properties of algorithmic subtyping for function types and a bottom type. Recall that, compared to declarative subtyping, algorithmic subtyping removes explicit typing rules for reflexivity (S-Refl) and transitivity (S-Trans), but makes them provable from the algorithmic subtyping rules. The algorithmic subtyping rules we consider in this problem are presented below:

$$Bot <: T$$
 (S-Bot)

$$\frac{\mathtt{T}_1 <: \mathtt{S}_1 \qquad \mathtt{S}_2 <: \mathtt{T}_2}{\mathtt{S}_1 \to \mathtt{S}_2 <: \mathtt{T}_1 \to \mathtt{T}_2} \tag{S-Arrow}$$

where the types are defined as follows:

$$\mathtt{T} ::= \mathtt{Bot} \quad | \quad \mathtt{T} \to \mathtt{T}$$

We define *reflexivity* and *transitivity* of subtyping as follows:

- 1. Reflexivity: for any type S, S <: S.
- 2. Transitivity: for all types S, U, T, if S <: U and U <: T, then S <: T.

Question A

Prove transitivity for the algorithmic subtyping rules and types given above.

Question B

If we want to add a new type Nat for natural numbers, what additional subtyping rule(s) will be needed to preserve *reflexivity* and *transitivity*? You do not have to prove that the properties are preserved.

Question C

Many new programming languages, including Scala 3, support union types. A value of a union type S | T can be either of the type S or type T. Union types are different from sum types: Int is a subtype of Int | String, but Int is not a subtype of Int + String. In general, both A and B are subtypes of A | B. Conversely, if Int and String share a common supertype like Primitive, it is possible to use an Int | String where a Primitive is expected. This also generalizes to any three types A, B and C.

In most cases, union types express the same concept as sum types while being less verbose. For example, the integer 5 can take the type Int | String, while we need to write inl 5 for it to take the sum type Int + String.

Extend the above algorithmic subtyping rules for union types such that reflexivity and transitivity still hold. Your rules must stay algorithmic in the sense that every type variable in the premises of a rule exists in its conclusion (S-Trans is not algorithmic by that definition, for example). You do not have to prove that the properties are preserved. You may not add reflexivity nor transitivity themselves as rules.

Appendix: Hindley-Milner Type System

$$\begin{array}{lll} \mathrm{Type} & & \mathtt{T} & ::= & \mathtt{Bool} \ | \ \mathtt{T} \to \mathtt{T} \\ \mathrm{Type} \ \mathrm{Scheme} & \mathtt{S} & ::= & \mathtt{T} \ | \ \forall \mathtt{X.S} \end{array}$$

$$\frac{\mathtt{x}\!:\!\mathtt{S}\in\Gamma}{\Gamma\vdash\mathtt{x}\!:\!\mathtt{S}}$$
 (T-Var)

$$\frac{\Gamma \vdash \mathtt{t} \colon \mathtt{S}_1 \qquad \mathtt{X} \not\in \mathrm{FV}(\Gamma)}{\Gamma \vdash \mathtt{t} \colon \forall \mathtt{X} \cdot \mathtt{S}_1} \tag{T-TABS}$$

$$\frac{\Gamma \vdash \mathtt{t} \colon \forall \mathtt{X} . \mathtt{S}_1}{\Gamma \vdash \mathtt{t} \colon [\mathtt{X} \mapsto \mathtt{T}_2] \mathtt{S}_1} \tag{T-TAPP}$$

$$\frac{\Gamma \vdash \mathtt{t}_1 \colon \mathtt{S}_1 \qquad \Gamma, \mathtt{x} \colon \mathtt{S}_1 \vdash \mathtt{t}_2 \colon \mathtt{T}}{\Gamma \vdash \mathtt{let} \ \mathtt{x} = \mathtt{t}_1 \ \mathtt{in} \ \mathtt{t}_2 \colon \mathtt{T}} \tag{T-Let}$$

$$\frac{\Gamma, \mathbf{x} \colon T_1 \vdash \mathbf{t}_2 \colon T_2}{\Gamma \vdash \lambda \mathbf{x} \cdot \mathbf{t}_2 \colon T_1 \to T_2} \tag{T-Abs}$$

$$\frac{\Gamma \vdash \mathtt{t}_1 : \mathtt{T}_2 \rightarrow \mathtt{T}_{12} \qquad \Gamma \vdash \mathtt{t}_2 : \mathtt{T}_2}{\Gamma \vdash \mathtt{t}_1 \ \mathtt{t}_2 : \mathtt{T}_{12}} \tag{T-App)}$$

$$\Gamma \vdash \texttt{true:Bool}$$
 (T-True)

$$\Gamma \vdash \mathtt{false} : \mathtt{Bool}$$
 (T-False)