

# Foundations of Software Fall 2023

Week 5

1

## Plan

PREVIOUSLY: untyped lambda calculus

TODAY: types!!

1. Two example languages:
  - 1.1 typing arithmetic expressions
  - 1.2 simply typed lambda calculus (STLC)
2. For each:
  - 2.1 Define types
  - 2.2 Specify typing rules
  - 2.3 Prove soundness: *progress* and *preservation*

NEXT: lambda calculus extensions

NEXT: polymorphic typing

2

## Types

3

## Questions

What are your questions?

4

### Problematic arithmetic expressions

Consider the term

$t = \text{if true then (pred false) else 0}$

Clicker question: What can we say about it? (multiple possible answers)

- A.  $t$  is stuck
- B.  $t$  is a closed term
- C.  $t$  is typeable, i.e., there exists  $T$  such that  $t : T$
- D. there exists  $t'$  such that  $t \rightarrow^* t'$  and  $t'$  is stuck

URL: [ttpoll.eu](http://ttpoll.eu)  
Session ID: [cs452](#)

5

### Safety for arithmetic expressions

Recall from last week: safety = progress + preservation, given some definition of " $t$  is valid".

- Progress: if  $t$  is valid, then either  $t$  is a value, or  $t \rightarrow t'$ .
- Preservation: if  $t$  is valid and  $t \rightarrow t'$ , then  $t'$  is valid.

What is "is valid" for arithmetic expressions?

6

### The type of variables in STLC

Consider the term

$t = \lambda x : \text{Bool}. \text{if } x \text{ then false else true}$

Clicker question: What is  $T$  in  $x : T$ ?

- A.  $T = \text{Bool}$
- B.  $T = \text{Bool} \rightarrow \text{Bool}$
- C. there are multiple such  $T$ 's
- D. none of the above

URL: [ttpoll.eu](http://ttpoll.eu)  
Session ID: [cs452](#)

7

### Safety for STLC

What is "is valid" for the Simply Typed Lambda Calculus with Booleans?

8

## Outline

1. begin with a set of terms, a set of values, and an evaluation relation
2. define a set of *types* classifying values according to their "shapes"
3. define a *typing relation*  $t : T$  that classifies terms according to the shape of the values that result from evaluating them
4. check that the typing relation is *sound* in the sense that,
  - 4.1 if  $t : T$  and  $t \longrightarrow^* v$ , then  $v : T$
  - 4.2 if  $t : T$ , then evaluation of  $t$  will not get stuck

9

## Recall: Arithmetic Expressions – Syntax

$t ::=$	$\text{true}$ $\text{false}$ $\text{if } t \text{ then } t \text{ else } t$ $0$ $\text{succ } t$ $\text{pred } t$ $\text{iszero } t$	<i>terms</i> <i>constant true</i> <i>constant false</i> <i>conditional</i> <i>constant zero</i> <i>successor</i> <i>predecessor</i> <i>zero test</i>
$v ::=$	$\text{true}$ $\text{false}$ $nv$	<i>values</i> <i>true value</i> <i>false value</i> <i>numeric value</i>
$nv ::=$	$0$ $\text{succ } nv$	<i>numeric values</i> <i>zero value</i> <i>successor value</i>

10

## Recall: Arithmetic Expressions – Evaluation Rules

$\text{if true then } t_2 \text{ else } t_3 \longrightarrow t_2$	(E-IFTRUE)
$\text{if false then } t_2 \text{ else } t_3 \longrightarrow t_3$	(E-IFFALSE)
$\text{pred } 0 \longrightarrow 0$	(E-PREDZERO)
$\text{pred (succ } nv_1) \longrightarrow nv_1$	(E-PREDSUCC)
$\text{iszero } 0 \longrightarrow \text{true}$	(E-ISZEROZERO)
$\text{iszero (succ } nv_1) \longrightarrow \text{false}$	(E-ISZEROSUCC)

11

## Recall: Arithmetic Expressions – Evaluation Rules

$\frac{t_1 \longrightarrow t'_1}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \longrightarrow \text{if } t'_1 \text{ then } t_2 \text{ else } t_3}$	(E-IF)
$\frac{t_1 \longrightarrow t'_1}{\text{succ } t_1 \longrightarrow \text{succ } t'_1}$	(E-SUCC)
$\frac{t_1 \longrightarrow t'_1}{\text{pred } t_1 \longrightarrow \text{pred } t'_1}$	(E-PRED)
$\frac{t_1 \longrightarrow t'_1}{\text{iszero } t_1 \longrightarrow \text{iszero } t'_1}$	(E-ISZERO)

12

## Types

In this language, values have two possible “shapes”: they are either booleans or numbers.

$T ::=$

$\text{Bool}$	<i>types</i>
$\text{Nat}$	<i>type of booleans</i>
	<i>type of numbers</i>

13

## Typing Rules

$\text{true} : \text{Bool}$	(T-TRUE)
$\text{false} : \text{Bool}$	(T-FALSE)
$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T}$	(T-IF)
$0 : \text{Nat}$	(T-ZERO)
$\frac{t_1 : \text{Nat}}{\text{succ } t_1 : \text{Nat}}$	(T-SUCC)
$\frac{t_1 : \text{Nat}}{\text{pred } t_1 : \text{Nat}}$	(T-PRED)
$\frac{t_1 : \text{Nat}}{\text{iszero } t_1 : \text{Bool}}$	(T-ISZERO)

14

## Typing Derivations

Every pair  $(t, T)$  in the typing relation can be justified by a *derivation tree* built from instances of the inference rules.

$$\frac{\frac{\frac{}{0 : \text{Nat}} \text{T-ZERO} \quad \frac{}{\text{iszero } 0 : \text{Bool}} \text{T-ISZERO} \quad \frac{}{0 : \text{Nat}} \text{T-ZERO} \quad \frac{}{\text{pred } 0 : \text{Nat}} \text{T-PRED}}{\text{if iszero } 0 \text{ then } 0 \text{ else pred } 0 : \text{Nat}} \text{T-IF}$$

Proofs of properties about the typing relation often proceed by induction on typing derivations.

15

## Imprecision of Typing

Like other static program analyses, type systems are generally *imprecise*: they do not predict exactly what kind of value will be returned by every program, but just a conservative (safe) approximation.

$$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF})$$

Using this rule, we cannot assign a type to

$\text{if true then } 0 \text{ else false}$

even though this term will certainly evaluate to a number.

16

## Type Safety

The safety (or soundness) of this type system can be expressed by two properties:

1. *Progress*: A well-typed term is not stuck  
If  $t : T$ , then either  $t$  is a value or else  $t \longrightarrow t'$  for some  $t'$ .
2. *Preservation*: Types are preserved by one-step evaluation  
If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

17

## Inversion

*Lemma:*

1. If  $\text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $t_1 : \text{Bool}$ ,  $t_2 : R$ , and  $t_3 : R$ .
4. If  $0 : R$ , then  $R = \text{Nat}$ .
5. If  $\text{succ } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
6. If  $\text{pred } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
7. If  $\text{iszero } t_1 : R$ , then  $R = \text{Bool}$  and  $t_1 : \text{Nat}$ .

18

## Inversion

*Lemma:*

1. If  $\text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $t_1 : \text{Bool}$ ,  $t_2 : R$ , and  $t_3 : R$ .
4. If  $0 : R$ , then  $R = \text{Nat}$ .
5. If  $\text{succ } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
6. If  $\text{pred } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
7. If  $\text{iszero } t_1 : R$ , then  $R = \text{Bool}$  and  $t_1 : \text{Nat}$ .

*Proof:* ...

18

## Inversion

*Lemma:*

1. If  $\text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $t_1 : \text{Bool}$ ,  $t_2 : R$ , and  $t_3 : R$ .
4. If  $0 : R$ , then  $R = \text{Nat}$ .
5. If  $\text{succ } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
6. If  $\text{pred } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
7. If  $\text{iszero } t_1 : R$ , then  $R = \text{Bool}$  and  $t_1 : \text{Nat}$ .

*Proof:* ...

This leads directly to a recursive algorithm for calculating the type of a term...

18

## Typechecking Algorithm

```

typeof(t) = if t = true then Bool
           else if t = false then Bool
           else if t = if t1 then t2 else t3 then
             let T1 = typeof(t1) in
             let T2 = typeof(t2) in
             let T3 = typeof(t3) in
             if T1 = Bool and T2=T3 then T2
             else "not typable"
           else if t = 0 then Nat
           else if t = succ t1 then
             let T1 = typeof(t1) in
             if T1 = Nat then Nat else "not typable"
           else if t = pred t1 then
             let T1 = typeof(t1) in
             if T1 = Nat then Nat else "not typable"
           else if t = iszero t1 then
             let T1 = typeof(t1) in
             if T1 = Nat then Bool else "not typable"

```

19

## Properties of the Typing Relation

20

## Recall: Typing Rules

$\text{true} : \text{Bool}$	(T-TRUE)
$\text{false} : \text{Bool}$	(T-FALSE)
$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T}$	(T-IF)
$0 : \text{Nat}$	(T-ZERO)
$\frac{t_1 : \text{Nat}}{\text{succ } t_1 : \text{Nat}}$	(T-SUCC)
$\frac{t_1 : \text{Nat}}{\text{pred } t_1 : \text{Nat}}$	(T-PRED)
$\frac{t_1 : \text{Nat}}{\text{iszero } t_1 : \text{Bool}}$	(T-ISZERO)

21

## Recall: Inversion

*Lemma:*

1. If  $\text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $t_1 : \text{Bool}$ ,  $t_2 : R$ , and  $t_3 : R$ .
4. If  $0 : R$ , then  $R = \text{Nat}$ .
5. If  $\text{succ } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
6. If  $\text{pred } t_1 : R$ , then  $R = \text{Nat}$  and  $t_1 : \text{Nat}$ .
7. If  $\text{iszero } t_1 : R$ , then  $R = \text{Bool}$  and  $t_1 : \text{Nat}$ .

22

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type `Nat`, then  $v$  is a numeric value.

*Proof:*

23

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type `Nat`, then  $v$  is a numeric value.

*Proof:* Recall the syntax of values:

$v ::=$	<code>true</code>	values
	<code>false</code>	true value
	<code>nv</code>	false value
		numeric value
$nv ::=$	<code>0</code>	numeric values
	<code>succ nv</code>	zero value
		successor value

For part 1,

23

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type `Nat`, then  $v$  is a numeric value.

*Proof:* Recall the syntax of values:

$v ::=$	<code>true</code>	values
	<code>false</code>	true value
	<code>nv</code>	false value
		numeric value
$nv ::=$	<code>0</code>	numeric values
	<code>succ nv</code>	zero value
		successor value

For part 1, if  $v$  is `true` or `false`, the result is immediate.

23

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type `Nat`, then  $v$  is a numeric value.

*Proof:* Recall the syntax of values:

$v ::=$	<code>true</code>	values
	<code>false</code>	true value
	<code>nv</code>	false value
		numeric value
$nv ::=$	<code>0</code>	numeric values
	<code>succ nv</code>	zero value
		successor value

For part 1, if  $v$  is `true` or `false`, the result is immediate. But  $v$  cannot be `0` or `succ nv`, since the inversion lemma tells us that  $v$  would then have type `Nat`, not `Bool`.

23

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type `Nat`, then  $v$  is a numeric value.

*Proof:* Recall the syntax of values:

$v ::=$	<i>values</i>
<code>true</code>	<i>true value</i>
<code>false</code>	<i>false value</i>
<code>nv</code>	<i>numeric value</i>
$nv ::=$	<i>numeric values</i>
<code>0</code>	<i>zero value</i>
<code>succ nv</code>	<i>successor value</i>

For part 1, if  $v$  is `true` or `false`, the result is immediate. But  $v$  cannot be `0` or `succ nv`, since the inversion lemma tells us that  $v$  would then have type `Nat`, not `Bool`. Part 2 is similar.

23

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

24

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:*

24

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on a derivation of  $t : T$ .

24



## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on a derivation of  $t : T$ .

The T-TRUE, T-FALSE, and T-ZERO cases are immediate, since  $t$  in these cases is a value.

24

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on a derivation of  $t : T$ .

The T-TRUE, T-FALSE, and T-ZERO cases are immediate, since  $t$  in these cases is a value.

Case T-IF:  $t = \text{if } t_1 \text{ then } t_2 \text{ else } t_3$   
 $t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T$

24

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on a derivation of  $t : T$ .

The T-TRUE, T-FALSE, and T-ZERO cases are immediate, since  $t$  in these cases is a value.

Case T-IF:  $t = \text{if } t_1 \text{ then } t_2 \text{ else } t_3$   
 $t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T$

By the induction hypothesis, either  $t_1$  is a value or else there is some  $t'_1$  such that  $t_1 \longrightarrow t'_1$ . If  $t_1$  is a value, then the canonical forms lemma tells us that it must be either `true` or `false`, in which case either E-IFTRUE or E-IFFALSE applies to  $t$ . On the other hand, if  $t_1 \longrightarrow t'_1$ , then, by E-IF,  $t \longrightarrow \text{if } t'_1 \text{ then } t_2 \text{ else } t_3$ .

24

## Progress

*Theorem:* Suppose  $t$  is a well-typed term (that is,  $t : T$  for some type  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on a derivation of  $t : T$ .

The cases for rules T-ZERO, T-SUCC, T-PRED, and T-ISZERO are similar.

(Recommended: Try to reconstruct them.)

25

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

26

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

*Proof:* By induction on the given typing derivation.

26

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

*Proof:* By induction on the given typing derivation.

Case T-TRUE:  $t = \text{true}$   $T = \text{Bool}$

Then  $t$  is a value.

26

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

*Proof:* By induction on the given typing derivation.

Case T-IF:

$t = \text{if } t_1 \text{ then } t_2 \text{ else } t_3$   $t_1 : \text{Bool}$   $t_2 : T$   $t_3 : T$

There are three evaluation rules by which  $t \longrightarrow t'$  can be derived: E-IFTRUE, E-IFFALSE, and E-IF. Consider each case separately.

26

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

*Proof:* By induction on the given typing derivation.

Case T-IF:

$t = \text{if } t_1 \text{ then } t_2 \text{ else } t_3 \quad t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T$

There are three evaluation rules by which  $t \longrightarrow t'$  can be derived: E-IFTRUE, E-IFFALSE, and E-IF. Consider each case separately.

*Subcase E-IFTRUE:*  $t_1 = \text{true} \quad t' = t_2$

Immediate, by the assumption  $t_2 : T$ .

(E-IFFALSE subcase: Similar.)

26

## Preservation

*Theorem:* If  $t : T$  and  $t \longrightarrow t'$ , then  $t' : T$ .

*Proof:* By induction on the given typing derivation.

Case T-IF:

$t = \text{if } t_1 \text{ then } t_2 \text{ else } t_3 \quad t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T$

There are three evaluation rules by which  $t \longrightarrow t'$  can be derived: E-IFTRUE, E-IFFALSE, and E-IF. Consider each case separately.

*Subcase E-IF:*  $t_1 \longrightarrow t'_1 \quad t' = \text{if } t'_1 \text{ then } t_2 \text{ else } t_3$

Applying the IH to the subderivation of  $t_1 : \text{Bool}$  yields

$t'_1 : \text{Bool}$ . Combining this with the assumptions that  $t_2 : T$  and

$t_3 : T$ , we can apply rule T-IF to conclude that  
 $\text{if } t'_1 \text{ then } t_2 \text{ else } t_3 : T$ , that is,  $t' : T$ .

26

## Messing With It

27

## Messing with it: Remove a rule

What if we remove E-PREDZERO ?

28

### Messing with it: Remove a rule

What if we remove E-PREDZERO ?

Then `pred 0` type checks, but it is stuck and is not a value. Thus the progress theorem fails.

28

### Messing with it: If

What if we change the rule for typing `if`'s to the following ?:

$$\frac{t_1 : \text{Bool} \quad t_2 : \text{Nat} \quad t_3 : \text{Nat}}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : \text{Nat}} \quad (\text{T-IF})$$

29

### Messing with it: If

What if we change the rule for typing `if`'s to the following ?:

$$\frac{t_1 : \text{Bool} \quad t_2 : \text{Nat} \quad t_3 : \text{Nat}}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : \text{Nat}} \quad (\text{T-IF})$$

The system is still sound. Some `if`'s do not type, but those that do are fine.

29

### Messing with it: adding bit

`t ::=` *terms*  
`...`  
`bit(t)` *boolean to natural*

1. evaluation rule
2. typing rule
3. progress and preservation updates

30

# The Simply Typed Lambda-Calculus

31

## The simply typed lambda-calculus

The system we are about to define is commonly called the *simply typed lambda-calculus*, or  $\lambda_{\rightarrow}$  for short.

Unlike the untyped lambda-calculus, the “pure” form of  $\lambda_{\rightarrow}$  (with no primitive values or operations) is not very interesting; to talk about  $\lambda_{\rightarrow}$ , we always begin with some set of “base types.”

- ▶ So, strictly speaking, there are *many* variants of  $\lambda_{\rightarrow}$ , depending on the choice of base types.
- ▶ For now, we’ll work with a variant constructed over the booleans.

32

## Untyped lambda-calculus with booleans

$t ::=$	<i>terms</i>
$x$	<i>variable</i>
$\lambda x.t$	<i>abstraction</i>
$t\ t$	<i>application</i>
$true$	<i>constant true</i>
$false$	<i>constant false</i>
$if\ t\ then\ t\ else\ t$	<i>conditional</i>
$v ::=$	<i>values</i>
$\lambda x.t$	<i>abstraction value</i>
$true$	<i>true value</i>
$false$	<i>false value</i>

33

## “Simple Types”

$T ::=$	<i>types</i>
$Bool$	<i>type of booleans</i>
$T \rightarrow T$	<i>types of functions</i>

What are some examples?

34

## Type Annotations

We now have a choice to make. Do we...

- ▶ annotate lambda-abstractions with the expected type of the argument

$\lambda x:T_1. t_2$

(as in most mainstream programming languages), or

- ▶ continue to write lambda-abstractions as before

$\lambda x. t_2$

and ask the typing rules to “guess” an appropriate annotation (as in OCaml)?

Both are reasonable choices, but the first makes the job of defining the typing rules simpler. Let's take this choice for now.

35

## Typing rules

$\text{true} : \text{Bool}$  (T-TRUE)

$\text{false} : \text{Bool}$  (T-FALSE)

$$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF})$$

36

## Typing rules

$\text{true} : \text{Bool}$  (T-TRUE)

$\text{false} : \text{Bool}$  (T-FALSE)

$$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF})$$

$$\frac{???}{\lambda x:T_1. t_2 : T_1 \rightarrow T_2} \quad (\text{T-ABS})$$

36

## Typing rules

$\text{true} : \text{Bool}$  (T-TRUE)

$\text{false} : \text{Bool}$  (T-FALSE)

$$\frac{t_1 : \text{Bool} \quad t_2 : T \quad t_3 : T}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF})$$

$$\frac{\Gamma, x:T_1 \vdash t_2 : T_2}{\Gamma \vdash \lambda x:T_1. t_2 : T_1 \rightarrow T_2} \quad (\text{T-ABS})$$

$$\frac{x:T \in \Gamma}{\Gamma \vdash x : T} \quad (\text{T-VAR})$$

36

## Typing rules

$$\begin{array}{c}
 \Gamma \vdash \text{true} : \text{Bool} \quad (\text{T-TRUE}) \\
 \Gamma \vdash \text{false} : \text{Bool} \quad (\text{T-FALSE}) \\
 \frac{\Gamma \vdash t_1 : \text{Bool} \quad \Gamma \vdash t_2 : T \quad \Gamma \vdash t_3 : T}{\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad (\text{T-IF}) \\
 \frac{\Gamma, x:T_1 \vdash t_2 : T_2}{\Gamma \vdash \lambda x:T_1. t_2 : T_1 \rightarrow T_2} \quad (\text{T-ABS}) \\
 \frac{x:T \in \Gamma}{\Gamma \vdash x : T} \quad (\text{T-VAR}) \\
 \frac{\Gamma \vdash t_1 : T_{11} \rightarrow T_{12} \quad \Gamma \vdash t_2 : T_{11}}{\Gamma \vdash t_1 \ t_2 : T_{12}} \quad (\text{T-APP})
 \end{array}$$

36

## Typing Derivations

What derivations justify the following typing statements?

- ▶  $\vdash (\lambda x:\text{Bool}.x) \ \text{true} : \text{Bool}$
- ▶  $f:\text{Bool} \rightarrow \text{Bool} \vdash f \ (\text{if false then true else false}) : \text{Bool}$
- ▶  $f:\text{Bool} \rightarrow \text{Bool} \vdash \lambda x:\text{Bool}. f \ (\text{if } x \text{ then false else } x) : \text{Bool} \rightarrow \text{Bool}$

37

## Properties of $\lambda_{\rightarrow}$

The fundamental property of the type system we have just defined is *soundness* with respect to the operational semantics.

1. *Progress*: A closed, well-typed term is not stuck  
If  $\vdash t : T$ , then either  $t$  is a value or else  $t \rightarrow t'$  for some  $t'$ .
2. *Preservation*: Types are preserved by one-step evaluation  
If  $\Gamma \vdash t : T$  and  $t \rightarrow t'$ , then  $\Gamma \vdash t' : T$ .

38

## Proving progress

Same steps as before...

39

## Proving progress

Same steps as before...

- ▶ inversion lemma for typing relation
- ▶ canonical forms lemma
- ▶ progress theorem

39

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .

40

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then

40

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then  $x : R \in \Gamma$ .

40



## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then  $x : R \in \Gamma$ .
5. If  $\Gamma \vdash \lambda x : T_1. t_2 : R$ , then

40

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then  $x : R \in \Gamma$ .
5. If  $\Gamma \vdash \lambda x : T_1. t_2 : R$ , then  $R = T_1 \rightarrow R_2$  for some  $R_2$  with  $\Gamma, x : T_1 \vdash t_2 : R_2$ .

40

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then  $x : R \in \Gamma$ .
5. If  $\Gamma \vdash \lambda x : T_1. t_2 : R$ , then  $R = T_1 \rightarrow R_2$  for some  $R_2$  with  $\Gamma, x : T_1 \vdash t_2 : R_2$ .
6. If  $\Gamma \vdash t_1 \ t_2 : R$ , then

40

## Inversion

*Lemma:*

1. If  $\Gamma \vdash \text{true} : R$ , then  $R = \text{Bool}$ .
2. If  $\Gamma \vdash \text{false} : R$ , then  $R = \text{Bool}$ .
3. If  $\Gamma \vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : R$ , then  $\Gamma \vdash t_1 : \text{Bool}$  and  $\Gamma \vdash t_2, t_3 : R$ .
4. If  $\Gamma \vdash x : R$ , then  $x : R \in \Gamma$ .
5. If  $\Gamma \vdash \lambda x : T_1. t_2 : R$ , then  $R = T_1 \rightarrow R_2$  for some  $R_2$  with  $\Gamma, x : T_1 \vdash t_2 : R_2$ .
6. If  $\Gamma \vdash t_1 \ t_2 : R$ , then there is some type  $T_{11}$  such that  $\Gamma \vdash t_1 : T_{11} \rightarrow R$  and  $\Gamma \vdash t_2 : T_{11}$ .

40

## Canonical Forms

*Lemma:*

41

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then

41

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.

41

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type `Bool`, then  $v$  is either `true` or `false`.
2. If  $v$  is a value of type  `$T_1 \rightarrow T_2$` , then

41

## Canonical Forms

*Lemma:*

1. If  $v$  is a value of type  $\text{Bool}$ , then  $v$  is either  $\text{true}$  or  $\text{false}$ .
2. If  $v$  is a value of type  $T_1 \rightarrow T_2$ , then  $v$  has the form  $\lambda x:T_1. t_2$ .

41

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction

42

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on typing derivations.

42

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on typing derivations. The cases for boolean constants and conditions are the same as before. The variable case is trivial (because  $t$  is closed). The abstraction case is immediate, since abstractions are values.

42

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on typing derivations. The cases for boolean constants and conditions are the same as before. The variable case is trivial (because  $t$  is closed). The abstraction case is immediate, since abstractions are values.

Consider the case for application, where  $t = t_1 \ t_2$  with  $\vdash t_1 : T_{11} \rightarrow T_{12}$  and  $\vdash t_2 : T_{11}$ .

42

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on typing derivations. The cases for boolean constants and conditions are the same as before. The variable case is trivial (because  $t$  is closed). The abstraction case is immediate, since abstractions are values.

Consider the case for application, where  $t = t_1 \ t_2$  with  $\vdash t_1 : T_{11} \rightarrow T_{12}$  and  $\vdash t_2 : T_{11}$ . By the induction hypothesis, either  $t_1$  is a value or else it can make a step of evaluation, and likewise  $t_2$ .

42

## Progress

*Theorem:* Suppose  $t$  is a closed, well-typed term (that is,  $\vdash t : T$  for some  $T$ ). Then either  $t$  is a value or else there is some  $t'$  with  $t \longrightarrow t'$ .

*Proof:* By induction on typing derivations. The cases for boolean constants and conditions are the same as before. The variable case is trivial (because  $t$  is closed). The abstraction case is immediate, since abstractions are values.

Consider the case for application, where  $t = t_1 \ t_2$  with  $\vdash t_1 : T_{11} \rightarrow T_{12}$  and  $\vdash t_2 : T_{11}$ . By the induction hypothesis, either  $t_1$  is a value or else it can make a step of evaluation, and likewise  $t_2$ . If  $t_1$  can take a step, then rule E-APP1 applies to  $t$ . If  $t_1$  is a value and  $t_2$  can take a step, then rule E-APP2 applies. Finally, if both  $t_1$  and  $t_2$  are values, then the canonical forms lemma tells us that  $t_1$  has the form  $\lambda x:T_{11}.t_{12}$ , and so rule E-APPABS applies to  $t$ .

42

## Reading for next week

- Chapter 11 until section 11.7 (Tuples) included

43