

Foundations of Software Fall 2023

Week 8

1

Plan

PREVIOUSLY: unit, sequencing, let, pairs, sums

TODAY:

1. recursion
2. state
3. ???

NEXT: exceptions?

NEXT: polymorphic (not so simple) typing

2

Recursion

3

Recursion in λ_{\rightarrow}

- ▶ In λ_{\rightarrow} , all programs terminate. (Cf. Chapter 12.)
- ▶ Hence, untyped terms like `omega` and `fix` are not typable.
- ▶ But we can *extend* the system with a (typed) fixed-point operator...

4

Example

```
ff = λie:Nat→Bool.
    λx:Nat.
      if iszero x then true
      else if iszero (pred x) then false
      else ie (pred (pred x));

iseven = fix ff;

iseven 7;
```

5

New syntactic forms

$t ::= \dots$
 $\text{fix } t$

terms
fixed point of t

New evaluation rules

$t \longrightarrow t'$

$$\frac{\text{fix } (\lambda x:T_1.t_2)}{\longrightarrow [x \mapsto (\text{fix } (\lambda x:T_1.t_2))]t_2} \quad (\text{E-FIXBETA})$$

$$\frac{t_1 \longrightarrow t'_1}{\text{fix } t_1 \longrightarrow \text{fix } t'_1} \quad (\text{E-FIX})$$

What would be the typing rule for terms of the form $\text{fix } t$?

6

New typing rules

$\Gamma \vdash t : T$

$$\frac{\Gamma \vdash t_1 : T_1 \rightarrow T_1}{\Gamma \vdash \text{fix } t_1 : T_1} \quad (\text{T-FIX})$$

7

A more convenient form

$\text{letrec } x:T_1=t_1 \text{ in } t_2 \stackrel{\text{def}}{=} \text{let } x = \text{fix } (\lambda x:T_1.t_1) \text{ in } t_2$

```
letrec iseven : Nat→Bool =
  λx:Nat.
    if iszero x then true
    else if iszero (pred x) then false
    else iseven (pred (pred x))
in
  iseven 7;
```

8

Reading for next week

- ▶ Chapter 13 – References

9

References

10

Mutability

- ▶ In most programming languages, *variables* are mutable — i.e., a variable provides both
 - ▶ a name that refers to a previously calculated value, and
 - ▶ the possibility of *overwriting* this value with another (which will be referred to by the same name)
- ▶ In some languages (e.g., OCaml), these features are separate:
 - ▶ variables are only for naming — the binding between a variable and its value is immutable
 - ▶ introduce a new class of *mutable values* (called *reference cells* or *references*)
 - ▶ at any given moment, a reference holds a value (and can be *dereferenced* to obtain this value)
 - ▶ a new value may be *assigned* to a reference

We choose OCaml's style, which is easier to work with formally.

So a variable of type `T` in most languages (except OCaml) will correspond to a `Ref T` here.

11

Basic Examples

```
r = ref 5
!r
r := 7
(r:=succ(!r); !r)
(r:=succ(!r); r:=succ(!r); r:=succ(!r);
r:=succ(!r); !r)
```

12

Basic Examples

```
r = ref 5
!r
r := 7
(r:=succ(!r); !r)
(r:=succ(!r); r:=succ(!r); r:=succ(!r);
 r:=succ(!r); !r)
i.e.,
(((r:=succ(!r); r:=succ(!r)); r:=succ(!r));
 r:=succ(!r); !r)
```

12

Aliasing

A value of type `Ref T` is a *pointer* to a cell holding a value of type `T`.



If this value is “copied” by assigning it to another variable, the cell pointed to is not copied.



So we can change `r` by assigning to `s`:

```
(s:=6; !r)
```

13

Aliasing all around us

Reference cells are not the only language feature that introduces the possibility of aliasing.

- ▶ object references
- ▶ explicit pointers in C
- ▶ arrays
- ▶ communication channels
- ▶ I/O devices (disks, etc.)

14

The difficulties of aliasing

The possibility of aliasing invalidates all sorts of useful forms of reasoning about programs, both by programmers...

The function $\lambda r:\text{Ref Nat}. \lambda s:\text{Ref Nat}. (r:=2; s:=3; !r)$ always returns 2 unless r and s are aliases.

...and by compilers:

Code motion out of loops, common subexpression elimination, allocation of variables to registers, and detection of uninitialized variables all depend upon the compiler knowing which objects a load or a store operation could reference.

High-performance compilers spend significant energy on *alias analysis* to try to establish when different variables cannot possibly refer to the same storage.

15

The difficulties of side effects

The order of operations now matters.

```
f (r := 1) (r := 2)
```

16

The benefits of aliasing

The problems of aliasing have led some language designers simply to disallow it (e.g., Haskell).

But there are good reasons why most languages do provide constructs involving aliasing:

- ▶ efficiency (e.g., arrays)
- ▶ “action at a distance” (e.g., symbol tables)
- ▶ dependency-driven data flow (e.g., in GUI's)
- ▶ shared resources (e.g., locks) in concurrent systems
- ▶ etc.

17

Example

```
c = ref 0
incc = λx:Unit. (c := succ (!c); !c)
decc = λx:Unit. (c := pred (!c); !c)
incc unit
decc unit
o = {i = incc, d = decc}
```

18

```
let newcounter =
  λ_:Unit.
    let c = ref 0 in
    let incc = λx:Unit. (c := succ (!c); !c) in
    let decc = λx:Unit. (c := pred (!c); !c) in
    let o = {i = incc, d = decc} in
    o
```

19

Syntax

<code>t ::= ...</code>	<i>terms</i>
<code>unit</code>	<i>unit value</i>
<code>ref t</code>	<i>reference creation</i>
<code>!t</code>	<i>dereference</i>
<code>t:=t</code>	<i>assignment</i>
 <code>T ::= ...</code>	 <i>types</i>
<code>Unit</code>	<i>unit type</i>
<code>Ref T</code>	<i>reference type</i>

... plus other familiar terms and types, in examples.

20

Typing Rules

$\frac{\Gamma \vdash t_1 : T_1}{\Gamma \vdash \text{ref } t_1 : \text{Ref } T_1}$	(T-REF)
$\frac{\Gamma \vdash t_1 : \text{Ref } T_1}{\Gamma \vdash !t_1 : T_1}$	(T-DEREF)
$\frac{\Gamma \vdash t_1 : \text{Ref } T_1 \quad \Gamma \vdash t_2 : T_1}{\Gamma \vdash t_1 := t_2 : \text{Unit}}$	(T-ASSIGN)

21

Final example

```

NatArray = Ref (Nat → Nat);

newarray = λ_:Unit. ref (λn:Nat.0);
          : Unit → NatArray

lookup = λa:NatArray. λn:Nat. (!a) n;
        : NatArray → Nat → Nat

update = λa:NatArray. λm:Nat. λv:Nat.
         let oldf = !a in
         a := (λn:Nat. if equal m n then v else oldf n);
         : NatArray → Nat → Nat → Unit

```

22

Evaluation

Clicker question: What is the *value* of the expression `ref 0`?

- A. 0
- B. `ref 0`, i.e., reference terms with value "arguments" are values themselves, like `succ v`
- C. it has no value; it remains as a stuck term
- D. something else

URL: tppoll.eu
 Session ID: `cs452`

23

Evaluation

What is the *value* of the expression `ref 0`?

Crucial observation: evaluating `ref 0` must *do* something.
Otherwise,

```
r = ref 0
s = ref 0
```

and

```
r = ref 0
s = r
```

would behave the same.

24

Evaluation

What is the *value* of the expression `ref 0`?

Crucial observation: evaluating `ref 0` must *do* something.
Otherwise,

```
r = ref 0
s = ref 0
```

and

```
r = ref 0
s = r
```

would behave the same.

Specifically, evaluating `ref 0` should *allocate some storage* and
yield a *reference* (or *pointer*) to that storage.

24

Evaluation

What is the *value* of the expression `ref 0`?

Crucial observation: evaluating `ref 0` must *do* something.
Otherwise,

```
r = ref 0
s = ref 0
```

and

```
r = ref 0
s = r
```

would behave the same.

Specifically, evaluating `ref 0` should *allocate some storage* and
yield a *reference* (or *pointer*) to that storage.

So what is a reference?

24

The Store

A reference names a *location* in the *store* (also known as the *heap*
or just the *memory*).

What is the store?

25

The Store

A reference names a *location* in the *store* (also known as the *heap* or just the *memory*).

What is the store?

- ▶ *Concretely*: An array of 8-bit bytes, indexed by 64-bit integers.

25

The Store

A reference names a *location* in the *store* (also known as the *heap* or just the *memory*).

What is the store?

- ▶ *Concretely*: An array of 8-bit bytes, indexed by 64-bit integers.
- ▶ *More abstractly*: an array of *values*

25

The Store

A reference names a *location* in the *store* (also known as the *heap* or just the *memory*).

What is the store?

- ▶ *Concretely*: An array of 8-bit bytes, indexed by 64-bit integers.
- ▶ *More abstractly*: an array of *values*
- ▶ *Even more abstractly*: a partial function from *locations* to *values*.

25

Locations

Syntax of values:

```
v ::=
    unit
  | λx:T.t
  |
```

values
unit constant
abstraction value
store location

... and since all values are terms...

26

Syntax of Terms

$t ::=$	<i>terms</i>
<code>unit</code>	<i>unit constant</i>
<code>x</code>	<i>variable</i>
<code>$\lambda x:T.t$</code>	<i>abstraction</i>
<code>$t\ t$</code>	<i>application</i>
<code>ref t</code>	<i>reference creation</i>
<code>!t</code>	<i>dereference</i>
<code>$t := t$</code>	<i>assignment</i>
<code>l</code>	<i>store location</i>

27

Aside

Does this mean we are going to allow programmers to write explicit locations in their programs??

No: This is just a modeling trick. We are enriching the “source language” to include some run-time structures, so that we can continue to formalize evaluation as a relation between source terms.

Aside: If we formalize evaluation in the big-step style, then we can add locations to the set of values (results of evaluation) without adding them to the set of terms.

28

Evaluation

The result of evaluating a term now depends on the store in which it is evaluated. Moreover, the result of evaluating a term is not just a value — we must also keep track of the changes that get made to the store.

I.e., the evaluation relation should now map a term and a store to a reduced term and a new store.

$$t \mid \mu \longrightarrow t' \mid \mu'$$

We use the metavariable μ to range over stores.

29

Evaluation

An assignment $t_1 := t_2$ first evaluates t_1 and t_2 until they become values...

$$\frac{t_1 \mid \mu \longrightarrow v_1 \mid \mu'}{t_1 := t_2 \mid \mu \longrightarrow v_1 := t_2 \mid \mu'} \quad (\text{E-ASSIGN1})$$

$$\frac{t_2 \mid \mu \longrightarrow v_2 \mid \mu'}{v_1 := t_2 \mid \mu \longrightarrow v_1 := v_2 \mid \mu'} \quad (\text{E-ASSIGN2})$$

... and then returns `unit` and updates the store:

$$l := v_2 \mid \mu \longrightarrow \text{unit} \mid [l \mapsto v_2] \mu \quad (\text{E-ASSIGN})$$

30

A term of the form $\text{ref } t_1$ first evaluates inside t_1 until it becomes a value...

$$\frac{t_1 \mid \mu \longrightarrow t'_1 \mid \mu'}{\text{ref } t_1 \mid \mu \longrightarrow \text{ref } t'_1 \mid \mu'} \quad (\text{E-REF})$$

... and then chooses (allocates) a fresh location l , augments the store with a binding from l to v_1 , and returns l :

$$\frac{l \notin \text{dom}(\mu)}{\text{ref } v_1 \mid \mu \longrightarrow l \mid (\mu, l \mapsto v_1)} \quad (\text{E-REFV})$$

31

A term $!t_1$ first evaluates in t_1 until it becomes a value...

$$\frac{t_1 \mid \mu \longrightarrow t'_1 \mid \mu'}{!t_1 \mid \mu \longrightarrow !t'_1 \mid \mu'} \quad (\text{E-DEREF})$$

... and then looks up this value (which must be a location, if the original term was well typed) and returns its contents in the current store:

$$\frac{\mu(l) = v}{!l \mid \mu \longrightarrow v \mid \mu} \quad (\text{E-DEREFLOC})$$

32

Evaluation rules for function abstraction and application are augmented with stores, but don't do anything with them directly.

$$\frac{t_1 \mid \mu \longrightarrow t'_1 \mid \mu'}{t_1 \ t_2 \mid \mu \longrightarrow t'_1 \ t_2 \mid \mu'} \quad (\text{E-APP1})$$

$$\frac{t_2 \mid \mu \longrightarrow t'_2 \mid \mu'}{v_1 \ t_2 \mid \mu \longrightarrow v_1 \ t'_2 \mid \mu'} \quad (\text{E-APP2})$$

$$(\lambda x:T_{11}. t_{12}) \ v_2 \mid \mu \longrightarrow [x \mapsto v_2] t_{12} \mid \mu \quad (\text{E-APPABS})$$

33

Aside: garbage collection

Note that we are not modeling garbage collection — the store just grows without bound.

34

Aside: pointer arithmetic

We can't do any!

35

Store Typings

36

Typing Locations

Q: What is the *type* of a *location*?

37

Typing Locations

Q: What is the *type* of a *location*?

A: It depends on the store!

E.g., in the store $(l_1 \mapsto \text{unit}, l_2 \mapsto \text{unit})$, the term $!l_2$ has type `Unit`.

But in the store $(l_1 \mapsto \text{unit}, l_2 \mapsto \lambda x:\text{Unit}.x)$, the term $!l_2$ has type `Unit→Unit`.

37

Typing Locations — first try

Roughly:

$$\frac{\Gamma \vdash \mu(l) : T_1}{\Gamma \vdash l : \text{Ref } T_1}$$

38

Typing Locations — first try

Roughly:

$$\frac{\Gamma \vdash \mu(l) : T_1}{\Gamma \vdash l : \text{Ref } T_1}$$

More precisely:

$$\frac{\Gamma \mid \mu \vdash \mu(l) : T_1}{\Gamma \mid \mu \vdash l : \text{Ref } T_1}$$

I.e., typing is now a *four*-place relation (between contexts, stores, terms, and types).

38

Problem

However, this rule is not completely satisfactory. For one thing, it can make typing derivations very large!

E.g., if

$$\begin{aligned} (\mu = & l_1 \mapsto \lambda x:\text{Nat}. 999, \\ & l_2 \mapsto \lambda x:\text{Nat}. !l_1 (x), \\ & l_3 \mapsto \lambda x:\text{Nat}. !l_2 (x), \\ & l_4 \mapsto \lambda x:\text{Nat}. !l_3 (x), \\ & l_5 \mapsto \lambda x:\text{Nat}. !l_4 (x)), \end{aligned}$$

then how big is the typing derivation for $!l_5$?

39

Problem!

But wait... it gets worse. Suppose

$$\begin{aligned} (\mu = & l_1 \mapsto \lambda x:\text{Nat}. !l_2 x, \\ & l_2 \mapsto \lambda x:\text{Nat}. !l_1 x), \end{aligned}$$

Now how big is the typing derivation for $!l_2$?

40

Store Typings

Observation: The typing rules we have chosen for references guarantee that a given location in the store is *always* used to hold values of the *same* type.

These intended types can be collected into a *store typing* — a partial function from locations to types.

41

E.g., for

$$\mu = (l_1 \mapsto \lambda x:\text{Nat}. 999, \\ l_2 \mapsto \lambda x:\text{Nat}. !l_1 (!l_1 x), \\ l_3 \mapsto \lambda x:\text{Nat}. !l_2 (!l_2 x), \\ l_4 \mapsto \lambda x:\text{Nat}. !l_3 (!l_3 x), \\ l_5 \mapsto \lambda x:\text{Nat}. !l_4 (!l_4 x)),$$

A reasonable store typing would be

$$\Sigma = (l_1 \mapsto \text{Nat} \rightarrow \text{Nat}, \\ l_2 \mapsto \text{Nat} \rightarrow \text{Nat}, \\ l_3 \mapsto \text{Nat} \rightarrow \text{Nat}, \\ l_4 \mapsto \text{Nat} \rightarrow \text{Nat}, \\ l_5 \mapsto \text{Nat} \rightarrow \text{Nat})$$

42

Now, suppose we are given a store typing Σ describing the store μ in which we intend to evaluate some term t . Then we can use Σ to look up the types of locations in t instead of calculating them from the values in μ .

$$\frac{\Sigma(l) = T_1}{\Gamma \mid \Sigma \vdash l : \text{Ref } T_1} \quad (\text{T-LOC})$$

I.e., typing is now a four-place relation between contexts, *store typings*, terms, and types.

43

Final typing rules

$$\frac{\Sigma(l) = T_1}{\Gamma \mid \Sigma \vdash l : \text{Ref } T_1} \quad (\text{T-LOC})$$

$$\frac{\Gamma \mid \Sigma \vdash t_1 : T_1}{\Gamma \mid \Sigma \vdash \text{ref } t_1 : \text{Ref } T_1} \quad (\text{T-REF})$$

$$\frac{\Gamma \mid \Sigma \vdash t_1 : \text{Ref } T_{11}}{\Gamma \mid \Sigma \vdash !t_1 : T_{11}} \quad (\text{T-DEREF})$$

$$\frac{\Gamma \mid \Sigma \vdash t_1 : \text{Ref } T_{11} \quad \Gamma \mid \Sigma \vdash t_2 : T_{11}}{\Gamma \mid \Sigma \vdash t_1 := t_2 : \text{Unit}} \quad (\text{T-ASSIGN})$$

44

Q: Where do these store typings come from?

45

Q: Where do these store typings come from?

A: When we first typecheck a program, there will be no explicit locations, so we can use an empty store typing.

So, when a new location is created during evaluation,

$$\frac{l \notin \text{dom}(\mu)}{\text{ref } v_1 \mid \mu \longrightarrow l \mid (\mu, l \mapsto v_1)} \quad (\text{E-REFV})$$

we can extend the “current store typing” with the type of v_1 .

45

Safety

46

Preservation

First attempt: just add stores and store typings in the appropriate places.

Theorem (?): If $\Gamma \mid \Sigma \vdash t : T$ and $t \mid \mu \longrightarrow t' \mid \mu'$, then $\Gamma \mid \Sigma \vdash t' : T$.

47

Preservation

First attempt: just add stores and store typings in the appropriate places.

Theorem (?): If $\Gamma \mid \Sigma \vdash t : T$ and $t \mid \mu \longrightarrow t' \mid \mu'$, then $\Gamma \mid \Sigma \vdash t' : T$. **Wrong!**

Why is this wrong?

47

Preservation

First attempt: just add stores and store typings in the appropriate places.

Theorem (?): If $\Gamma \mid \Sigma \vdash t : T$ and $t \mid \mu \longrightarrow t' \mid \mu'$, then $\Gamma \mid \Sigma \vdash t' : T$. **Wrong!**

Why is this wrong?

Because Σ and μ here are not constrained to have anything to do with each other!

(Exercise: Construct an example that breaks this statement of preservation.)

47

Preservation

A store μ is said to be *well typed* with respect to a typing context Γ and a store typing Σ , written $\Gamma \mid \Sigma \vdash \mu$, if $\text{dom}(\mu) = \text{dom}(\Sigma)$ and $\Gamma \mid \Sigma \vdash \mu(l) : \Sigma(l)$ for every $l \in \text{dom}(\mu)$.

48

Preservation

A store μ is said to be *well typed* with respect to a typing context Γ and a store typing Σ , written $\Gamma \mid \Sigma \vdash \mu$, if $\text{dom}(\mu) = \text{dom}(\Sigma)$ and $\Gamma \mid \Sigma \vdash \mu(l) : \Sigma(l)$ for every $l \in \text{dom}(\mu)$.

Next attempt:

Theorem (?): If
 $\Gamma \mid \Sigma \vdash t : T$
 $t \mid \mu \longrightarrow t' \mid \mu'$
 $\Gamma \mid \Sigma \vdash \mu$
then $\Gamma \mid \Sigma \vdash t' : T$.

48

Preservation

A store μ is said to be *well typed* with respect to a typing context Γ and a store typing Σ , written $\Gamma \mid \Sigma \vdash \mu$, if $\text{dom}(\mu) = \text{dom}(\Sigma)$ and $\Gamma \mid \Sigma \vdash \mu(l) : \Sigma(l)$ for every $l \in \text{dom}(\mu)$.

Next attempt:

Theorem (?): If

$$\begin{array}{l} \Gamma \mid \Sigma \vdash t : T \\ t \mid \mu \longrightarrow t' \mid \mu' \\ \Gamma \mid \Sigma \vdash \mu \end{array}$$

then $\Gamma \mid \Sigma \vdash t' : T$.

Still wrong!

What's wrong now?

48

Preservation

A store μ is said to be *well typed* with respect to a typing context Γ and a store typing Σ , written $\Gamma \mid \Sigma \vdash \mu$, if $\text{dom}(\mu) = \text{dom}(\Sigma)$ and $\Gamma \mid \Sigma \vdash \mu(l) : \Sigma(l)$ for every $l \in \text{dom}(\mu)$.

Next attempt:

Theorem (?): If

$$\begin{array}{l} \Gamma \mid \Sigma \vdash t : T \\ t \mid \mu \longrightarrow t' \mid \mu' \\ \Gamma \mid \Sigma \vdash \mu \end{array}$$

then $\Gamma \mid \Sigma \vdash t' : T$.

Still wrong!

Creation of a new reference cell...

$$\frac{l \notin \text{dom}(\mu)}{\text{ref } v_1 \mid \mu \longrightarrow l \mid (\mu, l \mapsto v_1)} \quad (\text{E-REFV})$$

... breaks the correspondence between the store typing and the store.

48

Preservation (correct version)

Theorem: If

$$\begin{array}{l} \Gamma \mid \Sigma \vdash t : T \\ \Gamma \mid \Sigma \vdash \mu \\ t \mid \mu \longrightarrow t' \mid \mu' \end{array}$$

then, for **some** $\Sigma' \supseteq \Sigma$,

$$\begin{array}{l} \Gamma \mid \Sigma' \vdash t' : T \\ \Gamma \mid \Sigma' \vdash \mu'. \end{array}$$

49

Preservation (correct version)

Theorem: If

$$\begin{array}{l} \Gamma \mid \Sigma \vdash t : T \\ \Gamma \mid \Sigma \vdash \mu \\ t \mid \mu \longrightarrow t' \mid \mu' \end{array}$$

then, for **some** $\Sigma' \supseteq \Sigma$,

$$\begin{array}{l} \Gamma \mid \Sigma' \vdash t' : T \\ \Gamma \mid \Sigma' \vdash \mu'. \end{array}$$

Proof: Easy extension of the preservation proof for λ_{\rightarrow} .

49

Progress

Theorem: Suppose t is a closed, well-typed term (that is, $\emptyset \mid \Sigma \vdash t : T$ for some T and Σ). Then either t is a value or else, for any store μ such that $\emptyset \mid \Sigma \vdash \mu$, there is some term t' and store μ' with $t \mid \mu \longrightarrow t' \mid \mu'$.

50

Reading for next week

- ▶ Chapter 22 – Type Reconstruction
But do not pay too much attention to the \mathcal{X} sets.

51