

Foundations of Software Fall 2020

Week 9

Different Kinds of Maps

What is missing?

$$\begin{array}{lll} \textit{Term} & \rightarrow & \textit{Term} \quad (\lambda x.t) \\ \textit{Type} & \rightarrow & \textit{Term} \quad (\Lambda X.t) \end{array}$$

Different Kinds of Maps

What is missing?

<i>Term</i>	\rightarrow	<i>Term</i>	$(\lambda x.t)$
<i>Type</i>	\rightarrow	<i>Term</i>	$(\Lambda X.t)$
<i>Type</i>	\rightarrow	<i>Type</i>	???
<i>Term</i>	\rightarrow	<i>Type</i>	???

Agenda today:

- ▶ Type operators
- ▶ Dependent types

Type Operators and System F_ω

Type Operators

Example. Type operators in Scala:

```
type MkFun[T] = T => T  
val f: MkFun[Int] = (x: Int) => x
```

Type Operators

Example. Type operators in Scala:

```
type MkFun[T] = T => T  
val f: MkFun[Int] = (x: Int) => x
```

Type operators are functions at type-level.

$$\lambda X :: K. T$$

Type Operators

Example. Type operators in Scala:

```
type MkFun[T] = T => T  
val f: MkFun[Int] = (x: Int) => x
```

Type operators are functions at type-level.

$$\lambda X :: K. T$$

Two Problems:

- ▶ Type checking of type operators
- ▶ Equivalence of types

Kinding

Problem: avoid meaningless types, like *MkFun[Int, String]*.

Kinding


Problem: avoid meaningless types, like *MkFun[Int, String]*.

- * proper types, e.g. *Bool*, *Int* \rightarrow *Int*
- * \Rightarrow * type operators: map proper type to proper type
- * \Rightarrow * \Rightarrow * two-argument operators
- (* \Rightarrow *) \Rightarrow * type operators: map type operators to proper types

Kinding

Problem: avoid meaningless types, like *MkFun[Int, String]*.

- * proper types, e.g. *Bool*, *Int* \rightarrow *Int*
- * \Rightarrow * type operators: map proper type to proper type
- * \Rightarrow * \Rightarrow * two-argument operators
- (* \Rightarrow *) \Rightarrow * type operators: map type operators to proper types



Equivalence of Types

Problem: all the types below are equivalent

$$\begin{array}{lll} \text{Nat} \rightarrow \text{Bool} & \text{Nat} \rightarrow \text{Id Bool} & \text{Id Nat} \rightarrow \text{Id Bool} \\ \text{Id Nat} \rightarrow \text{Bool} & \text{Id}(\text{Nat} \rightarrow \text{Bool}) & \text{Id}(\text{Id}(\text{Id Nat} \rightarrow \text{Bool})) \end{array}$$

We need to introduce *definitional equivalence* relation on types, written $S \equiv T$. The most important rule is:

$$(\lambda X :: K.S) T \equiv [X \mapsto T]S \quad (\text{Q-APPABS})$$

And we need one typing rule:

$$\frac{\Gamma \vdash t : S \quad S \equiv T}{\Gamma \vdash t : T} \quad (\text{T-EQ})$$

First-class Type Operators

Scala supports passing type operators as argument:

```
def makeInt[F[_]](f: () => F[Int]): F[Int] = f()
```

```
makeInt[List]() => List[Int](3)
```

```
makeInt[Option]() => None
```

First-class type operators supports *polymorphism* for type operators, which enables more patterns in type-safe functional programming.

System F_ω

Formalizing first-class type operators leads to System F_ω :

$t ::= \dots$ *terms*
 $\lambda X :: K. t$ *type abstraction*

$T ::=$ *types*
 X *type variable*
 $T \rightarrow T$ *type of functions*
 $\forall X :: K. T$ *universal type*
 $\lambda X :: K. T$ *operator abstraction*
 $T \ T$ *operator application*

$K ::=$ *kinds*
 $*$ *kind of proper types*
 $K \Rightarrow K$ *kind of operators*

Dependent Types

Why Does It Matter?

Example 1. Track length of vectors in types:

$Vector \quad :: \quad Nat \rightarrow *$

$first \quad : \quad (n:Nat) \rightarrow Vector \ (n + 1) \rightarrow D$

$(x:S) \rightarrow T$ is called **dependent function type**. It is impossible to pass a vector of length 0 to the function *first*.

Why Does It Matter?

Example 1. Track length of vectors in types:

$$\begin{aligned} \text{Vector} &:: \text{Nat} \rightarrow * \\ \text{first} &: (n:\text{Nat}) \rightarrow \text{Vector } (n + 1) \rightarrow D \end{aligned}$$

$(x:S) \rightarrow T$ is called **dependent function type**. It is impossible to pass a vector of length 0 to the function *first*.

Example 2. Safe formatting for *sprintf*:

$$\text{sprintf} : (f:\text{Format}) \rightarrow \text{Data}(f) \rightarrow \text{String}$$
$$\begin{aligned} \text{Data}([]) &= \text{Unit} \\ \text{Data}("%d" :: cs) &= \text{Nat} * \text{Data}(cs) \\ \text{Data}("%s" :: cs) &= \text{String} * \text{Data}(cs) \\ \text{Data}(c :: cs) &= \text{Data}(cs) \end{aligned}$$

Dependent Function Type (a.k.a. Π Types)

A dependent function type is inhabited by *a dependent function*:

$$\lambda x:S.t \quad : \quad (x:S) \rightarrow T$$

Dependent Function Type (a.k.a. Π Types)

A dependent function type is inhabited by *a dependent function*:

$$\lambda x:S.t \quad : \quad (x:S) \rightarrow T$$

If T does not depend on x , it degenerates to function types:

$$(x:S) \rightarrow T = S \rightarrow T \quad \text{where } x \text{ does not appear free in } T$$

The Calculus of Constructions

The Calculus of Constructions: Syntax

$t ::=$

s

x

$\lambda x:t. t$

$t \ t$

$(x:t) \rightarrow t$

terms

sort

variable

abstraction

application

dependent type

$s ::=$

$*$

\square

sorts

sort of proper types

sort of kinds

$\Gamma ::=$

\emptyset

$\Gamma, x:T$

contexts

empty context

term variable binding

The semantics is the usual β -reduction.

The Calculus of Constructions: Typing

$$\vdash * : \square \text{ (T-AXIOM)} \qquad \frac{x:T \in \Gamma}{\Gamma \vdash x : T} \text{ (T-VAR)}$$

$$\frac{\Gamma \vdash S : s_1 \quad \Gamma, x:S \vdash t : T}{\Gamma \vdash \lambda x:S. t : (x:S) \rightarrow T} \text{ (T-ABS)}$$

$$\frac{\Gamma \vdash t_1 : (x:S) \rightarrow T \quad \Gamma \vdash t_2 : S}{\Gamma \vdash t_1 \ t_2 : [x \mapsto t_2] T} \text{ (T-APP)}$$

$$\frac{\Gamma \vdash S : s_1 \quad \Gamma, x:S \vdash T : s_2}{\Gamma \vdash (x:S) \rightarrow T : s_2} \text{ (T-PI)}$$

$$\frac{\Gamma \vdash t : T \quad T \equiv T' \quad \Gamma \vdash T' : s}{\Gamma \vdash t : T'} \text{ (T-CONV)}$$

The equivalence relation $T \equiv T'$ is based on β -reduction.

Four Kinds of Lambdas

Example	Type
$\lambda x:\mathbb{N}.x + 1$	$\mathbb{N} \rightarrow \mathbb{N}$
$\lambda f:\mathbb{N} \rightarrow \mathbb{N}.f\ x$	$(\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N}$

Four Kinds of Lambdas

Example	Type
$\lambda x:\mathbb{N}.x + 1$	$\mathbb{N} \rightarrow \mathbb{N}$
$\lambda f:\mathbb{N} \rightarrow \mathbb{N}.f\ x$	$(\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N}$
$\lambda X:*. \lambda x:X. x$	$(X:*) \rightarrow X \rightarrow X$
$\lambda F:* \rightarrow *. \lambda x:F\ \mathbb{N}. x$	$(F:* \rightarrow *) \rightarrow (F\ \mathbb{N}) \rightarrow (F\ \mathbb{N})$

Four Kinds of Lambdas

Example	Type
$\lambda x:\mathbb{N}.x + 1$	$\mathbb{N} \rightarrow \mathbb{N}$
$\lambda f:\mathbb{N} \rightarrow \mathbb{N}.f\ x$	$(\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N}$
$\lambda X:*. \lambda x:X. x$	$(X:*) \rightarrow X \rightarrow X$
$\lambda F:* \rightarrow *. \lambda x:F\ \mathbb{N}. x$	$(F:* \rightarrow *) \rightarrow (F\ \mathbb{N}) \rightarrow (F\ \mathbb{N})$
$\lambda X:*. X$	$* \rightarrow *$
$\lambda F:* \rightarrow *. F\ \mathbb{N}$	$(* \rightarrow *) \rightarrow *$

Four Kinds of Lambdas

Example	Type
$\lambda x:\mathbb{N}.x + 1$	$\mathbb{N} \rightarrow \mathbb{N}$
$\lambda f:\mathbb{N} \rightarrow \mathbb{N}.f\ x$	$(\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N}$
$\lambda X:*. \lambda x:X. x$	$(X:*) \rightarrow X \rightarrow X$
$\lambda F:* \rightarrow *. \lambda x:F\ \mathbb{N}. x$	$(F:* \rightarrow *) \rightarrow (F\ \mathbb{N}) \rightarrow (F\ \mathbb{N})$
$\lambda X:*. X$	$* \rightarrow *$
$\lambda F:* \rightarrow *. F\ \mathbb{N}$	$(* \rightarrow *) \rightarrow *$
$\lambda n:\mathbb{N}. \text{Vec}\ n$	$\mathbb{N} \rightarrow *$
$\lambda f:\mathbb{N} \rightarrow \mathbb{N}. \text{Vec}\ (f\ 6)$	$(\mathbb{N} \rightarrow \mathbb{N}) \rightarrow *$

Strong Normalization

Given the following β -reduction rules

$$\frac{t_1 \longrightarrow t'_1}{\lambda x: T_1. t_1 \longrightarrow \lambda x: T_1. t'_1} \quad (\beta\text{-ABS})$$

$$\frac{t_1 \longrightarrow t'_1}{t_1 \ t_2 \longrightarrow t'_1 \ t_2} \quad (\beta\text{-APP1})$$

$$\frac{t_2 \longrightarrow t'_2}{t_1 \ t_2 \longrightarrow t_1 \ t'_2} \quad (\beta\text{-APP2})$$


$$(\lambda x: T_1. t_1) t_2 \longrightarrow [x \mapsto t_2] t_1 \quad (\beta\text{-APPAbs})$$

Theorem [Strong Normalization]: if $\Gamma \vdash t : T$, then there is no infinite sequence of terms t_i such that $t = t_1$ and $t_i \longrightarrow t_{i+1}$.

Pure Type Systems

$$\frac{\Gamma \vdash S : s_i \quad \Gamma, x:S \vdash T : s_j}{\Gamma \vdash (x:S) \rightarrow T : s_j} \quad (\text{T-PI})$$

System	(s_i, s_j)			
λ_{\rightarrow}	{	$(*, *)$		}
λP	{	$(*, *)$,	$(*, \square)$	}
F	{	$(*, *)$,	$(\square, *)$	}
F^ω	{	$(*, *)$,	$(\square, *)$ (\square, \square)	}
CC	{	$(*, *)$,	$(*, \square)$ $(\square, *)$ (\square, \square)	}



The Lambda Cube

$$\lambda_{\rightarrow} \longrightarrow F \longrightarrow F^{\omega} \longrightarrow CC$$

Dependent Types in Coq

Proof Assistants

Dependent type theories are at the foundation of proof assistants, like Coq, Agda, etc.

By *Curry-Howard Correspondence*

- ▶ proofs \longleftrightarrow programs
- ▶ propositions \longleftrightarrow types

Coq is based on *Calculus of Inductive Construction*, which is an extension of CC with inductive definition.

Proof Assistants

Dependent type theories are at the foundation of proof assistants, like Coq, Agda, etc.

By *Curry-Howard Correspondence*

- ▶ proofs \longleftrightarrow programs
- ▶ propositions \longleftrightarrow types

Coq is based on *Calculus of Inductive Construction*, which is an extension of CC with inductive definition.

Two impactful projects based on Coq:

- ▶ CompCert: certified C compiler
- ▶ Mechanized proof of 4-color theorem

Coq 101 - inductive definitions and recursion

```
1 Inductive nat : Type :=  
2   | 0  
3   | S (n : nat).
```

Coq 101 - inductive definitions and recursion

```
1 Inductive nat : Type :=  
2   | 0  
3   | S (n : nat).
```

```
1 Fixpoint double (n : nat) : nat :=  
2   match n with  
3     | 0 => 0  
4     | S n' => S (S (double n'))  
5   end.
```

Recursion has to be structural.

Coq 101 - inductive definitions and recursion

```
1 Inductive nat : Type :=  
2   | 0  
3   | S (n : nat).
```

```
1 Fixpoint double (n : nat) : nat :=  
2   match n with  
3     | 0 => 0  
4     | S n' => S (S (double n'))  
5   end.
```

Recursion has to be structural.

```
1 Inductive even : nat -> Prop :=  
2   | even0 : even 0  
3   | evenS : forall x:nat, even x -> even (S (S x)).
```

Coq 101 - proofs

```
1 Definition even_prop := forall x:nat, even (double x).  
2  
3 Fixpoint even_proof(x: nat): even (double x) :=  
4   match x with  
5     | 0      => even0  
6     | S n'   => evenS (double n') (even_proof n')  
7   end.  
8  
9 Check even_proof : even_prop.
```

Coq 101 - proofs

```
1 Definition even_prop := forall x:nat, even (double x).
2
3 Fixpoint even_proof(x: nat): even (double x) :=
4   match x with
5   | 0      => even0
6   | S n'   => evenS (double n') (even_proof n')
7   end.
8
9 Check even_proof : even_prop.
```

The 2nd branch has the type $\text{even } S (S (\text{double } n'))$, and Coq knows by normalizing the types:

$$\text{even } S (S (\text{double } n')) \equiv_{\beta} \text{even } (\text{double } (S n'))$$

Recap: Curry-Howard Correspondence

Propositions as types in the context of intuitionistic logic.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$

Recap: Curry-Howard Correspondence

Propositions as **types** in the context of **intuitionistic logic**.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$

Recap: Curry-Howard Correspondence

Propositions as types in the context of intuitionistic logic.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$
$A \rightarrow B$	$t : A \rightarrow B$

Recap: Curry-Howard Correspondence

Propositions as *types* in the context of *intuitionistic logic*.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$
$A \rightarrow B$	$t : A \rightarrow B$
$\neg A$	$t : A \rightarrow \textit{False}$

Recap: Curry-Howard Correspondence

Propositions as *types* in the context of *intuitionistic logic*.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$
$A \rightarrow B$	$t : A \rightarrow B$
$\neg A$	$t : A \rightarrow \textit{False}$
\perp	$t : \textit{False}$

Recap: Curry-Howard Correspondence

Propositions as types in the context of intuitionistic logic.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$
$A \rightarrow B$	$t : A \rightarrow B$
$\neg A$	$t : A \rightarrow \text{False}$
\perp	$t : \text{False}$
$\forall x:A. B$	$t : (x : A) \rightarrow B$

Recap: Curry-Howard Correspondence

Propositions as *types* in the context of *intuitionistic logic*.

Proposition	Term & Type
$A \wedge B$	$t : (A, B)$
$A \vee B$	$t : A + B$
$A \rightarrow B$	$t : A \rightarrow B$
$\neg A$	$t : A \rightarrow \text{False}$
\perp	$t : \text{False}$
$\forall x:A. B$	$t : (x : A) \rightarrow B$
$\exists x:A. B$	$t : (x:A, B)$

Curry-Howard correspondence in Coq

```
1 Inductive and (A B:Prop) : Prop :=  
2   conj : A -> B -> A /\ B  
3 where "A /\ B" := (and A B) : type_scope.
```

Curry-Howard correspondence in Coq

```
1 Inductive and (A B:Prop) : Prop :=  
2   conj : A -> B -> A /\ B  
3 where "A /\ B" := (and A B) : type_scope.
```

```
1 Inductive or (A B:Prop) : Prop :=  
2   | or_introl : A -> A \/ B  
3   | or_intror : B -> A \/ B  
4 where "A \/ B" := (or A B) : type_scope.
```

Curry-Howard correspondence in Coq

```
1 Inductive and (A B:Prop) : Prop :=  
2   conj : A -> B -> A /\ B  
3 where "A /\ B" := (and A B) : type_scope.
```

```
1 Inductive or (A B:Prop) : Prop :=  
2   | or_introl : A -> A \/ B  
3   | or_intror : B -> A \/ B  
4 where "A \/ B" := (or A B) : type_scope.
```

```
1 Inductive False : Prop :=.
```

Curry-Howard correspondence in Coq

```
1 Inductive and (A B:Prop) : Prop :=  
2   conj : A -> B -> A /\ B  
3 where "A /\ B" := (and A B) : type_scope.
```

```
1 Inductive or (A B:Prop) : Prop :=  
2   | or_introl : A -> A \/ B  
3   | or_intror : B -> A \/ B  
4 where "A \/ B" := (or A B) : type_scope.
```

```
1 Inductive False : Prop :=.
```

```
1 Definition not (A:Prop) := A -> False.  
2 Notation "~ x" := (not x) : type_scope.
```

Curry-Howard correspondence in Coq - continued

```
1 Notation "A -> B" := (forall (_ : A), B) : type_scope.  
2 Definition iff (A B:Prop) := (A -> B) /\ (B -> A).  
3 Notation "A <-> B" := (iff A B) : type_scope.
```

Curry-Howard correspondence in Coq - continued

```
1 Notation "A -> B" := (forall (_ : A), B) : type_scope.  
2 Definition iff (A B:Prop) := (A -> B) /\ (B -> A).  
3 Notation "A <-> B" := (iff A B) : type_scope.
```

```
1 Inductive ex (A:Type) (P:A -> Prop) : Prop :=  
2   ex_intro : forall x:A, P x -> ex (A:=A) P.  
3  
4 Notation "'exists' x .. y , p" :=  
5   (ex (fun x => .. (ex (fun y => p)) ..)) : type_scope.
```


Curry-Howard correspondence in Coq - continued

```
1 Notation "A -> B" := (forall (_ : A), B) : type_scope.  
2 Definition iff (A B:Prop) := (A -> B) /\ (B -> A).  
3 Notation "A <-> B" := (iff A B) : type_scope.
```

```
1 Inductive ex (A:Type) (P:A -> Prop) : Prop :=  
2   ex_intro : forall x:A, P x -> ex (A:=A) P.  
3  
4 Notation "'exists' x .. y , p" :=  
5   (ex (fun x => .. (ex (fun y => p)) ..)) : type_scope.
```

```
1 Inductive eq (A:Type) (x:A) : A -> Prop :=  
2   eq_refl : x = x :>A  
3  
4 Notation "x = y" := (eq x y) : type_scope.
```

The equivalence between LEM and DNE

In **intuitionistic logics**, the *law of excluded middle* (LEM) and the *law of double negation* (DNE) do not hold.

▶ LEM: $\forall P. P \vee \neg P$

▶ DNE: $\forall P. \neg\neg P \rightarrow P$

By curry-howard correspondence, there are no terms that inhabit the types above.

The equivalence between LEM and DNE

In **intuitionistic logics**, the *law of excluded middle* (LEM) and the *law of double negation* (DNE) do not hold.

▶ LEM: $\forall P. P \vee \neg P$

▶ DNE: $\forall P. \neg\neg P \rightarrow P$

By curry-howard correspondence, there are no terms that inhabit the types above.

However, $\forall P. P \rightarrow \neg\neg P$ can be proved.

The equivalence between LEM and DNE

In **intuitionistic logics**, the *law of excluded middle* (LEM) and the *law of double negation* (DNE) do not hold.

▶ LEM: $\forall P. P \vee \neg P$

▶ DNE: $\forall P. \neg\neg P \rightarrow P$

By curry-howard correspondence, there are no terms that inhabit the types above.

However, $\forall P. P \rightarrow \neg\neg P$ can be proved. **How?**

The equivalence between LEM and DNE

In **intuitionistic logics**, the *law of excluded middle* (LEM) and the *law of double negation* (DNE) do not hold.

► LEM: $\forall P. P \vee \neg P$

► DNE: $\forall P. \neg\neg P \rightarrow P$

By curry-howard correspondence, there are no terms that inhabit the types above.

However, $\forall P. P \rightarrow \neg\neg P$ can be proved. **How?**

We will prove that LEM is equivalent to DNE:

- 1 **Definition** LEM: Prop := forall P: Prop, P \vee \neg P.
- 2 **Definition** DNE: Prop := forall P: Prop, $\neg\neg$ P \rightarrow P.
- 3 **Definition** LEM_DNE_EQ: Prop := LEM \leftrightarrow DNE.

LEM \rightarrow DNE

```
1 Definition LEM_To_DNE :=
2   fun (lem: forall P : Prop, P \ / ~ P) (Q:Prop) (q: ~~Q)
3     =>
4     match lem Q with
5     | or_introl l =>
6       l
7     | or_intror r =>
8       match (q r) with end
9     end.
10
11 Check LEM_To_DNE : LEM -> DNE.
```

DNE \rightarrow LEM

```
1 Definition DNE_To_LEM :=
2   fun (dne: forall P : Prop, ~~P -> P) (Q:Prop) =>
3     (dne (Q \ / ~ Q))
4     (fun H: ~(Q \ / ~Q) =>
5       let nq := (fun q: Q => H (or_introl q))
6       in H (or_intror nq)
7     ).
8
9 Check DNE_To_LEM : DNE -> LEM.
10
11 Definition proof := conj LEM_To_DNE DNE_To_LEM.
12 Check proof : LEM <-> DNE.
```

Dependent Types in Programming Languages

Despite the huge success in proof assistants, its adoption in programming languages is limited.

- ▶ Scala supports *path-dependent types* and *literal types*.
- ▶ Dependent Haskell is proposed by researchers.

Dependent Types in Programming Languages

Despite the huge success in proof assistants, its adoption in programming languages is limited.

- ▶ Scala supports *path-dependent types* and *literal types*.
- ▶ Dependent Haskell is proposed by researchers.

Challenge: the decidability of type checking.

Problem with Type Checking: Vector Again

Value constructors:

$$\begin{aligned} \text{Vec} &: \mathbb{N} \rightarrow * \\ \text{nil} &: \text{Vec } 0 \\ \text{cons} &: (n:\mathbb{N}) \rightarrow \mathbb{N} \rightarrow \text{Vec } n \rightarrow \text{Vec } n + 1 \end{aligned}$$

Appending vectors:

$$\begin{aligned} \text{append} &: (m:\mathbb{N}) \rightarrow (n:\mathbb{N}) \rightarrow \text{Vec } m \rightarrow \text{Vec } n \rightarrow \text{Vec } (m + n) \\ \text{append} &= \lambda m:\mathbb{N}. \lambda n:\mathbb{N}. \lambda l:\text{Vec } m. \lambda t:\text{Vec } n. \\ &\quad \text{match } l \text{ with} \\ &\quad | \text{nil} \Rightarrow t \\ &\quad | \text{cons } r \times y \Rightarrow \text{cons } (r + n) \times (\text{append } r \ n \ y \ t) \end{aligned}$$

Question: How does the type checker know $r + 1 + n = r + n + 1$?