



COMP 6721

Applied Artificial Intelligence Project Report

Implementation of Naïve Bayes Algorithm used for Email Classification

GROUP: HA-G10	
Full Names	ID
Che Shao Chen	40055392
Ufuoma Ubor	40072909
Yunan Zhang	40105680

Submitted to: Dr. Rene Witte

Abbreviations:

TP – True Positive

FP – False Positive

TN – True Negative

FN – False Negative

- **Analysis**

An important validation factor in Machine Learning classification is the performance of a model, a good model must have a certain acceptable level of accuracy. Using accuracy for performance measure is not sufficient enough as it can sometimes be misleading, e.g. a model might be very bad in predicting a certain category but its accuracy can still be very high. For this reason, we computed other metrics like precision, recall and f-measure. Table 1 below display the performance for classifying spam and ham using the Naïve Bayes algorithm we implemented from scratch. The accuracies for classifying spam and ham are 89% and 99% respectively, precision of 100% for both, recall of 89% and 99% respectively, and f-measure of 94% and 99 % respectively.

	Spam	Ham	Formula
Accuracy	0.89	0.99	$A = (TP+TN) / (TP+FP+TN+FN)$
Precision	1.0	1.0	$P = TP / (TP+FP)$
Recall	0.89	0.99	$P = TP / (TP+FN)$
F1-measure	0.94	0.99	$F1\text{-measure} = 2PR / (P+R)$

Table 1: Performance results for classification

After prediction, the expected labels were separated into the two categories (spam, ham) with their respective predicted labels. After the separation we compute the accuracy, precision, recall and f1-measure for each category. Table 2, 3 shows the confusion matrix for spam and ham respectively. For the spam category, the classifier was able to correctly predict 356 test samples as spam (true positive) and misclassified 44 as ham (false negative).

	Expected	
Predicted	Spam	Ham
Spam	356	0
Ham	44	0

Table 2: Confusion matrix for spam category

	Expected	
Predicted	Ham	Spam
Ham	394	0
Spam	6	0

Table 3: Confusion matrix for ham category

On the other hand, the classifier correctly predicted 394 test samples as ham but wrongly predicted 6 as spam.

Table 4 shows the joint confusion matrix for both categories with which we computed the joint accuracy, precision, recall and f1-measure to be 94%, 90%, 99%, and 94% respectively.

	Expected	
Predicted	Ham	Spam
Ham	394	44
Spam	6	356

Table 4: Joint confusion matrix for ham category

References

- [1] Aisha, J. (2018, August 26). Unfolding Naïve Bayes from Scratch.
- [2] Praveen, D. (2018, December 18). An Introduction to Bag of Words And How To Implement it in Python for NLP
- [3] <https://stackoverflow.com/questions/12995937/count-all-values-in-a-matrix-greater-than-a-value>