


# CST463 - WEB PROGRAMMING



# Module 4 (CO3, Cognitive Knowledge Level: Apply)

---

- ▶ Form processing and Business Logic
- ▶ Cookies- Sessions
- ▶ MySQL Integration-Connecting to MySQL with PHP
- ▶ Performing CREATE, DELETE, INSERT, SELECT and UPDATE operations on MySQL table
- ▶ Working with MySQL data
- ▶ Reading from Database-Dynamic Content.

# Form processing and Business Logic

# Form processing

- ▶ Superglobal arrays are associative arrays predefined by PHP that hold variables acquired from user input, the environment or the web server, and are accessible in any variable scope. Some of PHP's superglobal arrays

| Variable name          | Description   |
|------------------------|---|
| <code>\$_SERVER</code> | Data about the currently running server.            |
| <code>\$_ENV</code>    | Data about the client's environment.                |
| <code>\$_GET</code>    | Data sent to the server by a get request.           |
| <code>\$_POST</code>   | Data sent to the server by a post request.          |
| <code>\$_COOKIE</code> | Data contained in cookies on the client's computer. |
| <code>\$GLOBALS</code> | Array containing all global variables.              |

- ▶ The arrays `$_GET` and `$_POST` retrieve information sent to the server by HTTP get and post requests, respectively, making it possible for a script to have access to this data when it loads another page

# Form processing

---

- ▶ when PHP is used for form handling, the PHP script is embedded in an XHTML document, like other uses of PHP.
- ▶ The recommended approach is to use the implicit arrays for form values, `$_POST` and `$_GET`.
- ▶ These arrays have keys that match the form element names and values that were input by the client.
- ▶ For example, if a form has a text box named `phone` and the form method is `POST`, the value of that element is available in the PHP script as follows:

`$_POST["phone"]`

- ▶ The built-in `$_GET` function is used to collect values from a form sent with `method="get"`.
- ▶ Information sent from a form with the `GET` method is visible to everyone and has limits on the amount of information to send (max. 100 characters).

# Form processing \$\_POST Function

```
<?php
if(isset($_POST['submit']))
{
if(($_POST["name"]!="")||($_POST["age"]!=""))
{
    echo "Welcome ". $_POST['name']. "<br />";
    echo "You are ". $_POST['age']. " years old.";
    exit();
}
else
{
    print "invalid";
}
}
else
{
?>
```

```
<html><body>
    <form method = "POST" action="testform.php">
        Name: <input type = "text" name = "name" />
        Age: <input type = "text" name = "age" />
        <input type="submit" name="submit" value="Submit">
    </form>
</body>
</html><?php}>
```

localhost/dashboard/smith/testform.php

Name:  Age:

localhost/dashboard/smith/testform.php

Welcome smitha  
You are 40 years old.

localhost/dashboard/smith/testform.php

Name:  Age:

localhost/

invalid

# Form processing \$\_GET Function

```
<?php
if(isset($_GET['submit']))
{
if(($_GET["name"]!="")||($_GET["age"]!=""))
{
    echo "Welcome ". $_GET['name']. "<br />";
    echo "You are ". $_GET['age']. " years old.";
    exit();
}else
{print "invalid"; }
}
else
{
?>
<html><body>
    <form method = "GET" action="testform.php">
        Name: <input type = "text" name = "name" />
        Age: <input type = "text" name = "age" />
        <input type="submit" name="submit" value="Submit">
    </form>
</body></html>
<?php
}??|
```

← → ↻ ⓘ localhost/dashboard/smith/testform.php

Name:  Age:

← → ↻ ⓘ localhost/

invalid

← → ↻ ⓘ localhost/dashboard/smith/testform.php

Name:  Age:

← → ↻ ⓘ localhost/dashboard/smith/testform.php?name=smitha&age=40&submit=Submit

Welcome smitha  
You are 40 years old.



---

```
<!DOCTYPE html>
```

```
<!-- Fig. 19.13: form.html -->
```

```
<!-- HTML form for gathering user input. -->
```

```
<html>
```

```
  <head>
```

```
    <meta charset = "utf-8">
```

```
    <title>Sample Form</title>
```

```
    <style type = "text/css">
```

```
      label { width: 5em; float: left; }
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <h1>Registration Form</h1>
```

```
    <p>Please fill in all fields and click Register.</p>
```

```
    <!-- post form data to form.php -->
```

```
    <form method = "post" action = "form.php">
```

```
      <h2>User Information</h2>
```

```
      <!-- create four text boxes for user input -->
```

```
      <div><label>First name:</label>
```

```
        <input type = "text" name = "fname"></div>
```

```
      <div><label>Last name:</label>
```

```
        <input type = "text" name = "lname"></div>
```

```
      <div><label>Email:</label>
```

```
        <input type = "text" name = "email"></div>
```

```
      <div><label>Phone:</label>
```

```
        <input type = "text" name = "phone"
```

```
          placeholder = "(555) 555-5555"></div>
```

```
      </div>
```

```
      <h2>Publications</h2>
```

```
      <p>Which book would you like information about?</p>
```

```
      <!-- create drop-down list containing book names -->
```

```
      <select name = "book">
```

```
        <option>Internet and WWW How to Program</option>
```

---



```

<option>C++ How to Program</option>
<option>Java How to Program</option>
<option>Visual Basic How to Program</option>
</select>

```

```

<h2>Operating System</h2>
<p>Which operating system do you use?</p>

```

```

<!-- create five radio buttons -->
<p><input type = "radio" name = "os" value = "Windows"
    checked>Windows
    <input type = "radio" name = "os" value = "Mac OS X">Mac OS
    <input type = "radio" name = "os" value = "Linux">Linux
    <input type = "radio" name = "os" value = "Other">Other</p>

```

```

<!-- create a submit button -->
<p><input type = "submit" name = "submit" value = "Register"></p>
</form>

```

```

</body>

```

```

</html>

```

The form is filled out  
with an incorrect  
phone number

Sample Form

localhost/ch19/fig19\_13-14/form.html

## Registration Form

Please fill in all fields and click Register.

### User Information

First name:

Last name:

Email:

Phone:

### Publications

Which book would you like information about?

### Operating System

Which operating system do you use?

☒ Windows ☐ Mac OS X ☐ Linux ☐ Other

```
<!DOCTYPE html>
```

```
<!-- Fig. 19.14: form.php -->
```

```
<!-- Process information sent from form.html. -->
```

```
<html>
```

```
  <head>
```

```
    <meta charset = "utf-8">
```

```
    <title>Form Validation</title>
```

```
    <style type = "text/css">
```

```
      p      { margin: 0px; }
```

```
      .error  { color: red }
```

```
      p.head  { font-weight: bold; margin-top: 10px; }
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <?php
```

```
      // determine whether phone number is valid and print
```

```
      // an error message if not
```

```
      if (!preg_match( "/^\([0-9]{3}\) [0-9]{3}-[0-9]{4}$/",  
        $_POST["phone"]))
```

```
      {
```

```
        print( "<p class = 'error'>Invalid phone number</p>
```

```
        <p>A valid phone number must be in the form
```

```
        (555) 555-5555</p><p>Click the Back button,
```

```
        enter a valid phone number and resubmit.</p>
```

```
        <p>Thank You.</p></body></html>" );
```

```
        die(); // terminate script execution
```


```
      }
```

```
    ?><!-- end PHP script -->
```


```
    <p>Hi <?php print( $_POST["fname"] ); ?>. Thank you for  
    completing the survey. You have been added to the
```

```
<?php print( $_POST["book"] ); ?>mailing list.</p>
<p class = "head">The following information has been saved
in our database:</p>
<p>Name: <?php print( $_POST["fname"] );
print( $_POST["lname"] ); ?></p>
<p>Email: <?php print( "$email" ); ?></p>
<p>Phone: <?php print( "$phone" ); ?></p>
<p>OS: <?php print( $_POST["os"] ); ?></p>
<p class = "head">This is only a sample form.
You have not been added to a mailing list.</p>
</body>
</html>
```

a) Submitting the form in Fig. 19.13 redirects the user to `form.php`, which gives appropriate instructions if the phone number is in an incorrect format



b) The results of `form.php` after the user submits the form in Fig. 19.13 with a phone number in a valid format



---

Use business logic to ensure that invalid information is not stored in databases. Validate important or sensitive form data on the server, since JavaScript may be disabled by the client.


Some data, such as passwords, must always be validated on the server side

---




# Simple PHP Program to generate a simple calculator

- ▶ To find basic mathematical operations on two numbers




A screenshot of a web browser window. The address bar shows 'localhost/dashboard/smith/sum.php'. The page content includes the instruction 'Insert two numbers in the form and hit submit button'. Below this, there are two input fields: 'First number : 16' and 'Second number: 2'. A 'Submit' button is located at the bottom of the form.



A screenshot of a web browser window showing the results of the calculator. The address bar shows 'localhost/dashboard/smith/sum.php'. The page content displays the following results:

- The sum of the two numbers 16 and 2 is 18
- The difference of the two numbers is 14
- The product of the two numbers is 32
- The difference of the two numbers is 8
- The sqrt of the number 1 is 4
- The power of the number 1 is 256

# Simple PHP Program to generate a simple calculator

C: > xampp > htdocs > dashboard > smith >  sum.php

```
1  <?php
2  if(isset($_POST['submit']))
3  {   $num1 = $_POST['num1'];
4      $num2 = $_POST['num2'];
5      $sum = $num1 + $num2;
6      $diff = $num1 - $num2;
7      $mul = $num1 * $num2;
8      $div = $num1 / $num2;
9      $sq=sqrt($num1);
10     $po=pow($num1,$num2);
11     echo "<br/>The sum of the two numbers" . $num1 . " and " . $num2 . " is " . $sum;
12     echo "<br/>The difference of the two numbers is " . $diff;
13     echo "<br/>The product  of the two numbers is " . $mul;
14     echo "<br/>The difference of the two numbers is " . $div;
15     echo "<br/>The sqrt of the  number1 is " . $sq;
16     echo "<br/>The power of the  number1 is " . $po;
17 }
18 else
19 {
20 ?>
```

# Simple PHP Program to generate a simple calculator

- ▶ To find basic mathematical operations on two numbers

[illegible]



# Modified PHP Program to generate a simple calculator

- ▶ To find basic mathematical operations on two numbers

## PHP - Simple Calculator

|          |               |
|----------|---------------|
| 16       | First Number  |
| 2        | Second Number |
| 18       | Result        |
| Add      | Subtract      |
| Multiply | Divide        |

|          |               |
|----------|---------------|
| 16       | First Number  |
| 2        | Second Number |
| 32       | Result        |
| Add      | Subtract      |
| Multiply | Divide        |

|          |               |
|----------|---------------|
| 16       | First Number  |
| 2        | Second Number |
| 14       | Result        |
| Add      | Subtract      |
| Multiply | Divide        |

|          |               |
|----------|---------------|
| 16       | First Number  |
| 2        | Second Number |
| 8        | Result        |
| Add      | Subtract      |
| Multiply | Divide        |

C: > xampp > htdocs > dashboard > smith > 🐘 calculator.php

```
1  <?php
2  if(isset($_POST["operator"]))
3  {$first_num = $_POST['first_num'];
4  $second_num = $_POST['second_num'];
5  $operator = $_POST['operator'];
6  $result = '';}
7  else
8  {$first_num = "";$second_num = "";$operator = "";$result = '';}
9  if (is_numeric($first_num) && is_numeric($second_num)) {
10     switch ($operator) {
11         case "Add":
12             $result = $first_num + $second_num;
13             break;
14         case "Subtract":
15             $result = $first_num - $second_num;
16             break;
17         case "Multiply":
18             $result = $first_num * $second_num;
19             break;
20         case "Divide":
21             $result = $first_num / $second_num;
22     }
23 }?>
```

# Modified PHP Program to generate a simple calculator

```
25 <html><body><h1>PHP - Simple Calculator</h1>
26     <form action="calculator.php" method="post" >
27         <p>
28             <input type="number" name="first_num" id="first_num" required="required"
29             value="<?php echo $first_num; ?>" /> <b>First Number</b>
30         </p>
31         <p>
32             <input type="number" name="second_num" id="second_num" required="required"
33             value="<?php echo $second_num; ?>" /> <b>Second Number</b>
34         </p>
35         <p>
36             <input readonly="readonly" name="result" value="<?php echo $result; ?>">
37             <b>Result</b>
38         </p>
39         <input type="submit" name="operator" value="Add" />
40         <input type="submit" name="operator" value="Subtract" />
41         <input type="submit" name="operator" value="Multiply" />
42         <input type="submit" name="operator" value="Divide" />
43     </form>
44 </body></html>
```

# Cookies and Session

# Cookies

---

- ▶ A cookie is often used to identify a user.
  - ▶ A cookie is a piece of information that's stored by a server in a text file on a client's computer to maintain information about the client during and between browsing sessions.
  - ▶ Each time the same computer requests a page with a browser, it will send the cookie too.
  - ▶ With PHP, you can both create and retrieve cookie values.
  - ▶ The server is given this information when the browser makes subsequent requests for Web resources from the server.
  - ▶ Cookies allow the server to present a customized interface to the client.
  - ▶ They also allow the server to connect requests from a particular client to previous requests, thereby connecting sequences of requests into a session.
-

# Cookies

---

- ▶ A cookie is a small object of information that consists of a name and a textual value.
  - ▶ A cookie is created by some software system on the server.
  - ▶ A message from a browser to a server is a request; a message from a server to a browser is a response. The header part of an HTTP communication can include cookies. So, every request sent from a browser to a server, and every response from a server to a browser, can include one or more cookies.
  - ▶ At the time it is created, a cookie is assigned a lifetime. When the time a cookie has existed reaches its associated lifetime, the cookie is deleted from the browser's host machine.
  - ▶ a particular cookie is information that is exchanged exclusively between one specific browser and one specific server.
-

# Cookies- setcookie function

---

- ▶ A cookie is set in PHP with the setcookie function. This function takes one or more parameters.

**`setcookie(name, value, expire, path)`**

- ▶ The first parameter, which is mandatory, is the cookie's name given as a string. The second, if present, is the new value for the cookie, also a string. If the value is absent, setcookie undefines the cookie. The third parameter, when present, is the expiration time in seconds for the cookie, given as an integer.
- ▶ The default value for the expiration time is zero, which specifies that the cookie is destroyed at the end of the current session

**`setcookie("valid", "true", time() + 86400);`**

- ▶ This call creates a cookie named "valid" whose value is "true" and whose lifetime is one day (86,400 is the number of seconds in a day).
-



# Cookies- setcookie function

```
1  <?php
2  $cookie_name = "user";
3  $cookie_value = "admin123";
4  setcookie($cookie_name, $cookie_value, time() + (86400*30), "/");
5  ?>
6  <html>
7      <body>
8          <?php
9              if(!isset($_COOKIE[$cookie_name]))
10             {
11                 echo "Cookie named ". $cookie_name ."is not set!";
12             }
13             else
14             {
15                 echo "Cookie $cookie_name is set!<br>";
16                 echo "Value is: ".$_COOKIE[$cookie_name];
17             }
18             ?>
19         </body>
20     </html>
```

localhost/dashboard/smith/cookieTest.php


Advance your skills... CSE-new LMS SJCE...

Cookie user is set!  
Value is: admin123

# Cookies- setcookie-delete function

- ▶ The example creates a cookie named "user" with the value "admin123".
- ▶ The cookie will expire after 30 days ( $86400 * 30$ ).
- ▶ The "/" means that the cookie is available in entire website (otherwise, select the directory you prefer).
- ▶ retrieve the value of the cookie "user" (using the global variable `$_COOKIE`).
- ▶ use the `isset()` function to find out if the cookie is set:
- ▶ To delete a cookie, use `setcookie()` function with an expiration date in the past:
- ▶ Example

```
1 <?php
2
3 setcookie("user","", time() -3600);
4 ?>
5 <html>
6     <body>
7         <?php
8             echo "Cookie 'user' is deleted.";
9         ?>
10    </body>
11 </html>
```



# Cookies- setcookie function

---

- ▶ In PHP, **cookie values are treated much like form values.**
  - ▶ All cookies that arrive with a request are placed in the implicit `$_COOKIE` array, which has the cookie names as keys and the cookie values as values.
  - ▶ most browsers have a limit on the number of cookies that will be accepted from a particular server site.
  - ▶ In many cases, information about a session is needed only during the session
  - ▶ Rather than using one or more cookies, a single session array can be used to store information about the previous requests of a client during a session.
  - ▶ In particular, session arrays often store a unique session ID for a session.
-

# Cookies- setcookie function

localhost/dashboard/smith/savecook.php

.. [Advance your skills...](#) [CSE-new LMS SJCE...](#)

Name:

Height:

Favorite Color:

localhost/dashboard/smith/savecook.php

[Paatshala: Log in to...](#) [Advance your skills...](#) [CSE-new LMS SJCE](#)

Cookies set successfully with the following data

SMITHA JACOB

Height: 162

Favorite Color: blue'

Name:

Height:

Favorite Color:

- smitha
- SMITHA JACOB
- smitha
- sdsd
- sanu joseph
- sdaa

# Cookies- setcookie function

savecook.php

```
1  <?php
2  if(isset($_POST["submit"]))
3  {
4      define( "FIVE_DAYS", 60 * 60 * 24 * 5 );
5      // define constant
6      // write each form field's value to a cookie and set the
7      // cookie's expiration date
8      setcookie( "name", $_POST["name"], time() + FIVE_DAYS );
9      setcookie( "height", $_POST["height"], time() + FIVE_DAYS );
10     setcookie( "color", $_POST["color"], time() + FIVE_DAYS );
11     $name=$_COOKIE["name"];
12     $height=$_COOKIE["height"];
13     $color=$_COOKIE["color"];
14     echo "Cookies set successfully with the following data";
15     echo "<p>$name</p> <p>Height: $height<p>Favorite Color:
16     <span style = 'color: $color'> $color'</span></p> ";
17 }
18 else
19 {
20  >>
```

Name:

Height:

Favorite Color:

Write Cookie

smitha

SMITHA JACOB

smitha

sdsd

sanu joseph

sdaa

## Cookies- setcookie function

```
21 <!DOCTYPE html>
22 <html lang="en">
23 <head>
24     <meta charset="UTF-8">
25     <meta http-equiv="X-UA-Compatible" content="IE=edge">
26     <meta name="viewport" content="width=device-width, initial-scale=1.0">
27     <title>Document</title>
28 </head>
29 <body>
30 <form method = "post" action = "savecook.php">
31     <div><label>Name:</label>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~
32     <input type = "text" name = "name"><br/>
33     <label>Height:</label>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~
34     <input type = "text" name = "height"><br/>
35     <label>Favorite Color:</label>&nbsp;&nbsp;&~
36     <input type = "text" name = "color"><br/>
37     <p><input type = "submit" name="submit" value = "Write Cookie">
38 </form>
39 </body>
40 </html>
41 <?php
42 }??>
```



# Session

---

- ▶ When you work with an application, you open it, do some changes, and then you close it. This is much like a Session.
  - ▶ The computer knows who you are. It knows when you start the application and when you end.
  - ▶ But on the internet the web server does not know who you are or what you do, because **the HTTP address doesn't maintain state**.
  - ▶ Session variables solve this problem by storing user information to be used across multiple pages (e.g. username ,pwd etc). By default, session variables last until the user closes the browser.
  - ▶ So; **Session variables hold information about one single user, and are available to all pages in one application.**
-



# Session


---

- ▶ One significant way that session arrays differ from cookies is that they can be stored on the server, whereas cookies are stored on the client.
  - ▶ In PHP, a session ID is an internal value that identifies a session.
  - ▶ Session IDs need not be known or handled in any way by PHP scripts.
  - ▶ PHP is made aware that a script is interested in session tracking by calling the `session_start` function, which takes no parameters. The first call to `session_start` in a session causes a session ID to be created and recorded.
  - ▶ On subsequent calls to `session_start` in the same session, the function retrieves the `$_SESSION` array, which stores any session variables and their values that were registered in previously executed scripts in this session.
  - ▶ A session is started with the `session_start()` function.
  - ▶ Session variables are set with the PHP global variable: `$_SESSION`
-

# Set Session variables


```
C: > xampp > htdocs > dashboard > smith > 🐘 setsession.php
```

```
1  <?php
2  // Start the session
3  session_start();
4  ?>
5  <!DOCTYPE html>
6  <html><body>
7      <?php
8
9      $_SESSION["uname"] ="admin";
10     $_SESSION["pwd"] ="admin123";
11     echo "Session variables are set.";
12     ?>
13 </body></html>
```



# Modify Session variables

```
C: > xampp > htdocs > dashboard > smith > 🐘 setsession.php
1  <?php
2  // Start the session
3  session_start();
4  ?>
5  <!DOCTYPE html>
6  <html><body>
7      <?php
8
9      // to change a session variable, just overwrite it
10     $_SESSION["uname"]="administrator";
11     print ("welcome ".$_SESSION["uname"] );
12     ?>
13 </body></html>
```



# Destroy a Session

- ▶ To remove all global session variables and destroy the session, use `session_unset()` and `session_destroy()`:
- ▶ Example

```
1  <?php
2  // Start the session
3  session_start();
4  ?>
5  <!DOCTYPE html>
6  <html><body>
7      <?php
8          // remove all session variables
9          session_unset();
10         // destroy the session
11         session_destroy();
12         echo "session cleared";
13     ?>
14 </body></html>
```

localhost/dashboard/smith/setsession.php

Advance your skills... CSE-new LMS SJCE..

session cleared

# MySQL Integration-Connecting to MySQL with PHP

# Connecting PHP to MySQL

---

- ▶ When users enter any data into the fields of your forms, you need to collect that information and add it to the database. To do that, you want to know how to connect PHP with MySQL.
- ▶ In order to connect a MySQL database to PHP, you require MySQL on your computer, a tool to create and manage databases, and PHP installed. The most popular ways to connect a PHP script to MySQL are MySQLi and PDO



# Connecting PHP to MySQL

---

- ▶ **What is MySQL?**
  - ▶ MySQL is an open-source relational database management system (RDBMS). It is the most popular database system used with PHP.
  - ▶ Structured Query Language (SQL). The data in a MySQL database are stored in tables that consist of columns and rows.
  - ▶ MySQL is a database system that runs on a server. MySQL is ideal for both small and large applications. MySQL is a very fast, reliable, and easy-to-use database system. It uses standard SQL. MySQL compiles on a number of platforms.
  - ▶ **How we can connect PHP to MySQL?**
  - ▶ PHP 5 and later can work with a MySQL database using:
  - ▶ MySQLi extension (the 'i' is abbreviation for improved)
  - ▶ PDO (PHP Data Objects)
-



# Connecting PHP to MySQL

---

- ▶ **Connection to MySQL using MySQLi**
  - ▶ PHP provides `mysql_connect()` function to open a database connection.
  - ▶ This function takes a single parameter, which is a connection returned by the `mysql_connect()` function.
  - ▶ You can disconnect from the MySQL database anytime using another PHP function `mysql_close()`.
  - ▶ There is also a procedural approach of MySQLi to establish a connection to MySQL database from a PHP script.
-

# Form processing with DB- Making a Connection

---

- ▶ The basic syntax for a connection to MySQL is as follows:

```
$mysqli = mysqli_connect("hostname", "username", "password", "database");
```

- ▶ The value of \$mysqli is the result of the function and is used in later functions for communicating with MySQL.
  - ▶ With sample values inserted, the connection code looks like this:  

```
$mysqli = mysqli_connect("localhost", "root", " ", "test");
```
  - ▶ It creates a new connection in line 2 and then tests to see whether an error occurred. If an error occurred, an error message and uses the `mysqli_connect_error()` function to print the message.
-

# Form processing with DB- Making a Connection

localhost/phpmyadmin/index.php?route=/database/structure&server=1&db=test

Paatshala: Log in to... Advance your skills... CSE-new LMS SJCE... Log in | MongoDB Portfolio of Smitha... Welcome to XAMPP Heroku | Login Settings - Passwords

phpMyAdmin

Recent Favorites

Server: 127.0.0.1 » Database: test

Structure SQL Search Query Export Import Operations Privileges Routines Events

Filters

Containing the word:

|                          | Table     | Action                                      | Rows | Type   | Collation         | Size     | Overhead |
|--------------------------|-----------|---|------|--------|-------------------|----------|----------|
| <input type="checkbox"/> | test      | ★ Browse Structure Search Insert Empty Drop | 0    | InnoDB | latin1_swedish_ci | 16.0 KiB | -        |
| <input type="checkbox"/> | testtable | ★ Browse Structure Search Insert Empty Drop | 5    | InnoDB | latin1_swedish_ci | 16.0 KiB | -        |
| <input type="checkbox"/> | ttest     | ★ Browse Structure Search Insert Empty Drop | 3    | InnoDB | latin1_swedish_ci | 16.0 KiB | -        |
|                          | 3 tables  | Sum   | 8    | InnoDB | latin1_swedish_ci | 48.0 KiB | 0 B      |


☐ Check all With selected:

# Form processing with DB- Making a Connection with 'test' DB

```
1  <?php
2  $servername = "localhost";
3  $username = "root";
4  $password = "";
5  $dbname="test";
6  // Connection
7  $conn= mysqli_connect($servername,$username, $password,$dbname);
8  // For checking if connection is successful or not
9  if ($conn->connect_error) {
10  die("Connection failed: ". $conn->connect_error);
11  }
12  echo "Connected to ".$dbname." Establised successfully";
13  ?>
```

MySQL\_i\_Connect\_error

**Warning:** mysqli::\_\_construct(): (HY000/1045): Access denied for user 'username'@'localhost' (using password: NO) in  
**C:\xampp\htdocs\dashboard\smith\conTest.php** on line 7  
Connection failed: Access denied for user 'username'@'localhost' (using password: NO)



# Form processing with DB- Making a Connection

---

- ▶ The basic syntax for a connection to MySQL is as follows:


```
$mysqli = mysqli_connect("hostname", "username", "password", "database");
```

- ▶ The value of \$mysqli is the result of the function and is used in later functions for communicating with MySQL.
  - ▶ With sample values inserted, the connection code looks like this:  

```
$mysqli = mysqli_connect("localhost", "root", " ", "test");
```
  - ▶ It creates a new connection in line 2 and then tests to see whether an error occurred. If an error occurred, an error message and uses the `mysqli_connect_error()` function to print the message.
-

# Form processing with DB-Executing Queries-Insert records

- ▶ PHP to MySQL connection is required to insert information into our database.
- ▶ Also we should use `INSERT INTO ... VALUES` syntax for that:



Document x localhost / 127 x


localhost/dashboard/smith/insertform.html

Advance your skills... CSE-new LMS SJCE

Text to Add:

I am from Pala


Insert Record



localhost/dashboard/smith/insTest.php

Advance your skills... CSE-new LMS SJCE...

Connection to DB Established successfully  
Data Inserted successfully!



| + Options                |      |      |                            |
|--------------------------|------|------|----------------------------|
|                          |      |      |                            |
| <input type="checkbox"/> | Edit | Copy | Delete 3 cccc              |
| <input type="checkbox"/> | Edit | Copy | Delete 4 wwwww             |
| <input type="checkbox"/> | Edit | Copy | Delete 5 god bless you     |
| <input type="checkbox"/> | Edit | Copy | Delete 6 my name is smitha |
| <input type="checkbox"/> | Edit | Copy | Delete 8 I am from Pala    |




# Form processing with DB-Executing Queries-Insert records

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "test");
3  // For checking if connection is successful or not
4  if ($conn->connect_error) {
5      die("Connection failed: ". $conn->connect_error);
6  }
7  echo "Connection to DB Establised successfully";
8  $sql = "INSERT INTO testTable(testField) VALUES ('$_POST[testfield]')";
9      $res = mysqli_query($conn, $sql);
10     //if ($conn->query($sql) === TRUE)
11     if($res===TRUE)
12     {
13         echo '<br/>Data Inserted successfully!';
14     }
15     else
16     {
17         echo "Error: " . $sql . "<br>" . $conn->error;
18     }
19     $conn->close();
20
21  ?>
```

# Form processing-Registration form

---




← → ↻ 🏠 ⓘ localhost/dashboard/smith/register.php

🔍 Paatshala: Log in to... 📺 Advance your skills... 📺 CSE-new LMS SJCE...

Name:

Address:

Gender: ☐ Female ☐ Male





# Form processing with DB- Executing Queries

---

- ▶ The `mysqli_query()` function in PHP is used to send your SQL query to MySQL
- ▶ the `mysqli_error()` function returns a helpful error message when you make a mistake

```
$conn = new mysqli($servername, $username, $password, $dbname);  
$sql = "INSERT INTO ttest(name,address,gender) VALUES ('$_POST[name]',  
'$_POST[address]', '$_POST[gender]')";  
    if ($conn->query($sql) === TRUE)  
    {  
echo "Data Inserted successfully!";  
    }
```

# Form processing-Registration form

```
1  <?php
2  if(isset($_POST["submit"]))
3  { // Check if we click on SUBMIT BUTTON
4      $servername = "localhost";
5      $username = "root";
6      $password = "";
7      $dbname = "test";
8      $conn = new mysqli($servername, $username, $password, $dbname);
9      if ($conn->connect_error)
10     {
11         die("Connection failed: " . $conn->connect_error);
12     } // insert Query
13     $sql = "INSERT INTO ttest(name,address,gender) VALUES ('$_POST[name]', '$_POST[address]', '$_POST[gender]')";
14     $res = mysqli_query($conn, $sql);
15     //if ($conn->query($sql) === TRUE)
16     // {
17         if($res===TRUE)
18         {
19             echo '<script>alert("Data Inserted successfully!");</script>';
20         }
21     else
22     {
23         echo "Error: " . $sql . "<br>" . $conn->error;
24     }
25     $conn->close();
26 }
27 else
28 {
29     ?>
```

# Form processing-Registration form

```
29 <form method="post" action="register.php">
30   <table>
31     <tr>
32       <td>Name: </td>
33       <td><input type="text" name="name"></td>
34     </tr>
35     <tr><td>Address:</td>
36     <td><textarea name="address"></textarea></td>
37     </tr>
38     <tr>
39       <td>Gender:</td>
40       <td><input type="radio" name="gender" value="female">Female
41       <input type="radio" name="gender" value="male">Male</td>
42     </tr>
43     <tr><td></td><td><input type="submit" name="submit" value="Submit"></td>
44     </tr>
45   </table>
46 </form>
47 <?php
48 }
49 ?>
```


## A Script to Create a Table

---

```
1:  <?php
2:  $mysqli = mysqli_connect("localhost", "testuser", "somepass", "testDB");
3:
4:  if (mysqli_connect_errno()) {
5:      printf("Connect failed: %s\n", mysqli_connect_error());
6:      exit();
7:  } else {
8:      $sql = "CREATE TABLE testTable
9:              (id INT NOT NULL PRIMARY KEY AUTO_INCREMENT,
10:               testField VARCHAR(75))";
11:      $res = mysqli_query($mysqli, $sql);
12:
13:      if ($res === TRUE) {
14:          echo "Table testTable successfully created.";
15:      } else {
16:          printf("Could not create table: %s\n", mysqli_error($mysqli));
17:      }
18:
19:      mysqli_close($mysqli);
20:  }
21:  ?>
```

---

# Form processing with DB- Creating Tables



phpMyAdmin

Server: 127.0.0.1 » Database: test » Table: test5


Browse Structure SQL Search Insert Export Import Privileges Operations

Table structure Relation view

| #                        | Name   | Type        | Collation         | Attributes | Null | Default | Comments | Extra          | Action             |
|--------------------------|--------|-------------|-------------------|------------|------|---------|----------|----------------|--------------------|
| <input type="checkbox"/> | 1 id   | int(11)     |                   |            | No   | None    |          | AUTO_INCREMENT | Change  Drop  More |
| <input type="checkbox"/> | 2 name | varchar(75) | latin1_swedish_ci |            | Yes  | NULL    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 3 mark | int(11)     |                   |            | Yes  | NULL    |          |                | Change  Drop  More |



# Form processing with DB- Creating Tables

C: > xampp >htdocs > dashboard > smith >  tcreate.php

```
1  <?php
2  $mysqli = mysqli_connect("localhost", "root", "", "test");
3  if (mysqli_connect_errno()) {
4  printf("Connect failed: %s\n", mysqli_connect_error());
5  exit();
6  } else {
7  $sql = "CREATE TABLE test5
8  (id INT NOT NULL PRIMARY KEY AUTO_INCREMENT,
9  name VARCHAR(75),mark INT)";
10 $res = mysqli_query($mysqli, $sql);
11 if ($res === TRUE) {
12 echo "Table testTable successfully created.";
13 } else {
14 printf("Could not create table: %s\n", mysqli_error($mysqli));
15 }
16 mysqli_close($mysqli);
17 }
18 ?>
```



## A Script to Insert a Record

---

```
1:  <?php
2:  $mysqli = mysqli_connect("localhost", "testuser", "somepass", "testDB");
3:
4:  if (mysqli_connect_errno()) {
5:      printf("Connect failed: %s\n", mysqli_connect_error());
6:      exit();
7:  } else {
8:      $sql = "INSERT INTO testTable (testField) VALUES ('some value')";
9:      $res = mysqli_query($mysqli, $sql);
10:
11:      if ($res === TRUE) {
12:          echo "A record has been inserted.";
13:      } else {
14:          printf("Could not insert record: %s\n", mysqli_error($mysqli));
15:      }
16:
17:      mysqli_close($mysqli);
18:  }
19:  ?>
```

Text to Add:

Insert Record

localhost/dashboard/smith/ttinsert.php




o... [Advance your skills...](#) [CSE-new LMS SJC](#)

A record has been inserted.

# Form processing with DB- Inserting Tables

```
1  <!DOCTYPE html>
2  <html lang="en">
3  > <head> ...
8  </head>
9  <body>
10     <form action="ttinsert.php" method="post">
11         <p><label for="testfield">Text to Add:</label><br>
12         <input type="text" id="testfield" name="testfield" size="30"></p>
13         <button type="submit" name="submit" value="insert">Insert Record</button>
14     </form>
15 </body>
16 </html>
```

localhost/dashboard/smith/insertform.html

o...  Advance your skills...  CSE-new LMS SJCE... 


Text to Add:

# Form processing with DB- Inserting Tables


```
1  <?php
2  $mysqli = mysqli_connect("localhost", "root", "", "test");
3
4  if (mysqli_connect_errno())
5  {
6  printf("Connect failed: %s\n", mysqli_connect_error());
7  exit();
8  }
9  else
10 {
11     $sql = "INSERT INTO testTable (testField) VALUES ('$_POST[testfield]')";
12
13 $res = mysqli_query($mysqli, $sql);
14 if ($res === TRUE)
15 {
16     echo "A record has been inserted.";
17 }
18 else
19 {
20     printf("Could not insert record: %s\n", mysqli_error($mysqli));
21 }
22 mysqli_close($mysqli);
23 }
24 ?>
```

# Select Data From a MySQL Database

- ▶ The SELECT statement is used to select data from one or more tables:  
SELECT column\_name(s) FROM table\_name
- ▶ or we can use the \* character to select ALL columns from a table:  
SELECT \* FROM table\_name
- ▶ Select Data With MySQLi can also be done in two ways
  - ▶ MySQLi Object-oriented
  - ▶ MySQLi Procedural



# Select Data From a MySQL Database-MySQLi Object-oriented


 selTest.php

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "test");
3  // For checking if connection is successful or not
4  if ($conn->connect_error) {
5      die("Connection failed: ". $conn->connect_error);
6  }
7  echo "Connection to DB Establised successfully";
8  $sql = "SELECT * FROM testTable";
9  $result = $conn->query($sql);
10
11  if ($result->num_rows > 0) {
12      // output data of each row
13      echo "<br/><b>.....id....My Message.....</b><br/>" ;
14      while($row = $result->fetch_assoc()) {
15          echo ".....".$row["id"]. "....." . $row["testField"]. "<br>";
16      }
17  } else {
18      echo "0 results";
19  }
20  $conn->close();
21  ?>
```



# Select Data From a MySQL Database

- ▶ First, we set up an SQL query that selects the id, testField columns from the testTable. The next line of code runs the query and puts the resulting data into a variable called \$result.
- ▶ Then, the function num\_rows() checks if there are more than zero rows returned.
- ▶ If there are more than zero rows returned, the function fetch\_assoc() puts all the results into an associative array that we can loop through. The while() loop loops through the result set and outputs the data from the id, testField columns.



The screenshot shows the phpMyAdmin interface. On the left, a tree view shows the database structure with a table named 'testtable'. The main area displays the table's contents. The table has two columns: 'id' and 'testField'. There are five rows of data. Each row has a checkbox, an 'Edit' button, a 'Copy' button, and a 'Delete' button. The data is as follows:

|                          | id | testField         |
|--------------------------|----|-------------------|
| <input type="checkbox"/> | 3  | cccc              |
| <input type="checkbox"/> | 4  | wwwwww            |
| <input type="checkbox"/> | 5  | god bless you     |
| <input type="checkbox"/> | 6  | my name is smitha |
| <input type="checkbox"/> | 8  | I am from Pala    |




The screenshot shows a web browser window with the address bar displaying 'localhost/dashboard/smith/selTest.php'. The page content shows the output of a PHP script, which is a table with two columns: 'id' and 'My Message'. The data is as follows:

| id | My Message        |
|----|-------------------|
| 3  | cccc              |
| 4  | wwwwww            |
| 5  | god bless you     |
| 6  | my name is smitha |
| 8  | I am from Pala    |



# Select Data From a MySQL Database-MySQLi Procedural

 selTestPro.php

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "test");
3  // For checking if connection is successful or not
4  if (!$conn) {
5      die("Connection failed: " . mysqli_connect_error());
6  }
7  $sql = "SELECT * FROM testTable";
8  $result = mysqli_query($conn, $sql);
9  if (mysqli_num_rows($result) > 0) {
10     // output data of each row
11     echo "<table border='border' width='300'><tr><th>id</th><td width='250'>My Message</td></tr>" ;
12     while($row = mysqli_fetch_assoc($result)) {
13         echo "<tr><td>".$row["id"]. "</td><td>" . $row["testField"]. "</td></tr>";
14     }
15     echo "</table>";
16 } else {
17     echo "0 results";
18 }
19 $conn->close();
20 ?>
```


localhost/dashboard/smith/selTestPro.php

Advance your skills... CSE-new LMS SJCE...

| id | My Message        |
|----|-------------------|
| 3  | cccc              |
| 4  | wwwwww            |
| 5  | god bless you     |
| 6  | my name is smitha |
| 8  | I am from Pala    |


# Update Data In a MySQL Table Using MySQLi

- ▶ The UPDATE statement is used to update existing records in a table:  
UPDATE table\_name SET column1=value, column2=value2,...  
WHERE some\_column=some\_value
- ▶ The WHERE clause specifies which record or records that should be updated. If you omit the WHERE clause, all records will be updated!



The screenshot shows a MySQL database interface. On the left, a tree view shows a database named 'test' with a table named 'testtable'. The main area displays the table structure and data. The table has two columns: 'id' and 'testField'. The data is as follows:

|                          | id | testField         |
|--------------------------|----|-------------------|
| <input type="checkbox"/> | 3  | cccc              |
| <input type="checkbox"/> | 4  | wwwwww            |
| <input type="checkbox"/> | 5  | god bless you     |
| <input type="checkbox"/> | 6  | my name is smitha |
| <input type="checkbox"/> | 8  | I am from Pala    |



The screenshot shows a web browser window with the address bar displaying 'localhost/dashboard/smith/selTest.php'. The page content shows the output of a PHP script that displays the contents of the 'test' table. The output is as follows:

| .....id..... | My Message.....   |
|--------------|-------------------|
| .....3.....  | cccc              |
| .....4.....  | wwwwww            |
| .....5.....  | god bless you     |
| .....6.....  | my name is smitha |
| .....8.....  | I am from Pala    |

# Update Data In a MySQL Table Using MySQLi-ObjectOriented

upTest.php

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "test");
3  // For checking if connection is successful or not
4  if ($conn->connect_error) {
5      die("Connection failed: ". $conn->connect_error);
6  }
7  //echo "Connection to DB Establised successfully";
8  $sql = "UPDATE testTable SET testField='India is my Country' WHERE id=3";
9  //update to db
10 if ($conn->query($sql) === TRUE) {
11     echo "Record updated successfully";
12 } else {
13     echo "Error updating record: " . $conn->error;
14 }
```

# Update Data In a MySQL Table Using MySQLi

contd....

```
15 $sql = "SELECT * FROM testTable";
16 $result = $conn->query($sql);
17
18 if ($result->num_rows > 0) {
19     // output data of each row
20     echo "<br/><b>.....id....My Message.....</b><br/>" ;
21     while($row = $result->fetch_assoc()) {
22         echo ".....".$row["id"]. "....." . $row["testField"]. "<br>";
23     }
24 } else {
25     echo "0 results";
26 }
27 $conn->close();
28 ?>
```

.....id....My Message.....  
....3.....cccc  
....4.....wwwww  
....5.....god bless you  
....6.....my name is smitha  
....8.....I am from Pala

Record updated successfully

.....id....My Message.....  
....3.....India is my Country  
....4.....wwwww  
....5.....god bless you  
....6.....my name is smitha  
....8.....I am from Pala

# Update Data In a MySQL Table Using MySQLi-procedural contd....

localhost/dashboard/smith/selTestPro.php

Advance your skills... CSE-new LMS SJCE...

| id | My Message        |
|----|-------------------|
| 3  | cccc              |
| 4  | wwwww             |
| 5  | god bless you     |
| 6  | my name is smitha |
| 8  | I am from Pala    |

localhost/dashboard/smith/upTestPro.php

Advance your skills... CSE-new LMS SJCE...

Record updated successfully

| id | My Message          |
|----|---------------------|
| 3  | India is my Country |
| 4  | I love India        |
| 5  | god bless you       |
| 6  | my name is smitha   |
| 8  | I am from Pala      |



# Update Data In a MySQL Table Using MySQLi-Procedural

---

 upTestPro.php

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "test");
3  // For checking if connection is successful or not
4  if (!$conn) {
5      die("Connection failed: " . mysqli_connect_error());
6  }
7  //update Db
8  $sql = "UPDATE testTable SET testField='I love India' WHERE id=4";
9  if (mysqli_query($conn, $sql)) {
10     echo "Record updated successfully";
11 } else {
12     echo "Error updating record: " . mysqli_error($conn);
13 }
```



# Update Data In a MySQL Table Using MySQLi-procedural

## contd....

---

```
14 $sql = "SELECT * FROM testTable";
15 $result = mysqli_query($conn, $sql);
16 if (mysqli_num_rows($result) > 0) {
17     // output data of each row
18     echo "<table border='border' width='300'><tr><th>id</th><td width='250'>My Message</td></tr>" ;
19     while($row = mysqli_fetch_assoc($result)) {
20         echo "<tr><td>".$row["id"]. "</td><td>" . $row["testField"]. "</td></tr>";
21     }
22     echo "</table>";
23 } else {
24     echo "0 results";
25 }
26 $conn->close();
27 ?>
```

## Working with sql Data

# Working with Mysql Data

---

## WARNING

- ▶ There is no more support for `mysql_*` functions, they are officially deprecated, no longer maintained and will be removed in the future.
- ▶ You should update your code with PDO or MySQLi to ensure the functionality of your project in the future

# Working with Mysql Data

The screenshot shows the phpMyAdmin web interface. On the left is a sidebar with a tree view of databases: 'books', 'goeat', 'information\_schema', 'mysql', 'performance\_schema', 'phpmyadmin', and 'test'. The 'books' database is selected, and the 'book' table is highlighted. The main panel shows the table's structure and data. At the top, it says 'Server: 127.0.0.1 » Database: books » Table: book'. Below this, a green message bar indicates 'Showing rows 0 - 3 (4 total, Query took 0.0004 seconds.)'. The SQL query 'SELECT \* FROM `book`' is displayed. Below the query, there are links for 'Profiling', 'Edit inline', 'Edit', and 'Explain SQL'. Further down, there are controls for 'Show all', 'Restore column order', 'Number of rows' (set to 25), and 'Filter row'. The table data is shown with columns 'bookid', 'bcategory', 'bookname', and 'isbn'. Each row has checkboxes for 'Edit', 'Copy', and 'Delete'.

phpMyAdmin

Recent Favorites

Server: 127.0.0.1 » Database: books » Table: book

Showing rows 0 - 3 (4 total, Query took 0.0004 seconds.)

`SELECT * FROM `book``

☐ Profiling [ [Edit inline](#) ] [ [Edit](#) ] [ [Explain SQL](#) ]


☐ Show all | Restore column order | Number of rows: 25 Filter row

+ Options

|                          |  |      |  | bookid | bcategory | bookname | isbn |             |                   |          |
|--------------------------|--|------|--|--------|-----------|----------|------|-------------|-------------------|----------|
| <input type="checkbox"/> |  | Edit |  | Copy   |           | Delete   | 1    | computer    | operating systems | 1234567  |
| <input type="checkbox"/> |  | Edit |  | Copy   |           | Delete   | 2    | programming | Java Black Book   | 22233367 |
| <input type="checkbox"/> |  | Edit |  | Copy   |           | Delete   | 3    | programming | Java programming  | 33333367 |
| <input type="checkbox"/> |  | Edit |  | Copy   |           | Delete   | 4    | programming | Complete hTML5    | 4444467  |


# Working with Mysql Data

---



| List of Books |                   |               |          |
|---------------|-------------------|---------------|----------|
| Booid         | Book Name         | Book Category | ISBN     |
| 1             | operating systems | computer      | 1234567  |
| 2             | Java Black Book   | programming   | 22233367 |
| 3             | Java programming  | programming   | 33333367 |
| 4             | Complete hTML5    | programming   | 4444467  |

# Working with Mysql Data


 selTestBook.php

```
1  <?php
2  $conn = mysqli_connect("localhost", "root", "", "books");
3  if (!$conn) { die("Connection failed: " . mysqli_connect_error()); }
4  $sql = "SELECT * FROM book";
5  $result = mysqli_query($conn, $sql);
6  if (mysqli_num_rows($result) > 0) {
7      // output data of each row
8      echo "<table align='center' border='border' width='600' cellpadding='10'>
9      <caption><b>List of Books </b></caption><br/> <tr><th>Booid</th>
10     <th width='250'>Book Name</th> <th width='250'>Book Category</th>
11     <th width='50'>ISBN</th></tr>" ;
12     // while($row = mysql_fetch_row( $result )) --Deprecated use fetch_assoc{
13     while($row = mysqli_fetch_assoc($result)) {
14         echo "<tr><td>".$row["bookid"]. "</td><td>" . $row["bookname"].
15         | "</td><td>" . $row["bcategory"]. "</td><td>" . $row["isbn"]. "</td></tr>";
16     }
17     echo "</table>";
18 } else {
19     echo "0 results";
20 }
21 $conn->close();
22 ?>
```



# Reading from Database Dynamically

# Accessing Mysql Data-through dynamic Form data




\*

Results of SELECT \* from book

|   |                   |             |          |
|---|-------------------|-------------|----------|
| 1 | operating systems | computer    | 1234567  |
| 2 | Java Black Book   | programming | 22233367 |
| 3 | Java programming  | programming | 33333367 |
| 4 | Complete hTML5    | programming | 4444467  |

# Working with Mysql Data-through Form data

---

 datab.php

```
1  <!DOCTYPE html>
2  <html lang="en">
3  > <head> ...
8  </head><body><br/>
9      <form action="datab.php" method="post">
10         <select name="select">
11             <option selected>*</option>
12             <option value="bookid">ID</option>
13             <option value="bookname">Title</option>
14             <option value="bcategory">Category</option>
15             <option value="isbn">ISBN</option>
16         </select>
17         <input type = "submit" name="submit" value = "Send Query">
18         <br/><br/>
19     </form>
20 </body></html>
```

# Working with Mysql Data-through Form data

```
21  <?php
22  if(isset($_POST["submit"]))
23  {
24      $conn = mysqli_connect("localhost", "root", "", "books");
25      if (!$conn) { die("Connection failed: " . mysqli_connect_error()); }
26      $select = $_POST["select"];
27      $sql = "SELECT ".$select." FROM book";
28      $result = mysqli_query($conn, $sql);
29      if (mysqli_num_rows($result) > 0) {
30          // output data of each row
31          echo "Results of SELECT ".$select ." from book";
32          echo "<table border='border' cellpadding='10'>";
33          // while($row = mysql_fetch_row( $result )) --Deprecated use fetch_assoc{
34          while($row = mysqli_fetch_assoc($result))
35          {
36              print "<tr>" ;
37              foreach ( $row as $key => $value )
38              {
39                  print( "<td>$value</td>" );
40              }
41              print( "</tr>" );
42          }
43          echo "</table>";
44      } else { echo "0 results";}
45      $conn->close();
46  }
47  ?>
```

# Dynamic Contents

# Dynamic Content

---

- ▶ PHP can dynamically change the HTML5 it outputs based on a user's input.
  - ▶ We can combine the HTML5 form & PHP script into one dynamic document.
  - ▶ The form is created using a series of loops, arrays and conditionals.
  - ▶ We add error checking to each of the text input fields and inform the user of invalid entries on the form itself, rather than on an error page.
  - ▶ If an error exists, the script maintains the previously submitted values in each form element.
  - ▶ Finally, after the form has been successfully completed, we store the input from the user in a MySQL database.
-



# Dynamic Content-Creation of mailinglist Table

localhost / 127.0.0.1 / books / mailinglist

localhost/phpmyadmin/index.php?route=/table/structure&db=books&table=mailinglist

Paatshala: Log in to... Advance your skills... CSE-new LMS SJCE... Log in | MongoDB Portfolio of Smitha... Welcome to XAMPP Heroku | Login Settings - Passv

phpMyAdmin

Recent Favorites

- New
- books
  - New
  - book
  - mailinglist
- goeat
- information\_schema
- mysql
- performance\_schema
- phpmyadmin
- test

Server: 127.0.0.1 » Database: books » Table: mailinglist

Browse Structure SQL Search Insert Export Import Privileges Operations

Table structure Relation view

| #                        | Name      | Type        | Collation          | Attributes | Null | Default | Comments | Extra          | Action             |
|--------------------------|-----------|-------------|--------------------|------------|------|---------|----------|----------------|--------------------|
| <input type="checkbox"/> | 1 id      | int(11)     |                    |            | No   | None    |          | AUTO_INCREMENT | Change  Drop  More |
| <input type="checkbox"/> | 2 fname   | varchar(11) | utf8mb4_general_ci |            | No   | None    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 3 lname   | varchar(11) | utf8mb4_general_ci |            | No   | None    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 4 email   | varchar(25) | utf8mb4_general_ci |            | No   | None    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 5 phone   | int(12)     |                    |            | No   | None    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 6 favbook | varchar(50) | utf8mb4_general_ci |            | No   | None    |          |                | Change  Drop  More |
| <input type="checkbox"/> | 7 favos   | varchar(15) | utf8mb4_general_ci |            | No   | None    |          |                | Change  Drop  More |

# Sample Registration Form

Please fill in all fields and click Register.

## User Information

|             |              |
|-------------|--------------|
| First Name: | saaa         |
| Last Name:  | qqq          |
| Email:      | xcx@bdsf.com |
| Phone:      | 2323323      |

## Publications

Which book would you like information about?

Internet and WWW How to Program ▾

## Operating System

Which operating system do you use?

☐ Windows ☐ Mac OS X ☒ Linux ☐ Other

Register

A record has been inserted.

Hi saaa. Thank you for completing the survey. You have been added to the Internet and WWW How to Program mailing list.

**The following information has been saved in our database:**

Name: saaa qqq

Email: xcx@bdsf.com

Phone: 2323323

OS: Linux

[Click here to view entire database.](#)

**This is only a sample form. You have not been added to a mailing list.**

# Mailing List Contacts

Contacts stored in the database

| ID | Last Name | First Name | E-mail Address       | Phone Number | Book                            | Operating System |
|----|-----------|------------|----------------------|--------------|---------------------------------|------------------|
| 1  | Smitha    | Jacob      | smitha.jacob@gmail.c | 1239727287   | Java BlackBook                  | Windows          |
| 2  | qqq       | saaa       | xcx@bdsf.com         | 2323323      | Internet and WWW How to Program | Linux            |

🐘 dynamicForm.php

```
1  <!DOCTYPE html>
2  <html lang="en">
3  <head>
4      <meta charset="UTF-8">
5      <meta http-equiv="X-UA-Compatible" content="IE=edge">
6      <meta name="viewport" content="width=device-width, initial-scale=1.0">
7      <title>Document</title>
8      <style type = "text/css">
9          p { margin: 0px; }
10         .error { color: red }
11         p.head { font-weight: bold; margin-top: 10px; }
12         label { width: 5em; float: left; }
13     </style>
14 </head>
15 <body>
16 <?php
17     // variables used in script
18     $fname = isset($_POST[ "fname" ]) ? $_POST[ "fname" ] : "";
19     $lname = isset($_POST[ "lname" ]) ? $_POST[ "lname" ] : "";
20     $email = isset($_POST[ "email" ]) ? $_POST[ "email" ] : "";
21     $phone = isset($_POST[ "phone" ]) ? $_POST[ "phone" ] : "";
22     $book = isset($_POST[ "book" ]) ? $_POST[ "book" ] : "";
23     $os = isset($_POST[ "os" ]) ? $_POST[ "os" ] : "";
```



# Dynamic Content-Variables & Arrays

---

- ▶ Lines 18–24 create variables that are used throughout the script to fill in form fields and check for errors.
- ▶ Line 25 creates an array for formerrors
- ▶ Lines 27,29,30 create three arrays, \$booklist, \$systemlist and \$inputlist, that are used to dynamically create the form's input fields.

```
24  $iserror = false;
25  $formerrors = array( "fnameerror" => false, "lnameerror" => false,
26    "emailerror" => false, "phoneerror" => false );
27  $booklist = array( "Internet and WWW How to Program", "C++ How to Program",
28    "Java How to Program", "Visual Basic How to Program" );
29  $systemlist = array( "Windows", "Mac OS X", "Linux", "Other" );
30  $inputlist = array( "fname" => "First Name", "lname" => "Last Name",
31    "email" => "Email", "phone" => "Phone" );
```

# Dynamic Content-Variables & Arrays

```
32  if (isset($_POST["submit"]))
33  { if ( $fname == "" )
34      {
35          $formerrors[ "fnameerror" ] = true;
36          $iserror = true;
37      }
38      if ( $lname == "" )
39      {
40          $formerrors[ "lnameerror" ] = true;
41          $iserror = true;
42      }
43      if ( $email == "" )
44      {
45          $formerrors[ "emailerror" ] = true;
46          $iserror = true;
47      }
48      if ( $phone == "" )
49      {
50          $formerrors[ "phoneerror" ] = true;
51          $iserror = true;
52      }
```

```
54  if (!$iserror)
55  {
56      $sql = "INSERT INTO mailinglist " .
57      "(fname, lname, email, phone, favbook, favos ) " .
58      "VALUES ( '$lname', '$fname', '$email', " .
59      "" . $phone . ", '$book', '$os' )";
60      $conn = mysqli_connect("localhost", "root", "", "books");
61      if (!$conn)
62      {die("Connection failed: " . mysqli_connect_error()); }
63      $result = mysqli_query($conn, $sql);
64      if ($result === TRUE)
65      {
66          echo "A record has been inserted.";
67      }
68      else
69      {
70          printf("Could not insert record: %s\n", mysqli_error($conn));
71      }
72      mysqli_close($conn);
```

# Dynamic Content-Variables & Arrays

```
73     print( "<p>Hi $fname. Thank you for completing the survey.  
74     You have been added to the $book mailing list.</p>  
75     <p class = 'head'>The following information has been  
76     saved in our database:</p>  
77     <p>Name: $fname $lname</p>  
78     <p>Email: $email</p>  
79     <p>Phone: $phone</p>  
80     <p>OS: $os</p>  
81     <p><a href = 'formDatabase.php'>Click here to view  
82     entire database.</a></p>  
83     <p class = 'head'>This is only a sample form.  
84     You have not been added to a mailing list.</p>  
85     </body></html>" );  
86     die(); // finish the page  
87 }  
88 }
```

A record has been inserted.

Hi saaa. Thank you for completing the survey. You have been added to the Internet and WWW How to Program mailing list.

**The following information has been saved in our database:**

Name: saaa qq

Email: xc@bdsf.com

Phone: 2323323

OS: Linux

[Click here to view entire database.](#)

**This is only a sample form. You have not been added to a mailing list.**



# Dynamic Content-Variables & Arrays

---

- ▶ We specify that the form created in this document is self-submitting (i.e., it posts to itself) by setting the action to the script 'dynamicForm.php' in line 94.
  - ▶ Lines 32-72 use the `isset` function to determine whether the `$_POST` array contains keys representing the various form fields.
  - ▶ These keys exist only after the form is submitted.
  - ▶ If function `isset` returns true, then the form has been submitted and we assign the value for each key to a variable. Otherwise, we assign the empty string to each variable.
  - ▶ Line 53 determines whether any errors were detected, while Dynamically Creating the Form
    - ▶ If `$iserror` is false (i.e., there were no input errors), lines 54–88 display the page indicating that the form was submitted successfully
-

# Dynamic Content- Dynamically Creating the Form

- ▶ If \$iserror is true, lines 54–88 are skipped, and the code from lines 92–128 executes.
- ▶ These lines include a series of print statements and conditionals to output the form, as seen in Fig.

## Sample Registration Form

Please fill in all fields and click Register.

### User Information

|             |   |
|-------------|---|
| First Name: | <input type="text" value="saaa"/>         |
| Last Name:  | <input type="text" value="qqq"/>          |
| Email:      | <input type="text" value="xcx@bdsf.com"/> |
| Phone:      | <input type="text" value="2323323"/>      |

### Publications

Which book would you like information about?

▼

### Operating System

Which operating system do you use?

☐ Windows ☐ Mac OS X ☒ Linux ☐ Other

```

89 print( "<h1>Sample Registration Form</h1><p>Please fill in all fields and click Register.</p>" );
90 if ( $iserror )
91 {
92     print( "<p class = 'error'>Fields with * need to be filled in properly.</p>" );
93 }
94 print( "<!-- post form data to dynamicForm.php --><form method = 'post' action = 'dynamicForm.php'>" );
95 <h2>User Information</h2> <!-- create four text boxes for user input -->" );
96 foreach ( $inputlist as $inputname => $inputalt )
97 {
98     print("<div><label>$inputalt:</label><input type = 'text' name = '$inputname' value = '' . $$inputname. "'">" );
99     if ( $formerrors[ ( $inputname )."error" ] == true )
100     print( "<span class = 'error'>*</span>" );
101     print( "</div>" );
102 }
103 if ( $formerrors[ "phoneerror" ] )
104     print( "<p class = 'error'>Must be in the form (555)555-5555" );
105     print( "<h2>Publications</h2>" );
106     <p>Which book would you like information about?</p>
107     <select name = 'book'>" );
108     foreach ( $booklist as $currbook )
109     {
110         print( "<option" . ( $currbook == $book ? " selected" : ">" ). $currbook . "</option>" );
111     } // end foreach

```



Don't Miss Out!

```
112 print( "</select>" )
113 <h2>Operating System</h2>
114 <p>Which operating system do you use?</p>
115 <!-- create five radio buttons -->" );
116 $counter = 0;
117 foreach ( $systemlist as $currsystem )
118 {
119 print( "<input type = 'radio' name = 'os' value = '$currsystem' " );
120 if ( ( !$os && $counter == 0 ) || ( $currsystem == $os ) )
121 | print( "checked" );
122 print( ">$currsystem" );
123 ++$counter;
124 } // end foreach
125
126 print( "<!-- create a submit button -->" );
127 <p class = 'head'><input type = 'submit' name = 'submit'
128 | value = 'Register'></p></form></body></html>" );
129 ?>
130 </body>
131 </html>
```

# Dynamically Creating the Form

---

- ▶ Lines 96–102 iterate through each element in the `$inputlist` array.
  - ▶ In line 98 the value of `$$inputname` is assigned to the text field's value attribute. If the form has not yet been submitted, this will be the empty string `""`.
  - ▶ The notation `$$variable` specifies a variable 'variable', which allows the code to reference variables dynamically.
  - ▶ You can use this expression to obtain the value of the variable whose name is equal to the value of `$variable`.
  - ▶ PHP first determines the value of `$variable`, then appends this value to the leading `$` to form the identifier of the variable you wish to reference dynamically.
-



# Dynamically Creating the Form

---

- ▶ we use `$$inputname` to reference the value of each form-field variable.
  - ▶ During the iteration of the loop, `$inputname` contains the name of one of the text input elements, such as "email".
  - ▶ PHP replaces `$inputname` in the expression `$$inputname` with the string representing that element's name forming the expression `${"email"}`.
  - ▶ The entire expression then evaluates to the value of the variable `$email`. Thus, the variable `$email`, which stores the value of the e-mail text field after the form has been submitted, is dynamically referenced.
  - ▶ This dynamic variable reference is added to the string as the value of the input field (using the concatenation operator) to maintain data over multiple submissions of the form.
-



## Dynamic Content- Dynamically Creating the Form

---

- ▶ Lines 99-101 add a red asterisk next to the text input fields that were filled out incorrectly.
  - ▶ Lines 103-104 display the phone number format instructions in red if the user entered an invalid phone number.
  - ▶ Lines 105-112 and 113-125 generate options for the book drop-down list and operating-system radio buttons, respectively.
  - ▶ Lines 120–123 select an operating system radio button under two conditions. If the form is begin displayed for the first time, the first radio button is selected. Otherwise, if the \$currssystem variable's value matches what's stored in the \$os variable, that specific radio button is selected
-

# Dynamic Content- Inserting Data into the Database

---

- ▶ If the form has been filled out correctly, lines 56-71 place the form information in the MySQL database MailingList using an INSERT statement.
- ▶ Lines 81 generate the web page indicating a successful form submission, which also provides a link to formDatabase.php (Fig.).

A record has been inserted.

Hi saaa. Thank you for completing the survey. You have been added to the Internet and WWW How to Program mailing list.

**The following information has been saved in our database:**

Name: saaa qq

Email: xcx@bdsf.com

Phone: 2323323

OS: Linux

[Click here to view entire database.](#)

**This is only a sample form. You have not been added to a mailing list.**

# Sample Registration Form

Please fill in all fields and click Register.

Fields with \* need to be filled in properly.

## User Information

First Name: \*

Last Name: \*

Email: \*

Phone: \*

Must be in the form (555)555-5555

## Publications

Which book would you like information about?

## Operating System

Which operating system do you use?

☒ Windows ☐ Mac OS X ☐ Linux ☐ Other

# Sample Registration Form

Please fill in all fields and click Register.

Fields with \* need to be filled in properly.

## User Information

First Name: \*

Last Name: \*

Email: \*

Phone: \*

Must be in the form (555)555-5555

## Publications

Which book would you like information about?

## Operating System

Which operating system do you use?

☐ Windows ☐ Mac OS X ☒ Linux ☐ Other

Hi qqqq. Thank you for completing the survey. You have been added to the C++ How to Program mailing list.

**The following information has been saved in our database:**

Name: qqqq qqq

Email: nunu12345@test.com

Phone: 2323323

OS: Linux

[Click here to view entire database.](#)

**This is only a sample form. You have not been added to a mailing list.**

| ←                               | →         | ↻          | 🏠                    | 📄 localhost/dashboard/smith/formDatabase.php | 🔗                               | ☆                | ⚙️ | 🗄️ | 🌈 | ⋮ |
|---------------------------------|-----------|------------|----------------------|--|---------------------------------|------------------|----|----|---|---|
| <h2>Mailing List Contacts</h2>  |           |            |                      |  |                                 |                  |    |    |   |   |
| Contacts stored in the database |           |            |                      |  |                                 |                  |    |    |   |   |
| ID                              | Last Name | First Name | E-mail Address       | Phone Number                                 | Book                            | Operating System |    |    |   |   |
| 1                               | Smitha    | Jacob      | smitha.jacob@gmail.c | 1239727287                                   | Java BlackBook                  | Windows          |    |    |   |   |
| 2                               | qqq       | saaa       | xcx@bdsf.com         | 2323323                                      | Internet and WWW How to Program | Linux            |    |    |   |   |
| 3                               | qqq       | qqqq       | nunu12345@test.com   | 2323323                                      | C++ How to Program              | Linux            |    |    |   |   |

➤ [Full program](#)



**Thank You**