

### A Tutorial on Git and Github

By Reyhane Askari and Arnaud Bergeron

### Table of contents:

- Version control systems and git
- Git Basics
- Branch Management
- Git Merge, Update and Rebase
- Git Conflicts and How to Resolve them
- Interaction with Remote Repos
- Git Stash
- Some Useful Tips
- Git cheat sheet


#### Version Control System

- Manage multiple versions of your source code.
- Great way to work as a team where you work concurrently.
- Go back and forth between the versions of your code.

THIS IS GIT. IT TRACKS COLLABORATIVE WORK ON PROJECTS THROUGH A BEAUTIFUL DISTRIBUTED GRAPH THEORY TREE MODEL. COOL. HOU DO WE USE IT? NO IDEA. JUST MEMORIZE THESE SHELL COMMANDS AND TYPE THEM TO SYNC UP. IF YOU GET ERRORS, SAVE YOUR WORK ELSEWHERE, DELETE THE PROJECT, AND DOUNLOAD A FRESH COPY.


Source: https://xkcd.com/1597/

#### Git Basics




- git clone /url/to/repository
- git config user.name <username>
- git config user.email <email>
- git add <filename>
- git status
- git diff
- git add <filename> -p
- git add .

### Git Basics





- git commit -m "Commit message"
- git status
- git log
- git push
- git pull



- The full project code and history is called a repository.
- A commit is a snapshot of your code at different stages of the project.
- Also, a branch is a pointer to a commit that you can change.








#### Create a new branch:

git branch new\_branch



#### Create a new branch:

git branch new\_branch

Move between branches:

git checkout new\_branch



#### Create a new branch:


git branch new\_branch

Move between branches:

git checkout new\_branch

Create a new branch and check it out:

git checkout -b new\_branch



#### Create a new branch:

git branch new\_branch

Move between branches:

git checkout new\_branch


Create a new branch and check it out:


git checkout -b new\_branch

Delete a branch:

git branch -d new\_branch

git checkout -b cool\_feature






git checkout -b cool\_feature

Add some code


git commit -m "Cool feature"




```
git checkout -b cool_feature
```

Add some code

```
git commit -m "Cool feature"
git checkout master
```



```
git checkout -b cool_feature
Add some code
git commit -m "Cool feature"
git checkout master
git checkout -b feature 2
```



```
git checkout -b cool feature
```


Add some code

```
git commit -m "Cool feature"
git checkout master
```


```
git checkout -b feature_2
```

Add some more code

```
git commit -m "Second feature"
```




You've just made some changes but someone else also did. What to do?




You've just made some changes but someone else also did. What to do?

git merge master



You've just made some changes but someone else also did. What to do?


git checkout master



You've just made some changes but someone else also did. What to do?


git checkout master
git merge cool\_feature

### Rebase



You've just made some changes but someone else also did. What to do?

### Rebase



You've just made some changes but someone else also did. What to do?

git rebase master

#### How to Resolve Git Conflicts?

Find which files have conflicts using:

git status

```
both modified: doc/install_generic.inc both modified: doc/install_windows.txt both modified: doc/requirements.inc
```

#### How to Resolve Git Conflicts?


 Go to that file and find the conflict and choose the line that you want to keep.

```
<<<<< HEAD
     * **Recommended**: MKL, which is free through Conda with ``mkl
-service`` package.
======
     * **Recommended**: MKL, which is free through Conda.
>>>>>> 1b62e953a... Merge pull request #5433 from notoraptor/windoc
```

#### How to Resolve Git Conflicts?

- Resolve all the conflicts and add them:
  - o git add path/to/files/with/conflicts
- Then commit your changes:
  - o git commit
- Continue to rebase or merge:
  - o git rebase --continue
  - o git merge --continue
- Or abort the rebase/merge in case you want to stop applying the changes:
  - o git rebase --abort
  - o git merge --abort

### Git Update




• Fetch the changes from a repository but do not merge them:

git fetch repo/branch

Update local repository to the newest commit:

git pull repo/branch

# Interaction with remote repos



• See your remote repos:

• Add a remote repository:

```
git remote add [name][url]
```

 Send the changes from a local repo to a remote repo:

```
git push repo/branch
```

Push and force the local changes to the remote:

```
git push -f repo/branch
```

### Workflows for contributing to other repos

- Fork the repo to contribute to
- Checkout your forked repo
- Add a remote pointing to the repo to contribute to
- Create a pull request

### Git Stash

• If you have unstaged files, and you want to checkout to another branch, you need to save your changes:

```
git stash
```

• To retrieve the saved changes on that branch:

```
git stash pop
```

• You can see the current stash list:

```
git stash list
```

### Some Useful Tips

- Never ever commit to the master, always create a new branch first.
- Make the commit messages informative not like: "new changes", give a short description like: "changed make\_node() to be more readable"
- Before starting to implement a new feature, always fetch and pull the changes in the remote branch which is often called the upstream.
- If you want to revert uncommitted local changes use:

```
git reset --hard
```

• If you want to go to a specific commit:

```
git checkout {shal-code}
```

Select one commit and apply it to the active branch:

```
git cherry-pick {shal-code}
```



#### **GIT** CHEAT SHEET

presented by TOWER > Version control with Git - made easy



#### CREATE

Clone an existing repository \$ git clone ssh://user@domain.com/repo.git

Create a new local repository \$ git init

#### LOCAL CHANGES

Changed files in your working directory \$ git status

Changes to tracked files

\$ git diff Add all current changes to the next commit

\$ git add . Add some changes in <file> to the next commit

\$ git add -p <file> Commit all local changes in tracked files

\$ git commit -a

Commit previously staged changes \$ git commit

Change the last commit

\$ git commit --amend

#### COMMIT HISTORY

Show all commits, starting with newest \$ git log

Show changes over time for a specific file \$ git log -p <file>

Who changed what and when in <file>

\$ git blame <file>

#### BRANCHES & TAGS

List all existing branches \$ git branch -av

Switch HEAD branch

\$ git checkout <branch>

Create a new branch based on your current HEAD

\$ git branch <new-branch>

Create a new tracking branch based on a remote branch

\$ git checkout --track <remote/bran-

Delete a local branch

\$ git branch -d <branch>

Mark the current commit with a tag \$ git tag <tag-name>

#### UPDATE & PUBLISH

List all currently configured remotes

\$ git remote -v

Show information about a remote \$ git remote show <remote>

Add new remote repository, named < remote> \$ git remote add <shortname> <url>

Download all changes from <remote>, but don't integrate into HEAD

\$ git fetch <remote> Download changes and directly

merge/integrate into HEAD \$ git pull <remote> <branch>

Publish local changes on a remote \$ git push <remote> <branch>

Delete a branch on the remote

\$ git branch -dr <remote/branch>

Publish your tags \$ git push -- tags

#### MERGE & REBASE

Merge < branch> into your current HEAD \$ git merge <branch>

Rebase your current HEAD onto <branch> Don't rebase published commits!

\$ git rebase <branch>

Abort a rebase

\$ git rebase --abort

Continue a rebase after resolving conflicts \$ git rebase --continue

Use your configured merge tool to solve conflicts

\$ git mergetool

Use your editor to manually solve conflicts and (after resolving) mark file as resolved \$ git add <resolved-file>

\$ git rm <resolved-file>

#### UNDO

Discard all local changes in your working

\$ git reset --hard HEAD

Discard local changes in a specific file \$ git checkout HEAD <file>

Revert a commit (by producing a new commit with contrary changes)

\$ git revert <commit>

Reset your HEAD pointer to a previous commit

...and discard all changes since then \$ git reset --hard <commit>

...and preserve all changes as unstaged changes

\$ git reset <commit>

...and preserve uncommitted local changes \$ git reset --keep <commit>

30-day free trial available at www.git-tower.com

**TOWER** Version control with Git - made easy

#### References:

- <a href="https://sites.google.com/a/lisa.iro.umontreal.ca/lisainfo/getting-started/welcome/tutorials-kick-off-meeting/tutorials-2015/git\_github\_tutorial">https://sites.google.com/a/lisa.iro.umontreal.ca/lisainfo/getting-started/welcome/tutorials-kick-off-meeting/tutorials-2015/git\_github\_tutorial</a>
- <a href="https://learngitbranching.js.org">https://learngitbranching.js.org</a>
- <a href="http://git-school.github.io/visualizing-git/">http://git-school.github.io/visualizing-git/</a>
- <a href="https://git-scm.com/docs/">https://git-scm.com/docs/</a>
- <a href="http://rogerdudler.github.io/git-guide/">http://rogerdudler.github.io/git-guide/</a>
- <a href="https://www.slideshare.net/anuragupadhaya/git-101-for-beginners">https://www.slideshare.net/anuragupadhaya/git-101-for-beginners</a>
- <a href="https://github.com/jlord/git-it-electron#what-to-install">https://github.com/jlord/git-it-electron#what-to-install</a>