Visual and Multimodal Agent Learning

Deep Dive into Kimi K3 — Chapter 25

Yin Yang

Foundation Books Project

The one idea of this chapter

Seeing is not acting: a returned image becomes evidence only when bound, a coordinate only with its frame, and an action only with a checked effect.

The one idea of this chapter

Seeing is not acting: a returned image becomes evidence only when bound, a coordinate only with its frame, and an action only with a checked effect.

Goal: type the visual episode, test whether images matter, follow a returned crop into an actual policy update, diagnose a perception–action mismatch — and keep every claim in its evidence class.

Roadmap


A typed evidence-to-action loop

Learning from visual outcomes

Interaction, diagnosis, and evidence


A typed evidence-to-action loop

From a chosen view to a checked effect




- Typed records: observation lineage, coordinate frames, grounding objects, and a validator that yields pre-action eligibility only.

From a chosen view to a checked effect



- Typed records: observation lineage, coordinate frames, grounding objects, and a validator that yields pre-action eligibility only.
- Swap and mask interventions test whether the image matters; a vision-indispensability certificate admits tasks into curriculum cells.

From a chosen view to a checked effect



- Typed records: observation lineage, coordinate frames, grounding objects, and a validator that yields pre-action eligibility only.
- Swap and mask interventions test whether the image matters; a vision-indispensability certificate admits tasks into curriculum cells.
- K3 reports Python over images with returned-image observations; its trainer, mixture, and rewards stay undisclosed. [REPORTED: K3 Sec. 4.2.3]

Learning from visual outcomes

Outcome feedback changes behavior — not always for the better

- Rewards come from an independent verifier; masks mark sampled assistant spans, while returned images condition without owning action terms.

Outcome feedback changes behavior — not always for the better

- Rewards come from an independent verifier; masks mark sampled assistant spans, while returned images condition without owning action terms.
- A crop is a budgeted information action; crop-only is optimal for $0.4 \leq \lambda \leq 2.7$ in the teaching fixture. [DERIVED: teaching inputs]

Outcome feedback changes behavior — not always for the better

- Rewards come from an independent verifier; masks mark sampled assistant spans, while returned images condition without owning action terms.
- A crop is a budgeted information action; crop-only is optimal for $0.4 \leq \lambda \leq 2.7$ in the teaching fixture. [DERIVED: teaching inputs]
- Panel study: replacing the crop's digit flips 13 of 16 answers, yet the trained inspection readout learns to answer 7 early — 14/16 cold falls to 10/16. [OBSERVED: book study]

Interaction, diagnosis, and evidence

Interaction, diagnosis, and evidence

- GUI witnesses bind state versions: a version-11 click at version 12 is rejected before dispatch.

Interaction, diagnosis, and evidence

- GUI witnesses bind state versions: a version-11 click at version 12 is rejected before dispatch.
- The studio's legacy click clipped to $(150, 159)$ selects nothing; an oracle-transform replay selects blue at state 22 and isolates T under single-fault assumptions.

Interaction, diagnosis, and evidence

- GUI witnesses bind state versions: a version-11 click at version 12 is rejected before dispatch.
- The studio's legacy click clipped to $(150, 159)$ selects nothing; an oracle-transform replay selects blue at state 22 and isolates T under single-fault assumptions.
- Released K3: CharXiv 84.8→91.3, MathVision 94.3→97.8 with Python — evaluation modes, not a training ablation. [REPORTED: K3 release]

Interaction, diagnosis, and evidence

- GUI witnesses bind state versions: a version-11 click at version 12 is rejected before dispatch.
- The studio's legacy click clipped to $(150, 159)$ selects nothing; an oracle-transform replay selects blue at state 22 and isolates T under single-fault assumptions.
- Released K3: CharXiv 84.8→91.3, MathVision 94.3→97.8 with Python — evaluation modes, not a training ablation. [REPORTED: K3 release]

Keep interface, sensitivity, and learning claims apart. Next: Chapter 26's Parallel-Agent Reinforcement Learning and Agent Swarms.