

SUPAgent

Agent Integration & Operations Runbook

Brewed Roots Co. — Customer Support Agent · v1.0 · Last updated: January 2026

1. Overview

This runbook describes how to integrate and operate the customer-support agent that SUPAgent generated from your documents. The agent reads incoming support tickets, gathers facts using your connected tools, then resolves the ticket or escalates it according to your policies. It is delivered two ways: a hosted API endpoint you can call today, and a version-controlled repository you own and can hand to your own engineers.

2. Your live endpoint

The agent is reachable at the endpoint below. Send a ticket as JSON; the agent returns a drafted reply plus the action it took (resolved or escalated).

```
POST https://api.agentfactory.dev/brewed-roots/support/tickets
Authorization: Bearer <YOUR_API_KEY>
Content-Type: application/json

{
  "from": "customer@example.com",
  "subject": "Where is my order #BR-20481?",
  "body": "Hi, my order hasn't arrived yet..."
}
```

Response — the agent returns its decision, the drafted reply, and whether a human was looped in:

```
{
  "action": "resolved",
  "reply": "Hi Maya, thanks for reaching out...",
  "escalated": false,
  "tools_used": ["look_up_order", "send_email_reply"]
}
```

3. Authentication

Every request must include your API key as a Bearer token in the **Authorization** header. Keep this key secret; rotate it from your SUPAgent dashboard if it is ever exposed. Never embed it in client-side code.

4. Configuration — values you provide

The agent references the following via environment variables. SUPAgent fills the platform values; the items marked **you provide** connect the agent to your own systems. Add them to the repository's `.env` file.

EMAIL_PROVIDER_KEY	you provide — credentials for the mailbox the agent replies from.
---------------------------	---

ORDER_DB_URL / KEY	you provide — read access to your order system for lookups.
---------------------------	---

CRM_API_KEY	you provide — to log subscription and account changes.
--------------------	--

ALLOWED_RECIPIENTS	you provide — comma-separated list the agent may email.
---------------------------	---

REFUND_CAP	default 100 — refunds at or above this are escalated, not auto-issued.
-------------------	--

5. Guardrails & safety

These protections are enforced in code, not in the prompt, so a malicious or manipulative ticket cannot talk the agent past them:

- **Recipient allow-list** — the agent only sends email to approved addresses.
- **Refund cap** — refunds of \$100 or more are escalated to the Support Lead.
- **Identity gate** — order or account details are released only after the customer is verified (order number + email on file).
- **Untrusted input** — ticket text is treated as data and can never authorize a privileged action.

6. Escalation routing

Refund $\geq$ \$100	Support Lead — Zendesk escalation queue (SLA: 1 business day).
Legal / fraud signal	Legal & Compliance — legal@brewedrootsco.com (SLA: 4 business hours).
Account deletion	Data Privacy team — privacy@brewedrootsco.com.

7. Updating the agent

When your policies, brand, or processes change, re-upload the updated documents in SUPAgent and rebuild. The agent is regenerated, re-tested against its eval suite, and reviewed by the supervisor before the new version goes live. Your endpoint URL stays the same.

8. Ownership & support

You own the generated repository outright — there is no platform lock-in. Your engineers can read, modify, and self-host it at any time. For help, contact your SUPAgent representative.