

Contents

Service Fusion API Reference	1
Authentication	1
Common Query Parameters (Traits)	1
Data Types	17
/me	65
/calendar-tasks	68
/calendar-tasks/{calendar-task-id}	71
/customers	75
/customers/{customer-id}	88
/customers/{customer-id}/equipment	93
/customers/{customer-id}/equipment/{equipment-id}	97
/jobs	101
/jobs/{job-id}	116
/job-categories	123
/job-categories/{job-category-id}	126
/job-statuses	129
/job-statuses/{job-status-id}	133
/estimates	136
/estimates/{estimate-id}	150
/invoices	156
/invoices/{invoice-id}	160
/payment-types	165
/payment-types/{payment-type-id}	168
/sources	172
/sources/{source-id}	175
/techs	179
/techs/{tech-id}	183
Known Issues	187

Service Fusion API Reference

Auto-generated from the official RAML spec at docs.servicefusion.com Generated: 2026-04-10

- **Base URL:** <https://api.servicefusion.com/{version}>
- **Version:** v1
- **Media Type:** application/json
- **Protocol:** HTTPS

Authentication

oauth_2_0

This API supports OAuth 2.0 for authenticating all API requests.

Query Parameters: - **access_token:** Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Headers: - **Authorization:** Used to send a valid OAuth 2 access token. Do not use together with the access_token query parameter.

Settings: - **accessTokenUri:** https://api.servicefusion.com/oauth/access_token - **authorization-Grants:** ["authorization_code", "client_credentials"]

Common Query Parameters (Traits)

tra.formatable

Parameter	Type	Required	Default	Description
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Enum: json, xml

tra.me-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, first_name, last_name, email
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.calendarTask-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, type, description, start_time, end_time, start_date, end_date, created_at, updated_at, is_public, is_completed, repeat_id, users_id, customers_id, jobs_id, estimates_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Enum: repeat

tra.calendarTask-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, type, description, start_time, end_time, start_date, end_date, created_at, updated_at, is_public, is_completed, repeat_id

tra.customer-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, customer_name, fully_qualified_name, account_number, account_balance, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_served_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Enum: contacts, contacts.phones, contacts.emails, locations, custom_fields

tra.customer-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, customer_name, fully_qualified_name, account_number, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_serviced_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry

tra.customer-filtrable

Parameter	Type	Required	Default	Description
filters[name]	string	No	-	Used to filter results by given name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[postal_code]	integer	No	-	Used to filter results by given postal code (full match).
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).

Parameter	Type	Required	Default	Description
filters[tags]	string	No	-	Used to filter results by given tags (full match). Accepted value is comma-separated string.
filters[last_serviced_date][lte]	string	No	-	Used to filter results by given less than or equal of last serviced date (format: Y-m-d).
filters[last_serviced_date][gte]	string	No	-	Used to filter results by given greater than or equal of last serviced date (format: Y-m-d).
filters[agreement_date][lte]	string	No	-	Used to filter results by given less than or equal of agreement date effective (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][gte]	string	No	-	Used to filter results by given greater than or equal of agreement date effective (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][lte]	string	No	-	Used to filter results by given less than or equal of agreement date expires (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][gte]	string	No	-	Used to filter results by given greater than or equal of agreement date expires (format RFC 3339: Y-m-d\TH:i:sP).

tra.job-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, number, check_number, priority, description, tech_notes, completion_notes, payment_status, taxes_fees_total, drive_labor_total, billable_expenses_total, total, payments_deposits_total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, called_in_by, is_requires_follow_up
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Enum: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, labor_charges, expenses, payments, invoices, signatures, printable_work_order, visits, visits.techs_assigned

tra.job-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, number, po_number, check_number, description, tech_notes, completion_notes, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, status, sub_status, category, source, payment_type, customer_payment_terms, contract, called_in_by

tra.job-filtrable

Parameter	Type	Required	Default	Description
filters[status]	string	No	-	Used to filter results by given statuses (full match). Accepted value is comma-separated string.
filters[number]	string	No	-	Used to filter results by given number (partial match).
filters[po_number]	string	No	-	Used to filter results by given po number (partial match).
filters[invoice_number]	string	No	-	Used to filter results by given invoice number (partial match).
filters[customer_name]	string	No	-	Used to filter results by given customer's name (partial match).
filters[parent_customer_name]	string	No	-	Used to filter results by given parent customer's name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).

Parameter	Type	Required	Default	Description
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[zip_code]	integer	No	-	Used to filter results by given zip code (full match).
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).
filters[category]	string	No	-	Used to filter results by given categories (full match). Accepted value is comma-separated string.
filters[source]	string	No	-	Used to filter results by given sources (full match). Accepted value is comma-separated string.
filters[start_date][lte]	string	No	-	Used to filter results by given less than or equal of start date (format: Y-m-d).
filters[start_date][gte]	string	No	-	Used to filter results by given greater than or equal of start date (format: Y-m-d).
filters[end_date][lte]	string	No	-	Used to filter results by given less than or equal of end date (format: Y-m-d).
filters[end_date][gte]	string	No	-	Used to filter results by given greater than or equal of end date (format: Y-m-d).
filters[updated_date][lte]	string	No	-	Used to filter results by given less than or equal of updated date (format RFC 3339: Y-m-d\TH:i:sP).
filters[updated_date][gte]	string	No	-	Used to filter results by given greater than or equal of updated date (format RFC 3339: Y-m-d\TH:i:sP).
filters[closed_date][lte]	string	No	-	Used to filter results by given less than or equal of closed date (format RFC 3339: Y-m-d\TH:i:sP).

Parameter	Type	Required	Default	Description
filters[closed_date] typed	string	No	-	Used to filter results by given greater than or equal of closed date (format RFC 3339: Y-m-d\TH:i:sP).

tra.jobCategory-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.jobCategory-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, name

tra.jobStatus-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, code, name, is_custom, category
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.jobStatus-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, code, name, is_custom, category

tra.estimate-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, number, description, tech_notes, payment_status, taxes_fees_total, total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, opportunity_rating, opportunity_owner

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Enum: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, payments, signatures, printable_work_order, tags

tra.estimate-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, number, po_number, description, tech_notes, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, status, sub_status, category, source, payment_type, customer_payment_terms, contract, opportunity_rating

tra.estimate-filtrable

Parameter	Type	Required	Default	Description
filters[status]	string	No	-	Used to filter results by given statuses (full match). Accepted value is comma-separated string.
filters[number]	string	No	-	Used to filter results by given number (partial match).
filters[po_number]	string	No	-	Used to filter results by given po number (partial match).

Parameter	Type	Required	Default	Description
filters[customer_name]	string	No	-	Used to filter results by given customer's name (partial match).
filters[parent_customer_name]	string	No	-	Used to filter results by given parent customer's name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[zip_code]	integer	No	-	Used to filter results by given zip code (full match).
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).
filters[category]	string	No	-	Used to filter results by given categories (full match). Accepted value is comma-separated string.
filters[source]	string	No	-	Used to filter results by given sources (full match). Accepted value is comma-separated string.
filters[start_date][lte]	string	No	-	Used to filter results by given less than or equal of start date (format: Y-m-d).
filters[start_date][gte]	string	No	-	Used to filter results by given greater than or equal of start date (format: Y-m-d).
filters[end_date][lte]	string	No	-	Used to filter results by given less than or equal of end date (format: Y-m-d).
filters[end_date][gte]	string	No	-	Used to filter results by given greater than or equal of end date (format: Y-m-d).
filters[requested_date][lte]	string	No	-	Used to filter results by given less than or equal of requested date (format RFC 3339: Y-m-d\TH:i:sP).

Parameter	Type	Required	Default	Description
filters[requested_date][gte]	string	No	-	Used to filter results by given greater than or equal of requested date (format RFC 3339: Y-m-d\TH:i:sP).

tra.invoice-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, number, currency, po_number, terms, customer_message, notes, pay_online_url, qbo_invoice_no, qbo_sync_token, qbo_synced_date, qbo_id, qbd_id, total, is_paid, date, mail_send_date, created_at, updated_at, customer, customer_contact, payment_terms, bill_to_customer_id, bill_to_customer_location_id, bill_to_customer_contact_id, bill_to_email_id, bill_to_phone_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.invoice-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, number, currency, po_number, terms, customer_message, notes, qbo_invoice_no, qbo_sync_token, qbo_synced_date, qbo_id, qbd_id, total, is_paid, date, mail_send_date, created_at, updated_at, customer, customer_contact, payment_terms, bill_to_customer_id, bill_to_customer_location_id, bill_to_customer_contact_id, bill_to_email_id, bill_to_phone_id

tra.paymentType-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, code, short_name, type, is_custom
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.paymentType-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, code, short_name, type, is_custom

tra.source-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, short_name, long_name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.source-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, short_name, long_name

tra.tech-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, first_name, last_name, nickname_on_workorder, nickname_on_dispatch, color_code, email, phone_1, phone_2, gender, department, title, bio, is_phone_1_mobile, is_phone_1_visible_to_client, is_phone_2_mobile, is_phone_2_visible_to_client, is_sales_rep, is_field_worker, created_at, updated_at
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

tra.tech-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, first_name, last_name, nickname_on_workorder, nickname_on_dispatch, color_code, email, phone_1, phone_2, gender, department, title, bio, is_phone_1_mobile, is_phone_1_visible_to_client, is_phone_2_mobile, is_phone_2_visible_to_client, is_sales_rep, is_field_worker, created_at, updated_at

tra.tech-filtrable

Parameter	Type	Required	Default	Description
filters[first_name]	string	No	-	Used to filter results by given first name (partial match).
filters[last_name]	string	No	-	Used to filter results by given last name (partial match).
filters[email]	string	No	-	Used to filter results by given email (partial match).
filters[nickname_on_workorder]	string	No	-	Used to filter results by given nickname on workorder (partial match).
filters[nickname_on_dispatch]	string	No	-	Used to filter results by given nickname on dispatch (partial match).

tra.equipment-fieldable

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Enum: id, type, make, model, sku, serial_number, location, notes, extended_warranty_provider, is_extended_warranty, extended_warranty_date, warranty_date, install_date, created_at, updated_at, customer_id, customer, customer_location
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Enum: custom_fields

tra.equipment-sortable

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Enum: id, type, make, model, sku, serial_number, location, notes, extended_warranty_provider, is_extended_warranty, extended_warranty_date, warranty_date, install_date, created_at, updated_at, customer_id, customer, customer_location

Data Types

OAuthToken

An authentication schema.

Field	Type	Required	Description
access_token	string	No	The access token string as issued by the authorization server.

Field	Type	Required	Description
token_type	string	No	The type of token this is.
expires_in	integer	No	The duration of time the access token is granted for.
refresh_token	string	No	When an access token expires (exceeds the expires_in time), the refresh_token is used to obtain a new access token.

OAuthTokenError

An authentication error's schema.

Field	Type	Required	Description
error	string	No	The error title.
error_description	string	No	The error description.

typ.Error

An error's schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.400Error

Bad request client's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.404Error

Not found client's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.405Error

Method not allowed client's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.415Error

Unsupported media type client's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.422Error

Unprocessable entity client's error schema.

typ.429Error

Too many requests client's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.500Error

Internal server's error schema.

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

typ.Agent

An agent's schema.

Field	Type	Required	Description
id	integer	No	The agent's identifier.
first_name	string	No	The agent's first name.
last_name	string	No	The agent's last name.

typ.AgentBody

An agent's body schema.

Field	Type	Required	Description
id	integer	No	Used to send the agent's identifier that will be searched. If this field is set then the entry will be searched by it, otherwise the search will be performed by its full name.
first_name	string	No	Used to send the agent's first name that will be searched. Required field for full name search.
last_name	string	No	Used to send the agent's last name that will be searched. Required field for full name search.

typ.AssignedTech

An assigned tech's schema.

Field	Type	Required	Description
id	integer	No	The assigned tech's identifier.
first_name	string	No	The assigned tech's first name.
last_name	string	No	The assigned tech's last name.

typ.AssignedTechBody

An assigned tech's body schema.

Field	Type	Required	Description
id	integer	No	Used to send the assigned tech's identifier that will be searched. If this field is set then the entry will be searched by it, otherwise the search will be performed by its full name.
first_name	string	No	Used to send the assigned tech's first name that will be searched. Required field for full name search.
last_name	string	No	Used to send the assigned tech's last name that will be searched. Required field for full name search.

typ.CalendarTask

A calendar task's schema.

Field	Type	Required	Description
id	integer	No	The calendar task's identifier.
type	string	No	The calendar task's type.
description	string	No	The calendar task's description.
start_time	string	No	The calendar task's start time.
end_time	string	No	The calendar task's end time.
start_date	datetime	No	The calendar task's start date.
end_date	datetime	No	The calendar task's end date.
created_at	datetime	No	The calendar task's created date.
updated_at	datetime	No	The calendar task's updated date.
is_public	boolean	No	The calendar task's is public flag.
is_completed	boolean	No	The calendar task's is completed flag.
repeat_id	integer	No	The calendar task's repeat id.
users_id	array	Yes	The calendar task's users list of identifiers.
customers_id	array	Yes	The calendar task's customers list of identifiers.
jobs_id	array	Yes	The calendar task's jobs list of identifiers.
estimates_id	array	Yes	The calendar task's estimates list of identifiers.
repeat	object	No	The calendar task's repeat.

typ.CalendarTaskView

A calendar task's schema.

Field	Type	Required	Description
id	integer	No	The calendar task's identifier.
type	string	No	The calendar task's type.
description	string	No	The calendar task's description.
start_time	string	No	The calendar task's start time.
end_time	string	No	The calendar task's end time.
start_date	datetime	No	The calendar task's start date.
end_date	datetime	No	The calendar task's end date.
created_at	datetime	No	The calendar task's created date.
updated_at	datetime	No	The calendar task's updated date.
is_public	boolean	No	The calendar task's is public flag.
is_completed	boolean	No	The calendar task's is completed flag.
repeat_id	integer	No	The calendar task's repeat id.
users_id	array	Yes	The calendar task's users list of identifiers.
customers_id	array	Yes	The calendar task's customers list of identifiers.
jobs_id	array	Yes	The calendar task's jobs list of identifiers.
estimates_id	array	Yes	The calendar task's estimates list of identifiers.
repeat	object	No	The calendar task's repeat.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.CalendarTaskRepeat

A calendar task repeat's schema.

Field	Type	Required	Description
id	integer	No	The repeat's identifier.
repeat_type	string	No	The repeat's type.
repeat_frequency	integer	No	The repeat's frequency.
repeat_weekly_days	array	Yes	The repeat's weekly days list.
repeat_monthly_type	string	No	The repeat's monthly type.
stop_repeat_type	string	No	The repeat's stop type.
stop_repeat_on_occurrence	integer	No	The repeat's stop on occurrence.
stop_repeat_on_date	datetime	No	The repeat's stop on date.
start_date	datetime	No	The repeat's start date.
end_date	datetime	No	The repeat's end date.

typ.CustomField

A custom field's schema.

Field	Type	Required	Description
name	string	No	The custom field's name.
value	any	No	The custom field's value.
type	string	No	The custom field's type.
group	string	No	The custom field's group.
created_at	datetime	No	The custom field's created date.
updated_at	datetime	No	The custom field's updated date.
is_required	boolean	No	The custom field's is required flag.

typ.CustomFieldBody

A custom field's body schema.

Field	Type	Required	Description
name	string	Yes	Used to send the custom field's name that will be set.
value	any	Yes	Used to send the custom field's value that will be set.

typ.Customer

A customer's schema.

Field	Type	Required	Description
id	integer	No	The customer's identifier.
customer_name	string	No	The customer's name.
fully_qualified_name	string	No	The customer's fully qualified name.
parent_customer	string	No	The header of attached parent customer to the customer (Note: header - [string] the parent customer's fields concatenated by pattern {first_name}{last_name} with space as separator).

Field	Type	Required	Description
account_number	string	No	The customer's account number.
account_balance	number	No	The customer's account balance.
private_notes	string	No	The customer's private notes.
public_notes	string	No	The customer's public notes.
credit_rating	string	No	The customer's credit rating.
labor_charge_type	string	No	The customer's labor charge type.
labor_charge_default_rate	number	No	The customer's labor charge default rate.
last_serviced_date	datetime	No	The customer's last serviced date.
is_bill_for_drive_time	boolean	No	The customer's is bill for drive time flag.
is_vip	boolean	No	The customer's is vip flag.
referral_source	string	No	The header of attached referral source to the customer (Note: header - [string] the referral source's fields concatenated by pattern {short_name}).
agent	string	No	The header of attached agent to the customer (Note: header - [string] the agent's fields concatenated by pattern {first_name} {last_name} with space as separator).
discount	number	No	The customer's discount.
discount_type	string	No	The customer's discount type.
payment_type	string	No	The header of attached payment type to the customer (Note: header - [string] the payment type's fields concatenated by pattern {name}).
payment_terms	string	No	The customer's payment terms.
assigned_contract	string	No	The header of attached contract to the customer (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
industry	string	No	The header of attached industry to the customer (Note: header - [string] the industry's fields concatenated by pattern {industry}).
is_taxable	boolean	No	The customer's is taxable flag.
tax_item_name	string	No	The header of attached tax item to the customer (Note: header - [string] the tax item's fields concatenated by pattern {short_name} with space as separator).
qbo_sync_token	integer	No	The customer's qbo sync token.
qbo_currency	string	No	The customer's qbo currency.
qbo_id	integer	No	The customer's qbo id.
qbd_id	string	No	The customer's qbd id.
created_at	datetime	No	The customer's created date.
updated_at	datetime	No	The customer's updated date.
contacts	array	No	The customer's contacts list.
locations	array	No	The customer's locations list.
custom_fields	array	No	The customer's custom fields list.

typ.CustomerBody

A customer's body schema.

Field	Type	Required	Description
customer_name	string	Yes	Used to send the customer's name that will be set.
parent_customer	string	No	Used to send a parent customer's id or header that will be attached to the customer (Note: id - [integer] the parent customer's identifier, header - [string] the parent customer's fields conca
account_number	string	No	Used to send the customer's account number that will be set.
private_notes	string	No	Used to send the customer's private notes that will be set.
public_notes	string	No	Used to send the customer's public notes that will be set.
credit_rating	string	No	Used to send the customer's credit rating that will be set.
labor_charge_type	string	No	Used to send the customer's labor charge type that will be set.
labor_charge_default_rate	float	No	Used to send the customer's labor charge default rate that will be set.
last_serviced_date	datetime	No	Used to send the customer's last serviced date that will be set.
is_bill_for_drive_time	boolean	No	Used to send the customer's is bill for drive time flag that will be set.
is_vip	boolean	No	Used to send the customer's is vip flag that will be set.
referral_source	string	No	Used to send a referral source's id or header that will be attached to the customer (Note: id - [integer] the referral source's identifier, header - [string] the referral source's fields conca

Field	Type	Required	Description
agent	string	No	Used to send an agent's id or header that will be attached to the customer (Note: id - [integer] the agent's identifier, header - [string] the agent's fields concatenated by pattern {first_na discount number No Used to send the customer's discount that will be set. discount_type string No Used to send the customer's discount type that will be set. payment_type string No Used to send a payment type's id or header that will be attached to the customer (Note: id - [integer] the payment type's identifier, header - [string] the payment type's fields concatenated by payment_terms string No Used to send the customer's payment terms that will be set. assigned_contract string No Used to send an assigned contract's id or header that will be attached to the customer (Note: id - [integer] the assigned contract's identifier, header - [string] the assigned contract's field industry string No Used to send an industry's id or header that will be attached to the customer (Note: id - [integer] the industry's identifier, header - [string] the industry's fields concatenated by pattern
is_taxable	boolean	No	Used to send the customer's is taxable flag that will be set.

Field	Type	Required	Description
tax_item_name	string	No	Used to send a tax item's id or header that will be attached to the customer (Note: id - [integer] the tax item's identifier, header - [string] the tax item's fields concatenated by pattern { qbo_sync_token integer No Used to send the customer's qbo sync token that will be set. qbo_currency string No Used to send the customer's qbo currency that will be set. contacts array No Used to send the customer's contacts list that will be set. locations array No Used to send the customer's locations list that will be set. custom_fields'

typ.CustomerView

A customer's schema.

Field	Type	Required	Description
id	integer	No	The customer's identifier.
customer_name	string	No	The customer's name.
fully_qualified_name	string	No	The customer's fully qualified name.
parent_customer	string	No	The header of attached parent customer to the customer (Note: header - [string] the parent customer's fields concatenated by pattern {first_name}{last_name} with space as separator).
account_number	string	No	The customer's account number.
account_balance	number	No	The customer's account balance.
private_notes	string	No	The customer's private notes.
public_notes	string	No	The customer's public notes.
credit_rating	string	No	The customer's credit rating.
labor_charge_type	string	No	The customer's labor charge type.
labor_charge_default_rate	number	No	The customer's labor charge default rate.
last_serviced_date	datetime	No	The customer's last serviced date.
is_bill_for_drive_time	boolean	No	The customer's is bill for drive time flag.
is_vip	boolean	No	The customer's is vip flag.
referral_source	string	No	The header of attached referral source to the customer (Note: header - [string] the referral source's fields concatenated by pattern {short_name}).

Field	Type	Required	Description
agent	string	No	The header of attached agent to the customer (Note: header - [string] the agent's fields concatenated by pattern {first_name} {last_name} with space as separator).
discount	number	No	The customer's discount.
discount_type	string	No	The customer's discount type.
payment_type	string	No	The header of attached payment type to the customer (Note: header - [string] the payment type's fields concatenated by pattern {name}).
payment_terms	string	No	The customer's payment terms.
assigned_contract	string	No	The header of attached contract to the customer (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
industry	string	No	The header of attached industry to the customer (Note: header - [string] the industry's fields concatenated by pattern {industry}).
is_taxable	boolean	No	The customer's is taxable flag.
tax_item_name	string	No	The header of attached tax item to the customer (Note: header - [string] the tax item's fields concatenated by pattern {short_name} with space as separator).
qbo_sync_token	integer	No	The customer's qbo sync token.
qbo_currency	string	No	The customer's qbo currency.
qbo_id	integer	No	The customer's qbo id.
qbd_id	string	No	The customer's qbd id.
created_at	datetime	No	The customer's created date.
updated_at	datetime	No	The customer's updated date.
contacts	array	No	The customer's contacts list.
locations	array	No	The customer's locations list.
custom_fields	array	No	The customer's custom fields list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.CustomerContact

A customer contact's schema.

Field	Type	Required	Description
prefix	string	No	The contact's prefix.
fname	string	No	The contact's first name.
lname	string	No	The contact's last name.
suffix	string	No	The contact's suffix.
contact_type	string	No	The contact's type.
dob	string	No	The contact's dob.
anniversary	string	No	The contact's anniversary.
job_title	string	No	The contact's job title.

Field	Type	Required	Description
department	string	No	The contact's department.
created_at	datetime	No	The contact's created date.
updated_at	datetime	No	The contact's updated date.
is_primary	boolean	No	The contact's is primary flag.
phones	array	No	The contact's phones list.
emails	array	No	The contact's emails list.

typ.CustomerContactBody

A customer contact's body schema.

Field	Type	Required	Description
prefix	string	No	Used to send the contact's prefix that will be set.
fname	string	Yes	Used to send the contact's first name that will be set.
lname	string	Yes	Used to send the contact's last name that will be set.
suffix	string	No	Used to send the contact's suffix that will be set.
contact_type	string	No	Used to send the contact's type that will be set.
dob	string	No	Used to send the contact's dob that will be set.
anniversary	string	No	Used to send the contact's anniversary that will be set.
job_title	string	No	Used to send the contact's job title that will be set.
department	string	No	Used to send the contact's department that will be set.
is_primary	boolean	No	Used to send the contact's is primary flag that will be set. When it is passed as true, then the customer's existing primary contact (if any) will become secondary, and this one will become the prim
phones	array	No	Used to send the contact's phones list that will be set.
emails	array	No	Used to send the contact's emails list that will be set.

typ.CustomerEmail

A customer email's schema.

Field	Type	Required	Description
email	string	No	The email's address.
class	string	No	The email's class.
types_accepted	string	No	The email's types accepted.
created_at	datetime	No	The email's created date.
updated_at	datetime	No	The email's updated date.

typ.CustomerEmailBody

A customer email's body schema.

Field	Type	Required	Description
email	string	Yes	Used to send the email's address that will be set.
class	string	No	Used to send the email's class that will be set.
types_accepted	string	No	Used to send the email's types accepted that will be set. Accepted value is comma-separated string.

typ.CustomerLocation

A customer location's schema.

Field	Type	Required	Description
street_1	string	No	The location's street 1.
street_2	string	No	The location's street 2.
city	string	No	The location's city.
state_prov	string	No	The location's state.
postal_code	string	No	The location's postal code.
country	string	No	The location's country.
nickname	string	No	The location's nickname.
gate_instructions	string	No	The location's gate instructions.
latitude	number	No	The location's latitude.
longitude	number	No	The location's longitude.
location_type	string	No	The location's type.
created_at	datetime	No	The location's created date.
updated_at	datetime	No	The location's updated date.
is_primary	boolean	No	The location's is primary flag.
is_gated	boolean	No	The location's is gated flag.
is_bill_to	boolean	No	The location's is bill to flag.
customer_contact	string	No	The header of attached customer contact to the location (Note: header - [string] the customer contact's fields concatenated by pattern {fname} {lname} with space as separator).

typ.CustomerLocationBody

A customer location's body schema.

Field	Type	Required	Description
street_1	string	Yes	Used to send the location's street 1 that will be set.
street_2	string	No	Used to send the location's street 2 that will be set.
city	string	No	Used to send the location's city that will be set.
state_prov	string	No	Used to send the location's state that will be set.
postal_code	string	No	Used to send the location's postal code that will be set.
country	string	No	Used to send the location's country that will be set.
nickname	string	No	Used to send the location's nickname that will be set.

Field	Type	Required	Description
gate_instructions	string	No	Used to send the location's gate instructions that will be set.
latitude	number	No	Used to send the location's latitude that will be set.
longitude	number	No	Used to send the location's longitude that will be set.
location_type	string	No	Used to send the location's type that will be set.
is_primary	boolean	No	Used to send the location's is primary flag that will be set. When it is passed as true, then the customer's existing primary location (if any) will become secondary, and this one will become the pr
is_gated	boolean	No	Used to send the location's is gated flag that will be set.
is_bill_to	boolean	No	Used to send the location's is bill to flag that will be set.
customer_contact	string	No	Used to send a customer contact's id or header that will be attached to the location (Note: id - [integer] the customer contact's identifier, header - [string] the customer contact's fields co

typ.CustomerPhone

A customer phone's schema.

Field	Type	Required	Description
phone	string	No	The phone's number.
ext	integer	No	The phone's extension.
type	string	No	The phone's type.
created_at	datetime	No	The phone's created date.
updated_at	datetime	No	The phone's updated date.
is_mobile	boolean	No	The phone's is mobile flag.

typ.CustomerPhoneBody

A customer phone's body schema.

Field	Type	Required	Description
phone	string	Yes	Used to send the phone's number that will be set.
ext	integer	No	Used to send the phone's extension that will be set.
type	string	No	Used to send the phone's type that will be set.

typ.Equipment

An equipment's schema.

Field	Type	Required	Description
id	integer	No	The equipment's identifier.
type	string	No	The equipment's type.
make	string	No	The equipment's make.
model	string	No	The equipment's model.
sku	string	No	The equipment's sku.
serial_number	string	No	The equipment's serial number.
location	string	No	The equipment's location.
notes	string	No	The equipment's notes.
extended_warranty_provider	string	No	The equipment's extended warranty provider.
is_extended_warranty	boolean	No	The equipment's is extended warranty flag.
extended_warranty_date	datetime	No	The equipment's extended warranty date.
warranty_date	datetime	No	The equipment's warranty date.
install_date	datetime	No	The equipment's install date.
created_at	datetime	No	The equipment's created date.
updated_at	datetime	No	The equipment's updated date.
customer_id	integer	No	The id of attached customer to the equipment (Note: id - [integer] the customer's identifier).
customer	string	No	The header of attached customer to the equipment (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_location	string	No	The header of attached customer location to the equipment (Note: header - [string] the customer location's fields concatenated by pattern {nickname} {street_1} {city} with space as separator).
custom_fields	array	No	The equipment's custom fields list.

typ.EquipmentBody

An equipment's body schema.

Field	Type	Required	Description
id	string	No	Used to send the equipment's identifier that will be searched. You may pass this parameter if you do not want to create new entry but assign existing one. You may assign by identifier or header (N
type	string	No	Used to send the equipment's type that will be set.
make	string	No	Used to send the equipment's make that will be set.
model	string	No	Used to send the equipment's model that will be set.
sku	string	No	Used to send the equipment's sku that will be set.
serial_number	string	No	Used to send the equipment's serial number that will be set.

Field	Type	Required	Description
location	string	No	Used to send the equipment's location that will be set.
notes	string	No	Used to send the equipment's notes that will be set.
extended_warranty_provider	string	No	Used to send the equipment's extended warranty provider that will be set.
is_extended_warranty	boolean	No	Used to send the equipment's is extended warranty flag that will be set.
extended_warranty_date	datetime	No	Used to send the equipment's extended warranty date that will be set.
warranty_date	datetime	No	Used to send the equipment's warranty date that will be set.
install_date	datetime	No	Used to send the equipment's install date that will be set.
customer_location	string	No	Used to send a customer location's id or header that will be attached to the equipment (Note: id - [integer] the customer location's identifier, header - [string] the customer location's field)
custom_fields	array	No	Used to send the equipment's custom fields list that will be set.

typ.EquipmentView

An equipment's schema.

Field	Type	Required	Description
id	integer	No	The equipment's identifier.
type	string	No	The equipment's type.
make	string	No	The equipment's make.
model	string	No	The equipment's model.
sku	string	No	The equipment's sku.
serial_number	string	No	The equipment's serial number.
location	string	No	The equipment's location.
notes	string	No	The equipment's notes.
extended_warranty_provider	string	No	The equipment's extended warranty provider.
is_extended_warranty	boolean	No	The equipment's is extended warranty flag.
extended_warranty_date	datetime	No	The equipment's extended warranty date.
warranty_date	datetime	No	The equipment's warranty date.
install_date	datetime	No	The equipment's install date.
created_at	datetime	No	The equipment's created date.
updated_at	datetime	No	The equipment's updated date.
customer_id	integer	No	The id of attached customer to the equipment (Note: id - [integer] the customer's identifier).

Field	Type	Required	Description
customer	string	No	The header of attached customer to the equipment (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_location	string	No	The header of attached customer location to the equipment (Note: header - [string] the customer location's fields concatenated by pattern {nickname} {street_1} {city} with space as separator).
custom_fields	array	No	The equipment's custom fields list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Estimate

An estimate's schema.

Field	Type	Required	Description
id	integer	No	The estimate's identifier.
number	string	No	The estimate's number.
description	string	No	The estimate's description.
tech_notes	string	No	The estimate's tech notes.
customer_payment_terms	string	No	The estimate's customer payment terms.
payment_status	string	No	The estimate's payment status.
taxes_fees_total	number	No	The estimate's taxes and fees total.
total	number	No	The estimate's total.
due_total	number	No	The estimate's due total.
cost_total	number	No	The estimate's cost total.
duration	integer	No	The estimate's duration (in seconds).
time_frame_promised_start	string	No	The estimate's time frame promised start.
time_frame_promised_end	string	No	The estimate's time frame promised end.
start_date	datetime	No	The estimate's start date.
created_at	datetime	No	The estimate's created date.
updated_at	datetime	No	The estimate's updated date.
customer_id	integer	No	The id of attached customer to the estimate (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the estimate (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the estimate (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).

Field	Type	Required	Description
status	string	No	The header of attached status to the estimate (Note: header - [string] the status's fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the estimate (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The estimate's contact first name.
contact_last_name	string	No	The estimate's contact last name.
street_1	string	No	The estimate's location street 1.
street_2	string	No	The estimate's location street 2.
city	string	No	The estimate's location city.
state_prov	string	No	The estimate's location state prov.
postal_code	string	No	The estimate's location postal code.
location_name	string	No	The estimate's location name.
is_gated	boolean	No	The estimate's location is gated flag.
gate_instructions	string	No	The estimate's location gate instructions.
category	string	No	The header of attached category to the estimate (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the estimate (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the estimate (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
project	string	No	The header of attached project to the estimate (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the estimate (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The estimate's po number.
contract	string	No	The header of attached contract to the estimate (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The estimate's note to customer.
opportunity_rating	integer	No	The estimate's opportunity rating.
opportunity_owner	string	No	The header of attached opportunity owner to the estimate (Note: header - [string] the opportunity owner's fields concatenated by pattern {first_name} {last_name} with space as separator).

Field	Type	Required	Description
agents	array	No	The estimate's agents list.
custom_fields	array	No	The estimate's custom fields list.
pictures	array	No	The estimate's pictures list.
documents	array	No	The estimate's documents list.
equipment	array	No	The estimate's equipments list.
techs_assigned	array	No	The estimate's techs assigned list.
tasks	array	No	The estimate's tasks list.
notes	array	No	The estimate's notes list.
products	array	No	The estimate's products list.
services	array	No	The estimate's services list.
other_charges	array	No	The estimate's other charges list.
payments	array	No	The estimate's payments list.
signatures	array	No	The estimate's signatures list.
printable_work_order	array	No	The estimate's printable work order list.
tags	array	No	The estimate's tags list.

typ.EstimateBody

An estimate's body schema.

Field	Type	Required	Description
description	string	No	Used to send the estimate's description that will be set.
tech_notes	string	No	Used to send the estimate's tech notes that will be set.
duration	integer	No	Used to send the estimate's duration (in seconds) that will be set.
time_frame_promised_start	string	No	Used to send the estimate's time frame promised start that will be set.
time_frame_promised_end	string	No	Used to send the estimate's time frame promised end that will be set.
start_date	datetime	No	Used to send the estimate's start date that will be set.
created_at	datetime	No	Used to send the estimate's created date that will be set.
customer_name	string	Yes	Used to send a customer's id or header that will be attached to the estimate (Note: id - [integer] the customer's identifier, header - [string] the customer's fields concatenated by pattern { status string No Used to send a status'es id or header that will be attached to the estimate (Note: id- [integer] the status'es identifier, header- [string] the status'es fields concatenated by pattern {nam

Field	Type	Required	Description
contact_first_name	string	No	Used to send the estimate's contact first name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached.
contact_last_name	string	No	Used to send the estimate's contact last name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached.
street_1	string	No	Used to send the estimate's location street 1 that will be set.
street_2	string	No	Used to send the estimate's location street 2 that will be set.
city	string	No	Used to send the estimate's location city that will be set.
state_prov	string	No	Used to send the estimate's location state prov that will be set.
postal_code	string	No	Used to send the estimate's location postal code that will be set.
location_name	string	No	Used to send the estimate's location name that will be set.
is_gated	boolean	No	Used to send the estimate's location is gated flag that will be set.
gate_instructions	string	No	Used to send the estimate's location gate instructions that will be set.
category	string	No	Used to send a category's id or header that will be attached to the estimate (Note: id - [integer] the category's identifier, header - [string] the category's fields concatenated by pattern { source string No Used to send a source's identifier that will be attached to the estimate (Note: id - [integer] the source's identifier, header - [string] the source's fields concatenated by pattern {short_

Field	Type	Required	Description
project	string	No	Used to send a project's id or header that will be attached to the estimate (Note: id - [integer] the project's identifier, header - [string] the project's fields concatenated by pattern {nam phase string No Used to send a phase's id or header that will be attached to the estimate (Note: id - [integer] the phase's identifier, header - [string] the phase's fields concatenated by pattern {name}). po_number string No Used to send the estimate's po number that will be set. contract string No Used to send a contract's id or header that will be attached to the estimate (Note: id - [integer] the contract's identifier, header - [string] the contract's fields concatenated by pattern {
note_to_customer	string	No	Used to send the estimate's note to customer that will be set.
opportunity_rating	integer	No	Used to send the estimate's opportunity rating that will be set.
opportunity_owner	string	No	Used to send an opportunity owner's id or header that will be attached to the estimate (Note: id - [integer] the opportunity owner's identifier, header - [string] the opportunity owner's field
custom_fields	array	No	Used to send the estimate's custom fields list that will be set.
equipment	array	No	Used to send the estimate's equipments list that will be set.
techs_assigned	array	No	Used to send the estimate's techs assigned list that will be set.
tasks	array	No	Used to send the estimate's tasks list that will be set.
notes	array	No	Used to send the estimate's notes list that will be set.
products	array	No	Used to send the estimate's products list that will be set.
services	array	No	Used to send the estimate's services list that will be set.
other_charges	array	No	Used to send the estimate's other charges list that will be set.
tags	array	No	Used to send the estimate's tags list that will be set.

typ.EstimateView

An estimate's schema.

Field	Type	Required	Description
id	integer	No	The estimate's identifier.
number	string	No	The estimate's number.
description	string	No	The estimate's description.
tech_notes	string	No	The estimate's tech notes.
customer_payment_terms	string	No	The estimate's customer payment terms.
payment_status	string	No	The estimate's payment status.
taxes_fees_total	number	No	The estimate's taxes and fees total.
total	number	No	The estimate's total.
due_total	number	No	The estimate's due total.
cost_total	number	No	The estimate's cost total.
duration	integer	No	The estimate's duration (in seconds).
time_frame_promised_start	string	No	The estimate's time frame promised start.
time_frame_promised_end	string	No	The estimate's time frame promised end.
start_date	datetime	No	The estimate's start date.
created_at	datetime	No	The estimate's created date.
updated_at	datetime	No	The estimate's updated date.
customer_id	integer	No	The id of attached customer to the estimate (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the estimate (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the estimate (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the estimate (Note: header - [string] the status's fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the estimate (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The estimate's contact first name.
contact_last_name	string	No	The estimate's contact last name.
street_1	string	No	The estimate's location street 1.
street_2	string	No	The estimate's location street 2.
city	string	No	The estimate's location city.
state_prov	string	No	The estimate's location state prov.
postal_code	string	No	The estimate's location postal code.
location_name	string	No	The estimate's location name.
is_gated	boolean	No	The estimate's location is gated flag.
gate_instructions	string	No	The estimate's location gate instructions.
category	string	No	The header of attached category to the estimate (Note: header - [string] the category's fields concatenated by pattern {category}).

Field	Type	Required	Description
source	string	No	The header of attached source to the estimate (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the estimate (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
project	string	No	The header of attached project to the estimate (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the estimate (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The estimate's po number.
contract	string	No	The header of attached contract to the estimate (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The estimate's note to customer.
opportunity_rating	integer	No	The estimate's opportunity rating.
opportunity_owner	string	No	The header of attached opportunity owner to the estimate (Note: header - [string] the opportunity owner's fields concatenated by pattern {first_name} {last_name} with space as separator).
agents	array	No	The estimate's agents list.
custom_fields	array	No	The estimate's custom fields list.
pictures	array	No	The estimate's pictures list.
documents	array	No	The estimate's documents list.
equipment	array	No	The estimate's equipments list.
techs_assigned	array	No	The estimate's techs assigned list.
tasks	array	No	The estimate's tasks list.
notes	array	No	The estimate's notes list.
products	array	No	The estimate's products list.
services	array	No	The estimate's services list.
other_charges	array	No	The estimate's other charges list.
payments	array	No	The estimate's payments list.
signatures	array	No	The estimate's signatures list.
printable_work_order	array	No	The estimate's printable work order list.
tags	array	No	The estimate's tags list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Invoice

An invoice's schema.

Field	Type	Required	Description
id	integer	No	The invoice's identifier.
number	integer	No	The invoice's number.
currency	string	No	The invoice's currency.
po_number	string	No	The invoice's po number.
terms	string	No	The invoice's terms.
customer_message	string	No	The invoice's customer message.
notes	string	No	The invoice's notes.
pay_online_url	string	No	The invoice's pay online url.
qbo_invoice_no	integer	No	The invoice's qbo invoice no.
qbo_sync_token	integer	No	The invoice's qbo sync token.
qbo_synced_date	datetime	No	The invoice's qbo synced date.
qbo_id	integer	No	The invoice's qbo class id.
qbd_id	string	No	The invoice's qbd class id.
total	number	No	The invoice's total.
is_paid	boolean	No	The invoice's is paid flag.
date	datetime	No	The invoice's date.
mail_send_date	datetime	No	The invoice's mail send date.
created_at	datetime	No	The invoice's created date.
updated_at	datetime	No	The invoice's updated date.
customer	string	No	The header of attached customer to the invoice (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_contact	string	No	The header of attached customer contact to the invoice (Note: header - [string] the customer contact's fields concatenated by pattern {fname} {lname} with space as separator).
payment_terms	string	No	The header of attached payment term to the invoice (Note: header - [string] the payment term's fields concatenated by pattern {name}).
bill_to_customer_id	integer	No	The id of attached bill to customer to the invoice (Note: id - [integer] the bill to customer's identifier).
bill_to_customer_location_id	integer	No	The id of attached bill to customer location to the invoice (Note: id - [integer] the bill to customer location's identifier).
bill_to_customer_contact_id	integer	No	The id of attached bill to customer contact to the invoice (Note: id - [integer] the bill to customer contact's identifier).
bill_to_email_id	integer	No	The id of attached bill to email to the invoice (Note: id - [integer] the bill to email's identifier).
bill_to_phone_id	integer	No	The id of attached bill to phone to the invoice (Note: id - [integer] the bill to phone's identifier).

typ.InvoiceView

An invoice's schema.

Field	Type	Required	Description
id	integer	No	The invoice's identifier.
number	integer	No	The invoice's number.
currency	string	No	The invoice's currency.
po_number	string	No	The invoice's po number.
terms	string	No	The invoice's terms.
customer_message	string	No	The invoice's customer message.
notes	string	No	The invoice's notes.
pay_online_url	string	No	The invoice's pay online url.
qbo_invoice_no	integer	No	The invoice's qbo invoice no.
qbo_sync_token	integer	No	The invoice's qbo sync token.
qbo_synced_date	datetime	No	The invoice's qbo synced date.
qbo_id	integer	No	The invoice's qbo class id.
qbd_id	string	No	The invoice's qbd class id.
total	number	No	The invoice's total.
is_paid	boolean	No	The invoice's is paid flag.
date	datetime	No	The invoice's date.
mail_send_date	datetime	No	The invoice's mail send date.
created_at	datetime	No	The invoice's created date.
updated_at	datetime	No	The invoice's updated date.
customer	string	No	The header of attached customer to the invoice (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_contact	string	No	The header of attached customer contact to the invoice (Note: header - [string] the customer contact's fields concatenated by pattern {fname} {lname} with space as separator).
payment_terms	string	No	The header of attached payment term to the invoice (Note: header - [string] the payment term's fields concatenated by pattern {name}).
bill_to_customer_id	integer	No	The id of attached bill to customer to the invoice (Note: id - [integer] the bill to customer's identifier).
bill_to_customer_location_id	integer	No	The id of attached bill to customer location to the invoice (Note: id - [integer] the bill to customer location's identifier).
bill_to_customer_contact_id	integer	No	The id of attached bill to customer contact to the invoice (Note: id - [integer] the bill to customer contact's identifier).
bill_to_email_id	integer	No	The id of attached bill to email to the invoice (Note: id - [integer] the bill to email's identifier).
bill_to_phone_id	integer	No	The id of attached bill to phone to the invoice (Note: id - [integer] the bill to phone's identifier).
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Job

A job's schema.

Field	Type	Required	Description
id	integer	No	The job's identifier.
number	string	No	The job's number.
check_number	string	No	The job's check number.
priority	string	No	The job's priority.
description	string	No	The job's description.
tech_notes	string	No	The job's tech notes.
completion_notes	string	No	The job's completion notes.
payment_status	string	No	The job's payment status.
taxes_fees_total	number	No	The job's taxes and fees total.
drive_labor_total	number	No	The job's drive and labor total.
billable_expenses_total	number	No	The job's billable expenses total.
total	number	No	The job's total.
payments_deposits_total	number	No	The job's payments and deposits total.
due_total	number	No	The job's due total.
cost_total	number	No	The job's cost total.
duration	integer	No	The job's duration (in seconds).
time_frame_promised_start	string	No	The job's time frame promised start.
time_frame_promised_end	string	No	The job's time frame promised end.
start_date	datetime	No	The job's start date.
end_date	datetime	No	The job's end date.
created_at	datetime	No	The job's created date.
updated_at	datetime	No	The job's updated date.
closed_at	datetime	No	The job's closed date.
customer_id	integer	No	The id of attached customer to the job (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the job (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the job (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the job (Note: header - [string] the status'es fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the job (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The job's contact first name.
contact_last_name	string	No	The job's contact last name.
street_1	string	No	The job's location street 1.
street_2	string	No	The job's location street 2.
city	string	No	The job's location city.
state_prov	string	No	The job's location state prov.
postal_code	string	No	The job's location postal code.
location_name	string	No	The job's location name.
is_gated	boolean	No	The job's location is gated flag.
gate_instructions	string	No	The job's location gate instructions.

Field	Type	Required	Description
category	string	No	The header of attached category to the job (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the job (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the job (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
customer_payment_term	string	No	The header of attached customer payment term to the job (Note: header - [string] the customer payment term's fields concatenated by pattern {name}).
project	string	No	The header of attached project to the job (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the job (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The job's po number.
contract	string	No	The header of attached contract to the job (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The job's note to customer.
called_in_by	string	No	The job's called in by.
is_requires_followup	boolean	No	The job's is requires follow up flag.
agents	array	No	The job's agents list.
custom_fields	array	No	The job's custom fields list.
pictures	array	No	The job's pictures list.
documents	array	No	The job's documents list.
equipment	array	No	The job's equipments list.
techs_assigned	array	No	The job's techs assigned list.
tasks	array	No	The job's tasks list.
notes	array	No	The job's notes list.
products	array	No	The job's products list.
services	array	No	The job's services list.
other_charges	array	No	The job's other charges list.
labor_charges	array	No	The job's labor charges list.
expenses	array	No	The job's expenses list.
payments	array	No	The job's payments list.
invoices	array	No	The job's invoices list.
signatures	array	No	The job's signatures list.
printable_work_order	array	No	The job's printable work order list.
visits	array	No	The job's visits list.

typ.JobBody

A job's body schema.

Field	Type	Required	Description
check_number	string	No	Used to send the job's check number that will be set.
priority	string	No	Used to send the job's priority that will be set.
description	string	No	Used to send the job's description that will be set.
tech_notes	string	No	Used to send the job's tech notes that will be set.
completion_notes	string	No	Used to send the job's completion notes that will be set.
duration	integer	No	Used to send the job's duration (in seconds) that will be set.
time_frame_promised_start	string	No	Used to send the job's time frame promised start that will be set.
time_frame_promised_end	string	No	Used to send the job's time frame promised end that will be set.
start_date	datetime	No	Used to send the job's start date that will be set.
end_date	datetime	No	Used to send the job's end date that will be set.

Field	Type	Required	Description
customer_name	string	Yes	Used to send a customer's id or header that will be attached to the job (Note: id - [integer] the customer's identifier, header - [string] the customer's fields concatenated by pattern {custo status string No Used to send a status'esidorheaderthat will be attached to the job (Note:id- [integer] the status'es identifier,header-[string] the status'es fields concatenated by pattern{name}). contact_first_name string No Used to send the job's contact first name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached. contact_last_name string No Used to send the job's contact last name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached. street_1 string No Used to send the job's location street 1 that will be set. street_2 string No Used to send the job's location street 2 that will be set. city string No Used to send the job's location city that will be set. state_prov string No Used to send the job's location state prov that will be set. postal_code string No Used to send the job's location postal code that will be set. location_name string No Used to send the job's location name that will be set. is_gated boolean No Used to send the job's location is gated flag that will be set. gate_instructions string No Used to send the job's location gate instructions that will be set. category string No Used to send a category'sidorheaderthat will be attached to the job (Note:id- [integer] the category's identifier,header-

Field	Type	Required	Description
source	string	No	Used to send a source's id or header that will be attached to the job (Note: id - [integer] the source's identifier, header - [string] the source's fields concatenated by pattern {short_name} payment_type string No Used to send a payment type's id or header that will be attached to the job (Note: id - [integer] the payment type's identifier, header - [string] the payment type's fields concatenated by pat customer_payment_terms string No Used to send a customer payment term's id or header that will be attached to the job (Note: id - [integer] the customer payment term's identifier, header - [string] the customer payment term's project string No Used to send a project's id or header that will be attached to the job (Note: id - [integer] the project's identifier, header - [string] the project's fields concatenated by pattern {name})). phase string No Used to send a phase's id or header that will be attached to the job (Note: id - [integer] the phase's identifier, header - [string] the phase's fields concatenated by pattern {name})). po_number string No Used to send the job's po number that will be set. contract string No Used to send a contract's id or header that will be attached to the job (Note: id - [integer] the contract's identifier, header - [string] the contract's fields concatenated by pattern {contr
note_to_customer	string	No	Used to send the job's note to customer that will be set.
called_in_by	string	No	Used to send the job's called in by that will be set.
is_requires_followup	boolean	No	Used to send the job's is requires follow up flag that will be set.
agents	array	No	Used to send the job's agents list that will be set.

Field	Type	Required	Description
custom_fields	array	No	Used to send the job's custom fields list that will be set.
equipment	array	No	Used to send the job's equipments list that will be set.
techs_assigned	array	No	Used to send the job's techs assigned list that will be set.
tasks	array	No	Used to send the job's tasks list that will be set.
notes	array	No	Used to send the job's notes list that will be set.
products	array	No	Used to send the job's products list that will be set.
services	array	No	Used to send the job's services list that will be set.
other_charges	array	No	Used to send the job's other charges list that will be set.
labor_charges	array	No	Used to send the job's labor charges list that will be set.
expenses	array	No	Used to send the job's expenses list that will be set.

typ.JobView

A job's schema.

Field	Type	Required	Description
id	integer	No	The job's identifier.
number	string	No	The job's number.
check_number	string	No	The job's check number.
priority	string	No	The job's priority.
description	string	No	The job's description.
tech_notes	string	No	The job's tech notes.
completion_notes	string	No	The job's completion notes.
payment_status	string	No	The job's payment status.
taxes_fees_total	number	No	The job's taxes and fees total.
drive_labor_total	number	No	The job's drive and labor total.
billable_expenses_total	number	No	The job's billable expenses total.
total	number	No	The job's total.
payments_deposits_total	number	No	The job's payments and deposits total.
due_total	number	No	The job's due total.
cost_total	number	No	The job's cost total.
duration	integer	No	The job's duration (in seconds).
time_frame_promised_start	string	No	The job's time frame promised start.
time_frame_promised_end	string	No	The job's time frame promised end.
start_date	datetime	No	The job's start date.
end_date	datetime	No	The job's end date.
created_at	datetime	No	The job's created date.
updated_at	datetime	No	The job's updated date.
closed_at	datetime	No	The job's closed date.
customer_id	integer	No	The id of attached customer to the job (Note: id - [integer] the customer's identifier).

Field	Type	Required	Description
customer_name	string	No	The header of attached customer to the job (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the job (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the job (Note: header - [string] the status'es fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the job (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The job's contact first name.
contact_last_name	string	No	The job's contact last name.
street_1	string	No	The job's location street 1.
street_2	string	No	The job's location street 2.
city	string	No	The job's location city.
state_prov	string	No	The job's location state prov.
postal_code	string	No	The job's location postal code.
location_name	string	No	The job's location name.
is_gated	boolean	No	The job's location is gated flag.
gate_instructions	string	No	The job's location gate instructions.
category	string	No	The header of attached category to the job (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the job (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the job (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
customer_payment_term	string	No	The header of attached customer payment term to the job (Note: header - [string] the customer payment term's fields concatenated by pattern {name}).
project	string	No	The header of attached project to the job (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the job (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The job's po number.
contract	string	No	The header of attached contract to the job (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).

Field	Type	Required	Description
note_to_customer	string	No	The job's note to customer.
called_in_by	string	No	The job's called in by.
is_requires_followup	boolean	No	The job's is requires follow up flag.
agents	array	No	The job's agents list.
custom_fields	array	No	The job's custom fields list.
pictures	array	No	The job's pictures list.
documents	array	No	The job's documents list.
equipment	array	No	The job's equipments list.
techs_assigned	array	No	The job's techs assigned list.
tasks	array	No	The job's tasks list.
notes	array	No	The job's notes list.
products	array	No	The job's products list.
services	array	No	The job's services list.
other_charges	array	No	The job's other charges list.
labor_charges	array	No	The job's labor charges list.
expenses	array	No	The job's expenses list.
payments	array	No	The job's payments list.
invoices	array	No	The job's invoices list.
signatures	array	No	The job's signatures list.
printable_work_order	array	No	The job's printable work order list.
visits	array	No	The job's visits list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.JobCategory

A job category's schema.

Field	Type	Required	Description
id	integer	No	The job category's identifier.
name	string	No	The job category's name.

typ.JobCategoryView

A job category's schema.

Field	Type	Required	Description
id	integer	No	The job category's identifier.
name	string	No	The job category's name.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.JobStatus

A job statuse's schema.

Field	Type	Required	Description
id	integer	No	The job statuse's identifier.
code	string	No	The job statuse's code.
name	string	No	The job statuse's name.
is_custom	string	No	The job statuse's is custom flag.

Field	Type	Required	Description
category	string	No	The header of attached category to the status (Note: header - [string] the category's fields concatenated by pattern {code}).

typ.JobStatusView

A job statuse's schema.

Field	Type	Required	Description
id	integer	No	The job statuse's identifier.
code	string	No	The job statuse's code.
name	string	No	The job statuse's name.
is_custom	string	No	The job statuse's is custom flag.
category	string	No	The header of attached category to the status (Note: header - [string] the category's fields concatenated by pattern {code}).
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.JobDocument

A job document's schema.

Field	Type	Required	Description
name	string	No	The document's name.
file_location	string	No	The document's file location.
doc_type	string	No	The document's type.
comment	string	No	The document's comment.
sort	integer	No	The document's sort.
is_private	boolean	No	The document's is private flag.
created_at	datetime	No	The document's created date.
updated_at	datetime	No	The document's updated date.
customer_doc_id	integer	No	The id of attached customer doc to the document (Note: id - [integer] the customer doc's identifier).

typ.JobExpense

A job expense's schema.

Field	Type	Required	Description
purchased_from	string	No	The expense's purchased from.
notes	string	No	The expense's notes.
amount	number	No	The expense's amount.
is_billable	boolean	No	The expense's is billable flag.
date	datetime	No	The expense's date.
created_at	datetime	No	The expense's created date.
updated_at	datetime	No	The expense's updated date.

Field	Type	Required	Description
user	string	No	The header of attached user to the expense (Note: header - [string] the user's fields concatenated by pattern {first_name} {last_name} with space as separator).
category	string	No	The header of attached category to the expense (Note: header - [string] the category's fields concatenated by pattern {category_name}).
qbo_class_id	integer	No	The id of attached qbo class to the expense (Note: id - [integer] the qbo class's identifier).
qbd_class_id	integer	No	The id of attached qbd class to the expense (Note: id - [integer] the qbd class's identifier).

typ.JobExpenseBody

A job expense's body schema.

Field	Type	Required	Description
purchased_from	string	No	Used to send the expense's purchased from that will be set.
notes	string	No	Used to send the expense's notes that will be set.
amount	number	No	Used to send the expense's amount that will be set.
is_billable	boolean	No	Used to send the expense's is billable flag that will be set.
date	datetime	No	Used to send the expense's date that will be set.
user	string	No	Used to send a user's id or header that will be attached to the expense (Note: id - [integer] the user's identifier, header - [string] the user's fields concatenated by pattern {first_name} { category string No Used to send a category's id or header that will be attached to the expense (Note: id - [integer] the category's identifier, header - [string] the category's fields concatenated by pattern {c

typ.JobLaborCharge

A job labor charge's schema.

Field	Type	Required	Description
drive_time	integer	No	The labor charge's drive time.
drive_time_rate	number	No	The labor charge's drive time rate.

Field	Type	Required	Description
drive_time_cost	number	No	The labor charge's drive time cost.
drive_time_start	string	No	The labor charge's drive time start.
drive_time_end	string	No	The labor charge's drive time end.
is_drive_time_billed	boolean	No	The labor charge's is drive time billed flag.
labor_time	integer	No	The labor charge's labor time.
labor_time_rate	number	No	The labor charge's labor time rate.
labor_time_cost	number	No	The labor charge's labor time cost.
labor_time_start	string	No	The labor charge's labor time start.
labor_time_end	string	No	The labor charge's labor time end.
labor_date	datetime	No	The labor charge's labor date.
is_labor_time_billed	boolean	No	The labor charge's is labor time billed flag.
total	number	No	The labor charge's total.
created_at	datetime	No	The labor charge's created date.
updated_at	datetime	No	The labor charge's updated date.
is_status_generated	boolean	No	The labor charge's is status generated flag.
user	string	No	The header of attached user to the labor charge (Note: header - [string] the user's fields concatenated by pattern {first_name} {last_name} with space as separator).
visit_id	integer	No	The id of attached visit to the labor charge (Note: id - [integer] the visit's identifier).
qbo_class_id	integer	No	The id of attached qbo class to the labor charge (Note: id - [integer] the qbo class's identifier).
qbd_class_id	integer	No	The id of attached qbd class to the labor charge (Note: id - [integer] the qbd class's identifier).

typ.JobLaborChargeBody

A job labor charge's body schema.

Field	Type	Required	Description
drive_time	integer	No	Used to send the labor charge's drive time that will be set. Forbidden if drive times start/end passed.
drive_time_rate	number	No	Used to send the labor charge's drive time rate that will be set.
drive_time_cost	number	No	Used to send the labor charge's drive time cost that will be set.
drive_time_start	string	No	Used to send the labor charge's drive time start that will be set. Required if drive time end passed.
drive_time_end	string	No	Used to send the labor charge's drive time end that will be set. Required if drive time start passed. Must be greater than drive time start.

Field	Type	Required	Description
is_drive_time_billed	boolean	No	Used to send the labor charge's is drive time billed flag that will be set.
labor_time	integer	No	Used to send the labor charge's labor time that will be set. Forbidden if labor times start/end passed.
labor_time_rate	number	No	Used to send the labor charge's labor time rate that will be set.
labor_time_cost	number	No	Used to send the labor charge's labor time cost that will be set.
labor_time_start	string	No	Used to send the labor charge's labor time start that will be set.
labor_time_end	string	No	Required if labor time end passed. Used to send the labor charge's labor time end that will be set. Required if labor time start passed. Must be greater than labor time start.
labor_date	datetime	No	Used to send the labor charge's labor date that will be set.
is_labor_time_billed	boolean	No	Used to send the labor charge's is labor time billed flag that will be set.
user	string	No	Used to send a user's id or header that will be attached to the labor charge (Note: id - [integer] the user's identifier, header - [string] the user's fields concatenated by pattern '{first_na

typ.JobNote

A job note's schema.

Field	Type	Required	Description
notes	string	No	The note's text.
created_at	datetime	No	The note's created date.
updated_at	datetime	No	The note's updated date.

typ.JobNoteBody

A job note's body schema.

Field	Type	Required	Description
notes	string	Yes	Used to send the note's text that will be set.

typ.JobOtherCharge

A job other charge's schema.

Field	Type	Required	Description
name	string	No	The other charge's name.
rate	number	No	The other charge's rate.
total	number	No	The other charge's total.
charge_index	integer	No	The other charge's index.
parent_index	integer	No	The other charge's parent index.
is_percentage	boolean	No	The other charge's is percentage flag.
is_discount	boolean	No	The other charge's is discount flag.
created_at	datetime	No	The other charge's created date.
updated_at	datetime	No	The other charge's updated date.
other_charge	string	No	The header of attached other charge to the other charge (Note: header - [string] the other charge's fields concatenated by pattern {short_name}).
applies_to	string	No	The other charge's applies to.
service_list_id	integer	No	The id of attached service list to the other charge (Note: id - [integer] the service list's identifier).
other_charge_id	integer	No	The id of attached other charge to the other charge (Note: id - [integer] the other charge's identifier).
pattern_row_id	integer	No	The id of attached pattern row to the other charge (Note: id - [integer] the pattern row's identifier).
qbo_class_id	integer	No	The id of attached qbo class to the other charge (Note: id - [integer] the qbo class's identifier).
qbd_class_id	integer	No	The id of attached qbd class to the other charge (Note: id - [integer] the qbd class's identifier).

typ.JobOtherChargeBody

A job other charge's body schema.

Field	Type	Required	Description
name	string	No	Used to send the other charge's name that will be set.
rate	number	No	Used to send the other charge's rate that will be set.
is_percentage	boolean	No	Used to send the other charge's is percentage flag that will be set.
other_charge	string	Yes	Used to send an other charge's id or header that will be attached to the other charge (Note: id - [integer] the other charge's identifier, header - [string] the other charge's fields concatenated

typ.JobProduct

A job product's schema.

Field	Type	Required	Description
name	string	No	The product's name.
description	string	No	The product's description.
multiplier	integer	No	The product's quantity.
rate	number	No	The product's rate.
total	number	No	The product's total.
cost	number	No	The product's cost.
actual_cost	number	No	The product's actual cost.
item_index	integer	No	The product's item index.
parent_index	integer	No	The product's parent index.
created_at	datetime	No	The product's created date.
updated_at	datetime	No	The product's updated date.
is_show_rate_items	boolean	No	The product's is show rate items flag.
tax	string	No	The header of attached tax to the product (Note: header - [string] the tax's fields concatenated by pattern {short_name}).
product	string	No	The header of attached product to the product (Note: header - [string] the product's fields concatenated by pattern {make}).
product_list_id	integer	No	The id of attached product list to the product (Note: id - [integer] the product list's identifier).
warehouse_id	integer	No	The id of attached warehouse to the product (Note: id - [integer] the warehouse's identifier).
pattern_row_id	integer	No	The id of attached pattern row to the product (Note: id - [integer] the pattern row's identifier).
qbo_class_id	integer	No	The id of attached qbo class to the product (Note: id - [integer] the qbo class's identifier).
qbd_class_id	integer	No	The id of attached qbd class to the product (Note: id - [integer] the qbd class's identifier).

typ.JobProductBody

A job product's body schema.

Field	Type	Required	Description
name	string	No	Used to send the product's name that will be set.
description	string	No	Used to send the product's description that will be set.
multiplier	integer	No	Used to send the product's quantity that will be set.
rate	number	No	Used to send the product's rate that will be set.
cost	number	No	Used to send the product's cost that will be set.
is_show_rate_items	boolean	No	Used to send the product's is show rate items flag that will be set.

Field	Type	Required	Description
tax	string	No	Used to send a tax's id or header that will be attached to the product (Note: id - [integer] the tax's identifier, header - [string] the tax's fields concatenated by pattern {short_name})
product	string	Yes	Used to send a product's id or header that will be attached to the product (Note: id - [integer] the product's identifier, header - [string] the product's fields concatenated by pattern '{make

typ.JobService

A job service's schema.

Field	Type	Required	Description
name	string	No	The service's name.
description	string	No	The service's description.
multiplier	integer	No	The service's quantity.
rate	number	No	The service's rate.
total	number	No	The service's total.
cost	number	No	The service's cost.
actual_cost	number	No	The service's actual cost.
item_index	integer	No	The service's item index.
parent_index	integer	No	The service's parent index.
created_at	datetime	No	The service's created date.
updated_at	datetime	No	The service's updated date.
is_show_rate_items	boolean	No	The service's is show rate items flag.
tax	string	No	The header of attached tax to the service (Note: header - [string] the tax's fields concatenated by pattern {short_name}).
service	string	No	The header of attached service to the service (Note: header - [string] the service's fields concatenated by pattern {short_description}).
service_list_id	integer	No	The id of attached service list to the service (Note: id - [integer] the service list's identifier).
service_rate_id	integer	No	The id of attached service rate to the service (Note: id - [integer] the service rate's identifier).
pattern_row_id	integer	No	The id of attached pattern row to the service (Note: id - [integer] the pattern row's identifier).
qbo_class_id	integer	No	The id of attached qbo class to the service (Note: id - [integer] the qbo class's identifier).
qbd_class_id	integer	No	The id of attached qbd class to the service (Note: id - [integer] the qbd class's identifier).

typ.JobServiceBody

A job service's body schema.

Field	Type	Required	Description
name	string	No	Used to send the service's name that will be set.
description	string	No	Used to send the service's description that will be set.
multiplier	integer	No	Used to send the service's quantity that will be set.
rate	number	No	Used to send the service's rate that will be set.
cost	number	No	Used to send the service's cost that will be set.
is_show_rate_items	boolean	No	Used to send the service's is show rate items flag that will be set.
tax	string	No	Used to send a tax's id or header that will be attached to the service (Note: id - [integer] the tax's identifier, header - [string] the tax's fields concatenated by pattern {short_name})
service	string	Yes	Used to send a service's id or header that will be attached to the service (Note: id - [integer] the service's identifier, header - [string] the service's fields concatenated by pattern '{shor

typ.JobSignature

A job signature's schema.

Field	Type	Required	Description
type	string	No	The signature's type.
file_name	string	No	The signature's file name.
created_at	datetime	No	The signature's created date.
updated_at	datetime	No	The signature's updated date.

typ.JobTag

A job tag's schema.

Field	Type	Required	Description
tag	string	No	The tag's unique tag.
created_at	datetime	No	The tag's created date.
updated_at	datetime	No	The tag's updated date.

typ.JobTagBody

A job tag's body schema.

Field	Type	Required	Description
tag	string	Yes	Used to send the tag's unique tag that will be set.

typ.JobTask

A job task's schema.

Field	Type	Required	Description
type	string	No	The task's type.
description	string	No	The task's description.
start_time	string	No	The task's start time.
start_date	datetime	No	The task's start date.
end_date	datetime	No	The task's end date.
is_completed	boolean	No	The task's is completed flag.
created_at	datetime	No	The task's created date.
updated_at	datetime	No	The task's updated date.

typ.JobTaskBody

A job task's body schema.

Field	Type	Required	Description
description	string	Yes	Used to send the task's description that will be set.
is_completed	boolean	No	Used to send the task's is completed flag that will be set.

typ.JobVisit

A job visit's schema.

Field	Type	Required	Description
notes_for_techs	string	No	The visit's notes for techs.
time_frame_promised_start	string	No	The visit's time frame promised start.
time_frame_promised_end	string	No	The visit's time frame promised end.
duration	integer	No	The visit's duration (in seconds).
is_text_notified	boolean	No	The visit's is text notified flag.
is_voice_notified	boolean	No	The visit's is voice notified flag.
start_date	datetime	No	The visit's start date.
techs_assigned	array	No	The visit's techs assigned list.

typ.MeView

An authenticated user's schema.

Field	Type	Required	Description
id	integer	No	The authenticated user's identifier.
first_name	string	No	The authenticated user's first name.
last_name	string	No	The authenticated user's last name.

Field	Type	Required	Description
email	string	No	The authenticated user's email.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Payment

A payment's schema.

Field	Type	Required	Description
transaction_type	string	No	The payment's transaction type.
transaction_token	string	No	The payment's transaction token.
transaction_id	string	No	The id of attached transaction to the payment (Note: id - [integer] the transaction's identifier).
payment_transaction_id	integer	No	The id of attached payment transaction to the payment (Note: id - [integer] the payment transaction's identifier).
original_transaction_id	integer	No	The id of attached original transaction to the payment (Note: id - [integer] the original transaction's identifier).
apply_to	string	No	The payment's apply to.
amount	number	No	The payment's amount.
memo	string	No	The payment's memo.
authorization_code	string	No	The payment's authorization code.
bill_to_street_address	string	No	The payment's bill to street address.
bill_to_postal_code	string	No	The payment's bill to postal code.
bill_to_country	string	No	The payment's bill to country.
reference_number	string	No	The payment's reference number.
is_resync_qbo	boolean	No	The payment's is resync qbo flag.
created_at	datetime	No	The payment's created date.
updated_at	datetime	No	The payment's updated date.
received_on	datetime	No	The payment's received date.
qbo_synced_date	datetime	No	The payment's qbo synced date.
qbo_id	integer	No	The id of attached qbo class to the payment (Note: id - [integer] the qbo class's identifier).
qbd_id	string	No	The id of attached qbd class to the payment (Note: id - [integer] the qbd class's identifier).
customer	string	No	The header of attached customer to the payment (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
type	string	No	The header of attached customer payment method to the payment (Note: header - [string] the customer payment method's fields concatenated by pattern {cc_type} {first_four} {last_four} with space

Field	Type	Required	Description
invoice_id	integer	No	The id of attached invoice to the payment (Note: id - [integer] the invoice's identifier).
gateway_id	integer	No	The id of attached gateway to the payment (Note: id - [integer] the gateway's identifier).
receipt_id	string	No	The id of attached receipt to the payment (Note: id - [integer] the receipt's identifier).

typ.PaymentType

A payment type's schema.

Field	Type	Required	Description
id	integer	No	The type's identifier.
code	string	No	The type's code.
short_name	string	No	The type's short name.
type	string	No	The type's type.
is_custom	boolean	No	The type's is custom flag.

typ.PaymentTypeView

A payment type's schema.

Field	Type	Required	Description
id	integer	No	The type's identifier.
code	string	No	The type's code.
short_name	string	No	The type's short name.
type	string	No	The type's type.
is_custom	boolean	No	The type's is custom flag.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.PrintableWorkOrder

A printable work order's schema.

Field	Type	Required	Description
name	string	No	The printable work order's name.
url	string	No	The printable work order's url.

typ.Source

A source's schema.

Field	Type	Required	Description
id	integer	No	The source's identifier.
short_name	string	No	The source's short name.
long_name	string	No	The source's long name.

typ.SourceView

A source's schema.

Field	Type	Required	Description
id	integer	No	The source's identifier.
short_name	string	No	The source's short name.
long_name	string	No	The source's long name.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Tech

A tech's schema.

Field	Type	Required	Description
id	integer	No	The tech's identifier.
first_name	string	No	The tech's first name.
last_name	string	No	The tech's last name.
nickname_on_workorder	string	No	The tech's nickname on workorder.
nickname_on_dispatch	string	No	The tech's nickname on dispatch.
color_code	string	No	The tech's color code.
email	string	No	The tech's email.
phone_1	string	No	The tech's phone 1.
phone_2	string	No	The tech's phone 2.
gender	string	No	The tech's gender.
department	string	No	The tech's department.
title	string	No	The tech's title.
bio	string	No	The tech's bio.
is_phone_1_mobile	boolean	No	The tech's is phone 1 mobile flag.
is_phone_1_visible_to_client	boolean	No	The tech's is phone 1 visible to client flag.
is_phone_2_mobile	boolean	No	The tech's is phone 2 mobile flag.
is_phone_2_visible_to_client	boolean	No	The tech's is phone 2 visible to client flag.
is_sales_rep	boolean	No	The tech's is sales rep flag.
is_field_worker	boolean	No	The tech's is field worker flag.
created_at	datetime	No	The tech's created date.
updated_at	datetime	No	The tech's updated date.

typ.TechView

A tech's schema.

Field	Type	Required	Description
id	integer	No	The tech's identifier.
first_name	string	No	The tech's first name.
last_name	string	No	The tech's last name.
nickname_on_workorder	string	No	The tech's nickname on workorder.
nickname_on_dispatch	string	No	The tech's nickname on dispatch.
color_code	string	No	The tech's color code.
email	string	No	The tech's email.
phone_1	string	No	The tech's phone 1.
phone_2	string	No	The tech's phone 2.
gender	string	No	The tech's gender.

Field	Type	Required	Description
department	string	No	The tech's department.
title	string	No	The tech's title.
bio	string	No	The tech's bio.
is_phone_1_mobile	boolean	No	The tech's is phone 1 mobile flag.
is_phone_1_visible_to_client	boolean	No	The tech's is phone 1 visible to client flag.
is_phone_2_mobile	boolean	No	The tech's is phone 2 mobile flag.
is_phone_2_visible_to_client	boolean	No	The tech's is phone 2 visible to client flag.
is_sales_rep	boolean	No	The tech's is sales rep flag.
is_field_worker	boolean	No	The tech's is field worker flag.
created_at	datetime	No	The tech's created date.
updated_at	datetime	No	The tech's updated date.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

typ.Picture

A picture's schema.

Field	Type	Required	Description
name	string	No	The document's name.
file_location	string	No	The document's file location.
doc_type	string	No	The document's type.
comment	string	No	The document's comment.
sort	integer	No	The document's sort.
is_private	boolean	No	The document's is private flag.
created_at	datetime	No	The document's created date.
updated_at	datetime	No	The document's updated date.
customer_doc_id	integer	No	The id of attached customer doc to the document (Note: id - [integer] the customer doc's identifier).

typ.Document

A document's schema.

Field	Type	Required	Description
name	string	No	The document's name.
file_location	string	No	The document's file location.
doc_type	string	No	The document's type.
comment	string	No	The document's comment.
sort	integer	No	The document's sort.
is_private	boolean	No	The document's is private flag.
created_at	datetime	No	The document's created date.
updated_at	datetime	No	The document's updated date.
customer_doc_id	integer	No	The id of attached customer doc to the document (Note: id - [integer] the customer doc's identifier).

API
End-
points

Table
of
Con-
tents

- **GET**
/me -
GET
/calendar-
tasks
- **GET**
/calendar-
tasks/{calendar-
task-
id} -
POST
/cus-
tomers
- **GET**
/cus-
tomers
- **GET**
/customers/{customer-
id} -
GET
/customers/{customer-
id}/equipment
- **GET**
/customers/{customer-
id}/equipment/{equipment-
id} -
POST
/jobs
- **GET**
/jobs
- **GET**
/jobs/{job-
id} -
GET
/job-
categories
- **GET**
/job-
categories/{job-
category-
id} -
GET
/job-
statuses
- **GET**
/job-
statuses/{job-
status-
id} -
POST
/es-
ti-
mates
- **GET**
/es-
ti-
mates
- **GET**
/estimates/{estimate-
id} -
GET
/in-

/me

GET /me

Authorized user information.

Traits: tra.me-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, first_name, last_name, email
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The authenticated user's identifier.
first_name	string	No	The authenticated user's first name.
last_name	string	No	The authenticated user's last name.
email	string	No	The authenticated user's email.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

/calendar-tasks

GET /calendar-tasks

List all CalendarTasks matching query criteria, if provided, otherwise list all CalendarTasks.

Traits: tra.calendarTask-fieldable, tra.calendarTask-sortable, tra.calendarTask-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, type, description, start_time, end_time, start_date, end_date, created_at, updated_at, is_public, is_completed, repeat_id, users_id, customers_id, jobs_id, estimates_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: repeat
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, type, description, start_time, end_time, start_date, end_date, created_at, updated_at, is_public, is_completed, repeat_id

Parameter	Type	Required	Default	Description
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/calendar-tasks/{calendar-task-id}

Get a CalendarTask by identifier.

URI Parameters:

Parameter	Type	Required	Description
calendar-task-id	integer	Yes	Used to send an identifier of the CalendarTask to be used.

GET /calendar-tasks/{calendar-task-id}

Get a CalendarTask by identifier.

Traits: tra.calendarTask-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, type, description, start_time, end_time, start_date, end_date, created_at, updated_at, is_public, is_completed, repeat_id, users_id, customers_id, jobs_id, estimates_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: repeat
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The calendar task's identifier.
type	string	No	The calendar task's type.
description	string	No	The calendar task's description.
start_time	string	No	The calendar task's start time.
end_time	string	No	The calendar task's end time.
start_date	datetime	No	The calendar task's start date.
end_date	datetime	No	The calendar task's end date.
created_at	datetime	No	The calendar task's created date.
updated_at	datetime	No	The calendar task's updated date.
is_public	boolean	No	The calendar task's is public flag.
is_completed	boolean	No	The calendar task's is completed flag.
repeat_id	integer	No	The calendar task's repeat id.

Field	Type	Required	Description
users_id	array	Yes	The calendar task's users list of identifiers.
customers_id	array	Yes	The calendar task's customers list of identifiers.
jobs_id	array	Yes	The calendar task's jobs list of identifiers.
estimates_id	array	Yes	The calendar task's estimates list of identifiers.
repeat	object	No	The calendar task's repeat.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/customers

POST /customers

Create a new Customer.

Traits: tra.customer-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, customer_name, fully_qualified_name, account_number, account_balance, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_serviced_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: contacts, contacts.phones, contacts.emails, locations, custom_fields
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Request Body: - Type: object

Field	Type	Required	Description
customer_name	string	Yes	Used to send the customer's name that will be set.

Field	Type	Required	Description
parent_customer	string	No	Used to send a parent customer's id or header that will be attached to the customer (Note: id - [integer] the parent customer's identifier, header - [string] the parent customer's fields conca
account_number	string	No	Used to send the customer's account number that will be set.
private_notes	string	No	Used to send the customer's private notes that will be set.
public_notes	string	No	Used to send the customer's public notes that will be set.
credit_rating	string	No	Used to send the customer's credit rating that will be set.
labor_charge_type	string	No	Used to send the customer's labor charge type that will be set.
labor_charge_default_rate	number	No	Used to send the customer's labor charge default rate that will be set.
last_serviced_date	datetime	No	Used to send the customer's last serviced date that will be set.
is_bill_for_drive_time	boolean	No	Used to send the customer's is bill for drive time flag that will be set.
is_vip	boolean	No	Used to send the customer's is vip flag that will be set.
referral_source	string	No	Used to send a referral source's id or header that will be attached to the customer (Note: id - [integer] the referral source's identifier, header - [string] the referral source's fields conca

Field	Type	Required	Description
agent	string	No	Used to send an agent's id or header that will be attached to the customer (Note: id - [integer] the agent's identifier, header - [string] the agent's fields concatenated by pattern {first_na discount number No Used to send the customer's discount that will be set. discount_type string No Used to send the customer's discount type that will be set. payment_type string No Used to send a payment type's id or header that will be attached to the customer (Note: id - [integer] the payment type's identifier, header - [string] the payment type's fields concatenated by payment_terms string No Used to send the customer's payment terms that will be set. assigned_contract string No Used to send an assigned contract's id or header that will be attached to the customer (Note: id - [integer] the assigned contract's identifier, header - [string] the assigned contract's field industry string No Used to send an industry's id or header that will be attached to the customer (Note: id - [integer] the industry's identifier, header - [string] the industry's fields concatenated by pattern
is_taxable	boolean	No	Used to send the customer's is taxable flag that will be set.

Field	Type	Required	Description
tax_item_name	string	No	Used to send a tax item's id or header that will be attached to the customer (Note: id - [integer] the tax item's identifier, header - [string] the tax item's fields concatenated by pattern { qbo_sync_token integer No Used to send the customer's qbo sync token that will be set. qbo_currency string No Used to send the customer's qbo currency that will be set. contacts array No Used to send the customer's contacts list that will be set. locations array No Used to send the customer's locations list that will be set. custom_fields'

Responses:

201

201 Created (Success)

The request has been fulfilled, resulting in the creation of a new resource.

- Type: object

Field	Type	Required	Description
id	integer	No	The customer's identifier.
customer_name	string	No	The customer's name.
fully_qualified_name	string	No	The customer's fully qualified name.
parent_customer	string	No	The header of attached parent customer to the customer (Note: header - [string] the parent customer's fields concatenated by pattern {first_name} {last_name} with space as separator).
account_number	string	No	The customer's account number.
account_balance	number	No	The customer's account balance.
private_notes	string	No	The customer's private notes.
public_notes	string	No	The customer's public notes.
credit_rating	string	No	The customer's credit rating.
labor_charge_type	string	No	The customer's labor charge type.
labor_charge_default_rate	number	No	The customer's labor charge default rate.
last_serviced_date	datetime	No	The customer's last serviced date.
is_bill_for_drive_time	boolean	No	The customer's is bill for drive time flag.
is_vip	boolean	No	The customer's is vip flag.

Field	Type	Required	Description
referral_source	string	No	The header of attached referral source to the customer (Note: header - [string] the referral source's fields concatenated by pattern {short_name}).
agent	string	No	The header of attached agent to the customer (Note: header - [string] the agent's fields concatenated by pattern {first_name} {last_name} with space as separator).
discount	number	No	The customer's discount.
discount_type	string	No	The customer's discount type.
payment_type	string	No	The header of attached payment type to the customer (Note: header - [string] the payment type's fields concatenated by pattern {name}).
payment_terms	string	No	The customer's payment terms.
assigned_contract	string	No	The header of attached contract to the customer (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
industry	string	No	The header of attached industry to the customer (Note: header - [string] the industry's fields concatenated by pattern {industry}).
is_taxable	boolean	No	The customer's is taxable flag.
tax_item_name	string	No	The header of attached tax item to the customer (Note: header - [string] the tax item's fields concatenated by pattern {short_name} with space as separator).
qbo_sync_token	integer	No	The customer's qbo sync token.
qbo_currency	string	No	The customer's qbo currency.
qbo_id	integer	No	The customer's qbo id.
qbd_id	string	No	The customer's qbd id.
created_at	datetime	No	The customer's created date.
updated_at	datetime	No	The customer's updated date.
contacts	array	No	The customer's contacts list.
locations	array	No	The customer's locations list.
custom_fields	array	No	The customer's custom fields list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

422

422 Unprocessable Entity (Client Error)

The request was well-formed but was unable to be followed due to semantic errors.

- Type: array

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

GET /customers

List all Customers matching query criteria, if provided, otherwise list all Customers.

Traits: tra.customer-fieldable, tra.customer-sortable, tra.customer-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, customer_name, fully_qualified_name, account_number, account_balance, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_served_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: contacts, contacts.phones, contacts.emails, locations, custom_fields
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, customer_name, fully_qualified_name, account_number, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_served_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry
filters[name]	string	No	-	Used to filter results by given name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[postal_code]	integer	No	-	Used to filter results by given postal code (full match).

Parameter	Type	Required	Default	Description
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).
filters[tags]	string	No	-	Used to filter results by given tags (full match). Accepted value is comma-separated string.
filters[last_serviced_date][lte]	string	No	-	Used to filter results by given less than or equal of last serviced date (format: Y-m-d).
filters[last_serviced_date][gte]	string	No	-	Used to filter results by given greater than or equal of last serviced date (format: Y-m-d).
filters[agreement_date][lte]	string	No	-	Used to filter results by given less than or equal of agreement date effective (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][gte]	string	No	-	Used to filter results by given greater than or equal of agreement date effective (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][lte]	string	No	-	Used to filter results by given less than or equal of agreement date expires (format RFC 3339: Y-m-d\TH:i:sP).
filters[agreement_date][gte]	string	No	-	Used to filter results by given greater than or equal of agreement date expires (format RFC 3339: Y-m-d\TH:i:sP).
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope. The extra-field's list that are not expanded and can be expanded into objects.
_expandable	array	Yes	
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error.
name	string	No	

Field	Type	Required	Description
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/customers/{customer-id}

Get a Customer by identifier.

URI Parameters:

Parameter	Type	Required	Description
customer-id	integer	Yes	Used to send an identifier of the Customer to be used.

GET /customers/{customer-id}

Get a Customer by identifier.

Traits: tra.customer-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, customer_name, fully_qualified_name, account_number, account_balance, private_notes, public_notes, payment_terms, discount, discount_type, credit_rating, labor_charge_type, labor_charge_default_rate, qbo_sync_token, qbo_currency, qbo_id, qbd_id, created_at, updated_at, last_serviced_date, is_bill_for_drive_time, is_vip, is_taxable, parent_customer, referral_source, agent, assigned_contract, payment_type, tax_item_name, industry
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: contacts, contacts.phones, contacts.emails, locations, custom_fields
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The customer's identifier.
customer_name	string	No	The customer's name.
fully_qualified_name	string	No	The customer's fully qualified name.
parent_customer	string	No	The header of attached parent customer to the customer (Note: header - [string] the parent customer's fields concatenated by pattern {first_name} {last_name} with space as separator).
account_number	string	No	The customer's account number.
account_balance	number	No	The customer's account balance.
private_notes	string	No	The customer's private notes.
public_notes	string	No	The customer's public notes.
credit_rating	string	No	The customer's credit rating.
labor_charge_type	string	No	The customer's labor charge type.
labor_charge_default_rate	number	No	The customer's labor charge default rate.
last_serviced_date	datetime	No	The customer's last serviced date.
is_bill_for_drive_time	boolean	No	The customer's is bill for drive time flag.
is_vip	boolean	No	The customer's is vip flag.
referral_source	string	No	The header of attached referral source to the customer (Note: header - [string] the referral source's fields concatenated by pattern {short_name}).
agent	string	No	The header of attached agent to the customer (Note: header - [string] the agent's fields concatenated by pattern {first_name} {last_name} with space as separator).
discount	number	No	The customer's discount.
discount_type	string	No	The customer's discount type.
payment_type	string	No	The header of attached payment type to the customer (Note: header - [string] the payment type's fields concatenated by pattern {name}).
payment_terms	string	No	The customer's payment terms.
assigned_contract	string	No	The header of attached contract to the customer (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
industry	string	No	The header of attached industry to the customer (Note: header - [string] the industry's fields concatenated by pattern {industry}).
is_taxable	boolean	No	The customer's is taxable flag.

Field	Type	Required	Description
tax_item_name	string	No	The header of attached tax item to the customer (Note: header - [string] the tax item's fields concatenated by pattern {short_name} with space as separator).
qbo_sync_token	integer	No	The customer's qbo sync token.
qbo_currency	string	No	The customer's qbo currency.
qbo_id	integer	No	The customer's qbo id.
qbd_id	string	No	The customer's qbd id.
created_at	datetime	No	The customer's created date.
updated_at	datetime	No	The customer's updated date.
contacts	array	No	The customer's contacts list.
locations	array	No	The customer's locations list.
custom_fields	array	No	The customer's custom fields list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/customers/{customer-id}/equipment

GET /customers/{customer-id}/equipment

List all Equipment matching query criteria, if provided, otherwise list all Equipment.

Traits: tra.equipment-fieldable, tra.equipment-sortable, tra.equipment-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.

Parameter	Type	Required	Default	Description
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, type, make, model, sku, serial_number, location, notes, extended_warranty_provider, is_extended_warranty, extended_warranty_date, warranty_date, install_date, created_at, updated_at, customer_id, customer, customer_location
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: custom_fields
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, type, make, model, sku, serial_number, location, notes, extended_warranty_provider, is_extended_warranty, extended_warranty_date, warranty_date, install_date, created_at, updated_at, customer_id, customer, customer_location
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope. The extra-field's list that are not expanded and can be expanded into objects.
_expandable	array	Yes	
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/customers/{customer-id}/equipment/{equipment-id}

Get a Equipment by identifier.

URI Parameters:

Parameter	Type	Required	Description
equipment-id	integer	Yes	Used to send an identifier of the Equipment to be used.

GET /customers/{customer-id}/equipment/{equipment-id}

Get a Equipment by identifier.

Traits: tra.equipment-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, type, make, model, sku, serial_number, location, notes, extended_warranty_provider, is_extended_warranty, extended_warranty_date, warranty_date, install_date, created_at, updated_at, customer_id, customer, customer_location
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: custom_fields
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The equipment's identifier.
type	string	No	The equipment's type.
make	string	No	The equipment's make.
model	string	No	The equipment's model.
sku	string	No	The equipment's sku.
serial_number	string	No	The equipment's serial number.
location	string	No	The equipment's location.
notes	string	No	The equipment's notes.
extended_warranty_provider	string	No	The equipment's extended warranty provider.
is_extended_warranty	boolean	No	The equipment's is extended warranty flag.

Field	Type	Required	Description
extended_warranty_date	datetime	No	The equipment's extended warranty date.
warranty_date	datetime	No	The equipment's warranty date.
install_date	datetime	No	The equipment's install date.
created_at	datetime	No	The equipment's created date.
updated_at	datetime	No	The equipment's updated date.
customer_id	integer	No	The id of attached customer to the equipment (Note: id - [integer] the customer's identifier).
customer	string	No	The header of attached customer to the equipment (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_location	string	No	The header of attached customer location to the equipment (Note: header - [string] the customer location's fields concatenated by pattern {nickname} {street_1} {city} with space as separator).
custom_fields	array	No	The equipment's custom fields list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/jobs

POST /jobs

Create a new Job.

Traits: tra.job-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, check_number, priority, description, tech_notes, completion_notes, payment_status, taxes_fees_total, drive_labor_total, billable_expenses_total, total, payments_deposits_total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, called_in_by, is_requires_follow_up

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, labor_charges, expenses, payments, invoices, signatures, printable_work_order, visits, visits.techs_assigned
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Request Body: - Type: object

Field	Type	Required	Description
check_number	string	No	Used to send the job's check number that will be set.
priority	string	No	Used to send the job's priority that will be set.
description	string	No	Used to send the job's description that will be set.
tech_notes	string	No	Used to send the job's tech notes that will be set.
completion_notes	string	No	Used to send the job's completion notes that will be set.
duration	integer	No	Used to send the job's duration (in seconds) that will be set.
time_frame_promised_start	string	No	Used to send the job's time frame promised start that will be set.
time_frame_promised_end	string	No	Used to send the job's time frame promised end that will be set.
start_date	datetime	No	Used to send the job's start date that will be set.
end_date	datetime	No	Used to send the job's end date that will be set.

Field	Type	Required	Description
customer_name	string	Yes	Used to send a customer's id or header that will be attached to the job (Note: id - [integer] the customer's identifier, header - [string] the customer's fields concatenated by pattern {custo status string No Used to send a status'esidorheaderthat will be attached to the job (Note:id- [integer] the status'es identifier,header-[string] the status'es fields concatenated by pattern{name}). contact_first_name string No Used to send the job's contact first name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached. contact_last_name string No Used to send the job's contact last name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached. street_1 string No Used to send the job's location street 1 that will be set. street_2 string No Used to send the job's location street 2 that will be set. city string No Used to send the job's location city that will be set. state_prov string No Used to send the job's location state prov that will be set. postal_code string No Used to send the job's location postal code that will be set. location_name string No Used to send the job's location name that will be set. is_gated boolean No Used to send the job's location is gated flag that will be set. gate_instructions string No Used to send the job's location gate instructions that will be set. category string No Used to send a category'sidorheaderthat will be attached to the job (Note:id- [integer] the category's identifier,header-

Field	Type	Required	Description
source	string	No	Used to send a source's id or header that will be attached to the job (Note: id - [integer] the source's identifier, header - [string] the source's fields concatenated by pattern {short_name} payment_type string No Used to send a payment type's id or header that will be attached to the job (Note: id - [integer] the payment type's identifier, header - [string] the payment type's fields concatenated by pat customer_payment_terms string No Used to send a customer payment term's id or header that will be attached to the job (Note: id - [integer] the customer payment term's identifier, header - [string] the customer payment term's project string No Used to send a project's id or header that will be attached to the job (Note: id - [integer] the project's identifier, header - [string] the project's fields concatenated by pattern {name})). phase string No Used to send a phase's id or header that will be attached to the job (Note: id - [integer] the phase's identifier, header - [string] the phase's fields concatenated by pattern {name})). po_number string No Used to send the job's po number that will be set. contract string No Used to send a contract's id or header that will be attached to the job (Note: id - [integer] the contract's identifier, header - [string] the contract's fields concatenated by pattern {contr
note_to_customer	string	No	Used to send the job's note to customer that will be set.
called_in_by	string	No	Used to send the job's called in by that will be set.
is_requires_followup	boolean	No	Used to send the job's is requires follow up flag that will be set.
agents	array	No	Used to send the job's agents list that will be set.

Field	Type	Required	Description
custom_fields	array	No	Used to send the job's custom fields list that will be set.
equipment	array	No	Used to send the job's equipments list that will be set.
techs_assigned	array	No	Used to send the job's techs assigned list that will be set.
tasks	array	No	Used to send the job's tasks list that will be set.
notes	array	No	Used to send the job's notes list that will be set.
products	array	No	Used to send the job's products list that will be set.
services	array	No	Used to send the job's services list that will be set.
other_charges	array	No	Used to send the job's other charges list that will be set.
labor_charges	array	No	Used to send the job's labor charges list that will be set.
expenses	array	No	Used to send the job's expenses list that will be set.

Responses:

201

201 Created (Success)

The request has been fulfilled, resulting in the creation of a new resource.

- Type: object

Field	Type	Required	Description
id	integer	No	The job's identifier.
number	string	No	The job's number.
check_number	string	No	The job's check number.
priority	string	No	The job's priority.
description	string	No	The job's description.
tech_notes	string	No	The job's tech notes.
completion_notes	string	No	The job's completion notes.
payment_status	string	No	The job's payment status.
taxes_fees_total	number	No	The job's taxes and fees total.
drive_labor_total	number	No	The job's drive and labor total.
billable_expenses_total	number	No	The job's billable expenses total.
total	number	No	The job's total.
payments_deposits_total	number	No	The job's payments and deposits total.
due_total	number	No	The job's due total.
cost_total	number	No	The job's cost total.
duration	integer	No	The job's duration (in seconds).
time_frame_promised_start	string	No	The job's time frame promised start.
time_frame_promised_end	string	No	The job's time frame promised end.
start_date	datetime	No	The job's start date.
end_date	datetime	No	The job's end date.
created_at	datetime	No	The job's created date.
updated_at	datetime	No	The job's updated date.

Field	Type	Required	Description
closed_at	datetime	No	The job's closed date.
customer_id	integer	No	The id of attached customer to the job (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the job (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the job (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the job (Note: header - [string] the status'es fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the job (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The job's contact first name.
contact_last_name	string	No	The job's contact last name.
street_1	string	No	The job's location street 1.
street_2	string	No	The job's location street 2.
city	string	No	The job's location city.
state_prov	string	No	The job's location state prov.
postal_code	string	No	The job's location postal code.
location_name	string	No	The job's location name.
is_gated	boolean	No	The job's location is gated flag.
gate_instructions	string	No	The job's location gate instructions.
category	string	No	The header of attached category to the job (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the job (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the job (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
customer_payment_term	string	No	The header of attached customer payment term to the job (Note: header - [string] the customer payment term's fields concatenated by pattern {name}).
project	string	No	The header of attached project to the job (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the job (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The job's po number.

Field	Type	Required	Description
contract	string	No	The header of attached contract to the job (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The job's note to customer.
called_in_by	string	No	The job's called in by.
is_requires_followup	boolean	No	The job's is requires follow up flag.
agents	array	No	The job's agents list.
custom_fields	array	No	The job's custom fields list.
pictures	array	No	The job's pictures list.
documents	array	No	The job's documents list.
equipment	array	No	The job's equipments list.
techs_assigned	array	No	The job's techs assigned list.
tasks	array	No	The job's tasks list.
notes	array	No	The job's notes list.
products	array	No	The job's products list.
services	array	No	The job's services list.
other_charges	array	No	The job's other charges list.
labor_charges	array	No	The job's labor charges list.
expenses	array	No	The job's expenses list.
payments	array	No	The job's payments list.
invoices	array	No	The job's invoices list.
signatures	array	No	The job's signatures list.
printable_work_order	array	No	The job's printable work order list.
visits	array	No	The job's visits list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

422

422 Unprocessable Entity (Client Error)

The request was well-formed but was unable to be followed due to semantic errors.

- Type: array

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

GET /jobs

List all Jobs matching query criteria, if provided, otherwise list all Jobs.

Traits: tra.job-fieldable, tra.job-sortable, tra.job-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, check_number, priority, description, tech_notes, completion_notes, payment_status, taxes_fees_total, drive_labor_total, bill-able_expenses_total, total, payments_deposits_total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, called_in_by, is_requires_follow_up

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, labor_charges, expenses, payments, invoices, signatures, printable_work_order, visits, visits.techs_assigned
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, number, po_number, check_number, description, tech_notes, completion_notes, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, status, sub_status, category, source, payment_type, customer_payment_terms, contract, called_in_by
filters[status]	string	No	-	Used to filter results by given statuses (full match). Accepted value is comma-separated string.
filters[number]	string	No	-	Used to filter results by given number (partial match).
filters[po_number]	string	No	-	Used to filter results by given po number (partial match).
filters[invoice_number]	string	No	-	Used to filter results by given invoice number (partial match).

Parameter	Type	Required	Default	Description
filters[customer_name]	string	No	-	Used to filter results by given customer's name (partial match).
filters[parent_customer_name]	string	No	-	Used to filter results by given parent customer's name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[zip_code]	integer	No	-	Used to filter results by given zip code (full match).
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).
filters[category]	string	No	-	Used to filter results by given categories (full match). Accepted value is comma-separated string.
filters[source]	string	No	-	Used to filter results by given sources (full match). Accepted value is comma-separated string.
filters[start_date][lte]	string	No	-	Used to filter results by given less than or equal of start date (format: Y-m-d).
filters[start_date][gt]	string	No	-	Used to filter results by given greater than or equal of start date (format: Y-m-d).
filters[end_date][lte]	string	No	-	Used to filter results by given less than or equal of end date (format: Y-m-d).
filters[end_date][gt]	string	No	-	Used to filter results by given greater than or equal of end date (format: Y-m-d).
filters[updated_date][lte]	string	No	-	Used to filter results by given less than or equal of updated date (format RFC 3339: Y-m-d\TH:i:sP).

Parameter	Type	Required	Default	Description
filters[updated_date]>=] [int]	integer	No	-	Used to filter results by given greater than or equal of updated date (format RFC 3339: Y-m-d\TH:i:sP).
filters[closed_date]<=] [int]	integer	No	-	Used to filter results by given less than or equal of closed date (format RFC 3339: Y-m-d\TH:i:sP).
filters[closed_date]>=] [int]	integer	No	-	Used to filter results by given greater than or equal of closed date (format RFC 3339: Y-m-d\TH:i:sP).
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/jobs/{job-id}

Get a Job by identifier.

URI Parameters:

Parameter	Type	Required	Description
job-id	integer	Yes	Used to send an identifier of the Job to be used.

GET /jobs/{job-id}

Get a Job by identifier.

Traits: tra.job-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, check_number, priority, description, tech_notes, completion_notes, payment_status, taxes_fees_total, drive_labor_total, billable_expenses_total, total, payments_deposits_total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, end_date, created_at, updated_at, closed_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, called_in_by, is_requires_follow_up

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, labor_charges, expenses, payments, invoices, signatures, printable_work_order, visits, visits.techs_assigned
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The job's identifier.
number	string	No	The job's number.
check_number	string	No	The job's check number.
priority	string	No	The job's priority.
description	string	No	The job's description.
tech_notes	string	No	The job's tech notes.
completion_notes	string	No	The job's completion notes.
payment_status	string	No	The job's payment status.
taxes_fees_total	number	No	The job's taxes and fees total.
drive_labor_total	number	No	The job's drive and labor total.
billable_expenses_total	number	No	The job's billable expenses total.
total	number	No	The job's total.
payments_deposits_total	number	No	The job's payments and deposits total.
due_total	number	No	The job's due total.

Field	Type	Required	Description
cost_total	number	No	The job's cost total.
duration	integer	No	The job's duration (in seconds).
time_frame_promised_start	integer	No	The job's time frame promised start.
time_frame_promised_end	integer	No	The job's time frame promised end.
start_date	datetime	No	The job's start date.
end_date	datetime	No	The job's end date.
created_at	datetime	No	The job's created date.
updated_at	datetime	No	The job's updated date.
closed_at	datetime	No	The job's closed date.
customer_id	integer	No	The id of attached customer to the job (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the job (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the job (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the job (Note: header - [string] the status'es fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the job (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The job's contact first name.
contact_last_name	string	No	The job's contact last name.
street_1	string	No	The job's location street 1.
street_2	string	No	The job's location street 2.
city	string	No	The job's location city.
state_prov	string	No	The job's location state prov.
postal_code	string	No	The job's location postal code.
location_name	string	No	The job's location name.
is_gated	boolean	No	The job's location is gated flag.
gate_instructions	string	No	The job's location gate instructions.
category	string	No	The header of attached category to the job (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the job (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the job (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
customer_payment_term	string	No	The header of attached customer payment term to the job (Note: header - [string] the customer payment term's fields concatenated by pattern {name}).

Field	Type	Required	Description
project	string	No	The header of attached project to the job (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the job (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The job's po number.
contract	string	No	The header of attached contract to the job (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The job's note to customer.
called_in_by	string	No	The job's called in by.
is_requires_followup	boolean	No	The job's is requires follow up flag.
agents	array	No	The job's agents list.
custom_fields	array	No	The job's custom fields list.
pictures	array	No	The job's pictures list.
documents	array	No	The job's documents list.
equipment	array	No	The job's equipments list.
techs_assigned	array	No	The job's techs assigned list.
tasks	array	No	The job's tasks list.
notes	array	No	The job's notes list.
products	array	No	The job's products list.
services	array	No	The job's services list.
other_charges	array	No	The job's other charges list.
labor_charges	array	No	The job's labor charges list.
expenses	array	No	The job's expenses list.
payments	array	No	The job's payments list.
invoices	array	No	The job's invoices list.
signatures	array	No	The job's signatures list.
printable_work_order	array	No	The job's printable work order list.
visits	array	No	The job's visits list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/job-categories

GET /job-categories

List all JobCategories matching query criteria, if provided, otherwise list all JobCategories.

Traits: tra.jobCategory-fieldable, tra.jobCategory-sortable, tra.jobCategory-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: id, name
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, name
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope. The extra-field's list that are not expanded and can be expanded into objects.
_expandable	array	Yes	
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/job-categories/{job-category-id}

Get a JobCategory by identifier.

URI Parameters:

Parameter	Type	Required	Description
job-category-id	integer	Yes	Used to send an identifier of the JobCategory to be used.

GET /job-categories/{job-category-id}

Get a JobCategory by identifier.

Traits: tra.jobCategory-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml

Parameter	Type	Required	Default	Description
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The job category's identifier.
name	string	No	The job category's name.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/job-statuses

GET /job-statuses

List all JobStatuses matching query criteria, if provided, otherwise list all JobStatuses.

Traits: tra.jobStatus-fieldable, tra.jobStatus-sortable, tra.jobStatus-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, code, name, is_custom, category
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: id, code, name, is_custom, category
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, code, name, is_custom, category
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/job-statuses/{job-status-id}

Get a JobStatus by identifier.

URI Parameters:

Parameter	Type	Required	Description
job-status-id	integer	Yes	Used to send an identifier of the JobStatus to be used.

GET /job-statuses/{job-status-id}

Get a JobStatus by identifier.

Traits: tra.jobStatus-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, code, name, is_custom, category
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The job statute's identifier.
code	string	No	The job statute's code.
name	string	No	The job statute's name.
is_custom	string	No	The job statute's is custom flag.
category	string	No	The header of attached category to the status (Note: header - [string] the category's fields concatenated by pattern {code}).
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/estimates

POST /estimates

Create a new Estimate.

Traits: tra.estimate-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, description, tech_notes, payment_status, taxes_fees_total, total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, opportunity_rating, opportunity_owner
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, payments, signatures, printable_work_order, tags
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml

Parameter	Type	Required	Default	Description
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Request Body: - Type: object

Field	Type	Required	Description
description	string	No	Used to send the estimate's description that will be set.
tech_notes	string	No	Used to send the estimate's tech notes that will be set.
duration	integer	No	Used to send the estimate's duration (in seconds) that will be set.
time_frame_promised_start	string	No	Used to send the estimate's time frame promised start that will be set.
time_frame_promised_end	string	No	Used to send the estimate's time frame promised end that will be set.
start_date	datetime	No	Used to send the estimate's start date that will be set.
created_at	datetime	No	Used to send the estimate's created date that will be set.
customer_name	string	Yes	Used to send a customer's id or header that will be attached to the estimate (Note: id - [integer] the customer's identifier, header - [string] the customer's fields concatenated by pattern { status string No Used to send a status's id or header that will be attached to the estimate (Note: id - [integer] the status's identifier, header - [string] the status's fields concatenated by pattern {nam
contact_first_name	string	No	Used to send the estimate's contact first name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached
contact_last_name	string	No	Used to send the estimate's contact last name that will be set. If a contact with the passed name and surname already exists, then a new contact will not be created, but the existing one will be attached
street_1	string	No	Used to send the estimate's location street 1 that will be set.
street_2	string	No	Used to send the estimate's location street 2 that will be set.
city	string	No	Used to send the estimate's location city that will be set.

Field	Type	Required	Description
state_prov	string	No	Used to send the estimate's location state prov that will be set.
postal_code	string	No	Used to send the estimate's location postal code that will be set.
location_name	string	No	Used to send the estimate's location name that will be set.
is_gated	boolean	No	Used to send the estimate's location is gated flag that will be set.
gate_instructions	string	No	Used to send the estimate's location gate instructions that will be set.
category	string	No	Used to send a category's id or header that will be attached to the estimate (Note: id - [integer] the category's identifier, header - [string] the category's fields concatenated by pattern { source string No Used to send a source's id or header that will be attached to the estimate (Note: id - [integer] the source's identifier, header - [string] the source's fields concatenated by pattern {short_
project	string	No	Used to send a project's id or header that will be attached to the estimate (Note: id - [integer] the project's identifier, header - [string] the project's fields concatenated by pattern {nam phase string No Used to send a phase's id or header that will be attached to the estimate (Note: id - [integer] the phase's identifier, header - [string] the phase's fields concatenated by pattern {name}). po_number string No Used to send the estimate's po number that will be set. contract string No Used to send a contract's id or header that will be attached to the estimate (Note: id - [integer] the contract's identifier, header - [string] the contract's fields concatenated by pattern {
note_to_customer	string	No	Used to send the estimate's note to customer that will be set.
opportunity_rating	integer	No	Used to send the estimate's opportunity rating that will be set.

Field	Type	Required	Description
opportunity_owner	string	No	Used to send an opportunity owner's id or header that will be attached to the estimate (Note: id - [integer] the opportunity owner's identifier, header - [string] the opportunity owner's field)
custom_fields	array	No	Used to send the estimate's custom fields list that will be set.
equipment	array	No	Used to send the estimate's equipments list that will be set.
techs_assigned	array	No	Used to send the estimate's techs assigned list that will be set.
tasks	array	No	Used to send the estimate's tasks list that will be set.
notes	array	No	Used to send the estimate's notes list that will be set.
products	array	No	Used to send the estimate's products list that will be set.
services	array	No	Used to send the estimate's services list that will be set.
other_charges	array	No	Used to send the estimate's other charges list that will be set.
tags	array	No	Used to send the estimate's tags list that will be set.

Responses:

201

201 Created (Success)

The request has been fulfilled, resulting in the creation of a new resource.

- Type: object

Field	Type	Required	Description
id	integer	No	The estimate's identifier.
number	string	No	The estimate's number.
description	string	No	The estimate's description.
tech_notes	string	No	The estimate's tech notes.
customer_payment_terms	string	No	The estimate's customer payment terms.
payment_status	string	No	The estimate's payment status.
taxes_fees_total	number	No	The estimate's taxes and fees total.
total	number	No	The estimate's total.
due_total	number	No	The estimate's due total.
cost_total	number	No	The estimate's cost total.
duration	integer	No	The estimate's duration (in seconds).
time_frame_promised_start	string	No	The estimate's time frame promised start.
time_frame_promised_end	string	No	The estimate's time frame promised end.
start_date	datetime	No	The estimate's start date.
created_at	datetime	No	The estimate's created date.
updated_at	datetime	No	The estimate's updated date.

Field	Type	Required	Description
customer_id	integer	No	The id of attached customer to the estimate (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the estimate (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the estimate (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the estimate (Note: header - [string] the status's fields concatenated by pattern {name}).
sub_status	string	No	The header of attached sub status to the estimate (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The estimate's contact first name.
contact_last_name	string	No	The estimate's contact last name.
street_1	string	No	The estimate's location street 1.
street_2	string	No	The estimate's location street 2.
city	string	No	The estimate's location city.
state_prov	string	No	The estimate's location state prov.
postal_code	string	No	The estimate's location postal code.
location_name	string	No	The estimate's location name.
is_gated	boolean	No	The estimate's location is gated flag.
gate_instructions	string	No	The estimate's location gate instructions.
category	string	No	The header of attached category to the estimate (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the estimate (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the estimate (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
project	string	No	The header of attached project to the estimate (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the estimate (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The estimate's po number.

Field	Type	Required	Description
contract	string	No	The header of attached contract to the estimate (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The estimate's note to customer.
opportunity_rating	integer	No	The estimate's opportunity rating.
opportunity_owner	string	No	The header of attached opportunity owner to the estimate (Note: header - [string] the opportunity owner's fields concatenated by pattern {first_name} {last_name} with space as separator).
agents	array	No	The estimate's agents list.
custom_fields	array	No	The estimate's custom fields list.
pictures	array	No	The estimate's pictures list.
documents	array	No	The estimate's documents list.
equipment	array	No	The estimate's equipments list.
techs_assigned	array	No	The estimate's techs assigned list.
tasks	array	No	The estimate's tasks list.
notes	array	No	The estimate's notes list.
products	array	No	The estimate's products list.
services	array	No	The estimate's services list.
other_charges	array	No	The estimate's other charges list.
payments	array	No	The estimate's payments list.
signatures	array	No	The estimate's signatures list.
printable_work_order	array	No	The estimate's printable work order list.
tags	array	No	The estimate's tags list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

422

422 Unprocessable Entity (Client Error)

The request was well-formed but was unable to be followed due to semantic errors.

- Type: array

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

GET /estimates

List all Estimates matching query criteria, if provided, otherwise list all Estimates.

Traits: tra.estimate-fieldable, tra.estimate-sortable, tra.estimate-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, description, tech_notes, payment_status, taxes_fees_total, total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, opportunity_rating, opportunity_owner
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, payments, signatures, printable_work_order, tags

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, number, po_number, description, tech_notes, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, status, sub_status, category, source, payment_type, customer_payment_terms, contract, opportunity_rating
filters[status]	string	No	-	Used to filter results by given statuses (full match). Accepted value is comma-separated string.
filters[number]	string	No	-	Used to filter results by given number (partial match).
filters[po_number]	string	No	-	Used to filter results by given po number (partial match).
filters[customer_name]	string	No	-	Used to filter results by given customer's name (partial match).
filters[parent_customer_name]	string	No	-	Used to filter results by given parent customer's name (partial match).
filters[contact_first_name]	string	No	-	Used to filter results by given contact's first name (partial match).
filters[contact_last_name]	string	No	-	Used to filter results by given contact's last name (partial match).
filters[address]	string	No	-	Used to filter results by given address (partial match).
filters[city]	string	No	-	Used to filter results by given city (full match).
filters[zip_code]	integer	No	-	Used to filter results by given zip code (full match).
filters[phone]	string	No	-	Used to filter results by given phone (partial match).
filters[email]	string	No	-	Used to filter results by given email (full match).

Parameter	Type	Required	Default	Description
filters[category]	string	No	-	Used to filter results by given categories (full match). Accepted value is comma-separated string.
filters[source]	string	No	-	Used to filter results by given sources (full match). Accepted value is comma-separated string.
filters[start_date][lte]	string	No	-	Used to filter results by given less than or equal of start date (format: Y-m-d).
filters[start_date][gte]	string	No	-	Used to filter results by given greater than or equal of start date (format: Y-m-d).
filters[end_date][lte]	string	No	-	Used to filter results by given less than or equal of end date (format: Y-m-d).
filters[end_date][gte]	string	No	-	Used to filter results by given greater than or equal of end date (format: Y-m-d).
filters[requested_date][lte]	string	No	-	Used to filter results by given less than or equal of requested date (format RFC 3339: Y-m-d\TH:i:sP).
filters[requested_date][gte]	string	No	-	Used to filter results by given greater than or equal of requested date (format RFC 3339: Y-m-d\TH:i:sP).
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope. The extra-field's list that are not expanded and can be expanded into objects.
_expandable	array	Yes	
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error.
name	string	No	

Field	Type	Required	Description
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/estimates/{estimate-id}

Get a Estimate by identifier.

URI Parameters:

Parameter	Type	Required	Description
estimate-id	integer	Yes	Used to send an identifier of the Estimate to be used.

GET /estimates/{estimate-id}

Get a Estimate by identifier.

Traits: tra.estimate-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, description, tech_notes, payment_status, taxes_fees_total, total, due_total, cost_total, duration, time_frame_promised_start, time_frame_promised_end, start_date, created_at, updated_at, customer_id, customer_name, parent_customer, status, sub_status, contact_first_name, contact_last_name, street_1, street_2, city, state_prov, postal_code, location_name, is_gated, gate_instructions, category, source, payment_type, customer_payment_terms, project, phase, po_number, contract, note_to_customer, opportunity_rating, opportunity_owner
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string. Values: agents, custom_fields, pictures, documents, equipment, equipment.custom_fields, techs_assigned, tasks, notes, products, services, other_charges, payments, signatures, printable_work_order, tags
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml

Parameter	Type	Required	Default	Description
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The estimate's identifier.
number	string	No	The estimate's number.
description	string	No	The estimate's description.
tech_notes	string	No	The estimate's tech notes.
customer_payment_terms	string	No	The estimate's customer payment terms.
payment_status	string	No	The estimate's payment status.
taxes_fees_total	number	No	The estimate's taxes and fees total.
total	number	No	The estimate's total.
due_total	number	No	The estimate's due total.
cost_total	number	No	The estimate's cost total.
duration	integer	No	The estimate's duration (in seconds).
time_frame_promised_start	string	No	The estimate's time frame promised start.
time_frame_promised_end	string	No	The estimate's time frame promised end.
start_date	datetime	No	The estimate's start date.
created_at	datetime	No	The estimate's created date.
updated_at	datetime	No	The estimate's updated date.
customer_id	integer	No	The id of attached customer to the estimate (Note: id - [integer] the customer's identifier).
customer_name	string	No	The header of attached customer to the estimate (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
parent_customer	string	No	The header of attached parent customer to the estimate (Note: header - [string] the parent customer's fields concatenated by pattern {customer_name}).
status	string	No	The header of attached status to the estimate (Note: header - [string] the status's fields concatenated by pattern {name}).

Field	Type	Required	Description
sub_status	string	No	The header of attached sub status to the estimate (Note: header - [string] the sub status's fields concatenated by pattern {name}).
contact_first_name	string	No	The estimate's contact first name.
contact_last_name	string	No	The estimate's contact last name.
street_1	string	No	The estimate's location street 1.
street_2	string	No	The estimate's location street 2.
city	string	No	The estimate's location city.
state_prov	string	No	The estimate's location state prov.
postal_code	string	No	The estimate's location postal code.
location_name	string	No	The estimate's location name.
is_gated	boolean	No	The estimate's location is gated flag.
gate_instructions	string	No	The estimate's location gate instructions.
category	string	No	The header of attached category to the estimate (Note: header - [string] the category's fields concatenated by pattern {category}).
source	string	No	The header of attached source to the estimate (Note: header - [string] the source's fields concatenated by pattern {short_name}).
payment_type	string	No	The header of attached payment type to the estimate (Note: header - [string] the payment type's fields concatenated by pattern {short_name}).
project	string	No	The header of attached project to the estimate (Note: header - [string] the project's fields concatenated by pattern {name}).
phase	string	No	The header of attached phase to the estimate (Note: header - [string] the phase's fields concatenated by pattern {name}).
po_number	string	No	The estimate's po number.
contract	string	No	The header of attached contract to the estimate (Note: header - [string] the contract's fields concatenated by pattern {contract_title}).
note_to_customer	string	No	The estimate's note to customer.
opportunity_rating	integer	No	The estimate's opportunity rating.
opportunity_owner	string	No	The header of attached opportunity owner to the estimate (Note: header - [string] the opportunity owner's fields concatenated by pattern {first_name} {last_name} with space as separator).
agents	array	No	The estimate's agents list.
custom_fields	array	No	The estimate's custom fields list.
pictures	array	No	The estimate's pictures list.
documents	array	No	The estimate's documents list.

Field	Type	Required	Description
equipment	array	No	The estimate's equipments list.
techs_assigned	array	No	The estimate's techs assigned list.
tasks	array	No	The estimate's tasks list.
notes	array	No	The estimate's notes list.
products	array	No	The estimate's products list.
services	array	No	The estimate's services list.
other_charges	array	No	The estimate's other charges list.
payments	array	No	The estimate's payments list.
signatures	array	No	The estimate's signatures list.
printable_work_order	array	No	The estimate's printable work order list.
tags	array	No	The estimate's tags list.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/invoices

GET /invoices

List all Invoices matching query criteria, if provided, otherwise list all Invoices.

Traits: tra.invoice-fieldable, tra.invoice-sortable, tra.invoice-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.

Parameter	Type	Required	Default	Description
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, currency, po_number, terms, customer_message, notes, pay_online_url, qbo_invoice_no, qbo_sync_token, qbo_synced_date, qbo_id, qbd_id, total, is_paid, date, mail_send_date, created_at, updated_at, customer, customer_contact, payment_terms, bill_to_customer_id, bill_to_customer_location_id, bill_to_customer_contact_id, bill_to_email_id, bill_to_phone_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, number, currency, po_number, terms, customer_message, notes, qbo_invoice_no, qbo_sync_token, qbo_synced_date, qbo_id, qbd_id, total, is_paid, date, mail_send_date, created_at, updated_at, customer, customer_contact, payment_terms, bill_to_customer_id, bill_to_customer_location_id, bill_to_customer_contact_id, bill_to_email_id, bill_to_phone_id

Parameter	Type	Required	Default	Description
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/invoices/{invoice-id}

Get a Invoice by identifier.

URI Parameters:

Parameter	Type	Required	Description
invoice-id	integer	Yes	Used to send an identifier of the Invoice to be used.

GET /invoices/{invoice-id}

Get a Invoice by identifier.

Traits: tra.invoice-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, number, currency, po_number, terms, customer_message, notes, pay_online_url, qbo_invoice_no, qbo_sync_token, qbo_synced_date, qbo_id, qbd_id, total, is_paid, date, mail_send_date, created_at, updated_at, customer, customer_contact, payment_terms, bill_to_customer_id, bill_to_customer_location_id, bill_to_customer_contact_id, bill_to_email_id, bill_to_phone_id
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The invoice's identifier.
number	integer	No	The invoice's number.
currency	string	No	The invoice's currency.
po_number	string	No	The invoice's po number.

Field	Type	Required	Description
terms	string	No	The invoice's terms.
customer_message	string	No	The invoice's customer message.
notes	string	No	The invoice's notes.
pay_online_url	string	No	The invoice's pay online url.
qbo_invoice_no	integer	No	The invoice's qbo invoice no.
qbo_sync_token	integer	No	The invoice's qbo sync token.
qbo_synced_date	datetime	No	The invoice's qbo synced date.
qbo_id	integer	No	The invoice's qbo class id.
qbd_id	string	No	The invoice's qbd class id.
total	number	No	The invoice's total.
is_paid	boolean	No	The invoice's is paid flag.
date	datetime	No	The invoice's date.
mail_send_date	datetime	No	The invoice's mail send date.
created_at	datetime	No	The invoice's created date.
updated_at	datetime	No	The invoice's updated date.
customer	string	No	The header of attached customer to the invoice (Note: header - [string] the customer's fields concatenated by pattern {customer_name}).
customer_contact	string	No	The header of attached customer contact to the invoice (Note: header - [string] the customer contact's fields concatenated by pattern {fname} {lname} with space as separator).
payment_terms	string	No	The header of attached payment term to the invoice (Note: header - [string] the payment term's fields concatenated by pattern {name}).
bill_to_customer_id	integer	No	The id of attached bill to customer to the invoice (Note: id - [integer] the bill to customer's identifier).
bill_to_customer_location_id	integer	No	The id of attached bill to customer location to the invoice (Note: id - [integer] the bill to customer location's identifier).
bill_to_customer_contact_id	integer	No	The id of attached bill to customer contact to the invoice (Note: id - [integer] the bill to customer contact's identifier).
bill_to_email_id	integer	No	The id of attached bill to email to the invoice (Note: id - [integer] the bill to email's identifier).
bill_to_phone_id	integer	No	The id of attached bill to phone to the invoice (Note: id - [integer] the bill to phone's identifier).
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/payment-types

GET /payment-types

List all PaymentTypes matching query criteria, if provided, otherwise list all PaymentTypes.

Traits: tra.paymentType-fieldable, tra.paymentType-sortable, tra.paymentType-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, code, short_name, type, is_custom
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, code, short_name, type, is_custom
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/payment-types/{payment-type-id}

Get a PaymentType by identifier.

URI Parameters:

Parameter	Type	Required	Description
payment-type-id	integer	Yes	Used to send an identifier of the PaymentType to be used.

GET /payment-types/{payment-type-id}

Get a PaymentType by identifier.

Traits: tra.paymentType-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, code, short_name, type, is_custom
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The type's identifier.
code	string	No	The type's code.
short_name	string	No	The type's short name.
type	string	No	The type's type.
is_custom	boolean	No	The type's is custom flag.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.

Field	Type	Required	Description
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/sources

GET /sources

List all Sources matching query criteria, if provided, otherwise list all Sources.

Traits: tra.source-fieldable, tra.source-sortable, tra.source-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, short_name, long_name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, short_name, long_name

Parameter	Type	Required	Default	Description
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/sources/{source-id}

Get a Source by identifier.

URI Parameters:

Parameter	Type	Required	Description
source-id	integer	Yes	Used to send an identifier of the Source to be used.

GET /sources/{source-id}

Get a Source by identifier.

Traits: tra.source-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, short_name, long_name
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The source's identifier.
short_name	string	No	The source's short name.
long_name	string	No	The source's long name.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/techs

GET /techs

List all Techs matching query criteria, if provided, otherwise list all Techs.

Traits: tra.tech-fieldable, tra.tech-sortable, tra.tech-filtrable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
page	integer	No	1	Used to send a page number to be displayed.
per-page	integer	No	10	Used to send a number of items displayed per page (min 1, max 50).
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, first_name, last_name, nickname_on_workorder, nickname_on_dispatch, color_code, email, phone_1, phone_2, gender, department, title, bio, is_phone_1_mobile, is_phone_1_visible_to_client, is_phone_2_mobile, is_phone_2_visible_to_client, is_sales_rep, is_field_worker, created_at, updated_at
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.

Parameter	Type	Required	Default	Description
sort	string	No	id	Used to sort the results by given fields. Use minus - before field name to sort DESC. Accepted value is comma-separated string. Values: id, first_name, last_name, nickname_on_workorder, nickname_on_dispatch, color_code, email, phone_1, phone_2, gender, department, title, bio, is_phone_1_mobile, is_phone_1_visible_to_client, is_phone_2_mobile, is_phone_2_visible_to_client, is_sales_rep, is_field_worker, created_at, updated_at
filters[first_name]	string	No	-	Used to filter results by given first name (partial match).
filters[last_name]	string	No	-	Used to filter results by given last name (partial match).
filters[email]	string	No	-	Used to filter results by given email (partial match).
filters[nickname_on_workorder]	string	No	-	Used to filter results by given nickname on workorder (partial match).
filters[nickname_on_dispatch]	string	No	-	Used to filter results by given nickname on dispatch (partial match).
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
items	array	Yes	Collection envelope. The extra-field's list that are not expanded and can be expanded into objects.
_expandable	array	Yes	
_meta	object	Yes	Meta information.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error. The error message associated with the error.
name	string	No	
message	string	No	

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error. The error name associated with the error.
name	string	No	

Field	Type	Required	Description
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

/techs/{tech-id}

Get a Tech by identifier.

URI Parameters:

Parameter	Type	Required	Description
tech-id	integer	Yes	Used to send an identifier of the Tech to be used.

GET /techs/{tech-id}

Get a Tech by identifier.

Traits: tra.tech-fieldable, tra.formatable

Query Parameters:

Parameter	Type	Required	Default	Description
fields	string	No	If not passed, will be displayed all available.	Used to send a list of fields to be displayed. Accepted value is comma-separated string. Values: id, first_name, last_name, nickname_on_workorder, nickname_on_dispatch, color_code, email, phone_1, phone_2, gender, department, title, bio, is_phone_1_mobile, is_phone_1_visible_to_client, is_phone_2_mobile, is_phone_2_visible_to_client, is_sales_rep, is_field_worker, created_at, updated_at

Parameter	Type	Required	Default	Description
expand	string	No	If not passed, will be displayed nothing.	Used to send a list of extra-fields to be displayed. Accepted value is comma-separated string.
format	string	No	json	Used to send a format of data of the response. Do not use together with the Accept header. Values: json, xml
access_token	string	No	-	Used to send a valid OAuth 2 access token. Do not use together with the Authorization header.

Responses:

200

200 OK (Success)

Standard response for successful HTTP requests.

- Type: object

Field	Type	Required	Description
id	integer	No	The tech's identifier.
first_name	string	No	The tech's first name.
last_name	string	No	The tech's last name.
nickname_on_workorder	string	No	The tech's nickname on workorder.
nickname_on_dispatch	string	No	The tech's nickname on dispatch.
color_code	string	No	The tech's color code.
email	string	No	The tech's email.
phone_1	string	No	The tech's phone 1.
phone_2	string	No	The tech's phone 2.
gender	string	No	The tech's gender.
department	string	No	The tech's department.
title	string	No	The tech's title.
bio	string	No	The tech's bio.
is_phone_1_mobile	boolean	No	The tech's is phone 1 mobile flag.
is_phone_1_visible_to_client	boolean	No	The tech's is phone 1 visible to client flag.
is_phone_2_mobile	boolean	No	The tech's is phone 2 mobile flag.
is_phone_2_visible_to_client	boolean	No	The tech's is phone 2 visible to client flag.
is_sales_rep	boolean	No	The tech's is sales rep flag.
is_field_worker	boolean	No	The tech's is field worker flag.
created_at	datetime	No	The tech's created date.
updated_at	datetime	No	The tech's updated date.
_expandable	array	Yes	The extra-field's list that are not expanded and can be expanded into objects.

400

400 Bad Request (Client Error)

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

401

401 Unauthorized (Client Error)

Authentication is required and has failed or has not yet been provided.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

403

403 Forbidden (Client Error)

Access to the requested resource is forbidden. The server understood the request, but will not fulfill it.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

404

404 Not Found (Client Error)

The requested resource could not be found but may be available in the future.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

405

405 Method Not Allowed (Client Error)

A request method is not supported for the requested resource. For example, a GET request on a form that requires data to be presented via POST.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

415

415 Unsupported Media Type (Client Error)

The request entity has a media type which the server or resource does not support. For example, the client set request data as application/xml, but the server requires that request data use a different format.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

429

429 Too Many Requests (Client Error)

The user has sent too many requests in a given amount of time.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.

Field	Type	Required	Description
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

500

500 Internal Server Error (Server Error)

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.

- Type: object

Field	Type	Required	Description
code	integer	No	The error code associated with the error.
name	string	No	The error name associated with the error.
message	string	No	The error message associated with the error.

Known Issues

Sort parameter required on /jobs (as of 2026-04-09)

The /jobs endpoint hangs indefinitely when queried without a sort parameter. Always include sort=-start_date (or another valid sort field) in all /jobs GET requests.

Equipment is a nested resource (not top-level)

There is no GET /equipment endpoint. Equipment must be fetched via GET /customers/{customer-id}/equipment.