

# **Reduce redundant configuration using Macros**

## Redundant Configuration example in Virtual host – multiple web site hosting

Macros

Redundant configs

Welcome

```
<VirtualHost *:80>
  ServerName server1.com
  DocumentRoot "/var/www/html/server1_websites"
  ErrorLog /var/log/server1_websites-error_log
  CustomLog /var/log/server1_websites-access_log common

  <Directory "/var/www/html/server1_websites">
    Require all granted
  </Directory>

</VirtualHost>
```

```
<VirtualHost *:80>
  ServerName server2.com
  DocumentRoot "/var/www/html/server2_websites"
  ErrorLog /var/log/server2_websites-error_log
  CustomLog /var/log/server2_websites-access_log common

  <Directory "/var/www/html/server2_websites">
    Require all granted
  </Directory>

</ VirtualHost>
```

```
<VirtualHost *:80>
  ServerName server3.com
  DocumentRoot "/var/www/html/server3_websites"
  ErrorLog /var/log/server3_websites-error_log
  CustomLog /var/log/server3_websites-access_log common

  <Directory "/var/www/html/server3_websites">
    Require all granted
  </Directory>

</VirtualHost >
```

```
<VirtualHost *:80>
  ServerName server4.com
  DocumentRoot "/var/www/html/server4_websites"
  ErrorLog /var/log/server4_websites-error_log
  CustomLog /var/log/server4_websites-access_log common

  <Directory "/var/www/html/server4_websites">
    Require all granted
  </Directory>

</VirtualHost>
```

## Macro module

Add this modules line httpd.conf

➔ LoadModule macro\_module modules/mod\_macro.so

```
<Macro CommonVHost $servername $adminid $DCRoot $errlog $CSlog >
<VirtualHost *:80>
  ServerName $servername
  ServerAdmin $adminid
  DocumentRoot "/var/www/html/$DCRoot"
  ErrorLog /var/log/httpd/$errlog
  CustomLog /var/log/httpd/$CSlog common
  <Directory "/var/www/html/$DCRoot">
    Require all granted
  </Directory>
</VirtualHost>
</Macro>
```


```
use CommonVHost server1.com admin@server1.com server1_websites server1_websites-error_log server1_websites-access_log
use CommonVHost server2.com admin@server2.com server2_websites server2_websites-error_log server2_websites-access_log
use CommonVHost server3.com admin@server3.com server3_websites server3_websites-error_log server3_websites-access_log
use CommonVHost server4.com admin@server4.com server4_websites server4_websites-error_log server4_websites-access_log
```

Macros

Redundant configs

Welcome

Let's Try out Macro in the **Lab..**



*Macros*

*Redundant configs*

*Welcome*