

## List of *php.ini* directives ¶

This list includes the *php.ini* directives you can set to configure your PHP setup.

The "Changeable" column shows the modes determining when and where a directive may be set. See the [Changeable mode values](#) section for their definitions.

Name	Default	Configuration options		Changelog
			Changeable	
<a href="#">allow_url_fopen</a>	"1"		PHP_INI_SYSTEM	
<a href="#">allow_url_include</a>	"0"		PHP_INI_SYSTEM	Deprecated as of PHP 7.4.0.
<a href="#">arg_separator.input</a>	"&"		PHP_INI_PERDIR	
<a href="#">arg_separator.output</a>	"&"		PHP_INI_ALL	
<a href="#">assert.active</a>	"1"		PHP_INI_ALL	
<a href="#">assert.bail</a>	"0"		PHP_INI_ALL	
<a href="#">assert.callback</a>	NULL		PHP_INI_ALL	
<a href="#">assert.exception</a>	"0"		PHP_INI_ALL	
<a href="#">assert.quiet_eval</a>	"0"		PHP_INI_ALL	
<a href="#">assert.warning</a>	"1"		PHP_INI_ALL	
<a href="#">auto_append_file</a>	NULL		PHP_INI_PERDIR	
<a href="#">auto_detect_line_endings</a>	"0"		PHP_INI_ALL	
<a href="#">auto_globals_jit</a>	"1"		PHP_INI_PERDIR	
<a href="#">auto_prepend_file</a>	NULL		PHP_INI_PERDIR	
<a href="#">bcmath.scale</a>	"0"		PHP_INI_ALL	
<a href="#">browscap</a>	NULL		PHP_INI_SYSTEM	
<a href="#">cgi.check_shebang_line</a>	"1"		PHP_INI_SYSTEM	
<a href="#">cgi.discard_path</a>	"0"		PHP_INI_SYSTEM	
<a href="#">cgi.fix_pathinfo</a>	"1"		PHP_INI_SYSTEM	
<a href="#">cgi.force_redirect</a>	"1"		PHP_INI_SYSTEM	
<a href="#">cgi.nph</a>	"0"		PHP_INI_ALL	
<a href="#">cgi.redirect_status_env</a>	NULL		PHP_INI_SYSTEM	
<a href="#">cgi.rfc2616_headers</a>	"0"		PHP_INI_ALL	
<a href="#">child_terminate</a>	"0"		PHP_INI_ALL	
<a href="#">cli.pager</a>	""		PHP_INI_ALL	
<a href="#">cli.prompt</a>	"\b \> "		PHP_INI_ALL	
<a href="#">cli_server.color</a>	"0"		PHP_INI_ALL	
<a href="#">com.allow_dcom</a>	"0"		PHP_INI_SYSTEM	
<a href="#">com.autoregister_typelib</a>	"0"		PHP_INI_ALL	
<a href="#">com.autoregister_verbose</a>	"0"		PHP_INI_ALL	
<a href="#">com.autoregister_casesensitive</a>	"1"		PHP_INI_ALL	
<a href="#">com.code_page</a>	""		PHP_INI_ALL	
<a href="#">com.dotnet_version</a>	""		PHP_INI_SYSTEM	As of PHP 8.0.0
<a href="#">com.typelib_file</a>	""		PHP_INI_SYSTEM	
<a href="#">curl.cainfo</a>	NULL		PHP_INI_SYSTEM	
<a href="#">date.default_latitude</a>	"31.7667"		PHP_INI_ALL	
<a href="#">date.default_longitude</a>	"35.2333"		PHP_INI_ALL	
<a href="#">date.sunrise_zenith</a>	"90.583333"		PHP_INI_ALL	
<a href="#">date.sunset_zenith</a>	"90.583333"		PHP_INI_ALL	
<a href="#">date.timezone</a>	""		PHP_INI_ALL	
<a href="#">dba.default_handler</a>	DBA_DEFAULT		PHP_INI_ALL	
<a href="#">default_charset</a>	"UTF-8"		PHP_INI_ALL	Default to "UTF-8".
<a href="#">default_mimetype</a>	"text/html"		PHP_INI_ALL	
<a href="#">default_socket_timeout</a>	"60"		PHP_INI_ALL	
<a href="#">disable_classes</a>	""		<i>php.ini</i> only	
<a href="#">disable_functions</a>	""		<i>php.ini</i> only	
<a href="#">display_errors</a>	"1"		PHP_INI_ALL	
<a href="#">display_startup_errors</a>	"0"		PHP_INI_ALL	
<a href="#">docref_ext</a>	""		PHP_INI_ALL	
<a href="#">docref_root</a>	""		PHP_INI_ALL	
<a href="#">doc_root</a>	NULL		PHP_INI_SYSTEM	
<a href="#">enable_dl</a>	"1"		PHP_INI_SYSTEM	This deprecated feature <i>will</i> certainly be <i>removed</i> in the future.
<a href="#">enable_post_data_reading</a>	On		PHP_INI_PERDIR	
<a href="#">engine</a>	"1"		PHP_INI_ALL	
<a href="#">error_append_string</a>	NULL		PHP_INI_ALL	
<a href="#">error_log</a>	NULL		PHP_INI_ALL	
<a href="#">error_prepend_string</a>	NULL		PHP_INI_ALL	
<a href="#">error_reporting</a>	NULL		PHP_INI_ALL	
<a href="#">exif.encode_unicode</a>	"ISO-8859-15"		PHP_INI_ALL	
<a href="#">exif.decode_unicode_motorola</a>	"UCS-2BE"		PHP_INI_ALL	

Name	Default	Changeable	Changelog
<a href="#">exif.decode_unicode_intel</a>	"UCS-2LE"	PHP_INI_ALL	
<a href="#">exif.encode_jis</a>	""	PHP_INI_ALL	
<a href="#">exif.decode_jis_motorola</a>	"JIS"	PHP_INI_ALL	
<a href="#">exif.decode_jis_intel</a>	"JIS"	PHP_INI_ALL	
<a href="#">exit_on_timeout</a>	""	PHP_INI_ALL	
<a href="#">expect.timeout</a>	"10"	PHP_INI_ALL	
<a href="#">expect.loguser</a>	"1"	PHP_INI_ALL	
<a href="#">expect.logfile</a>	""	PHP_INI_ALL	
<a href="#">expect.match_max</a>	""	PHP_INI_ALL	
<a href="#">expose_php</a>	"1"	<i>php.ini</i> only	
<a href="#">extension</a>	NULL	<i>php.ini</i> only	
<a href="#">extension_dir</a>	"/path/to/php"	PHP_INI_SYSTEM	
<a href="#">fastcgi.impersonate</a>	"0"	PHP_INI_SYSTEM	
<a href="#">fastcgi.logging</a>	"1"	PHP_INI_SYSTEM	
<a href="#">fbsql.allow_persistent</a>	"1"	PHP_INI_SYSTEM	
<a href="#">fbsql.autocommit</a>	"1"	PHP_INI_SYSTEM	
<a href="#">fbsql.batchsize</a>	"1000"	PHP_INI_ALL	
<a href="#">fbsql.default_database</a>	""	PHP_INI_SYSTEM	
<a href="#">fbsql.default_database_password</a>	""	PHP_INI_SYSTEM	
<a href="#">fbsql.default_host</a>	NULL	PHP_INI_SYSTEM	
<a href="#">fbsql.default_password</a>	""	PHP_INI_SYSTEM	
<a href="#">fbsql.default_user</a>	"_SYSTEM"	PHP_INI_SYSTEM	
<a href="#">fbsql.generate_warnings</a>	"0"	PHP_INI_SYSTEM	
<a href="#">fbsql.max_connections</a>	"128"	PHP_INI_SYSTEM	
<a href="#">fbsql.max_links</a>	"128"	PHP_INI_SYSTEM	
<a href="#">fbsql.max_persistent</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">fbsql.max_results</a>	"128"	PHP_INI_SYSTEM	
<a href="#">fbsql.show_timestamp_decimals</a>	"0"	PHP_INI_SYSTEM	
<a href="#">file_uploads</a>	"1"	PHP_INI_SYSTEM	
<a href="#">filter.default</a>	"unsafe_raw"	PHP_INI_PERDIR	
<a href="#">filter.default_flags</a>	NULL	PHP_INI_PERDIR	
<a href="#">from</a>	""	PHP_INI_ALL	
<a href="#">gd.jpeg_ignore_warning</a>	"1"	PHP_INI_ALL	
<a href="#">geoip.custom_directory</a>	""	PHP_INI_ALL	
<a href="#">hard_timeout</a>	"2"	PHP_INI_SYSTEM Available since PHP 7.1.0.	
<a href="#">highlight.comment</a>	"#FF8000"	PHP_INI_ALL	
<a href="#">highlight.default</a>	"#0000BB"	PHP_INI_ALL	
<a href="#">highlight.html</a>	"#000000"	PHP_INI_ALL	
<a href="#">highlight.keyword</a>	"#007700"	PHP_INI_ALL	
<a href="#">highlight.string</a>	"#DD0000"	PHP_INI_ALL	
<a href="#">html_errors</a>	"1"	PHP_INI_ALL	
<a href="#">ibase.allow_persistent</a>	"1"	PHP_INI_SYSTEM	
<a href="#">ibase.max_persistent</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">ibase.max_links</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">ibase.default_db</a>	NULL	PHP_INI_SYSTEM	
<a href="#">ibase.default_user</a>	NULL	PHP_INI_ALL	
<a href="#">ibase.default_password</a>	NULL	PHP_INI_ALL	
<a href="#">ibase.default_charset</a>	NULL	PHP_INI_ALL	
<a href="#">ibase.timestampformat</a>	"%Y-%m-%d %H:%M:%S"	PHP_INI_ALL	
<a href="#">ibase.dateformat</a>	"%Y-%m-%d"	PHP_INI_ALL	
<a href="#">ibase.timeformat</a>	"%H:%M:%S"	PHP_INI_ALL	
<a href="#">ibm_db2.binmode</a>	"1"	PHP_INI_ALL	
<a href="#">ibm_db2.i5_all_pconnect</a>	"0"	PHP_INI_SYSTEM Available since ibm_db2 1.6.5.	
<a href="#">ibm_db2.i5_allow_commit</a>	"0"	PHP_INI_SYSTEM Available since ibm_db2 1.4.9.	
<a href="#">ibm_db2.i5_dbcs_alloc</a>	"0"	PHP_INI_SYSTEM Available since ibm_db2 1.5.0.	
<a href="#">ibm_db2.instance_name</a>	NULL	PHP_INI_SYSTEM Available since ibm_db2 1.0.2.	
<a href="#">ibm_db2.i5_ignore_userid</a>	"0"	PHP_INI_SYSTEM Available since ibm_db2 1.8.0.	
<a href="#">iconv.input_encoding</a>	""	PHP_INI_ALL Deprecated in PHP 5.6.0.	
<a href="#">iconv.output_encoding</a>	""	PHP_INI_ALL Deprecated in PHP 5.6.0.	
<a href="#">iconv.internal_encoding</a>	""	PHP_INI_ALL Deprecated in PHP 5.6.0.	
<a href="#">ignore_repeated_errors</a>	"0"	PHP_INI_ALL	
<a href="#">ignore_repeated_source</a>	"0"	PHP_INI_ALL	
<a href="#">ignore_user_abort</a>	"0"	PHP_INI_ALL	
<a href="#">implicit_flush</a>	"0"	PHP_INI_ALL	
<a href="#">include_path</a>	".:/path/to/php/pear"	PHP_INI_ALL	
<a href="#">intl.default_locale</a>		PHP_INI_ALL	
<a href="#">intl.error_level</a>	0	PHP_INI_ALL	

PHP: List of php.ini directives - Manual				
Name	Default	Changeable	Changelog	
<a href="#">intl.use_exceptions</a>	0	PHP_INI_ALL	Available since PECL 3.0.0a1	
<a href="#">last_modified</a>	"0"	PHP_INI_ALL		
<a href="#">ldap.max_links</a>	"-1"	PHP_INI_SYSTEM		
<a href="#">log_errors</a>	"0"	PHP_INI_ALL		
<a href="#">log_errors_max_len</a>	"1024"	PHP_INI_ALL		
<a href="#">mail.add_x_header</a>	"0"	PHP_INI_PERDIR		
<a href="#">mail.force_extra_parameters</a>	NULL	<i>php.ini</i> only		
<a href="#">mail.log</a>	""	PHP_INI_PERDIR		
<a href="#">max_execution_time</a>	"30"	PHP_INI_ALL		
<a href="#">max_input_nesting_level</a>	"64"	PHP_INI_PERDIR		
<a href="#">max_input_vars</a>	1000	PHP_INI_PERDIR		
<a href="#">max_input_time</a>	"-1"	PHP_INI_PERDIR		
<a href="#">mbstring.language</a>	"neutral"	PHP_INI_ALL		
<a href="#">mbstring.detect_order</a>	NULL	PHP_INI_ALL		
<a href="#">mbstring.http_input</a>	"pass"	PHP_INI_ALL	Deprecated	
<a href="#">mbstring.http_output</a>	"pass"	PHP_INI_ALL	Deprecated	
<a href="#">mbstring.internal_encoding</a>	NULL	PHP_INI_ALL	Deprecated	
<a href="#">mbstring.substitute_character</a>	NULL	PHP_INI_ALL		
<a href="#">mbstring.func_overload</a>	"0"	PHP_INI_SYSTEM	Deprecated as of PHP 7.2.0; removed as of PHP 8.0.0.	
<a href="#">mbstring.encoding_translation</a>	"0"	PHP_INI_PERDIR		
<a href="#">mbstring.http_output_conv_mimetypes</a>	"^(text/application/xhtml\+xml)"	PHP_INI_ALL		
<a href="#">mbstring.strict_detection</a>	"0"	PHP_INI_ALL		
<a href="#">mcrypt.algorithms_dir</a>	<b>null</b>	PHP_INI_ALL		
<a href="#">mcrypt.modes_dir</a>	<b>null</b>	PHP_INI_ALL		
<a href="#">memcache.allow_failover</a>	"1"	PHP_INI_ALL	Available since memcache 2.0.2.	
<a href="#">memcache.max_failover_attempts</a>	"20"	PHP_INI_ALL	Available since memcache 2.1.0.	
<a href="#">memcache.chunk_size</a>	"8192"	PHP_INI_ALL	Available since memcache 2.0.2.	
<a href="#">memcache.default_port</a>	"11211"	PHP_INI_ALL	Available since memcache 2.0.2.	
<a href="#">memcache.hash_strategy</a>	"standard"	PHP_INI_ALL	Available since memcache 2.2.0.	
<a href="#">memcache.hash_function</a>	"crc32"	PHP_INI_ALL	Available since memcache 2.2.0.	
<a href="#">session.save_handler</a>	"files"	PHP_INI_ALL	Supported since memcache 2.1.2	
<a href="#">session.save_path</a>	""	PHP_INI_ALL	Supported since memcache 2.1.2	
<a href="#">memcache.protocol</a>	ascii	>PHP_INI_ALL	Supported since memcache 3.0.0	
<a href="#">memcache.redundancy</a>	1	>PHP_INI_ALL	Supported since memcache 3.0.0	
<a href="#">memcache.session_redundancy</a>	2	>PHP_INI_ALL	Supported since memcache 3.0.0	
<a href="#">memcache.compress_threshold</a>	20000	>PHP_INI_ALL	Supported since memcache 3.0.3	
<a href="#">memcache.lock_timeout</a>	15	>PHP_INI_ALL	Supported since memcache 3.0.4	
<a href="#">memory_limit</a>	"128M"	PHP_INI_ALL		
<a href="#">mysql.allow_local_infile</a>	"1"	PHP_INI_SYSTEM		
<a href="#">mysql.allow_persistent</a>	"1"	PHP_INI_SYSTEM		
<a href="#">mysql.max_persistent</a>	"-1"	PHP_INI_SYSTEM		
<a href="#">mysql.max_links</a>	"-1"	PHP_INI_SYSTEM		
<a href="#">mysql.trace_mode</a>	"0"	PHP_INI_ALL		
<a href="#">mysql.default_port</a>	NULL	PHP_INI_ALL		
<a href="#">mysql.default_socket</a>	NULL	PHP_INI_ALL		
<a href="#">mysql.default_host</a>	NULL	PHP_INI_ALL		
<a href="#">mysql.default_user</a>	NULL	PHP_INI_ALL		
<a href="#">mysql.default_password</a>	NULL	PHP_INI_ALL		
<a href="#">mysql.connect_timeout</a>	"60"	PHP_INI_ALL		
<a href="#">mysqli.allow_local_infile</a>	"0"	PHP_INI_SYSTEM	Before PHP 7.2.16 and 7.3.3 the default was "1".	
<a href="#">mysqli.local_infile_directory</a>		PHP_INI_SYSTEM		
<a href="#">mysqli.allow_persistent</a>	"1"	PHP_INI_SYSTEM		
<a href="#">mysqli.max_persistent</a>	"-1"	PHP_INI_SYSTEM		
<a href="#">mysqli.max_links</a>	"-1"	PHP_INI_SYSTEM		
<a href="#">mysqli.default_port</a>	"3306"	PHP_INI_ALL		
<a href="#">mysqli.default_socket</a>	NULL	PHP_INI_ALL		
<a href="#">mysqli.default_host</a>	NULL	PHP_INI_ALL		
<a href="#">mysqli.default_user</a>	NULL	PHP_INI_ALL		
<a href="#">mysqli.default_pw</a>	NULL	PHP_INI_ALL		
<a href="#">mysqli.reconnect</a>	"0"	PHP_INI_SYSTEM		
<a href="#">mysqli.rollback_on_cached_plink</a>	"0"	PHP_INI_SYSTEM		
<a href="#">mysqlnd.collect_statistics</a>	"1"	PHP_INI_SYSTEM		
<a href="#">mysqlnd.collect_memory_statistics</a>	"0"	PHP_INI_SYSTEM		
<a href="#">mysqlnd.debug</a>	""	PHP_INI_SYSTEM		
<a href="#">mysqlnd.log_mask</a>	0	PHP_INI_ALL		
<a href="#">mysqlnd.mempool_default_size</a>	16000	PHP_INI_ALL		

PHP: List of php.ini directives - Manual			
Name	Default	Changeable	Changelog
<a href="#">mysqlnd.net_read_timeout</a>	"86400"	PHP_INI_ALL	Before PHP 7.2.0 the default value was "31536000" and the changeability was <b>PHP_INI_SYSTEM</b>
<a href="#">mysqlnd.net_cmd_buffer_size</a>	"4096"	PHP_INI_SYSTEM	
<a href="#">mysqlnd.net_read_buffer_size</a>	"32768"	PHP_INI_SYSTEM	
<a href="#">mysqlnd.sha256_server_public_key</a>	""	PHP_INI_PERDIR	
<a href="#">mysqlnd.trace_alloc</a>	""	PHP_INI_SYSTEM	
<a href="#">mysqlnd.fetch_data_copy</a>	0	PHP_INI_ALL	
<a href="#">oci8.connection_class</a>	""	PHP_INI_ALL	Available since PECL OCI8 1.3.
<a href="#">oci8.default_prefetch</a>	"100"	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.events</a>	Off	PHP_INI_SYSTEM	Available since PECL OCI8 1.3.
<a href="#">oci8.max_persistent</a>	"-1"	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.old_oci_close_semantics</a>	Off	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.persistent_timeout</a>	"-1"	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.ping_interval</a>	"60"	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.privileged_connect</a>	Off	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">oci8.statement_cache_size</a>	"20"	PHP_INI_SYSTEM	Available since PECL OCI8 1.1.
<a href="#">odbc.default_db</a> *	NULL	PHP_INI_ALL	
<a href="#">odbc.default_user</a> *	NULL	PHP_INI_ALL	
<a href="#">odbc.default_pw</a> *	NULL	PHP_INI_ALL	
<a href="#">odbc.allow_persistent</a>	"1"	PHP_INI_SYSTEM	
<a href="#">odbc.check_persistent</a>	"1"	PHP_INI_SYSTEM	
<a href="#">odbc.max_persistent</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">odbc.max_links</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">odbc.defaultlrl</a>	"4096"	PHP_INI_ALL	
<a href="#">odbc.defaultbinmode</a>	"1"	PHP_INI_ALL	
<a href="#">odbc.default_cursortype</a>	"3"	PHP_INI_ALL	
<a href="#">opcache.enable</a>	"1"	PHP_INI_ALL	
<a href="#">opcache.enable_cli</a>	"0"	PHP_INI_SYSTEM	Between PHP 7.1.2 and 7.1.6 inclusive, the default was "1"
<a href="#">opcache.memory_consumption</a>	"128"	PHP_INI_SYSTEM	
<a href="#">opcache.interned_strings_buffer</a>	"8"	PHP_INI_SYSTEM	
<a href="#">opcache.max_accelerated_files</a>	"10000"	PHP_INI_SYSTEM	
<a href="#">opcache.max_wasted_percentage</a>	"5"	PHP_INI_SYSTEM	
<a href="#">opcache.use_cwd</a>	"1"	PHP_INI_SYSTEM	
<a href="#">opcache.validate_timestamps</a>	"1"	PHP_INI_ALL	
<a href="#">opcache.revalidate_freq</a>	"2"	PHP_INI_ALL	
<a href="#">opcache.revalidate_path</a>	"0"	PHP_INI_ALL	
<a href="#">opcache.save_comments</a>	"1"	PHP_INI_SYSTEM	
<a href="#">opcache.fast_shutdown</a>	"0"	PHP_INI_SYSTEM	Removed in PHP 7.2.0
<a href="#">opcache.enable_file_override</a>	"0"	PHP_INI_SYSTEM	
<a href="#">opcache.optimization_level</a>	"0x7FFEBFFF"	PHP_INI_SYSTEM	Changed from 0x7FFFBFFF in PHP 7.3.0
<a href="#">opcache.inherited_hack</a>	"1"	PHP_INI_SYSTEM	Removed in PHP 7.3.0
<a href="#">opcache.dups_fix</a>	"0"	PHP_INI_ALL	
<a href="#">opcache.blacklist_filename</a>	""	PHP_INI_SYSTEM	
<a href="#">opcache.max_file_size</a>	"0"	PHP_INI_SYSTEM	
<a href="#">opcache.consistency_checks</a>	"0"	PHP_INI_ALL	
<a href="#">opcache.force_restart_timeout</a>	"180"	PHP_INI_SYSTEM	
<a href="#">opcache.error_log</a>	""	PHP_INI_SYSTEM	
<a href="#">opcache.log_verbosity_level</a>	"1"	PHP_INI_SYSTEM	
<a href="#">opcache.preferred_memory_model</a>	""	PHP_INI_SYSTEM	
<a href="#">opcache.protect_memory</a>	"0"	PHP_INI_SYSTEM	
<a href="#">opcache.mmap_base</a>	<b>null</b>	PHP_INI_SYSTEM	
<a href="#">opcache.restrict_api</a>	""	PHP_INI_SYSTEM	
<a href="#">opcache.file_update_protection</a>	"2"	PHP_INI_ALL	
<a href="#">opcache.huge_code_pages</a>	"0"	PHP_INI_SYSTEM	
<a href="#">opcache.lockfile_path</a>	"/tmp"	PHP_INI_SYSTEM	
<a href="#">opcache.opt_debug_level</a>	"0"	PHP_INI_SYSTEM	Available as of PHP 7.1.0
<a href="#">opcache.file_cache</a>	NULL	PHP_INI_SYSTEM	
<a href="#">opcache.file_cache_only</a>	"0"	PHP_INI_SYSTEM	
<a href="#">opcache.file_cache_consistency_checks</a>	"1"	PHP_INI_SYSTEM	
<a href="#">opcache.file_cache_fallback</a>	"1"	PHP_INI_SYSTEM	Windows only.
<a href="#">opcache.validate_permission</a>	"0"	PHP_INI_SYSTEM	Available as of PHP 7.0.14
<a href="#">opcache.validate_root</a>	"0"	PHP_INI_SYSTEM	Available as of PHP 7.0.14
<a href="#">opcache.preload</a>	""	PHP_INI_SYSTEM	Available as of PHP 7.4.0
<a href="#">opcache.preload_user</a>	""	PHP_INI_SYSTEM	Available as of PHP 7.4.0
<a href="#">opcache.cache_id</a>	""	PHP_INI_SYSTEM	Windows only. Available as of PHP 7.4.0
<a href="#">opcache.jit</a>	"tracing"	PHP_INI_ALL	Available as of PHP 8.0.0



Name	Default	Changeable	Changelog
<a href="#">opcache.jit_buffer_size</a>	"0"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_debug</a>	"0"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_bisect_limit</a>	"0"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_prof_threshold</a>	"0.005"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_root_traces</a>	"1024"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_side_traces</a>	"128"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_exit_counters</a>	"8192"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_hot_loop</a>	"64"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_hot_func</a>	"127"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_hot_return</a>	"8"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_hot_side_exit</a>	"8"	PHP_INI_SYSTEM	Available as of PHP 8.0.0
<a href="#">opcache.jit_blacklist_root_trace</a>	"16"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_blacklist_side_trace</a>	"8"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_loop_unrolls</a>	"8"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_recursive_calls</a>	"2"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_recursive_returns</a>	"2"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">opcache.jit_max_polymorphic_calls</a>	"2"	PHP_INI_ALL	Available as of PHP 8.0.0
<a href="#">open_basedir</a>	NULL	PHP_INI_ALL	
<a href="#">output_buffering</a>	"0"	PHP_INI_PERDIR	
<a href="#">output_handler</a>	NULL	PHP_INI_PERDIR	
<a href="#">pcre.backtrack_limit</a>	"1000000"	PHP_INI_ALL	
<a href="#">pcre.recursion_limit</a>	"100000"	PHP_INI_ALL	
<a href="#">pcre.jit</a>	"1"	PHP_INI_ALL	
<a href="#">pdo.dsn.*</a>		<i>php.ini</i> only	
<a href="#">pdo_odbc.connection_pooling</a>	"strict"	PHP_INI_ALL	
<a href="#">pdo_odbc.db2_instance_name</a>	NULL	PHP_INI_SYSTEM	This deprecated feature <i>will</i> certainly be <i>removed</i> in the future.
<a href="#">pgsql.allow_persistent</a>	"1"	PHP_INI_SYSTEM	
<a href="#">pgsql.max_persistent</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">pgsql.max_links</a>	"-1"	PHP_INI_SYSTEM	
<a href="#">pgsql.auto_reset_persistent</a>	"0"	PHP_INI_SYSTEM	
<a href="#">pgsql.ignore_notice</a>	"0"	PHP_INI_ALL	
<a href="#">pgsql.log_notice</a>	"0"	PHP_INI_ALL	
<a href="#">phar.readonly</a>	"1"	PHP_INI_ALL	
<a href="#">phar.require_hash</a>	"1"	PHP_INI_ALL	
<a href="#">phar.cache_list</a>	""	PHP_INI_SYSTEM	
<a href="#">post_max_size</a>	"8M"	PHP_INI_PERDIR	
<a href="#">precision</a>	"14"	PHP_INI_ALL	
<a href="#">realpath_cache_size</a>	"16K"	PHP_INI_SYSTEM	
<a href="#">realpath_cache_ttl</a>	"120"	PHP_INI_SYSTEM	
<a href="#">register_argc_argv</a>	"1"	PHP_INI_PERDIR	
<a href="#">report_memleaks</a>	"1"	PHP_INI_ALL	
<a href="#">report_zend_debug</a>	"1"	PHP_INI_ALL	
<a href="#">request_order</a>	""	PHP_INI_PERDIR	
<a href="#">runkit.superglobal</a>	""	PHP_INI_PERDIR	
<a href="#">runkit.internal_override</a>	"0"	PHP_INI_SYSTEM	
<a href="#">sendmail_from</a>	NULL	PHP_INI_ALL	
<a href="#">sendmail_path</a>	"/usr/sbin/sendmail -t -i"	PHP_INI_SYSTEM	
<a href="#">serialize_precision</a>	"-1"	PHP_INI_ALL	Prior to PHP 7.1.0, the default value was 17.
<a href="#">session.save_path</a>	""	PHP_INI_ALL	
<a href="#">session.name</a>	"PHPSESSID"	PHP_INI_ALL	
<a href="#">session.save_handler</a>	"files"	PHP_INI_ALL	
<a href="#">session.auto_start</a>	"0"	PHP_INI_PERDIR	
<a href="#">session.gc_probability</a>	"1"	PHP_INI_ALL	
<a href="#">session.gc_divisor</a>	"100"	PHP_INI_ALL	
<a href="#">session.gc_maxlifetime</a>	"1440"	PHP_INI_ALL	
<a href="#">session.serialize_handler</a>	"php"	PHP_INI_ALL	
<a href="#">session.cookie_lifetime</a>	"0"	PHP_INI_ALL	
<a href="#">session.cookie_path</a>	"/"	PHP_INI_ALL	
<a href="#">session.cookie_domain</a>	""	PHP_INI_ALL	
<a href="#">session.cookie_secure</a>	""	PHP_INI_ALL	
<a href="#">session.cookie_httponly</a>	""	PHP_INI_ALL	
<a href="#">session.cookie_samesite</a>	""	PHP_INI_ALL	Available as of PHP 7.3.0.
<a href="#">session.use_strict_mode</a>	"0"	PHP_INI_ALL	
<a href="#">session.use_cookies</a>	"1"	PHP_INI_ALL	
<a href="#">session.use_only_cookies</a>	"1"	PHP_INI_ALL	
<a href="#">session.referer_check</a>	""	PHP_INI_ALL	

7/27/2021		PHP: List of php.ini directives - Manual	
Name	Default	Changeable	Changelog
<a href="#">session.cache_limiter</a>	"nocache"	PHP_INI_ALL	
<a href="#">session.cache_expire</a>	"180"	PHP_INI_ALL	
<a href="#">session.use_trans_sid</a>	"0"	PHP_INI_ALL	
<a href="#">session.trans_sid_tags</a>	"a=href,area=href,frame=src,form="	PHP_INI_ALL	Available as of PHP 7.1.0.
<a href="#">session.trans_sid_hosts</a>	\$_SERVER[ 'HTTP_HOST' ]	PHP_INI_ALL	Available as of PHP 7.1.0.
<a href="#">session.sid_length</a>	"32"	PHP_INI_ALL	Available as of PHP 7.1.0.
<a href="#">session.sid_bits_per_character</a>	"4"	PHP_INI_ALL	Available as of PHP 7.1.0.
<a href="#">session.upload_progress.enabled</a>	"1"	PHP_INI_PERDIR	
<a href="#">session.upload_progress.cleanup</a>	"1"	PHP_INI_PERDIR	
<a href="#">session.upload_progress.prefix</a>	"upload_progress_"	PHP_INI_PERDIR	
<a href="#">session.upload_progress.name</a>	"PHP_SESSION_UPLOAD_PROGRESS"	PHP_INI_PERDIR	
<a href="#">session.upload_progress.freq</a>	"1%"	PHP_INI_PERDIR	
<a href="#">session.upload_progress.min_freq</a>	"1"	PHP_INI_PERDIR	
<a href="#">session.lazy_write</a>	"1"	PHP_INI_ALL	
<a href="#">session.hash_function</a>	"0"	PHP_INI_ALL	Removed as of PHP 7.1.0.
<a href="#">session.hash_bits_per_character</a>	"4"	PHP_INI_ALL	Removed as of PHP 7.1.0.
<a href="#">session.entropy_file</a>	""	PHP_INI_ALL	Removed as of PHP 7.1.0.
<a href="#">session.entropy_length</a>	"0"	PHP_INI_ALL	Removed as of PHP 7.1.0
<a href="#">short_open_tag</a>	"1"	PHP_INI_PERDIR	
<a href="#">SMTP</a>	"localhost"	PHP_INI_ALL	
<a href="#">smtp_port</a>	"25"	PHP_INI_ALL	
<a href="#">soap.wsdl_cache_enabled</a>	1	PHP_INI_ALL	
<a href="#">soap.wsdl_cache_dir</a>	/tmp	PHP_INI_ALL	
<a href="#">soap.wsdl_cache_ttl</a>	86400	PHP_INI_ALL	
<a href="#">soap.wsdl_cache</a>	1	PHP_INI_ALL	
<a href="#">soap.wsdl_cache_limit</a>	5	PHP_INI_ALL	
<a href="#">sql.safe_mode</a>	"0"	PHP_INI_SYSTEM	
<a href="#">sqlite3.extension_dir</a>	""	PHP_INI_SYSTEM	
<a href="#">sqlite3.defensive</a>	1	PHP_INI_SYSTEM	Available as of PHP 7.2.17 and 7.3.4 for libsqlite ≥ 3.26.0.
<a href="#">syslog.facility</a>	"LOG_USER"	PHP_INI_SYSTEM	Available as of PHP 7.3.0.
<a href="#">syslog.filter</a>	"no-ctrl"	PHP_INI_ALL	Available as of PHP 7.3.0.
<a href="#">syslog.ident</a>	"php"	PHP_INI_SYSTEM	Available as of PHP 7.3.0.
<a href="#">sys_temp_dir</a>	""	PHP_INI_SYSTEM	
<a href="#">sysvshm.init_mem</a>	10000	PHP_INI_SYSTEM	
<a href="#">tidy.default_config</a>	""	PHP_INI_SYSTEM	
<a href="#">tidy.clean_output</a>	"0"	PHP_INI_USER	
<a href="#">track_errors</a>	"0"	PHP_INI_ALL	Deprecated as of PHP 7.2.0.
<a href="#">unserialize_callback_func</a>	NULL	PHP_INI_ALL	
<a href="#">uploadprogress.file.filename_template</a>	"/tmp/upt_%.s.txt"	PHP_INI_ALL	
<a href="#">upload_max_filesize</a>	"2M"	PHP_INI_PERDIR	
<a href="#">max_file_uploads</a>	20	PHP_INI_SYSTEM	
<a href="#">upload_tmp_dir</a>	NULL	PHP_INI_SYSTEM	
<a href="#">url_rewriter.tags</a>	"a=href,area=href,frame=src,form=,fieldset="	PHP_INI_ALL	
<a href="#">user_agent</a>	NULL	PHP_INI_ALL	
<a href="#">user_dir</a>	NULL	PHP_INI_SYSTEM	
<a href="#">user_ini.cache_ttl</a>	"300"	PHP_INI_SYSTEM	
<a href="#">user_ini.filename</a>	".user.ini"	PHP_INI_SYSTEM	
<a href="#">uopz.disable</a>	"0"	PHP_INI_SYSTEM	Available as of uopz 5.0.2
<a href="#">uopz.exit</a>	"0"	PHP_INI_SYSTEM	Available as of uopz 6.0.1
<a href="#">uopz.overloads</a>	"1"	PHP_INI_SYSTEM	Available as of uopz 2.0.2. Removed as of uopz 5.0.0.
<a href="#">variables_order</a>	"EGPCS"	PHP_INI_PERDIR	
<a href="#">vld.active</a>	"0"	PHP_INI_SYSTEM	
<a href="#">vld.execute</a>	"1"	PHP_INI_SYSTEM	Available since vld 0.8.0.
<a href="#">vld.skip_append</a>	"0"	PHP_INI_SYSTEM	Available since vld 0.8.0.
<a href="#">vld.skip_prepend</a>	"0"	PHP_INI_SYSTEM	Available since vld 0.8.0.
<a href="#">windows.show_crt_warning</a>	"0"	PHP_INI_ALL	
<a href="#">xbithack</a>	"0"	PHP_INI_ALL	
<a href="#">xmlrpc_errors</a>	"0"	PHP_INI_SYSTEM	
<a href="#">xmlrpc_error_number</a>	"0"	PHP_INI_ALL	
<a href="#">yaz.keepalive</a>	"120"	PHP_INI_ALL	
<a href="#">yaz.log_mask</a>	NULL	PHP_INI_ALL	Available since yaz 1.0.3.
<a href="#">zend.assertions</a>	"1"	PHP_INI_ALL	
<a href="#">zend.detect_unicode</a>	"1"	PHP_INI_ALL	
<a href="#">zend.enable_gc</a>	"1"	PHP_INI_ALL	
<a href="#">zend.multibyte</a>	"0"	PHP_INI_PERDIR	
<a href="#">zend.script_encoding</a>	NULL	PHP_INI_ALL	

Name	Default	Changeable	Changelog
<a href="#">zend.signal_check</a>	"0"	PHP_INI_SYSTEM	
<a href="#">zend_extension</a>	NULL	<i>php.ini</i> only	
<a href="#">zlib.output_compression</a>	"0"	PHP_INI_ALL	
<a href="#">zlib.output_compression_level</a>	"-1"	PHP_INI_ALL	
<a href="#">zlib.output_handler</a>	""	PHP_INI_ALL	