

How to Install and Configure ModEvasive with Apache on Ubuntu 18.04



February 22, 2020 by Hitesh Jethva (<https://www.atlantic.net/author/hitesh-jethva/>) (511

posts) under VPS Hosting (<https://www.atlantic.net/category/vps-hosting/>)

0 Comments (https://www.atlantic.net/vps-hosting/how-to-install-and-configure-modevasive-with-apache-on-ubuntu-18-04/#disqus_thread)

(mailto:?subject=How to Install and Configure ModEvasive with Apache on Ubuntu 18.04&body=<https://www.atlantic.net/vps-hosting/how-to-install-and-configure-modevasive-with-apache-on-ubuntu-18-04/>)

(<https://reddit.com/submit/?url=https://www.atlantic.net/vps-hosting/how-to-install-and-configure-modevasive-with-apache-on-ubuntu-18-04/&resubmit=true&title=How to Install and Configure ModEvasive with Apache on Ubuntu 18.04>)

(<https://news.ycombinator.com/submitlink?u=https://www.atlantic.net/vps-hosting/how-to-install-and-configure-modevasive-with-apache-on-ubuntu-18-04/&t=How to Install and Configure ModEvasive with Apache on Ubuntu 18.04>)

Protecting your web server against different kinds of attacks is a crucial responsibility for any system administrator. ModEvasive is an Apache web server module that helps you to protect your web server in the event of DoS, DDoS, and brute-force attacks. These types of attacks cause the server to run out of memory, crashing your website.

The `mod_evasive` module works by creating a hash table of IP Addresses and URIs and monitoring for suspicious incoming server requests, such as:

- Making more than 100 concurrent connections per second.
- Requesting the same page several times per second.

If such a suspicious request occurs, the `mod_evasive` module sends a 403 error and blocks the IP address.

In this tutorial, we will show you how to install and configure `mod_evasive` with Apache on an Ubuntu 18.04 server.

Prerequisites

- A fresh Ubuntu 18.04 VPS (<https://www.atlantic.net/vps-hosting/>) on the Atlantic.Net Cloud Platform.

- A static IP address configured on your server.

Step 1 – Create Atlantic.Net Cloud Server

First, log in to your Atlantic.Net Cloud Server (<https://cloud.atlantic.net/?page=userlogin>). Create a new server (<https://www.atlantic.net/cloud-hosting/how-to-create-new-atlantic-net-cloud-server/>), choosing Ubuntu 18.04 as the operating system with at least 1GB RAM. Connect to your Cloud Server via SSH and log in using the credentials highlighted at the top of the page.

Once you are logged into your Ubuntu 18.04 server, run the following command to update your base system with the latest available packages.

```
apt-get update -y
```

Step 2 – Install mod_evasive


Before starting, Apache webserver needs to be installed on your server. If not installed, you can install it with the following command:

```
apt-get install apache2 apache2-utils -y
```

Once Apache web server is installed, you can install mod_evasive with the following command:

```
apt-get install libapache2-mod-evasive -y
```

During the installation, you will be asked to configure a Postfix mail server for email notification. You can choose your desired option to complete the installation. If you are unsure, just choose *local only* or *no configuration*.



After installing mod_evasive, you can verify whether the mod_evasive module is enabled by running the following command:

```
apachectl -M | grep evasive
```

You should get the following output:

```
[Mon Jan 27 13:55:35.707317 2020] [so:warn] [pid 29031] AH01574: module
dav_module is already loaded, skipping
evasive20_module (shared)
```

At this point, the mod_evasive module is installed and enabled. You can now proceed to the next step.

Step 3 – Configure mod_evasive

The default configuration file of mod_evasive is located at /etc/apache2/mods-enabled/evasive.conf. You will need to configure this file per your requirements.

You can open this file using the nano editor as shown below:

```
nano /etc/apache2/mods-enabled/evasive.conf
```

Change the file as shown below. We recommend amending DOSEmailNotify to the address you want the email sent to (if configured) and DOSSystemCommand – for example “su – richard -c ‘/sbin... %s ...’”

```
<IfModule mod_evasive20.c>
    DOSHashTableSize    3097
    DOSPageCount        2
    DOSSiteCount        50
    DOSPageInterval     1
    DOSSiteInterval     1
    DOSBlockingPeriod   100
    DOSEmailNotify      root@ubuntu1804
    DOSSystemCommand    "su - someuser -c '/sbin/... %s ...'"
    DOSLogDir           "/var/log/mod_evasive"
</IfModule>
```

Save and close the file when you are finished.

A brief explanation of each option is shown below:

- **DOSHashTableSize:** mod_evasive uses this option to control the hash table size. It is recommended to increase this if you have a busy web server.
- **DOSPageCount:** This option specifies the threshold limit for the number of requests allowed to the same URI per second. Once the threshold limit has been exceeded, the client's IP address will be blacklisted.
- **DOSSiteCount:** This option specifies the limit on the total number of requests allowed to the same IP address.
- **DOSPageInterval:** This option specifies the page count interval.
- **DOSSiteInterval:** This option specifies the site count interval.
- **DOSBlockingPeriod :** This option defines the amount of time in seconds that a client will be blocked.
- **DOSEmailNotify:** This option sends an email to the specified address when an IP address has been blacklisted.
- **DOSSystemCommand:** Whenever an IP address has been blacklisted, the specified system command will be executed.
- **DOSLogDir:** This option defines the mod_evasive log directory.

Next, create a directory to store the mod_evasive log and change its ownership to www-data with the following command:

```
mkdir /var/log/mod_evasive
chown -R www-data:www-data /var/log/mod_evasive
```

Finally, restart the Apache service to implement the changes:

```
systemctl restart apache2
```

Step 4 – Test mod_evasive

At this point, the mod_evasive module is installed and configured. It's time to test whether the module is working correctly.

Go to the remote system and send a bulk page request to the server using the ab command:

```
ab -n 1000 -c 20 http://your-server-ip/
```

```
Finished 1000 requests

Server Software:      Apache/2.4.29
Server Hostname:      208.117.83.137
Server Port:          80

Document Path:        /
Document Length:      10918 bytes

Concurrency Level:     20
Time taken for tests:  7.700 seconds
Complete requests:     1000
Failed requests:       994
  (Connect: 0, Receive: 0, Length: 994, Exceptions: 0)
Non-2xx responses:     994
Total transferred:     523398 bytes
HTML transferred:     342834 bytes
Requests per second:   129.86 [#/sec] (mean)
Time per request:      154.006 [ms] (mean)
Time per request:      7.700 [ms] (mean, across all concurrent requests)
Transfer rate:         66.38 [Kbytes/sec] received

Connection Times (ms)
      min    mean[+/-sd] median    max
Connect:    75     76   1.2     77     80
Processing:  75     77   1.9     77     91
Waiting:    75     77   1.9     77     91
Total:      150    153   2.8    154    168

Percentage of the requests served within a certain time (ms)
 50%    154
 66%    155
 75%    155
 80%    156
 90%    156
 95%    156
 98%    157
 99%    163
100%    168 (longest request)
root@Server2AtlanticNet:~#
```

This command will cause the equivalent of a DoS attack by sending 1000 page requests in 10 concurrent connections.

On the server, check the mail log by running the following command:

```
tail -15 /var/mail/root
```

You should see that the client IP address has been blacklisted by mod_evasive:

To: root@ubuntu1804
Subject: HTTP BLACKLIST 103.250.161.100

```
mod_evasive HTTP Blacklisted 103.250.161.100
```

You can edit the script as shown below:

```
nano /usr/share/doc/libapache2-mod-evasive/examples/test.pl
```

```
print $SOCKET "GET /?$_ HTTP/1.0\n\n";
```

```
print $SOCKET "GET /?$_ HTTP/1.0\n\n";
```

```
print $SOCKET "GET /?$_ HTTP/1.0\r\nHost: 127.0.0.1\r\n\r\n";
```

```
print $SOCKET "GET /?$_ HTTP/1.0\r\nHost: 127.0.0.1\r\n\r\n";
```

```
perl /usr/share/doc/libapache2-mod-evasive/examples/test.pl
```

```
perl /usr/share/doc/libapache2-mod-evasive/examples/test.pl
```

[illegible][illegible]

Conclusion

Congratulations! The mod_evasive module is now configured to protect your server against DDoS and Brute force attacks.

< Older post (<https://www.atlantic.net/vps-hosting/how-to-install-and-configure-mariadb-galera-cluster-on-ubuntu-18-04/>)

Newer post > (<https://www.atlantic.net/vps-hosting/how-to-set-up-ssh-keys-on-ubuntu-18-04/>)

Get started with 12 months of free cloud VPS hosting

Free Tier includes:

- G3.2GB Cloud VPS Server Free to Use for One Year
- 50 GB of Block Storage Free to Use for One Year
- 50 GB of Snapshots Free to Use for One Year

(/vps-hosting/)

ALSO ON ATLANTIC.NET

Getting Started with DNS Records

2 years ago · 2 comments

Atlantic.Net's Cloud Portal includes a DNS management module that ...

Top 8 Cloud-Based Software Testing ...

2 years ago · 2 comments

There is no shortage of good software testing tools on the market. Here's our ...

Install OpenLiteSpeed, MariaDB, PHP8.0 on ...

2 years ago · 1 comment

In this tutorial post, we will show you how to install Openlightspeed, ...

Post-Pand Cybersecu

a year ago · 2

How have cy threats chan pandemic? E