06/09/2026 09:17

bashrc_drift_wars

```
alias banc='cd /storage/emulated/0/RootBase/
CodeCity-Bench && bash workbench.sh'


export OPENCLAW_GATEWAY_TOKEN=HighFives26!
# source ~/janebot-motherbrain/scripts/jane_cmds.sh
alias swarmlint='find . -name "__pycache__" -exec rm -rf
{} + && find . -name "*.db" -type f -delete'
alias locals='ollama serve &'
export PATH=/data/data/com.termux/files/
home/.npm-global/bin:$PATH
export NODE_OPTIONS="--max-old-space-size=2048"
# --- OpenClaw Start ---
# WARNING: This section contains your access token -
keep ~/.bashrc secure
export TERMUX_VERSION=1
export TMPDIR=$HOME/tmp
export PATH=/data/data/com.termux/files/
home/.npm-global/bin:$PATH
```

06/09/2026 09:17

```
# OpenClaw color definitions
GREEN='\033[0;32m'
BLUE='\033[0;34m'
YELLOW='\033[1;33m'
RED='\033[0;31m'
CYAN='\033[0;36m'
NC='\033[0m'

# OpenClaw service management functions
ocr() {
  echo -e "${YELLOW}Starting/restarting OpenClaw service...${NC}"
  pkill -9 -f 'openclaw_final' 2>/dev/null
  tmux kill-session -t openclaw_final 2>/dev/null
  sleep 1
  tmux new -d -s openclaw_final
  sleep 1
  tmux send-keys -t openclaw_final "export PATH=/data/data/com.termux/files/home/.npm-global/bin:
```

06/09/2026 09:17

```
$PATH TMPDIR=$HOME/tmp
OPENCLAW_GATEWAY_TOKEN=$OPENCLAW_GATEWA
Y_TOKEN; openclaw_final gateway --bind loopback
--port 18789 --token \$OPENCLAW_GATEWAY_TOKEN
--allow-unconfigured" C-m
  sleep 2
  if tmux has-session -t openclaw_final 2>/dev/null; then
    echo ""
    echo -e "${GREEN}✅ OpenClaw service started${NC}"
    echo ""
    echo -e "${CYAN}📖 Usage:${NC}"
    echo "  1. Open in phone browser::
http://localhost:18789/?token=$OPENCLAW_GATEWAY_TOKEN"
    echo "  2. Or run command: openclaw_final tui"
    echo "  3. Or use Telegram bot (if configured)"
    echo ""
    echo -e "${BLUE} 💡 oclog to view logs I ockill to stop
```

06/09/2026 09:17

```
service${NC}"
    else
        echo -e "${RED}❌ Service failed to start, please
check logs (openclaw_final logs)${NC}"
    fi
}

oclog() {
    if tmux has-session -t openclaw_final 2>/dev/null; then
        tmux attach -t openclaw_final
    else
        echo -e "${YELLOW}⚠️ OpenClaw service not
running, use ocr to start${NC}"
    fi
}

ockill() {
    echo -e "${YELLOW}Stopping OpenClaw service...$
{NC}"
```

06/09/2026 09:17

```
    pkill -9 -f "openclaw_final" 2>/dev/null
    tmux kill-session -t openclaw_final 2>/dev/null
    sleep 1
    if ! tmux has-session -t openclaw_final 2>/dev/null && ! pgrep -f "openclaw_final" > /dev/null; then
        echo -e "${GREEN}✅ OpenClaw service stopped${NC}"
    else
        echo -e "${RED}❌ Failed to stop service, please check manually${NC}"
    fi
}
# --- OpenClaw End ---
eval "$(zoxide init bash)"

# Navigation
alias l='bat'
alias cls='clear'
```

06/09/2026 09:17

```
# Agent Shortcuts
alias swarm='openclaw_final gateway start'
alias agent='aider --model gemini/gemini-1.5-flash' # Uses free tier
alias dev='tmux new-session -A -s BabyDickMike'

export PATH=$PATH:/storage/emulated/0/RootBase/codex_install/node_modules/.bin
eval "$(zoxide init bash)"
export PATH=$PATH:/storage/emulated/0/RootBase/bin
alias start_swarm='source /storage/emulated/0/RootBase/bin/start_swarm_tmux.sh'

# >>> Codex installer >>>
export PATH="/data/data/com.termux/files/home/.local/bin:$PATH"

# <<< Codex installer <<<
```

06/09/2026 09:17

```
export
GROQ_API_KEY="gsk_9NUXyX6yxHa0V6Sm2YjwWGdyb
3FYnNcFOrepkXY2n7NjEnfE3F5G"
export PATH="/storage/emulated/0/RootBase/
CodeMentor-MVP/bin:$PATH"
alias kimi-code="python3 /storage/emulated/0/
RootBase/Kimi-Code/kimi_code.py"

# MOLT v3 Background Swarm Orchestration Aliases
alias molt-start='nohup bash -c "while true; do ./
molt_v3.py --headless --iters 3; sleep 1800; done" > /
dev/null 2>&1 &'
alias molt-stop='pkill -f "molt_v3.py --headless"'
alias molt-status='ps aux | grep molt_v3.py | grep -v grep'

export OLLAMA_KEEP_ALIVE="0"
export OLLAMA_NUM_PARALLEL="1"
export OMP_NUM_THREADS="4"
export TELEGRAM_CHAT_ID="5210530438Ç"
```

06/09/2026 09:17

```
export
TELEGRAM_BOT_TOKEN="Ç8595103704:AAHNMLqCX-a
15QZaralfKdcbPz5QcNpZmK4"
export
VOLTAGE_API_KEY="vltg_dKd3LMr8nchzwt8tdTrPRbaRJ
hCDmYgk"

~/START_HERE.sh

# Prank Header - Needs to boot in normal shell and TUI
1st session but idk how yet
~/START_HERE.sh
export PS1="ButtsCorp \$ "
alias gemini-hl="bash ~/headless_gemini.sh"
export
LIGHTNING_ADDRESS="bleaknarratives@strike.me"
export
LIGHTNING_ADDRESS="ironicjewel052@walletofsatoshi
.com"
```

06/09/2026 09:17

```
export
C4P_TELEGRAM_BOT_TOKEN="8912003162:AAGzQ7m9
7NwM27ji-XNYk8MfvfVBgjLQsLI"

alias trigger-start='nohup ~/run_triggers.sh > /dev/null
2>&1 &'
# Added by flyctl installer
export FLYCTL_INSTALL="/data/data/com.termux/files/
home/.fly"
export PATH="$FLYCTL_INSTALL/bin:$PATH"
alias insight='python3 /data/data/com.termux/files/
home/tools/codementor_cli/insight_v2.py'
export ROOTBASE_LOGS=/storage/emulated/0/
RootBase/logs
alias boardroom='bash /storage/emulated/0/RootBase/
boardroom_launch.sh'
alias boardroom='cd /storage/emulated/0/RootBase &&
pkill -f boardroom_bridge 2>/dev/null; pkill -f http.server
2>/dev/null; OLLAMA_BOARDROOM_MODEL=llama3.2:1b
```

06/09/2026 09:17

```
python3 boardroom_bridge.py & python3 -m http.server
8080 & sleep 2 && termux-open-url
http://127.0.0.1:8080/vertical_ai_boardroom_3d.html'
alias ask='node ~/term-ai/ai.js'
export MATHLIB=m
export LDFLAGS=' -lpython3.13'
export
LIGHTNING_ADDRESS="ironicjewel052@walletofsatoshi
.com"
# Auto-start Mrs. Higgins daemon on shell launch
if ! pgrep -f "higgins_daemon.py" > /dev/null; then
   nohup python3 /storage/emulated/0/RootBase/
scripts/utilities/higgins_daemon.py > /storage/
emulated/0/RootBase/mrs_higgins_saas/logs/
daemon.log 2>&1 &
fi
export
OPENROUTER_API_KEY='sk-or-v1-2d8439d8c69369f0af
83e33fd79492449383e210132e2865fcf10d9845c7a087'
```

06/09/2026 09:17

```
export
GEMINI_API_KEY='AQ.Ab8RN6LY21MOty54OOdSNp6ORbpXI0DGxf1S4ai9Hjb69KJp3g'

# Define your protected asset roots
export SWARM_WORKSPACE="/storage/emulated/0/RootBase"

function guard_run() {
  local current_dir=$(pwd)

  # Check if we are running raw in Home without a repo context
  if [[ "$current_dir" == "$HOME" ]]; then
    echo -e "\n⚠️ \033[1;31m[Sentinel Block]\033[0m Running loose scripts directly in ~ is barred."
    echo -e "💡 Redirecting execution context to Workspace Root..."
    cd "$SWARM_WORKSPACE/Syntax-AI-CLI" || cd
```

06/09/2026 09:17

```
"$SWARM_WORKSPACE"
    fi

    # Execute the actual command passed to the guard
    "$@"

    # Post-execution cleanup: Catch files that escaped
into ~ anyway
    # Sweeps untracked standalone .tmp, .log, or stray
json out of ~
    find "$HOME" -maxdepth 1 -type f \( -name "*.tmp" -o
-name "*.log" -o -name "vai_output_*.json" \) -exec mv {}
"$SWARM_WORKSPACE/lost_found/" \; 2>/dev/null
}

# Wrap your critical execution hooks through the
sentinel
alias python3="guard_run python3"
alias ask="guard_run ask"
```

06/09/2026 09:17

==========

```
cat << 'EOF' >> ~/.bashrc
alias banc='cd /storage/emulated/0/RootBase/
CodeCity-Bench && bash workbench.sh'

export OPENCLAW_GATEWAY_TOKEN=HighFives26!
alias swarmlint='find . -name "__pycache__" -exec rm -rf
{} + && find . -name "*.db" -type f -delete'
alias locals='ollama serve &'
export PATH=/data/data/com.termux/files/
home/.npm-global/bin:$PATH
export NODE_OPTIONS="--max-old-space-size=2048"

# --- OpenClaw Start ---
export TERMUX_VERSION=1
export TMPDIR=$HOME/tmp

GREEN='\033[0;32m'
```

06/09/2026 09:17

```
BLUE='\033[0;34m'
YELLOW='\033[1;33m'
RED='\033[0;31m'
CYAN='\033[0;36m'
NC='\033[0m'

ocr() {
  echo -e "${YELLOW}Starting/restarting OpenClaw service...${NC}"
  pkill -9 -f 'openclaw_final' 2>/dev/null
  tmux kill-session -t openclaw_final 2>/dev/null
  cd /storage/emulated/0/RootBase/Syntax-AI-CLI || return
  tmux new-session -d -s openclaw_final 'python3 openclaw_final.py'
  echo -e "${GREEN}OpenClaw running in tmux session: openclaw_final${NC}"
}
```

06/09/2026 09:17

```
export
LIGHTNING_ADDRESS="ironicjewel052@walletofsatoshi
.com"

# Auto-start Mrs. Higgins daemon on shell launch
if ! pgrep -f "higgins_daemon.py" > /dev/null; then
   nohup python3 /storage/emulated/0/RootBase/
scripts/utilities/higgins_daemon.py > /storage/
emulated/0/RootBase/mrs_higgins_saas/logs/
daemon.log 2>&1 &
fi

export
OPENROUTER_API_KEY='sk-or-v1-2d8439d8c69369f0af
83e33fd79492449383e210132e2865fcf10d9845c7a087'
export
GEMINI_API_KEY='AQ.Ab8RN6LY21MOty54OOdSNp6OR
bpXI0DGxf1S4ai9Hjb69KJp3g'
```

06/09/2026 09:17

```
#
================================================
=======
# SYNTAX AI SWARM WORKSPACE & SENTINEL
#
================================================
=======
export SWARM_WORKSPACE="/storage/emulated/0/
RootBase"

function guard_run() {
  local current_dir=$(pwd)

  # Check if we are running raw in Home without a repo
context
  if [[ "$current_dir" == "$HOME" ]]; then
    echo -e "\n⚠️ \033[1;31m[Sentinel Block]\033[0m
Running loose scripts directly in ~ is barred."
    echo -e "💡 Redirecting execution context to
```

06/09/2026 09:17

```
Workspace Root..."
      cd "$SWARM_WORKSPACE/Syntax-AI-CLI" ll cd
"$SWARM_WORKSPACE"
   fi

   # Execute whatever command was passed
   "$@"

   # Sweep any stray json outputs or logs that escaped
into ~ down to lost_found
   find "$HOME" -maxdepth 1 -type f \( -name "*.tmp" -o
-name "*.log" -o -name "vai_output_*.json" \) -exec mv {}
"$SWARM_WORKSPACE/lost_found/" \; 2>/dev/null
}

# The clean aliases wrapped by the guard
alias ask="guard_run node ~/term-ai/ai.js"
alias python3="guard_run python3"
EOF
```

06/09/2026 09:17

==========

ButtsCorp $ cat ~/.bashrc
alias banc='cd /storage/emulated/0/RootBase/
CodeCity-Bench && bash workbench.sh'

export OPENCLAW_GATEWAY_TOKEN=HighFives26!

source ~/janebot-motherbrain/scripts/jane_cmds.sh

alias swarmlint='find . -name "__pycache__" -exec rm -rf
{} + && find . -name "*.db" -type f -delete'
alias locals='ollama serve &'
export PATH=/data/data/com.termux/files/
home/.npm-global/bin:$PATH
export NODE_OPTIONS="--max-old-space-size=2048"
--- OpenClaw Start ---
WARNING: This section contains your access token -
keep ~/.bashrc secure

06/09/2026 09:17

```
export TERMUX_VERSION=1
export TMPDIR=$HOME/tmp
export PATH=/data/data/com.termux/files/
home/.npm-global/bin:$PATH

# OpenClaw color definitions
GREEN='\033[0;32m'
BLUE='\033[0;34m'
YELLOW='\033[1;33m'
RED='\033[0;31m'
CYAN='\033[0;36m'
NC='\033[0m'

# OpenClaw service management functions
ocr() {
  echo -e "${YELLOW}Starting/restarting OpenClaw
service...${NC}"
  pkill -9 -f 'openclaw_final' 2>/dev/null
  tmux kill-session -t openclaw_final 2>/dev/null
```

06/09/2026 09:17

```
   sleep 1
   tmux new -d -s openclaw_final
   sleep 1
   tmux send-keys -t openclaw_final "export PATH=/
data/data/com.termux/files/home/.npm-global/bin:
$PATH TMPDIR=$HOME/tmp
OPENCLAW_GATEWAY_TOKEN=$OPENCLAW_GATEWA
Y_TOKEN; openclaw_final gateway --bind loopback
--port 18789 --token \$OPENCLAW_GATEWAY_TOKEN
--allow-unconfigured" C-m
   sleep 2
   if tmux has-session -t openclaw_final 2>/dev/null; then
      echo ""
      echo -e "${GREEN}✅ OpenClaw service started$
{NC}"
      echo ""
      echo -e "${CYAN}📖 Usage:${NC}"
      echo "   1. Open in phone browser::
http://localhost:18789/?token=$OPENCLAW_GATEWAY
```

```
_TOKEN"
      echo "   2. Or run command: openclaw_final tui"
      echo "   3. Or use Telegram bot (if configured)"
      echo ""
      echo -e "${BLUE}💡 oclog to view logs I ockill to stop
service${NC}"
   else
      echo -e "${RED}❌ Service failed to start, please
check logs (openclaw_final logs)${NC}"
   fi
}

oclog() {
   if tmux has-session -t openclaw_final 2>/dev/null; then
      tmux attach -t openclaw_final
   else
      echo -e "${YELLOW}⚠️ OpenClaw service not
running, use ocr to start${NC}"
   fi
```

06/09/2026 09:17

```
}

ockill() {
   echo -e "${YELLOW}Stopping OpenClaw service...${NC}"
   pkill -9 -f "openclaw_final" 2>/dev/null
   tmux kill-session -t openclaw_final 2>/dev/null
   sleep 1
   if ! tmux has-session -t openclaw_final 2>/dev/null && ! pgrep -f "openclaw_final" > /dev/null; then
      echo -e "${GREEN}✅ OpenClaw service stopped${NC}"
   else
      echo -e "${RED}❌ Failed to stop service, please check manually${NC}"
   fi
}
# --- OpenClaw End ---
eval "$(zoxide init bash)"
```

06/09/2026 09:17

```
# Navigation
alias l='bat'
alias cls='clear'

# Agent Shortcuts
alias swarm='openclaw_final gateway start'
alias agent='aider --model gemini/gemini-1.5-flash' # Uses free tier
alias dev='tmux new-session -A -s BabyDickMike'

export PATH=$PATH:/storage/emulated/0/RootBase/codex_install/node_modules/.bin
eval "$(zoxide init bash)"
export PATH=$PATH:/storage/emulated/0/RootBase/bin
alias start_swarm='source /storage/emulated/0/RootBase/bin/start_swarm_tmux.sh'
```

==========

06/09/2026 09:17

=====

ATTN GEMINI CLI: Last version listed is the oldest version of my ~/.bashrc in termux android, and it long predates gemini fucking with everything... the other two are supposed to be "the same" according to gemini and contain shit i now need i guess to run my Syntax AI CLI tool and other gemini surprises... idk. What i have now is tucked tho and thanks to gemini needs fixed, please... Cheers!