

The package `piton`*

F. Pantigny
fpantigny@wanadoo.fr

March 1, 2023

Abstract

The package `piton` provides tools to typeset Python listings with syntactic highlighting by using the Lua library LPEG. It requires LuaLaTeX.

1 Presentation

The package `piton` uses the Lua library LPEG¹ for parsing Python listings and typeset them with syntactic highlighting. Since it uses Lua code, it works with `lualatex` only (and won't work with the other engines: `latex`, `pdflatex` and `xelatex`). It does not use external program and the compilation does not require `--shell-escape`. The compilation is very fast since all the parsing is done by the library LPEG, written in C.

Here is an example of code typeset by `piton`, with the environment `{Piton}`.

```
from math import pi

def arctan(x,n=10):
    """Compute the mathematical value of arctan(x)

    n is the number of terms in the sum
    """
    if x < 0:
        return -arctan(-x) # recursive call
    elif x > 1:
        return pi/2 - arctan(1/x)
        (we have used that  $\arctan(x) + \arctan(1/x) = \frac{\pi}{2}$  for  $x > 0$ )2
    else:
        s = 0
        for k in range(n):
            s += (-1)**k/(2*k+1)*x**(2*k+1)
        return s
```

The package `piton` is entirely contained in the file `piton.sty`. This file may be put in the current directory or in a `texmf` tree. However, the best is to install `piton` with a TeX distribution such as MiKTeX, TeX Live or MacTeX.

*This document corresponds to the version 1.4 of `piton`, at the date of 2023/02/14.

¹LPEG is a pattern-matching library for Lua, written in C, based on *parsing expression grammars*: <http://www.inf.puc-rio.br/~roberto/lpeg/>

²This LaTeX escape has been done by beginning the comment by `#>`.

2 Use of the package

2.1 Loading the package

The package `piton` should be loaded with the classical command `\usepackage{piton}`. Nevertheless, we have two remarks:

- the package `piton` uses the package `xcolor` (but `piton` does *not* load `xcolor`: if `xcolor` is not loaded before the `\begin{document}`, a fatal error will be raised).
- the package `piton` must be used with LuaLaTeX exclusively: if another LaTeX engine (`latex`, `pdflatex`, `xelatex`,...) is used, a fatal error will be raised.

2.2 The tools provided to the user

The package `piton` provides several tools to typeset Python code: the command `\piton`, the environment `{Piton}` and the command `\PitonInputFile`.

- The command `\piton` should be used to typeset small pieces of code inside a paragraph. For example:

```
\piton{def square(x): return x*x}    def square(x): return x*x
```

The syntax and particularities of the command `\piton` are detailed below.

- The environment `{Piton}` should be used to typeset multi-lines code. Since it takes its argument in a verbatim mode, it can't be used within the argument of a LaTeX command. For sake of customization, it's possible to define new environments similar to the environment `{Piton}` with the command `\NewPitonEnvironment`: cf. 3.3 p. 6.
- The command `\PitonInputFile` is used to insert and typeset a whole external file.

That command takes in as optional argument (between square brackets) two keys `first-line` and `last-line`: only the part between the corresponding lines will be inserted.

2.3 The syntax of the command `\piton`

In fact, the command `\piton` is provided with a double syntax. It may be used as a standard command of LaTeX taking its argument between curly braces (`\piton{...}`) but it may also be used with a syntax similar to the syntax of the command `\verb`, that is to say with the argument delimited by two identical characters (e.g.: `\piton|...|`).

- **Syntax `\piton{...}`**

When its argument is given between curly braces, the command `\piton` does not take its argument in verbatim mode. In particular:

- several consecutive spaces will be replaced by only one space,
but the command `_` is provided to force the insertion of a space;
- it's not possible to use `%` inside the argument,
but the command `\%` is provided to insert a %;
- the braces must be appear by pairs correctly nested
but the commands `\{` and `\}` are also provided for individual braces;
- the LaTeX commands³ are fully expanded and not executed,
so it's possible to use `\\` to insert a backslash.

³That concerns the commands beginning with a backslash but also the active characters.

The other characters (including #, ^, _, &, \$ and @) must be inserted without backslash.

Examples :

<code>\piton{MyString = '\n'}</code>	<code>MyString = '\n'</code>
<code>\piton{def even(n): return n%2==0}</code>	<code>def even(n): return n%2==0</code>
<code>\piton{c="#" # an affectation }</code>	<code>c="#" # an affectation</code>
<code>\piton{c="#" \ \ \ # an affectation }</code>	<code>c="#" # an affectation</code>
<code>\piton{MyDict = {'a': 3, 'b': 4 }}</code>	<code>MyDict = {'a': 3, 'b': 4}</code>

It's possible to use the command `\piton` in the arguments of a LaTeX command.⁴

- **Syntaxe `\piton|...|`**

When the argument of the command `\piton` is provided between two identical characters, that argument is taken in a *verbatim mode*. Therefore, with that syntax, the command `\piton` can't be used within the argument of another command.

Examples :

<code>\piton MyString = '\n' </code>	<code>MyString = '\n'</code>
<code>\piton!def even(n): return n%2==0!</code>	<code>def even(n): return n%2==0</code>
<code>\piton+c="#" # an affectation +</code>	<code>c="#" # an affectation</code>
<code>\piton?MyDict = {'a': 3, 'b': 4}?</code>	<code>MyDict = {'a': 3, 'b': 4}</code>

3 Customization

3.1 The command `\PitonOptions`

The command `\PitonOptions` takes in as argument a comma-separated list of *key=value* pairs. The scope of the settings done by that command is the current TeX group.⁵

- The key `gobble` takes in as value a positive integer *n*: the first *n* characters are discarded (before the process of highlightning of the code) for each line of the environment `{Piton}`. These characters are not necessarily spaces.
- When the key `auto-gobble` is in force, the extension `piton` computes the minimal value *n* of the number of consecutive spaces beginning each (non empty) line of the environment `{Piton}` and applies `gobble` with that value of *n*.
- When the key `env-gobble` is in force, `piton` analyzes the last line of the environment `{Piton}`, that is to say the line which contains `\end{Piton}` and determines whether that line contains only spaces followed by the `\end{Piton}`. If we are in that situation, `piton` computes the number *n* of spaces on that line and applies `gobble` with that value of *n*. The name of that key comes from *environment gobble*: the effect of `gobble` is set by the position of the commands `\begin{Piton}` and `\end{Piton}` which delimit the current environment.
- With the key `line-numbers`, the *non empty* lines (and all the lines of the *docstrings*, even the empty ones) are numbered in the environments `{Piton}` and in the listings resulting from the use of `\PitonInputFile`.
- With the key `all-line-numbers`, *all* the lines are numbered, including the empty ones.
- With the key `resume`, the counter of lines is not set to zero at the beginning of each environment `{Piton}` or use of `\PitonInputFile` as it is otherwise. That allows a numbering of the lines across several environments.

⁴For example, it's possible to use the command `\piton` in a footnote. Example : `s = 'A string'`.

⁵We remind that a LaTeX environment is, in particular, a TeX group.

- The key `left-margin` corresponds to a margin on the left. That key may be useful in conjunction with the key `line-numbers` or the key `line-all-numbers` if one does not want the numbers in an overlapping position on the left.

It's possible to use the key `left-margin` with the value `auto`. With that value, if the key `line-numbers` or the key `all-line-numbers` is used, a margin will be automatically inserted to fit the numbers of lines. See an example part ?? on page ??.

- The key `background-color` sets the background color of the environments `{Piton}` and the listings produced by `\PitonInputFile` (that background has a width of `\linewidth`).

New 1.4 The key `background-color` supports also as value a *list* of colors. In this case, the successive rows are colored by using the colors of the list in a cyclic way.

Example : `\PitonOptions{background-color = {gray!5,white}}`

The key `background-color` accepts a color defined «on the fly». For example, it's possible to write `background-color = [cmyk]{0.1,0.05,0,0}`.

- With the key `prompt-background-color`, `piton` adds a color background to the lines beginning with the prompt “>>>” (and its continuation “...”) characteristic of the Python consoles with REPL (*read-eval-print loop*).
- When the key `show-spaces-in-strings` is activated, the spaces in the short strings (that is to say those delimited by ' or ") are replaced by the character `□` (U+2423 : OPEN BOX). Of course, that character U+2423 must be present in the monospaced font which is used.⁶

Example : `my_string = 'Very□good□answer'`

With the key `show-spaces`, all the spaces are replaced by U+2423 (and no line break can occur on those “visible spaces”, even when the key `break-lines`⁷ is in force).

```
\PitonOptions{line-numbers,auto-gobble,background-color = gray!15}
\begin{Piton}
  from math import pi
  def arctan(x,n=10):
      """Compute the mathematical value of arctan(x)

      n is the number of terms in the sum
      """
      if x < 0:
          return -arctan(-x) # recursive call
      elif x > 1:
          return pi/2 - arctan(1/x)
          #> (we have used that $\arctan(x)+\arctan(1/x)=\frac{\pi}{2}$ pour $x>0$)
      else
          s = 0
          for k in range(n):
              s += (-1)**k/(2*k+1)*x**(2*k+1)
          return s
\end{Piton}
```

⁶The package `piton` simply uses the current monospaced font. The best way to change that font is to use the command `\setmonofont` of the package `fontspec`.

⁷cf. ?? p. ??

```

1 from math import pi
2
3 def arctan(x,n=10):
4     """Compute the mathematical value of arctan(x)
5
6     n is the number of terms in the sum
7     """
8     if x < 0:
9         return -arctan(-x) # recursive call
10    elif x > 1:
11        return pi/2 - arctan(1/x)
12        (we have used that  $\arctan(x) + \arctan(1/x) = \frac{\pi}{2}$  for  $x > 0$ )
13    else
14        s = 0
15        for k in range(n):
16            s += (-1)**k/(2*k+1)*x**(2*k+1)
17    return s

```

The command `\PitonOptions` provides in fact several other keys which will be described further (see in particular the “Pages breaks and line breaks” p. ??).

3.2 The styles

The package `piton` provides the command `\SetPitonStyle` to customize the different styles used to format the syntactic elements of the Python listings. The customizations done by that command are limited to the current TeX group.⁸

The command `\SetPitonStyle` takes in as argument a comma-separated list of *key=value* pairs. The keys are names of styles and the value are LaTeX formatting instructions.

These LaTeX instructions must be formatting instructions such as `\color{...}`, `\bfseries`, `\slshape`, etc. (the commands of this kind are sometimes called *semi-global* commands). It’s also possible to put, *at the end of the list of instructions*, a LaTeX command taking exactly one argument.

Here an example which changes the style used to highlight, in the definition of a Python function, the name of the function which is defined. That code uses the command `\highLight` of `lua-ul` (that package requires also the package `luacolor`).

```
\SetPitonStyle{ Name.Function = \bfseries \highLight[red!50] }
```

In that example, `\highLight[red!50]` must be considered as the name of a LaTeX command which takes in exactly one argument, since, usually, it is used with `\highLight[red!50]{...}`.

With that setting, we will have : `def cube(x) : return x * x * x`

The different styles are described in the table ?? . The initial settings done by `piton` in `piton.sty` are inspired by the style `manni` de `Pygments`.⁹

New 1.4 The command `\PitonStyle` takes in as argument the name of a style and allows to retrieve the value (as a list of LaTeX instructions) of that style.

For example, it’s possible to write `{\PitonStyle{Keyword}{function}}` and we will have the word `function` formatted as a keyword.

The syntax `{\PitonStyle{style}{...}}` is mandatory in order to be able to deal both with the semi-global commands and the commands with arguments which may be present in the definition of the style *style*.

⁸We remind that a LaTeX environment is, in particular, a TeX group.

⁹See: <https://pygments.org/styles/>. Remark that, by default, Pygments provides for its style `manni` a colored background whose color is the HTML color `#F0F3F3`. It’s possible to have the same color in `{Pion}` with the instruction `\PitonOptions{background-color = [HTML]{F0F3F3}}`.

3.3 Creation of new environments

Since the environment `{Piton}` has to catch its body in a special way (more or less as verbatim text), it's not possible to construct new environments directly over the environment `{Piton}` with the classical commands `\newenvironment` or `\NewDocumentEnvironment`.

That's why `piton` provides a command `\NewPitonEnvironment`. That command takes in three mandatory arguments.

That command has the same syntax as the classical environment `\NewDocumentEnvironment`.

With the following instruction, a new environment `{Python}` will be constructed with the same behaviour as `{Piton}`:

```
\NewPitonEnvironment{Python}{}{}{}
```

If one wishes an environment `{Python}` with takes in as optional argument (between square brackets) the keys of the command `\PitonOptions`, it's possible to program as follows:

```
\NewPitonEnvironment{Python}{0{}}{\PitonOptions{#1}}{}
```

If one wishes to format Python code in a box of `tcolorbox`, it's possible to define an environment `{Python}` with the following code (of course, the package `tcolorbox` must be loaded).

```
\NewPitonEnvironment{Python}{}
{\begin{tcolorbox}}
{\end{tcolorbox}}
```

With this new environment `{Python}`, it's possible to write:

```
\begin{Python}
def square(x):
    """Compute the square of a number"""
    return x*x
\end{Python}
```

```
def square(x):
    """Compute the square of a number"""
    return x*x
```

4 Advanced features

4.1 Highlighting some identifiers

New 1.4 It's possible to require a changement of formatting for some identifiers with the key identifiers of `\PitonOptions`.

That key takes in as argument a value of the following format:

```
{ names = names, style = instructions }
```

- *names* is a (comma-separated) list of identifiers names;
- *instructions* is a list of LaTeX instructions of the same type that `piton` “styles” previously presented (cf 3.2 p. 5).

Caution: Only the identifiers may be concerned by that key. The keywords and the built-in functions won't be affected, even if their name is in the list `\textsl{\ttfamily names}`.

```

\PytonOptions
{
  identifiers =
  {
    names = { l1 , l2 } ,
    style = \color{red}
  }
}

\begin{Pyton}
def tri(l):
    """Segmentation sort"""
    if len(l) <= 1:
        return l
    else:
        a = l[0]
        l1 = [ x for x in l[1:] if x < a ]
        l2 = [ x for x in l[1:] if x >= a ]
        return tri(l1) + [a] + tri(l2)
\end{Pyton}

```

```

def tri(l):
    """Segmentation sort"""
    if len(l) <= 1:
        return l
    else:
        a = l[0]
        l1 = [ x for x in l[1:] if x < a ]
        l2 = [ x for x in l[1:] if x >= a ]
        return tri(l1) + [a] + tri(l2)

```

By using the key `identifier`, it's possible to add other built-in functions (or other new keywords, etc.) that will be detected by `pyton`.

```

\PytonOptions
{
  identifiers =
  {
    names = { cos, sin, tan, floor, ceil, trunc, pow, exp, ln, factorial } ,
    style = \PytonStyle{Name.Builtin}
  }
}

\begin{Pyton}
from math import *
cos(pi/2)
factorial(5)
ceil(-2.3)
floor(5.4)
\end{Pyton}

from math import *
cos(pi/2)
factorial(5)
ceil(-2.3)
floor(5.4)

```

4.2 Mechanisms to escape to LaTeX

The package `piton` provides several mechanisms for escaping to LaTeX:

- It's possible to compose comments entirely in LaTeX.
- It's possible to have the elements between `$` in the comments composed in LaTeX mathematical mode.
- It's also possible to insert LaTeX code almost everywhere in a Python listing.

One should also remark that, when the extension `piton` is used with the class `beamer`, `piton` detects in `{Piton}` many commands and environments of Beamer: cf. ?? p. ??.

4.2.1 The “LaTeX comments”

In this document, we call “LaTeX comments” the comments which begins by `#>`. The code following those characters, until the end of the line, will be composed as standard LaTeX code. There is two tools to customize those comments.

- It's possible to change the syntatic mark (which, by default, is `#>`). For this purpose, there is a key `comment-latex` available at load-time (that is to say at the `\usepackage`) which allows to choice the characters which, preceded by `#`, will be the syntatic marker.

For example, with the following loading:

```
\usepackage[comment-latex = LaTeX]{piton}
```

the LaTeX comments will begin by `#LaTeX`.

If the key `comment-latex` is used with the empty value, all the Python comments (which begins by `#`) will, in fact, be “LaTeX comments”.

- It's possible to change the formatting of the LaTeX comment itself by changing the `piton` style `Comment.LaTeX`.

For example, with `\SetPitonStyle{Comment.LaTeX = \normalfont\color{blue}}`, the LaTeX comments will be composed in blue.

If you want to have a character `#` at the beginning of the LaTeX comment in the PDF, you can use `set Comment.LaTeX` as follows:

```
\SetPitonStyle{Comment.LaTeX = \color{gray}\#\normalfont\space }
```

For other examples of customization of the LaTeX comments, see the part ?? p. ??

If the user has required line numbers in the left margin (with the key `line-numbers` or the key `all-line-numbers` of `\PitonOptions`), it's possible to refer to a number of line with the command `\label` used in a LaTeX comment.¹⁰

4.2.2 The key “math-comments”

It's possible to request that, in the standard Python comments (that is to say those beginning by `#` and not `#>`), the elements between `$` be composed in LaTeX mathematical mode (the other elements of the comment being composed verbatim).

That feature is activated by the key `math-comments` at load-time (that is to say with the `\usepackage`).

In the following example, we assume that the key `math-comments` has been used when loading `piton`.

¹⁰That feature is implemented by using a redefinition of the standard command `\label` in the environments `{Piton}`. Therefore, incompatibilities may occur with extensions which redefine (globally) that command `\label` (for example: `varioref`, `refcheck`, `showlabels`, etc.)


```
\begin{Piton}
def square(x):
    return x*x # compute  $x^2$ 
\end{Piton}
```

```
def square(x):
    return x*x # compute  $x^2$ 
```

4.2.3 The mechanism “escape-inside”

It’s also possible to overwrite the Python listings to insert LaTeX code almost everywhere (but between lexical units, of course). By default, `piton` does not fix any character for that kind of escape. In order to use this mechanism, it’s necessary to specify two characters which will delimit the escape (one for the beginning and one for the end) by using the key `escape-inside` at load-time (that is to say at the `\begin{documnt}`).

In the following example, we assume that the extension `piton` has been loaded by the following instruction.

```
\usepackage[escape-inside=$$]{piton}
```

In the following code, which is a recursive programming of the mathematical factorial, we decide to highlight in yellow the instruction which contains the recursive call. That example uses the command `\highLight` of `lua-ul` (that package requires itself the package `luacolor`).

```
\begin{Piton}
def fact(n):
    if n==0:
        return 1
    else:
         $\highLight{\$return n*fact(n-1)\$}$ 
\end{Piton}

def fact(n):
    if n==0:
        return 1
    else:
        return n*fact(n-1)
```

In fact, in that case, it’s probably easier to use the command `\@highLight` of `lua-ul`: that command sets a yellow background until the end of the current TeX group. Since the name of that command contains the character `@`, it’s necessary to define a synonym without `@` in order to be able to use it directly in `{Piton}`.

```
\makeatletter
\let\Yellow\@highLight
\makeatother

\begin{Piton}
def fact(n):
    if n==0:
        return 1
    else:
         $\Yellow\$return n*fact(n-1)$ 
\end{Piton}

def fact(n):
    if n==0:
        return 1
    else:
        return n*fact(n-1)
```

Caution : The escape to LaTeX allowed by the characters of `escape-inside` is not active in the strings nor in the Python comments (however, it's possible to have a whole Python comment composed in LaTeX by beginning it with `#>`; such comments are merely called “LaTeX comments” in this document).

4.3 Behaviour in the class Beamer

When the package `piton` is used within the class `beamer`¹¹, the behaviour of `piton` is slightly modified, as described now.

4.3.1 `{Piton}` et `\PitonInputFile` are “overlay-aware”

When `piton` is used in the class `beamer`, the environment `{Piton}` and the command `\PitonInputFile` accept the optional argument `<...>` of Beamer for the overlays which are involved.

For example, it's possible to write:

```
\begin{Piton}<2-5>
```

```
...
```

```
\end{Piton}
```

and

```
\PitonInputFile<2-5>\{my_file.py}
```

4.3.2 Commands of Beamer allowed in `{Piton}` and `\PitonInputFile`

When `piton` is used in the class `beamer`, the following commands of `beamer` (classified upon their number of arguments) are automatically detected in the environments `{Piton}` (and in the listings processed by `\PitonInputFile`):

- no mandatory argument : `\pause`¹² ;
- one mandatory argument : `\action`, `\alert`, `\invisible`, `\only`, `\uncover` and `\visible` ;
- two mandatory arguments : `\alt` ;
- three mandatory arguments : `\temporal`.

However, there is two restrictions for the content of the mandatory arguments of these commands.

- In the mandatory arguments of these commands, the braces must be balanced. However, the braces includes in short strings¹³ of Python are not considered.
- There must be **no carriage return** in the mandatory arguments of the command (if there is, a fatal error will be raised). For multi-lines elements, one should consider the corresponding environments (see below).

Remark that, since the environment `{Piton}` catches its body with a verbatim mode, it's necessary to use the environments `{Piton}` within environments `{frame}` of Beamer protected by the key `fragile`.¹⁴

Here is a complete example of file:

¹¹The extension `piton` detects the class `beamer` but, if needed, it's also possible to activate that mechanism with the key `beamer` provided by `piton` at load-time: `\usepackage[beamer]{piton}`

¹²One should remark that it's also possible to use the command `\pause` in a “LaTeX comment”, that is to say by writing `#> \pause`. By this way, if the Python code is copied, it's still executable by Python

¹³The short strings of Python are the strings delimited by characters `'` or the characters `"` and not `'''` nor `"""`. In Python, the short strings can't extend on several lines.

¹⁴Remind that for an environment `{frame}` of Beamer using the key `fragile`, the instruction `\end{frame}` must be alone on a single line (except for any leading whitespace).

```

\documentclass{beamer}
\usepackage{piton}
\begin{document}
\begin{frame}[fragile]
\begin{Piton}
def string_of_list(l):
    """Convert a list of numbers in string"""
    \only<2->{s = "{" + str(l[0])}
    \only<3->{for x in l[1:]: s = s + "," + str(x)}
    \only<4->{s = s + "}"}
    return s
\end{Piton}
\end{frame}
\end{document}

```

In the previous example, the braces in the Python strings "{" and "}" are correctly interpreted (without any escape character).

4.3.3 Environments of Beamer allowed in {Piton} and \PitonInputFile

When `piton` is used in the class `beamer`, the following environments of Beamer are directly detected in the environments `{Piton}` (and in the listings processed by `\PitonInputFile`): `{actionenv}`, `{alertenv}`, `{invisibleenv}`, `{onlyenv}`, `{uncoverenv}` and `{visibleenv}`.

However, there is a restriction: these environments must contain only *whole lines of Python code* in their body.

Here is an example:

```

\documentclass{beamer}
\usepackage{piton}
\begin{document}
\begin{frame}[fragile]
\begin{Piton}
def square(x):
    """Compute the square of its argument"""
    \begin{uncoverenv}<2>
    return x*x
    \end{uncoverenv}
\end{Piton}
\end{frame}
\end{document}

```

Remark concerning the command `\alert` and the environment `{alertenv}` of Beamer

Beamer provides an easy way to change the color used by the environment `{alertenv}` (and by the command `\alert` which relies upon it) to highlight its argument. Here is an example:

```

\setbeamercolor{alerted text}{fg=blue}

```

However, when used inside an environment `{Piton}`, such tuning will probably not be the best choice because `piton` will, by design, change (most of the time) the color the different elements of text. One may prefer an environment `{alertenv}` that will change the background color for the elements to be highlighted.

Here is a code that will do that job and add a yellow background. That code uses the command `\@highLight` of `lua-ul` (that extension requires also the package `luacolor`).

```

\setbeamercolor{alerted text}{bg=yellow!50}
\makeatletter
\AddToHook{env/Piton/begin}
{
\renewenvironment<>{alertenv}{\only#1{\@highLight[alerted text.bg]}}{}}
\makeatother

```

That code redefines locally the environment `{alertenv}` within the environments `{Piton}` (we recall that the command `\alert` relies upon that environment `{alertenv}`).

4.4 Page breaks and line breaks

4.4.1 Page breaks

By default, the listings produced by the environment `{Piton}` and the command `\PitonInputFile` are not breakable.

However, the command `\PitonOptions` provides the key `splittable` to allow such breaks.

- If the key `splittable` is used without any value, the listings are breakable everywhere.
- If the key `splittable` is used with a numeric value n (which must be a non-negative integer number), the listings are breakable but no break will occur within the first n lines and within the last n lines. Therefore, `splittable=1` is equivalent to `splittable`.

Even with a background color (set by the key `background-color`), the pages breaks are allowed, as soon as the key `splittable` is in force.¹⁵

4.4.2 Line breaks

By default, the elements produced by `piton` can't be broken by an end on line. However, there are keys to allow such breaks (the possible breaking points are the spaces, even the spaces in the Python strings).

- With the key `break-lines-in-piton`, the line breaks are allowed in the command `\piton{...}` (but not in the command `\piton|...|`, that is to say the command `\piton` in verbatim mode).
- With the key `break-lines-in-Piton`, the line breaks are allowed in the environment `{Piton}` (hence the capital letter P in the name) and in the listings produced by `\PitonInputFile`.
- The key `break-lines` is a conjunction of the two previous keys.

The package `piton` provides also several keys to control the appearance on the line breaks allowed by `break-lines-in-Piton`.

- With the key `indent-broken-lines`, the indentation of a broken line is respected at carriage return.
- The key `end-of-broken-line` corresponds to the symbol placed at the end of a broken line. The initial value is: `\hspace*{0.5em}\textbackslash`.
- The key `continuation-symbol` corresponds to the symbol placed at each carriage return. The initial value is: `+\;`.
- The key `continuation-symbol-on-indentation` corresponds to the symbol placed at each carriage return, on the position of the indentation (only when the key `indent-broken-line` is in force). The initial value is: `$_hookrightarrow\;`.

The following code has been composed in a standard LaTeX `{minipage}` of width 12 cm with the following tuning:

```
\PitonOptions{break-lines,indent-broken-lines,background-color=gray!15}
```

¹⁵With the key `splittable`, the environments `{Piton}` are breakable, even within a (breakable) environment of `tcolorbox`. Remind that an environment of `tcolorbox` included in another environment of `tcolorbox` is *not* breakable, even when both environments use the key `breakable` of `tcolorbox`.

```

def dict_of_list(l):
    """Converts a list of subrs and descriptions of glyphs in \
    ↪ a dictionary"""
    our_dict = {}
    for list_letter in l:
        if (list_letter[0][0:3] == 'dup'): # if it's a subr
            name = list_letter[0][4:-3]
            print("We treat the subr of number " + name)
        else:
            name = list_letter[0][1:-3] # if it's a glyph
            print("We treat the glyph of number " + name)
        our_dict[name] = [treat_Postscript_line(k) for k in \
        ↪ list_letter[1:-1]]
    return dict

```

4.5 Footnotes in the environments of piton

If you want to put footnotes in an environment `{Piton}` or (or, more unlikely, in a listing produced by `\PitonInputFile`), you can use a pair `\footnotemark`–`\footnotetext`.

However, it's also possible to extract the footnotes with the help of the package `footnote` or the package `footnotehyper`.

If `piton` is loaded with the option `footnote` (with `\usepackage[footnote]{piton}` or with `\PassOptionsToPackage`), the package `footnote` is loaded (if it is not yet loaded) and it is used to extract the footnotes.

If `piton` is loaded with the option `footnotehyper`, the package `footnotehyper` is loaded (if it is not yet loaded) and it is used to extract footnotes.

Caution: The packages `footnote` and `footnotehyper` are incompatible. The package `footnotehyper` is the successor of the package `footnote` and should be used preferently. The package `footnote` has some drawbacks, in particular: it must be loaded after the package `xcolor` and it is not perfectly compatible with `hyperref`.

In this document, the package `piton` has been loaded with the option `footnotehyper`. For examples of notes, cf. ??, p. ??.

4.6 Tabulations

Even though it's recommended to indent the Python listings with spaces (see PEP 8), `piton` accepts the characters of tabulation (that is to say the characters U+0009) at the beginning of the lines. Each character U+0009 is replaced by n spaces. The initial value of n is 4 but it's possible to change it with the key `tab-size` of `\PitonOptions`.

There exists also a key `tabs-auto-gobble` which computes the minimal value n of the number of consecutive characters U+0009 beginning each (non empty) line of the environment `{Piton}` and applies `gobble` with that value of n (before replacement of the tabulations by spaces, of course). Hence, that key is similar to the key `auto-gobble` but acts on U+0009 instead of U+0020 (spaces).

5 Examples

5.1 Line numbering

We remind that it's possible to have an automatic numbering of the lines in the Python listings by using the key `line-numbers` or the key `all-line-numbers`.

By default, the numbers of the lines are composed by `piton` in an overlapping position on the left (by using internally the command `\llap` of LaTeX).

In order to avoid that overlapping, it's possible to use the option `left-margin=auto` which will insert automatically a margin adapted to the numbers of lines that will be written (that margin is larger when the numbers are greater than 10).

```

\PytonOptions{background-color=gray!10, left-margin = auto, line-numbers}
\begin{Pyton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)          #> (appel récursif)
    elif x > 1:
        return pi/2 - arctan(1/x) #> (autre appel récursif)
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )
\end{Pyton}

```

```

1 def arctan(x,n=10):
2     if x < 0:
3         return -arctan(-x)          (appel récursif)
4     elif x > 1:
5         return pi/2 - arctan(1/x) (autre appel récursif)
6     else:
7         return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )

```

5.2 Formatting of the LaTeX comments

It's possible to modify the style `Comment.LaTeX` (with `\SetPytonStyle`) in order to display the LaTeX comments (which begin with `#>`) aligned on the right margin.

```

\PytonOptions{background-color=gray!10}
\SetPytonStyle{Comment.LaTeX = \hfill \normalfont\color{gray}}
\begin{Pyton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)          #> appel récursif
    elif x > 1:
        return pi/2 - arctan(1/x) #> autre appel récursif
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )
\end{Pyton}

```

```

def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)          appel récursif
    elif x > 1:
        return pi/2 - arctan(1/x)   autre appel récursif
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )

```

It's also possible to display these LaTeX comments in a kind of second column by limiting the width of the Python code by an environment `{minipage}` of LaTeX.

```

\PytonOptions{background-color=gray!10}
\NewDocumentCommand{\MyLaTeXCommand}{m}{\hfill \normalfont\itshape\rlap{\quad #1}}
\SetPytonStyle{Comment.LaTeX = \MyLaTeXCommand}
\begin{minipage}{12cm}
\begin{Pyton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)          #> appel récursif
    elif x > 1:
        return pi/2 - arctan(1/x) #> autre appel récursif
    else:
        s = 0
        for k in range(n):

```

```

        s += (-1)**k/(2*k+1)*x**(2*k+1)
    return s
\end{Piton}
\end{minipage}

```

```

def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)
    elif x > 1:
        return pi/2 - arctan(1/x)
    else:
        s = 0
        for k in range(n):
            s += (-1)**k/(2*k+1)*x**(2*k+1)
        return s

```

appel récursif

autre appel récursif

5.3 Notes in the listings

In order to be able to extract the notes (which are typeset with the command `\footnote`), the extension `piton` must be loaded with the key `footnote` or the key `footnotehyper` as explained in the section ?? p. ??. In this document, the extension `piton` has been loaded with the key `footnotehyper`. Of course, in an environment `{Piton}`, a command `\footnote` may appear only within a LaTeX comment (which begins with `#>`). It's possible to have comments which contain only that command `\footnote`. That's the case in the following example.

```

\PitonOptions{background-color=gray!10}
\begin{Piton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)#>\footnote{First recursive call.}
    elif x > 1:
        return pi/2 - arctan(1/x)#>\footnote{Second recursive call.}
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )
\end{Piton}

```

```

def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)16
    elif x > 1:
        return pi/2 - arctan(1/x)17
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )

```

If an environment `{Piton}` is used in an environment `{minipage}` of LaTeX, the notes are composed, of course, at the foot of the environment `{minipage}`. Recall that such `{minipage}` can't be broken by a page break.

```

\PitonOptions{background-color=gray!10}
\emphase\begin{minipage}{\linewidth}
\begin{Piton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)#>\footnote{First recursive call.}
    elif x > 1:

```

¹⁶First recursive call.

¹⁷Second recursive call.

```

        return pi/2 - arctan(1/x)#>\footnote{Second recursive call.}
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )
\end{Piton}
\end{minipage}

```

```

def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)a
    elif x > 1:
        return pi/2 - arctan(1/x)b
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )

```

^aFirst recursive call.

^bSecond recursive call.

If we embed an environment `{Piton}` in an environment `{minipage}` (typically in order to limit the width of a colored background), it's necessary to embed the whole environment `{minipage}` in an environment `{savenotes}` (of `footnote` or `footnotehyper`) in order to have the footnotes composed at the bottom of the page.

```

\PitonOptions{background-color=gray!10}
\begin{savenotes}
\begin{minipage}{13cm}
\begin{Piton}
def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)#>\footnote{First recursive call.}
    elif x > 1:
        return pi/2 - arctan(1/x)#>\footnote{Second recursive call.}
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )
\end{Piton}
\end{minipage}
\end{savenotes}

```

```

def arctan(x,n=10):
    if x < 0:
        return -arctan(-x)18
    elif x > 1:
        return pi/2 - arctan(1/x)19
    else:
        return sum( (-1)**k/(2*k+1)*x**(2*k+1) for k in range(n) )

```

5.4 An example of tuning of the styles

The graphical styles have been presented in the section 3.2, p. 5.

We present now an example of tuning of these styles adapted to the documents in black and white. We use the font *Deja Vu Sans Mono*²⁰ specified by the command `\setmonofont` of `fontspec`.

That tuning uses the command `\highLight` of `lua-ul` (that package requires itself the package `luacolor`).

```

\setmonofont[Scale=0.85]{DejaVu Sans Mono}

```

¹⁸First recursive call.

¹⁹Second recursive call.

²⁰See: <https://dejavu-fonts.github.io>


```

\SetPitonStyle
{
  Number = ,
  String = \itshape ,
  String.Doc = \color{gray} \slshape ,
  Operator = ,
  Operator.Word = \bfseries ,
  Name.Builtin = ,
  Name.Function = \bfseries \highLight[gray!20] ,
  Comment = \color{gray} ,
  Comment.LaTeX = \normalfont \color{gray},
  Keyword = \bfseries ,
  Name.Namespace = ,
  Name.Class = ,
  Name.Type = ,
  InitialValues = \color{gray}
}

```

```

from math import pi

```

```

def arctan(x,n=10):
    """Compute the mathematical value of arctan(x)

    n is the number of terms in the sum
    """
    if x < 0:
        return -arctan(-x) # appel récursif
    elif x > 1:
        return pi/2 - arctan(1/x)
        (we have used that arctan(x) + arctan(1/x) = π/2 for x > 0)
    else:
        s = 0
        for k in range(n):
            s += (-1)**k/(2*k+1)*x**(2*k+1)
        return s

```

5.5 Use with pyluatex

The package `pyluatex` is an extension which allows the execution of some Python code from `lualatex` (provided that Python is installed on the machine and that the compilation is done with `lualatex` and `--shell-escape`).

Here is, for example, an environment `{PitonExecute}` which formats a Python listing (with `piton`) but display also the output of the execution of the code with Python (for technical reasons, the `!` is mandatory in the signature of the environment).

```

\ExplSyntaxOn
\NewDocumentEnvironment { PitonExecute } { ! O { } } % the ! is mandatory
{
  \PyLTVerbatimEnv
  \begin{pythonq}
}
{
  \end{pythonq}
  \directlua
  {
    tex.print("\PitonOptions{#1}")
    tex.print("\begin{Piton}")
    tex.print(pyluatex.get_last_code())
  }
}
\ExplSyntaxOff

```

```

        tex.print("\\end{Piton}")
        tex.print("")
    }
    \\begin{center}
        \\directlua{tex.print(pyluatex.get_last_output())}
    \\end{center}
}
\\ExplSyntaxOff

```

This environment `{PitonExecute}` takes in as optional argument (between square brackets) the options of the command `\\PitonOptions`.

Table 1: Usage of the different styles

Style	Usage
<code>Number</code>	the numbers
<code>String.Short</code>	the short strings (between ' or ")
<code>String.Long</code>	the long strings (between ''' or """) except the documentation strings
<code>String</code>	that keys sets both <code>String.Short</code> and <code>String.Long</code>
<code>String.Doc</code>	the documentation strings (only between """ following PEP 257)
<code>String.Interpol</code>	the syntactic elements of the fields of the f-strings (that is to say the characters { and })
<code>Operator</code>	the following operators : <code>!= == << >> - ~ + / * % = < > & . @</code>
<code>Operator.Word</code>	the following operators : <code>in, is, and, or</code> and <code>not</code>
<code>Name.Builtin</code>	the predefined functions of Python
<code>Name.Function</code>	the name of the functions defined by the user, at the point of their definition (that is to say after the keyword <code>def</code>)
<code>Name.Decorator</code>	the decorators (instructions beginning by <code>@</code>)
<code>Name.Namespace</code>	the name of the modules (= external libraries)
<code>Name.Class</code>	the name of the classes at the point of their definition (that is to say after the keyword <code>class</code>)
<code>Exception</code>	the names of the exceptions (eg: <code>SyntaxError</code>)
<code>Comment</code>	the comments beginning with <code>#</code>
<code>Comment.LaTeX</code>	the comments beginning by <code>#></code> , which are composed in LaTeX by <code>piton</code> (and simply called “LaTeX comments” in this document)
<code>Keyword.Constant</code>	<code>True, False</code> and <code>None</code>
<code>Keyword</code>	the following keywords : <code>as, assert, break, case, continue, def, del, elif, else, except, exec, finally, for, from, global, if, import, lambda, non local, pass, raise, return, try, while, with, yield, yield from.</code>

6 Implementation

6.1 Introduction

The main job of the package `piton` is to take in as input a Python listing and to send back to LaTeX as output that code *with interlaced LaTeX instructions of formatting*.

In fact, all that job is done by a LPEG called `python`. That LPEG, when matched against the string of a Python listing, returns as capture a Lua table containing data to send to LaTeX. The only thing to do after will be to apply `tex.tprint` to each element of that table.²¹

Consider, for example, the following Python code:

```
def parity(x):  
    return x%2
```

The capture returned by the lpeg `python` against that code is the Lua table containing the following elements :

```
{ "\\_piton_begin_line:" }a  
{ "{\\PitonStyle{Keyword}{ " } }b  
{ luatexbase.catcodetables.CatcodeTableOtherc, "def" }  
{ "}}" }  
{ luatexbase.catcodetables.CatcodeTableOther, " " }  
{ "{\\PitonStyle{Name.Function}{ " }  
{ luatexbase.catcodetables.CatcodeTableOther, "parity" }  
{ "}}" }  
{ luatexbase.catcodetables.CatcodeTableOther, "(" }  
{ luatexbase.catcodetables.CatcodeTableOther, "x" }  
{ luatexbase.catcodetables.CatcodeTableOther, ")" }  
{ luatexbase.catcodetables.CatcodeTableOther, ":" }  
{ "\\_piton_end_line: \\_piton_newline: \\_piton_begin_line:" }  
{ luatexbase.catcodetables.CatcodeTableOther, " " }  
{ "{\\PitonStyle{Keyword}{ " }  
{ luatexbase.catcodetables.CatcodeTableOther, "return" }  
{ "}}" }  
{ luatexbase.catcodetables.CatcodeTableOther, " " }  
{ luatexbase.catcodetables.CatcodeTableOther, "x" }  
{ "{\\PitonStyle{Operator}{ " }  
{ luatexbase.catcodetables.CatcodeTableOther, "&" }  
{ "}}" }  
{ "{\\PitonStyle{Number}{ " }  
{ luatexbase.catcodetables.CatcodeTableOther, "2" }  
{ "}}" }  
{ "\\_piton_end_line:" }
```

^aEach line of the Python listings will be encapsulated in a pair: `_begin_line: - _end_line:`. The token `_end_line:` must be explicit because it will be used as marker in order to delimit the argument of the command `_begin_line:`. Both tokens `_begin_line:` and `_end_line:` will be nullified in the command `\\piton` (since there can't be lines breaks in the argument of a command `\\piton`).

^bThe lexical elements of Python for which we have a `piton` style will be formatted via the use of the command `\\PitonStyle`. Such an element is typeset in LaTeX via the syntax `{\\PitonStyle{style}{...}}` because the instructions inside an `\\PitonStyle` may be both semi-global declarations like `\\bfseries` and commands with one argument like `\\fbox`.

^c`luatexbase.catcodetables.CatcodeTableOther` is a mere number which corresponds to the “catcode table” whose all characters have the catcode “other” (which means that they will be typeset by LaTeX verbatim).

We give now the LaTeX code which is sent back by Lua to TeX (we have written on several lines for legibility but no character `\\r` will be sent to LaTeX). The characters which are greyed-out are sent to LaTeX with the catcode “other” (=12). All the others characters are sent with the regime of catcodes of L3 (as set by `\\ExplSyntaxOn`)

²¹Recall that `tex.tprint` takes in as argument a Lua table whose first component is a “catcode table” and the second element a string. The string will be sent to LaTeX with the regime of catcodes specified by the catcode table. If no catcode table is provided, the standard catcodes of LaTeX will be used.

```

\__piton_begin_line:{\PitonStyle{Keyword}{def}}
\__piton_end_line:\__piton_newline:
\__piton_begin_line:{\PitonStyle{Keyword}{return}}
\__piton_end_line:

```

6.2 The L3 part of the implementation

6.2.1 Declaration of the package

```

1 \NeedsTeXFormat{LaTeX2e}
2 \RequirePackage{l3keys2e}
3 \ProvidesExplPackage
4   {piton}
5   {\myfiledate}
6   {\myfileversion}
7   {Highlight Python codes with LPEG on LuaLaTeX}

8 \msg_new:nnn { piton } { LuaLaTeX-mandatory }
9   {
10     LuaLaTeX-is~mandatory.\\
11     The~package~'piton'~requires~the~engine~LuaLaTeX.\\
12     \str_if_eq:VnT \c_sys_jobname_str { output }
13       { If~you~use~Overleaf,~you~can~switch~to~LuaLaTeX~in~the~"Menu". }
14     If~you~go~on,~the~package~'piton'~won't~be~loaded.
15   }
16 \sys_if_engine luatex:F { \msg_critical:nn { piton } { LuaLaTeX-mandatory } }

17 \RequirePackage { luatexbase }

```

The boolean `\c_@@_footnotehyper_bool` will indicate if the option `footnotehyper` is used.

```
18 \bool_new:N \c_@@_footnotehyper_bool
```

The boolean `\c_@@_footnote_bool` will indicate if the option `footnote` is used, but quickly, it will also be set to true if the option `footnotehyper` is used.

```
19 \bool_new:N \c_@@_footnote_bool
```

The following boolean corresponds to the key `math-comments` (only at load-time).

```
20 \bool_new:N \c_@@_math_comments_bool
```

The following boolean corresponds to the key `beamer`.

```
21 \bool_new:N \c_@@_beamer_bool
```

We define a set of keys for the options at load-time.

```

22 \keys_define:nn { piton / package }
23   {
24     footnote .bool_set:N = \c_@@_footnote_bool ,
25     footnotehyper .bool_set:N = \c_@@_footnotehyper_bool ,
26     escape-inside .tl_set:N = \c_@@_escape_inside_tl ,
27     escape-inside .initial:n = ,
28     comment-latex .code:n = { \lua_now:n { comment_latex = "#1" } } ,
29     comment-latex .value_required:n = true ,
30     math-comments .bool_set:N = \c_@@_math_comments_bool ,
31     math-comments .default:n = true ,
32     beamer .bool_set:N = \c_@@_beamer_bool ,
33     beamer .default:n = true ,
34     unknown .code:n = \msg_error:nn { piton } { unknown-key-for-package }
35   }
36 \msg_new:nnn { piton } { unknown-key-for-package }
37   {
38     Unknown~key.\\
39     You~have~used~the~key~'\l_keys_key_str'~but~the~only~keys~available~here~

```

```

40     are~'beamer',~'comment-latex',~'escape-inside',~'footnote',~'footnotehyper'~and~
41     'math-comments'.~Other~keys~are~available~in~\token_to_str:N \PitonOptions.\\
42     That~key~will~be~ignored.
43 }

```

We process the options provided by the user at load-time.

```

44 \ProcessKeysOptions { piton / package }

45 \beginingroup
46 \cs_new_protected:Npn \@@_set_escape_char:nn #1 #2
47 {
48     \lua_now:n { piton_begin_escape = "#1" }
49     \lua_now:n { piton_end_escape = "#2" }
50 }
51 \cs_generate_variant:Nn \@@_set_escape_char:nn { x x }
52 \@@_set_escape_char:xx
53 { \tl_head:V \c_@@_escape_inside_tl }
54 { \tl_tail:V \c_@@_escape_inside_tl }
55 \endgroup

56 \ifclassloaded { beamer } { \bool_set_true:N \c_@@_beamer_bool } { }
57 \bool_if:NT \c_@@_beamer_bool { \lua_now:n { piton_beamer = true } }

58 \hook_gput_code:nnn { begindocument } { . }
59 {
60     \ifpackageloaded { xcolor }
61     { }
62     { \msg_fatal:nn { piton } { xcolor~not~loaded } }
63 }

64 \msg_new:nnn { piton } { xcolor~not~loaded }
65 {
66     xcolor~not~loaded \\
67     The~package~'xcolor'~is~required~by~'piton'.\\
68     This~error~is~fatal.
69 }

70 \msg_new:nnn { piton } { footnote~with~footnotehyper~package }
71 {
72     Footnote~forbidden.\\
73     You~can't~use~the~option~'footnote'~because~the~package~
74     footnotehyper~has~already~been~loaded.~
75     If~you~want,~you~can~use~the~option~'footnotehyper'~and~the~footnotes~
76     within~the~environments~of~piton~will~be~extracted~with~the~tools~
77     of~the~package~footnotehyper.\\
78     If~you~go~on,~the~package~footnote~won't~be~loaded.
79 }

80 \msg_new:nnn { piton } { footnotehyper~with~footnote~package }
81 {
82     You~can't~use~the~option~'footnotehyper'~because~the~package~
83     footnote~has~already~been~loaded.~
84     If~you~want,~you~can~use~the~option~'footnote'~and~the~footnotes~
85     within~the~environments~of~piton~will~be~extracted~with~the~tools~
86     of~the~package~footnote.\\
87     If~you~go~on,~the~package~footnotehyper~won't~be~loaded.
88 }

89 \bool_if:NT \c_@@_footnote_bool
90 {

```

The class beamer has its own system to extract footnotes and that's why we have nothing to do if beamer is used.

```

91     \ifclassloaded { beamer }

```

```

92     { \bool_set_false:N \c_@@_footnote_bool }
93     {
94         \@ifpackageloaded { footnotehyper }
95         { \@@_error:n { footnote~with~footnotehyper~package } }
96         { \usepackage { footnote } }
97     }
98 }
99 \bool_if:NT \c_@@_footnotehyper_bool
100 {

```

The class `beamer` has its own system to extract footnotes and that's why we have nothing to do if `beamer` is used.

```

101     \@ifclassloaded { beamer }
102     { \bool_set_false:N \c_@@_footnote_bool }
103     {
104         \@ifpackageloaded { footnote }
105         { \@@_error:n { footnotehyper~with~footnote~package } }
106         { \usepackage { footnotehyper } }
107         \bool_set_true:N \c_@@_footnote_bool
108     }
109 }

```

The flag `\c_@@_footnote_bool` is raised and so, we will only have to test `\c_@@_footnote_bool` in order to know if we have to insert an environment `{savenotes}`.

6.2.2 Parameters and technical definitions

The following string will contain the name of the informatic language considered (the initial value is `python`).

```

110 \str_new:N \l_@@_language_str
111 \str_set:Nn \l_@@_language_str { python }

```

We will compute (with Lua) the numbers of lines of the Python code and store it in the following counter.

```

112 \int_new:N \l_@@_nb_lines_int

```

The same for the number of non-empty lines of the Python codes.

```

113 \int_new:N \l_@@_nb_non_empty_lines_int

```

The following counter will be used to count the lines during the composition. It will count all the lines, empty or not empty. It won't be used to print the numbers of the lines.

```

114 \int_new:N \g_@@_line_int

```

The following token list will contains the (potential) informations to write on the `aux` (to be used in the next compilation).

```

115 \tl_new:N \g_@@_aux_tl

```

The following counter corresponds to the key `splittable` of `\PitonOptions`. If the value of `\l_@@_splittable_int` is equal to n , then no line break can occur within the first n lines or the last n lines of the listings.

```

116 \int_new:N \l_@@_splittable_int

```

An initial value of `splittable` equal to 100 is equivalent to say that the environments `{Piton}` are unbreakable.

```

117 \int_set:Nn \l_@@_splittable_int { 100 }

```

The following string corresponds to the key `background-color` of `\PitonOptions`.

```

118 \clist_new:N \l_@@_bg_color_clist

```

The package `piton` will also detect the lines of code which correspond to the user input in a Python console, that is to say the lines of code beginning with `>>>` and `....`. It's possible, with the key `prompt-background-color`, to require a background for these lines of code (and the other lines of code will have the standard background color specified by `background-color`).

```

119 \tl_new:N \l_@@_prompt_bg_color_tl

```

We will compute the maximal width of the lines of an environment `{Piton}` in `\g_@@_width_dim`. We need a global variable because, when the key `footnote` is in force, each line when be composed in an environment `{savenotes}` and (when `slim` is in force) we need to exit `\g_@@_width_dim` from that environment.

```
120 \dim_new:N \g_@@_width_dim
```

The value of that dimension as written on the `aux` file will be stored in `\l_@@_width_on_aux_dim`.

```
121 \dim_new:N \l_@@_width_on_aux_dim
```

We will count the environments `{Piton}` (and, in fact, also the commands `\PitonInputFile`, despite the name `\g_@@_env_int`).

```
122 \int_new:N \g_@@_env_int
```

The following boolean corresponds to the key `show-spaces`.

```
123 \bool_new:N \l_@@_show_spaces_bool
```

The following booleans correspond to the keys `break-lines` and `indent-broken-lines`.

```
124 \bool_new:N \l_@@_break_lines_in_Piton_bool
```

```
125 \bool_new:N \l_@@_indent_broken_lines_bool
```

The following token list corresponds to the key `continuation-symbol`.

```
126 \tl_new:N \l_@@_continuation_symbol_tl
```

```
127 \tl_set:Nn \l_@@_continuation_symbol_tl { + }
```

```
128 % The following token list corresponds to the key
```

```
129 % |continuation-symbol-on-indentation|. The name has been shorten to |csoi|.
```

```
130 \tl_new:N \l_@@_csoi_tl
```

```
131 \tl_set:Nn \l_@@_csoi_tl { $ \hookrightarrow ; $ }
```

The following token list corresponds to the key `end-of-broken-line`.

```
132 \tl_new:N \l_@@_end_of_broken_line_tl
```

```
133 \tl_set:Nn \l_@@_end_of_broken_line_tl { \hspace*{0.5em} \textbackslash }
```

The following boolean corresponds to the key `break-lines-in-piton`.

```
134 \bool_new:N \l_@@_break_lines_in_piton_bool
```

The following boolean corresponds to the key `slim` of `\PitonOptions`.

```
135 \bool_new:N \l_@@_slim_bool
```

The following dimension corresponds to the key `left-margin` of `\PitonOptions`.

```
136 \dim_new:N \l_@@_left_margin_dim
```

The following boolean correspond will be set when the key `left-margin=auto` is used.

```
137 \bool_new:N \l_@@_left_margin_auto_bool
```

The tabulators will be replaced by the content of the following token list.

```
138 \tl_new:N \l_@@_tab_tl
```

```
139 \cs_new_protected:Npn \@@_set_tab_tl:n #1
```

```
140 {
```

```
141   \tl_clear:N \l_@@_tab_tl
```

```
142   \prg_replicate:nn { #1 }
```

```
143     { \tl_put_right:Nn \l_@@_tab_tl { ~ } }
```

```
144 }
```

```
145 \@@_set_tab_tl:n { 4 }
```

The following integer corresponds to the key `gobble`.

```
146 \int_new:N \l_@@_gobble_int
```

```
147 \tl_new:N \l_@@_space_tl
```

```
148 \tl_set:Nn \l_@@_space_tl { ~ }
```


At each line, the following counter will count the spaces at the beginning.

```

149 \int_new:N \g_@@_indentation_int

150 \cs_new_protected:Npn \@@_an_indentation_space:
151 { \int_gincr:N \g_@@_indentation_int }

```

The following command `\@@_beamer_command:n` executes the argument corresponding to its argument but also stores it in `\l_@@_beamer_command_str`. That string is used only in the error message “cr~not~allowed” raised when there is a carriage return in the mandatory argument of that command.

```

152 \cs_new_protected:Npn \@@_beamer_command:n #1
153 {
154   \str_set:Nn \l_@@_beamer_command_str { #1 }
155   \use:c { #1 }
156 }

```

In the environment `{Piton}`, the command `\label` will be linked to the following command.

```

157 \cs_new_protected:Npn \@@_label:n #1
158 {
159   \bool_if:NTF \l_@@_line_numbers_bool
160   {
161     \@bsphack
162     \protected@write \@auxout { }
163     {
164       \string \newlabel { #1 }
165       {

```

Remember that the content of a line is typeset in a box *before* the composition of the potential number of line.

```

166         { \int_eval:n { \g_@@_visual_line_int + 1 } }
167         { \thepage }
168       }
169     }
170     \@esphack
171   }
172   { \msg_error:nn { piton } { label~with~lines~numbers } }
173 }

```

The following commands are a easy way to insert safely braces (`{` and `}`) in the TeX flow.

```

174 \cs_new_protected:Npn \@@_open_brace:
175 { \directlua { piton.open_brace() } }
176 \cs_new_protected:Npn \@@_close_brace:
177 { \directlua { piton.close_brace() } }

```

The following token list will be evaluated at the beginning of `\@@_begin_line:... \@@_end_line:` and cleared at the end. It will be used by LPEG acting between the lines of the Python code in order to add instructions to be executed at the beginning of the line.

```

178 \tl_new:N \g_@@_begin_line_hook_tl

```

For example, the LPEG Prompt will trigger the following command which will insert an instruction in the hook `\g_@@_begin_line_hook` to specify that a background must be inserted to the current line of code.

```

179 \cs_new_protected:Npn \@@_prompt:
180 {
181   \tl_gset:Nn \g_@@_begin_line_hook_tl
182   { \clist_set:NV \l_@@_bg_color_clist \l_@@_prompt_bg_color_tl }
183 }

```

You will keep track of the current style for the treatment of EOL (for the multi-line syntactic elements).

```
184 \clist_new:N \g_@@_current_style_clist
185 \clist_set:Nn \g_@@_current_style_clist { __end }
```

The element `__end` is an arbitrary syntactic marker.

```
186 \cs_new_protected:Npn \@@_close_current_styles:
187 {
188   \int_set:Nn \l_tmpa_int { \clist_count:N \g_@@_current_style_clist - 1 }
189   \exp_args:NV \@@_close_n_styles:n \l_tmpa_int
190 }

191 \cs_new_protected:Npn \@@_close_n_styles:n #1
192 {
193   \int_compare:nNnT { #1 } > 0
194   {
195     \@@_close_brace:
196     \@@_close_brace:
197     \@@_close_n_styles:n { #1 - 1 }
198   }
199 }

200 \cs_new_protected:Npn \@@_open_current_styles:
201 { \exp_last_unbraced:NV \@@_open_styles:w \g_@@_current_style_clist , }

202 \cs_new_protected:Npn \@@_open_styles:w #1 ,
203 {
204   \tl_if_eq:nnF { #1 } { __end }
205   { \@@_open_brace: #1 \@@_open_brace: \@@_open_styles:w }
206 }

207 \cs_new_protected:Npn \@@_pop_style:
208 {
209   \clist_greverse:N \g_@@_current_style_clist
210   \clist_gpop:NN \g_@@_current_style_clist \l_tmpa_tl
211   \clist_gpop:NN \g_@@_current_style_clist \l_tmpa_tl
212   \clist_gpush:Nn \g_@@_current_style_clist { __end }
213   \clist_greverse:N \g_@@_current_style_clist
214 }

215 \cs_new_protected:Npn \@@_push_style:n #1
216 {
217   \clist_greverse:N \g_@@_current_style_clist
218   \clist_gpop:NN \g_@@_current_style_clist \l_tmpa_tl
219   \clist_gpush:Nn \g_@@_current_style_clist { #1 }
220   \clist_gpush:Nn \g_@@_current_style_clist { __end }
221   \clist_greverse:N \g_@@_current_style_clist
222 }

223 \cs_new_protected:Npn \@@_push_and_exec:n #1
224 {
225   \@@_push_style:n { #1 }
226   \@@_open_brace: #1 \@@_open_brace:
227 }
```

6.2.3 Treatment of a line of code

```
228 \cs_new_protected:Npn \@@_replace_spaces:n #1
229 {
230   \tl_set:Nn \l_tmpa_tl { #1 }
231   \bool_if:NTF \l_@@_show_spaces_bool
232   { \regex_replace_all:nnN { \x20 } { \_ } \l_tmpa_tl } % U+2423
233   {
```

If the key `break-lines-in-Piton` is in force, we replace all the characters U+0020 (that is to say the spaces) by `\@@_breakable_space:`. Remark that, except the spaces inserted in the LaTeX comments (and maybe in the math comments), all these spaces are of catcode “other” (=12) and are unbreakable.

```

234     \bool_if:NT \l_@@_break_lines_in_Piton_bool
235     {
236         \regex_replace_all:nnN
237         { \x20 }
238         { \c { @@_breakable_space: } }
239         \l_tmpa_tl
240     }
241 }
242 \l_tmpa_tl
243 }
244 \cs_generate_variant:Nn \@@_replace_spaces:n { x }

```

In the contents provided by Lua, each line of the Python code will be surrounded by `\@@_begin_line:` and `\@@_end_line:`. `\@@_begin_line:` is a LaTeX that we will define now but `\@@_end_line:` is only a syntactic marker that has no definition.

```

245 \cs_set_protected:Npn \@@_begin_line: #1 \@@_end_line:
246 {
247     \group_begin:
248     \g_@@_begin_line_hook_tl
249     \int_gzero:N \g_@@_indentation_int

```

Be careful: there is curryfication in the following lines.

```

250     \bool_if:NTF \l_@@_slim_bool
251     { \hcoffin_set:Nn \l_tmpa_coffin }
252     {
253         \clist_if_empty:NTF \l_@@_bg_color_clist
254         {
255             \vcoffin_set:Nnn \l_tmpa_coffin
256             { \dim_eval:n { \linewidth - \l_@@_left_margin_dim } }
257         }
258         {
259             \vcoffin_set:Nnn \l_tmpa_coffin
260             { \dim_eval:n { \linewidth - \l_@@_left_margin_dim - 0.5 em } }
261         }
262     }
263     {
264         \language = -1
265         \raggedright
266         \strut
267         \@@_replace_spaces:n { #1 }
268         \strut \hfil
269     }
270     \hbox_set:Nn \l_tmpa_box
271     {
272         \skip_horizontal:N \l_@@_left_margin_dim
273         \bool_if:NT \l_@@_line_numbers_bool
274         {
275             \bool_if:NF \l_@@_all_line_numbers_bool
276             { \tl_if_empty:nF { #1 } }
277             \@@_print_number:
278         }
279         \clist_if_empty:NF \l_@@_bg_color_clist
280         { \skip_horizontal:n { 0.5 em } }
281         \coffin_typeset:Nnnnn \l_tmpa_coffin T l \c_zero_dim \c_zero_dim
282     }

```

We compute in `\g_@@_width_dim` the maximal width of the lines of the environment.

```

283     \dim_compare:nNnT { \box_wd:N \l_tmpa_box } > \g_@@_width_dim
284     { \dim_gset:Nn \g_@@_width_dim { \box_wd:N \l_tmpa_box } }
285     \box_set_dp:Nn \l_tmpa_box { \box_dp:N \l_tmpa_box + 1.25 pt }

```

```

286 \box_set_ht:Nn \l_tmpa_box { \box_ht:N \l_tmpa_box + 1.25 pt }
287 \clist_if_empty:NTF \l_@@_bg_color_clist
288   { \box_use_drop:N \l_tmpa_box }
289   {
290     \vbox_top:n
291     {
292       \hbox:n
293       {
294         \@@_color:N \l_@@_bg_color_clist
295         \vrule height \box_ht:N \l_tmpa_box
296           depth \box_dp:N \l_tmpa_box
297           width \l_@@_width_on_aux_dim
298       }
299       \skip_vertical:n { - \box_ht_plus_dp:N \l_tmpa_box }
300       \box_set_wd:Nn \l_tmpa_box \l_@@_width_on_aux_dim
301       \box_use_drop:N \l_tmpa_box
302     }
303   }
304 \vspace { - 2.5 pt }
305 \group_end:
306 \tl_gclear:N \g_@@_begin_line_hook_tl
307 }

```

The command `\@@_color:N` will take in as argument a reference to a comma-separated list of colors. A color will be picked by using the value of `\g_@@_line_int` (modulo the number of colors in the list).

```

308 \cs_set_protected:Npn \@@_color:N #1
309 {
310   \int_set:Nn \l_tmpa_int { \clist_count:N #1 }
311   \int_set:Nn \l_tmpb_int { \int_mod:nn \g_@@_line_int \l_tmpa_int + 1 }
312   \tl_set:Nx \l_tmpa_tl { \clist_item:Nn #1 \l_tmpb_int }
313   \tl_if_eq:NnTF \l_tmpa_tl { none }

```

By setting `\l_@@_width_on_aux_dim` to zero, the colored rectangle will be drawn with zero width and, thus, it will be a mere strut (and we need that strut).

```

314   { \dim_zero:N \l_@@_width_on_aux_dim }
315   { \exp_args:NV \@@_color_i:n \l_tmpa_tl }
316 }

```

The following command `\@@_color:n` will accept both the instruction `\@@_color:n { red!15 }` and the instruction `\@@_color:n { [rgb]{0.9,0.9,0} }`.

```

317 \cs_set_protected:Npn \@@_color_i:n #1
318 {
319   \tl_if_head_eq_meaning:nNTF { #1 } [
320     {
321       \tl_set:Nn \l_tmpa_tl { #1 }
322       \tl_set_rescan:Nno \l_tmpa_tl { } \l_tmpa_tl
323       \exp_last_unbraced:NV \color \l_tmpa_tl
324     }
325     { \color { #1 } }
326   }
327 \cs_generate_variant:Nn \@@_color:n { V }

328 \cs_new_protected:Npn \@@_newline:
329 {
330   \int_gincr:N \g_@@_line_int
331   \int_compare:nNnT \g_@@_line_int > { \l_@@_splittable_int - 1 }
332   {
333     \int_compare:nNnT
334       { \l_@@_nb_lines_int - \g_@@_line_int } > \l_@@_splittable_int
335     {
336       \egroup
337       \bool_if:NT \c_@@_footnote_bool { \end { savenotes } }
338       \newline

```

```

339         \bool_if:NT \c_@@_footnote_bool { \begin { savenotes } }
340         \vtop \bgroup
341     }
342 }
343 }

344 \cs_set_protected:Npn \@@_breakable_space:
345 {
346     \discretionary
347     { \hbox:n { \color { gray } \l_@@_end_of_broken_line_tl } }
348     {
349         \hbox_overlap_left:n
350         {
351             {
352                 \normalfont \footnotesize \color { gray }
353                 \l_@@_continuation_symbol_tl
354             }
355             \skip_horizontal:n { 0.3 em }
356             \clist_if_empty:NF \l_@@_bg_color_clist
357             { \skip_horizontal:n { 0.5 em } }
358         }
359         \bool_if:NT \l_@@_indent_broken_lines_bool
360         {
361             \hbox:n
362             {
363                 \prg_replicate:nn { \g_@@_indentation_int } { ~ }
364                 { \color { gray } \l_@@_csoi_tl }
365             }
366         }
367     }
368     { \hbox { ~ } }
369 }

```

6.2.4 PitonOptions

The following parameters correspond to the keys `line-numbers` and `all-line-numbers`.

```

370 \bool_new:N \l_@@_line_numbers_bool
371 \bool_new:N \l_@@_all_line_numbers_bool

```

The following flag corresponds to the key `resume`.

```

372 \bool_new:N \l_@@_resume_bool

```

Be careful! The name of the following set of keys must be considered as public! Hence, it should *not* be changed.

```

373 \keys_define:nn { PitonOptions }
374 {
375     language      .str_set:N          = \l_@@_language_str ,
376     language      .value_required:n   = true ,
377     gobble         .int_set:N          = \l_@@_gobble_int ,
378     gobble         .value_required:n   = true ,
379     auto-gobble    .code:n             = \int_set:Nn \l_@@_gobble_int { -1 } ,
380     auto-gobble    .value_forbidden:n  = true ,
381     env-gobble     .code:n             = \int_set:Nn \l_@@_gobble_int { -2 } ,
382     env-gobble     .value_forbidden:n  = true ,
383     tabs-auto-gobble .code:n           = \int_set:Nn \l_@@_gobble_int { -3 } ,
384     tabs-auto-gobble .value_forbidden:n = true ,
385     line-numbers    .bool_set:N         = \l_@@_line_numbers_bool ,
386     line-numbers    .default:n         = true ,
387     all-line-numbers .code:n           =
388         \bool_set_true:N \l_@@_line_numbers_bool
389         \bool_set_true:N \l_@@_all_line_numbers_bool ,

```

```

390 all-line-numbers .value_forbidden:n = true ,
391 resume          .bool_set:N        = \l_@@_resume_bool ,
392 resume          .value_forbidden:n = true ,
393 splittable       .int_set:N         = \l_@@_splittable_int ,
394 splittable       .default:n         = 1 ,
395 background-color .clist_set:N       = \l_@@_bg_color_clist ,
396 background-color .value_required:n = true ,
397 prompt-background-color .tl_set:N   = \l_@@_prompt_bg_color_tl ,
398 prompt-background-color .value_required:n = true ,
399 slim             .bool_set:N        = \l_@@_slim_bool ,
400 slim             .default:n         = true ,
401 left-margin      .code:n =
402   \str_if_eq:nnTF { #1 } { auto }
403   {
404     \dim_zero:N \l_@@_left_margin_dim
405     \bool_set_true:N \l_@@_left_margin_auto_bool
406   }
407   { \dim_set:Nn \l_@@_left_margin_dim { #1 } } ,
408 left-margin      .value_required:n = true ,
409 tab-size         .code:n            = \@@_set_tab_tl:n { #1 } ,
410 tab-size         .value_required:n = true ,
411 show-spaces      .bool_set:N        = \l_@@_show_spaces_bool ,
412 show-spaces      .default:n         = true ,
413 show-spaces-in-strings .code:n      = \tl_set:Nn \l_@@_space_tl { \_ } , % U+2423
414 show-spaces-in-strings .value_forbidden:n = true ,
415 break-lines-in-Piton .bool_set:N    = \l_@@_break_lines_in_Piton_bool ,
416 break-lines-in-Piton .default:n     = true ,
417 break-lines-in-piton .bool_set:N    = \l_@@_break_lines_in_piton_bool ,
418 break-lines-in-piton .default:n     = true ,
419 break-lines .meta:n = { break-lines-in-piton , break-lines-in-Piton } ,
420 break-lines .value_forbidden:n      = true ,
421 indent-broken-lines .bool_set:N     = \l_@@_indent_broken_lines_bool ,
422 indent-broken-lines .default:n      = true ,
423 end-of-broken-line .tl_set:N        = \l_@@_end_of_broken_line_tl ,
424 end-of-broken-line .value_required:n = true ,
425 continuation-symbol .tl_set:N      = \l_@@_continuation_symbol_tl ,
426 continuation-symbol .value_required:n = true ,
427 continuation-symbol-on-indentation .tl_set:N = \l_@@_csoi_tl ,
428 continuation-symbol-on-indentation .value_required:n = true ,
429 unknown          .code:n =
430   \msg_error:nn { piton } { Unknown~key~for~PitonOptions }
431 }

```

The argument of \PitonOptions is provided by curryfication.

```

432 \NewDocumentCommand \PitonOptions { } { \keys_set:nn { PitonOptions } }

```

6.2.5 The numbers of the lines

The following counter will be used to count the lines in the code when the user requires the numbers of the lines to be printed (with line-numbers or all-line-numbers).

```

433 \int_new:N \g_@@_visual_line_int
434 \cs_new_protected:Npn \@@_print_number:
435 {
436   \int_gincr:N \g_@@_visual_line_int
437   \hbox_overlap_left:n
438   {
439     { \color { gray } \footnotesize \int_to_arabic:n \g_@@_visual_line_int }
440     \skip_horizontal:n { 0.4 em }
441   }
442 }

```

6.2.6 The command to write on the aux file

```

443 \cs_new_protected:Npn \@@_write_aux:
444 {
445   \tl_if_empty:NF \g_@@_aux_tl
446   {
447     \iow_now:Nn \@mainaux { \ExplSyntaxOn }
448     \iow_now:Nx \@mainaux
449     {
450       \tl_gset:cn { c_@@_ \int_use:N \g_@@_env_int _ tl }
451       { \exp_not:V \g_@@_aux_tl }
452     }
453     \iow_now:Nn \@mainaux { \ExplSyntaxOff }
454   }
455   \tl_gclear:N \g_@@_aux_tl
456 }
457 \cs_new_protected:Npn \@@_width_to_aux:
458 {
459   \bool_if:NT \l_@@_slim_bool
460   {
461     \clist_if_empty:NF \l_@@_bg_color_clist
462     {
463       \tl_gput_right:Nx \g_@@_aux_tl
464       {
465         \dim_set:Nn \l_@@_width_on_aux_dim
466         { \dim_eval:n { \g_@@_width_dim + 0.5 em } }
467       }
468     }
469   }
470 }

```

6.2.7 The main commands and environments for the final user

```

471 \NewDocumentCommand { \piton } { } { }
472 { \peek_meaning:NTF \bgroup \@@_piton_standard \@@_piton_verbatim }
473 \NewDocumentCommand { \@@_piton_standard } { m }
474 {
475   \group_begin:
476   \ttfamily

```

The following tuning of LuaTeX in order to avoid all break of lines on the hyphens.

```

477 \automatichyphenmode = 1
478 \cs_set_eq:NN \ \c_backslash_str
479 \cs_set_eq:NN \% \c_percent_str
480 \cs_set_eq:NN \{ \c_left_brace_str
481 \cs_set_eq:NN \} \c_right_brace_str
482 \cs_set_eq:NN \$ \c_dollar_str
483 \cs_set_eq:cn { ~ } \space
484 \cs_set_protected:Npn \@@_begin_line: { }
485 \cs_set_protected:Npn \@@_end_line: { }
486 \tl_set:Nx \l_tmpa_tl
487 {
488   \lua_now:e
489   { piton.ParseBis('\l_@@_language_str',token.scan_string()) }
490   { #1 }
491 }
492 \bool_if:NTF \l_@@_show_spaces_bool
493 { \regex_replace_all:nnN { \x20 } { \_ } \l_tmpa_tl } % U+2423

```

The following code replaces the characters U+0020 (spaces) by characters U+0020 of catcode 10: thus, they become breakable by an end of line.

```

494 {
495   \bool_if:NT \l_@@_break_lines_in_piton_bool

```

```

496         { \regex_replace_all:nnN { \x20 } { \x20 } \l_tmpa_tl }
497     }
498     \l_tmpa_tl
499     \group_end:
500 }
501 \NewDocumentCommand { \@@_piton_verbatim } { v }
502 {
503     \group_begin:
504     \ttfamily
505     \automatichyphenmode = 1
506     \cs_set_protected:Npn \@@_begin_line: { }
507     \cs_set_protected:Npn \@@_end_line: { }
508     \tl_set:Nx \l_tmpa_tl
509     {
510         \lua_now:e
511         { piton.Parse('\l_@@_language_str',token.scan_string()) }
512         { #1 }
513     }
514     \bool_if:NT \l_@@_show_spaces_bool
515     { \regex_replace_all:nnN { \x20 } { \_ } \l_tmpa_tl } % U+2423
516     \l_tmpa_tl
517     \group_end:
518 }

```

The following command is not a user command. It will be used when we will have to “rescan” some chunks of Python code. For example, it will be the initial value of the Piton style `InitialValues` (the default values of the arguments of a Python function).

```

519 \cs_new_protected:Npn \@@_piton:n #1
520 {
521     \group_begin:
522     \cs_set_protected:Npn \@@_begin_line: { }
523     \cs_set_protected:Npn \@@_end_line: { }
524     \bool_lazy_or:nnTF
525     \l_@@_break_lines_in_piton_bool
526     \l_@@_break_lines_in_Piton_bool
527     {
528         \tl_set:Nx \l_tmpa_tl
529         {
530             \lua_now:e
531             { piton.ParseTer('\l_@@_language_str',token.scan_string()) }
532             { #1 }
533         }
534     }
535     {
536         \tl_set:Nx \l_tmpa_tl
537         {
538             \lua_now:e
539             { piton.Parse('\l_@@_language_str',token.scan_string()) }
540             { #1 }
541         }
542     }
543     \bool_if:NT \l_@@_show_spaces_bool
544     { \regex_replace_all:nnN { \x20 } { \_ } \l_tmpa_tl } % U+2423
545     \l_tmpa_tl
546     \group_end:
547 }

```

The following command is similar to the previous one but raise a fatal error if its argument contains a carriage return.

```

548 \cs_new_protected:Npn \@@_piton_no_cr:n #1
549 {

```



```

550 \group_begin:
551 \cs_set_protected:Npn \@@_begin_line: { }
552 \cs_set_protected:Npn \@@_end_line: { }
553 \cs_set_protected:Npn \@@_newline:
554 { \msg_fatal:nn { piton } { cr-not-allowed } }
555 \bool_lazy_or:nnTF
556 \l_@@_break_lines_in_piton_bool
557 \l_@@_break_lines_in_Piton_bool
558 {
559 \tl_set:Nx \l_tmpa_tl
560 {
561 \lua_now:e
562 { piton.ParseTer('\l_@@_language_str',token.scan_string()) }
563 { #1 }
564 }
565 }
566 {
567 \tl_set:Nx \l_tmpa_tl
568 {
569 \lua_now:e
570 { piton.Parse('\l_@@_language_str',token.scan_string()) }
571 { #1 }
572 }
573 }
574 \bool_if:NT \l_@@_show_spaces_bool
575 { \regex_replace_all:nnN { \x20 } { \_ } \l_tmpa_tl } % U+2423
576 \l_tmpa_tl
577 \group_end:
578 }

```

Despite its name, \@@_pre_env: will be used both in \PitonInputFile and in the environments such as {Piton}.

```

579 \cs_new:Npn \@@_pre_env:
580 {
581 \automatichyphenmode = 1
582 \int_gincr:N \g_@@_env_int
583 \tl_gclear:N \g_@@_aux_tl
584 \cs_if_exist_use:c { c_@@_ _ \int_use:N \g_@@_env_int _ tl }
585 \dim_compare:nNnT \l_@@_width_on_aux_dim = \c_zero_dim
586 { \dim_set_eq:NN \l_@@_width_on_aux_dim \linewidth }
587 \bool_if:NF \l_@@_resume_bool { \int_gzero:N \g_@@_visual_line_int }
588 \dim_gzero:N \g_@@_width_dim
589 \int_gzero:N \g_@@_line_int
590 \dim_zero:N \parindent
591 \dim_zero:N \lineskip
592 \dim_zero:N \parindent
593 \cs_set_eq:NN \label \@@_label:n
594 }

595 \keys_define:nn { PitonInputFile }
596 {
597 first-line .int_set:N = \l_@@_first_line_int ,
598 first-line .value_required:n = true ,
599 last-line .int_set:N = \l_@@_last_line_int ,
600 last-line .value_required:n = true ,
601 }

602 \NewDocumentCommand { \PitonInputFile } { d < > 0 { } m }
603 {
604 \tl_if_novalue:nF { #1 }
605 {
606 \bool_if:NTF \c_@@_beamer_bool

```

```

607     { \begin { uncoverenv } < #1 > }
608     { \msg_error:nn { piton } { overlay~without~beamer } }
609 }
610 \group_begin:
611   \int_zero_new:N \l_@@_first_line_int
612   \int_zero_new:N \l_@@_last_line_int
613   \int_set_eq:NN \l_@@_last_line_int \c_max_int
614   \keys_set:nn { PitonInputFile } { #2 }
615   \@@_pre_env:
616   \mode_if_vertical:TF \mode_leave_vertical: \newline

```

We count with Lua the number of lines of the argument. The result will be stored by Lua in `\l_@@_nb_lines_int`. That information will be used to allow or disallow page breaks.

```

617   \lua_now:n { piton.CountLinesFile(token.scan_argument()) } { #3 }

```

If the final user has used both `left-margin=auto` and `line-numbers` or `all-line-numbers`, we have to compute the width of the maximal number of lines at the end of the composition of the listing to fix the correct value to `left-margin`.

```

618   \bool_lazy_and:nnT \l_@@_left_margin_auto_bool \l_@@_line_numbers_bool
619   {
620     \hbox_set:Nn \l_tmpa_box
621     {
622       \footnotesize
623       \bool_if:NTF \l_@@_all_line_numbers_bool
624       {
625         \int_to_arabic:n
626         { \g_@@_visual_line_int + \l_@@_nb_lines_int }
627       }
628       {
629         \lua_now:n
630         { piton.CountNonEmptyLinesFile(token.scan_argument()) }
631         { #3 }
632         \int_to_arabic:n
633         { \g_@@_visual_line_int + \l_@@_nb_non_empty_lines_int }
634       }
635     }
636     \dim_set:Nn \l_@@_left_margin_dim { \box_wd:N \l_tmpa_box + 0.5em }
637   }

```

Now, the main job.

```

638   \ttfamily
639   \bool_if:NT \c_@@_footnote_bool { \begin { savenotes } }
640   \vtop \bgroup
641   \lua_now:e
642   {
643     piton.ParseFile('\l_@@_language_str',token.scan_argument() ,
644     \int_use:N \l_@@_first_line_int ,
645     \int_use:N \l_@@_last_line_int )
646   }
647   { #3 }
648   \egroup
649   \bool_if:NT \c_@@_footnote_bool { \end { savenotes } }
650   \@@_width_to_aux:
651 \group_end:
652 \tl_if_novalue:nF { #1 }
653   { \bool_if:NT \c_@@_beamer_bool { \end { uncoverenv } } }
654 \@@_write_aux:
655 }

```

```

656 \NewDocumentCommand { \NewPitonEnvironment } { m m m m }
657 {

```

We construct a TeX macro which will catch as argument all the tokens until `\end{name_env}` with, in that `\end{name_env}`, the catcodes of `\`, `{` and `}` equal to 12 (“other”). The latter explains why the definition of that function is a bit complicated.

```

658 \use:x
659 {
660   \cs_set_protected:Npn
661     \use:c { _@@_collect_ #1 :w }
662     #####1
663     \c_backslash_str end \c_left_brace_str #1 \c_right_brace_str
664 }
665 {
666   \group_end:
667   \mode_if_vertical:TF \mode_leave_vertical: \newline

```

We count with Lua the number of lines of the argument. The result will be stored by Lua in `\l_@@_nb_lines_int`. That information will be used to allow or disallow page breaks.

```

668   \lua_now:n { piton.CountLines(token.scan_argument()) } { ##1 }

```

If the final user has used both `left-margin=auto` and `line-numbers`, we have to compute the width of the maximal number of lines at the end of the environment to fix the correct value to `left-margin`.

```

669   \bool_lazy_and:nnT \l_@@_left_margin_auto_bool \l_@@_line_numbers_bool
670   {
671     \bool_if:NTF \l_@@_all_line_numbers_bool
672     {
673       \hbox_set:Nn \l_tmpa_box
674       {
675         \footnotesize
676         \int_to_arabic:n
677           { \g_@@_visual_line_int + \l_@@_nb_lines_int }
678       }
679     }
680     {
681       \lua_now:n
682       { piton.CountNonEmptyLines(token.scan_argument()) }
683       { ##1 }
684       \hbox_set:Nn \l_tmpa_box
685       {
686         \footnotesize
687         \int_to_arabic:n
688           { \g_@@_visual_line_int + \l_@@_nb_non_empty_lines_int }
689       }
690     }
691     \dim_set:Nn \l_@@_left_margin_dim
692     { \box_wd:N \l_tmpa_box + 0.5 em }
693   }

```

Now, the main job.

```

694   \ttfamily
695   \bool_if:NT \c_@@_footnote_bool { \begin { savenotes } }
696   \vtop \bgroup
697   \lua_now:e
698   {
699     piton.GobbleParse
700     (
701       '\l_@@_language_str' ,
702       \int_use:N \l_@@_gobble_int ,
703       token.scan_argument()
704     )
705   }
706   { ##1 }
707   \vspace { 2.5 pt }
708   \egroup
709   \bool_if:NT \c_@@_footnote_bool { \end { savenotes } }
710   \@@_width_to_aux:

```

The following `\end{##1}` is only for the groups and the stack of environments of LaTeX.

```

711   \end { #1 }
712   \@@_write_aux:
713 }

```

We can now define the new environment.

We are still in the definition of the command `\NewPitonEnvironment...`

```

714 \NewDocumentEnvironment { #1 } { #2 }
715 {
716     #3
717     \@@_pre_env:
718     \group_begin:
719     \tl_map_function:nN
720     { \ \ \ \{ \} \$ \% \# \^ \_ \% \~ \^^I }
721     \char_set_catcode_other:N
722     \use:c { _@@_collect_ #1 :w }
723 }
724 { #4 }

```

The following code is for technical reasons. We want to change the catcode of `^^M` before catching the arguments of the new environment we are defining. Indeed, if not, we will have problems if there is a final optional argument in our environment (if that final argument is not used by the user in an instance of the environment, a spurious space is inserted, probably because the `^^M` is converted to space).

```

725 \AddToHook { env / #1 / begin } { \char_set_catcode_other:N \^^M }
726 }

```

This is the end of the definition of the command `\NewPitonEnvironment`.

Now, we define the environment `{Piton}`, which is the main environment provided by the package `piton`. Of course, you use `\NewPitonEnvironment`.

```

727 \bool_if:NTF \c_@@_beamer_bool
728 {
729     \NewPitonEnvironment { Piton } { d < > }
730     {
731         \IfValueTF { #1 }
732         { \begin { uncoverenv } < #1 > }
733         { \begin { uncoverenv } }
734     }
735     { \end { uncoverenv } }
736 }
737 { \NewPitonEnvironment { Piton } { } { } { } { } }

```

6.2.8 The styles

The following command is fundamental: it will be used by the Lua code.

```

738 \NewDocumentCommand { \PitonStyle } { m } { \use:c { pitonStyle #1 } }

```

The following command takes in its argument by curryfication.

```

739 \NewDocumentCommand { \SetPitonStyle } { } { { \keys_set:nn { piton / Styles } } }

```

```

740 \cs_new_protected:Npn \@@_math_scantokens:n #1
741 { \normalfont \scantextokens { $#1$ } }

```

```

742 \keys_define:nn { piton / Styles }
743 {
744     String.Interpol .tl_set:c = pitonStyle String.Interpol ,
745     String.Interpol .value_required:n = true ,
746     FormattingType .tl_set:c = pitonStyle FormattingType ,
747     FormattingType .value_required:n = true ,
748     Dict.Value .tl_set:c = pitonStyle Dict.Value ,
749     Dict.Value .value_required:n = true ,
750     Name.Decorator .tl_set:c = pitonStyle Name.Decorator ,
751     Name.Decorator .value_required:n = true ,
752     Name.Function .tl_set:c = pitonStyle Name.Function ,
753     Name.Function .value_required:n = true ,
754     Name.UserFunction .tl_set:c = pitonStyle Name.UserFunction ,

```

```

755 Name.UserFunction .value_required:n = true ,
756 Keyword .tl_set:c = pitonStyle Keyword ,
757 Keyword .value_required:n = true ,
758 Keyword.Constant .tl_set:c = pitonStyle Keyword.Constant ,
759 Keyword.constant .value_required:n = true ,
760 String.Doc .tl_set:c = pitonStyle String.Doc ,
761 String.Doc .value_required:n = true ,
762 Interpol.Inside .tl_set:c = pitonStyle Interpol.Inside ,
763 Interpol.Inside .value_required:n = true ,
764 String.Long .tl_set:c = pitonStyle String.Long ,
765 String.Long .value_required:n = true ,
766 String.Short .tl_set:c = pitonStyle String.Short ,
767 String.Short .value_required:n = true ,
768 String .meta:n = { String.Long = #1 , String.Short = #1 } ,
769 Comment.Math .tl_set:c = pitonStyle Comment.Math ,
770 Comment.Math .default:n = \@@_math_scantokens:n ,
771 Comment.Math .initial:n = ,
772 Comment .tl_set:c = pitonStyle Comment ,
773 Comment .value_required:n = true ,
774 InitialValues .tl_set:c = pitonStyle InitialValues ,
775 InitialValues .value_required:n = true ,
776 Number .tl_set:c = pitonStyle Number ,
777 Number .value_required:n = true ,
778 Name.Namespace .tl_set:c = pitonStyle Name.Namespace ,
779 Name.Namespace .value_required:n = true ,
780 Name.Class .tl_set:c = pitonStyle Name.Class ,
781 Name.Class .value_required:n = true ,
782 Name.Builtin .tl_set:c = pitonStyle Name.Builtin ,
783 Name.Builtin .value_required:n = true ,
784 TypeParameter .tl_set:c = pitonStyle TypeParameter ,
785 TypeParameter .value_required:n = true ,
786 Name.Type .tl_set:c = pitonStyle Name.Type ,
787 Name.Type .value_required:n = true ,
788 Operator .tl_set:c = pitonStyle Operator ,
789 Operator .value_required:n = true ,
790 Operator.Word .tl_set:c = pitonStyle Operator.Word ,
791 Operator.Word .value_required:n = true ,
792 Exception .tl_set:c = pitonStyle Exception ,
793 Exception .value_required:n = true ,
794 Comment.LaTeX .tl_set:c = pitonStyle Comment.LaTeX ,
795 Comment.LaTeX .value_required:n = true ,
796 Identifier .tl_set:c = pitonStyle Identifier ,
797 Comment.LaTeX .value_required:n = true ,
798 ParseAgain.noCR .tl_set:c = pitonStyle ParseAgain.noCR ,
799 ParseAgain.noCR .value_required:n = true ,
800 ParseAgain .tl_set:c = pitonStyle ParseAgain ,
801 ParseAgain .value_required:n = true ,
802 Prompt .tl_set:c = pitonStyle Prompt ,
803 Prompt .value_required:n = true ,
804 unknown .code:n =
805 \msg_error:nn { piton } { Unknown~key~for~SetPitonStyle }
806 }

```

```

807 \msg_new:nnn { piton } { Unknown~key~for~SetPitonStyle }
808 {
809   The~style~'\l_keys_key_str'~is~unknown.\\
810   This~key~will~be~ignored.\\
811   The~available~styles~are~(in~alphabetic~order):~
812   Comment,~
813   Comment.LaTeX,~
814   Dict.Value,~
815   Exception,~
816   Identifier,~

```

```

817     InitialValues,~
818     Keyword,~
819     Keyword.Constant,~
820     Name.Builtin,~
821     Name.Class,~
822     Name.Decorator,~
823     Name.Function,~
824     Name.Namespace,~
825     Number,~
826     Operator,~
827     Operator.Word,~
828     Prompt,~
829     String,~
830     String.Doc,~
831     String.Long,~
832     String.Short,~and~
833     String.Interpol.
834 }

```

6.2.9 The initial style

The initial style is inspired by the style “manni” of Pygments.

```

835 \SetPitonStyle
836 {
837     Comment          = \color[HTML]{0099FF} \itshape ,
838     Exception        = \color[HTML]{CC0000} ,
839     Keyword          = \color[HTML]{006699} \bfseries ,
840     Keyword.Constant = \color[HTML]{006699} \bfseries ,
841     Name.Builtin     = \color[HTML]{336666} ,
842     Name.Decorator   = \color[HTML]{9999FF} ,
843     Name.Class       = \color[HTML]{00AA88} \bfseries ,
844     Name.Function    = \color[HTML]{CC00FF} ,
845     Name.Namespace   = \color[HTML]{00CCFF} ,
846     Number          = \color[HTML]{FF6600} ,
847     Operator         = \color[HTML]{555555} ,
848     Operator.Word    = \bfseries ,
849     String           = \color[HTML]{CC3300} ,
850     String.Doc       = \color[HTML]{CC3300} \itshape ,
851     String.Interpol   = \color[HTML]{AA0000} ,
852     Comment.LaTeX     = \normalfont \color[rgb]{.468,.532,.6} ,
853     Name.Type        = \color[HTML]{336666} ,
854     InitialValues    = \@@_piton:n ,
855     Dict.Value       = \@@_piton:n ,
856     Interpol.Inside  = \color{black}\@@_piton:n ,
857     TypeParameter    = \color[HTML]{008800} \itshape ,
858     Identifier       = \@@_identifier:n ,
859     Name.UserFunction = ,
860     Prompt          = ,
861     ParseAgain.noCR  = \@@_piton_no_cr:n ,
862     ParseAgain       = \@@_piton:n ,
863 }

```

The last styles `ParseAgain.noCR` and `ParseAgain` should be considered as “internal style” (not available for the final user). However, maybe we will change that and document these styles for the final user (why not?).

If the key `math-comments` has been used at load-time, we change the style `Comment.Math` which should be considered only at an “internal style”. However, maybe we will document in a future version the possibility to write change the style *locally* in a document)].

```

864 \bool_if:NT \c_@@_math_comments_bool { \SetPitonStyle { Comment.Math } }

```

6.2.10 Highlighting some identifiers

```

865 \cs_new_protected:Npn \@@_identifier:n #1
866 { \cs_if_exist_use:c { PitonIdentifier _ \l_@@_language_str _ #1 } { #1 } }

867 \keys_define:nn { PitonOptions }
868 { identifiers .code:n = \@@_set_identifiers:n { #1 } }

869 \keys_define:nn { Piton / identifiers }
870 {
871   names .clist_set:N = \l_@@_identifiers_names_tl ,
872   style .tl_set:N = \l_@@_style_tl ,
873 }

874 \cs_new_protected:Npn \@@_set_identifiers:n #1
875 {
876   \clist_clear_new:N \l_@@_identifiers_names_tl
877   \tl_clear_new:N \l_@@_style_tl
878   \keys_set:nn { Piton / identifiers } { #1 }
879   \clist_map_inline:Nn \l_@@_identifiers_names_tl
880   {
881     \tl_set_eq:cN
882     { PitonIdentifier _ \l_@@_language_str _ ##1 }
883     \l_@@_style_tl
884   }
885 }

```

In particular, we have an highlighting of the identifiers which are the names of Python functions previously defined by the user. Indeed, when a Python function is defined, the style `Name.Function.Internal` is applied to that name. We define now that style (you define it directly and you short-cut the function `\SetPitonStyle`).

```

886 \cs_new_protected:cpn { pitonStyle Name.Function.Internal } #1
887 {

```

First, the element is composed in the TeX flow with the style `Name.Function` which is provided to the final user.

```

888 { \PitonStyle { Name.Function } { #1 } }

```

Now, we specify that the name of the new Python function is a known identifier that will be formatted with the Piton style `Name.UserFunction`. Of course, here the affectation is global because we have to exit many groups and even the environments `{Piton}`.

```

889 \cs_gset_protected:cpn { PitonIdentifier _ \l_@@_language_str _ #1 }
890 { \PitonStyle{ Name.UserFunction } }

```

Now, we put the name of that new user function in the dedicated sequence (specific of the current language). That sequence will be used only by `\PitonClearUserFunctions`.

```

891 \seq_if_exist:cF { g_@@_functions _ \l_@@_language_str _ seq }
892 { \seq_new:c { g_@@_functions _ \l_@@_language_str _ seq } }
893 \seq_gput_right:cn { g_@@_functions _ \l_@@_language_str _ seq } { #1 }
894 }

895 \NewDocumentCommand \PitonClearUserFunctions { ! 0 { \l_@@_language_str } }
896 {
897   \seq_if_exist:cT { g_@@_functions _ #1 _ seq }
898   {
899     \seq_map_inline:cn { g_@@_functions _ #1 _ seq }
900     { \cs_undefine:c { PitonIdentifier _ #1 _ ##1 } }
901     \seq_gclear:c { g_@@_functions _ #1 _ seq }
902   }
903 }

```

6.2.11 Security

```

904 \AddToHook { env / piton / begin }
905   { \msg_fatal:nn { piton } { No-environment-piton } }
906
907 \msg_new:nnn { piton } { No-environment-piton }
908   {
909     There-is-no-environment-piton!\\
910     There-is-an-environment~{Piton}~and-a-command~
911     \token_to_str:N \piton\ but-there-is-no-environment~
912     {piton}~.~This-error-is-fatal.
913   }

```

6.2.12 The error messages of the package

```

914 \msg_new:nnnn { piton } { Unknown-key-for-PitonOptions }
915   {
916     Unknown-key. \\
917     The-key~'\l_keys_key_str'~is~unknown~for~\token_to_str:N \PitonOptions.~
918     It-will-be-ignored.\\
919     For-a-list-of-the-available-keys,~type-H~<return>.
920   }
921   {
922     The-available-keys-are~(in~alphabetic~order):~
923     all-line-numbers,~
924     auto-gobble,~
925     background-color,~
926     break-lines,~
927     break-lines-in-piton,~
928     break-lines-in-Piton,~
929     continuation-symbol,~
930     continuation-symbol-on-indentation,~
931     end-of-broken-line,~
932     env-gobble,~
933     gobble,~
934     identifiers,~
935     indent-broken-lines,~
936     language,~
937     left-margin,~
938     line-numbers,~
939     prompt-background-color,~
940     resume,~
941     show-spaces,~
942     show-spaces-in-strings,~
943     slim,~
944     splittable,~
945     tabs-auto-gobble~
946     and-tab-size.
947   }

948 \msg_new:nnn { piton } { label-with-lines-numbers }
949   {
950     You-can't-use-the-command~\token_to_str:N \label\
951     because-the-key~'line-numbers'~(or~'all-line-numbers')~
952     is~not~active.\\
953     If-you-go-on,~that-command-will-be-ignored.
954   }

955 \msg_new:nnn { piton } { cr-not-allowed }
956   {
957     You-can't-put-any-carriage-return-in-the-argument~
958     of-a-command~\c_backslash_str
959     \l_@@_beamer_command_str\ within-an~
960     environment-of~'piton'.~You-should-consider-using-the~
961     corresponding-environment.\\

```



```

962     That~error~is~fatal.
963 }

964 \msg_new:nnn { piton } { overlay~without~beamer }
965 {
966     You~can't~use~an~argument~<...>~for~your~command~
967     \token_to_str:N \PitonInputFile\ because~you~are~not~
968     in~Beamer.\\
969     If~you~go~on,~that~argument~will~be~ignored.
970 }

971 \msg_new:nnn { Piton } { Python~error }
972 { A~Python~error~has~been~detected. }

```

6.3 The Lua part of the implementation

```

973 \ExplSyntaxOff
974 \RequirePackage{luacode}

```

The Lua code will be loaded via a `{luacode*}` environment. The environment is by itself a Lua block and the local declarations will be local to that block. All the global functions (used by the L3 parts of the implementation) will be put in a Lua table `piton`.

```

975 \begin{luacode*}
976 piton = piton or { }
977 if piton.comment_latex == nil then piton.comment_latex = ">" end
978 piton.comment_latex = "#" .. piton.comment_latex

```

The following functions are an easy way to safely insert braces (`{` and `}`) in the TeX flow.

```

979 function piton.open_brace ()
980     tex.sprint("{")
981 end
982 function piton.close_brace ()
983     tex.sprint("}")
984 end

```

6.3.1 Special functions dealing with LPEG

We will use the Lua library `lpeg` which is built in LuaTeX. That's why we define first aliases for several functions of that library.

```

985 local P, S, V, C, Ct, Cc = lpeg.P, lpeg.S, lpeg.V, lpeg.C, lpeg.Ct, lpeg.Cc
986 local Cf, Cs, Cg, Cmt, Cb = lpeg.Cf, lpeg.Cs, lpeg.Cg, lpeg.Cmt, lpeg.Cb
987 local R = lpeg.R

```

The function `Q` takes in as argument a pattern and returns a LPEG *which does a capture* of the pattern. That capture will be sent to LaTeX with the catcode “other” for all the characters: it's suitable for elements of the Python listings that `piton` will typeset verbatim (thanks to the catcode “other”).

```

988 local function Q(pattern)
989     return Ct ( Cc ( luatexbase.catcodetables.CatcodeTableOther ) * C ( pattern ) )
990 end

```

The function `L` takes in as argument a pattern and returns a LPEG *which does a capture* of the pattern. That capture will be sent to LaTeX with standard LaTeX catcodes for all the characters: the elements captured will be formatted as normal LaTeX codes. It's suitable for the “LaTeX comments” in the environments `{Piton}` and the elements between “`escape-inside`”. That function won't be much used.

```

991 local function L(pattern)
992     return Ct ( C ( pattern ) )
993 end

```

The function `Lc` (the *c* is for *constant*) takes in as argument a string and returns a LPEG *with does a constant capture* which returns that string. The elements captured will be formatted as L3 code. It will be used to send to LaTeX all the formatting LaTeX instructions we have to insert in order to do the syntactic highlighting (that's the main job of `piton`). That function will be widely used.

```

994 local function Lc(string)
995     return Cc ( { luatexbase.catcodetables.expl , string } )
996 end

```

The function `K` creates a LPEG which will return as capture the whole LaTeX code corresponding to a Python chunk (that is to say with the LaTeX formatting instructions corresponding to the syntactic nature of that Python chunk). The first argument is a Lua string corresponding to the name of a `piton` style and the second element is a pattern (that is to say a LPEG without capture)

```

997 local function K(style, pattern)
998     return
999         Lc ( "{\\PitonStyle{" .. style .. "}" )
1000         * Q ( pattern )
1001         * Lc ( "}" )
1002 end

```

The formatting commands in a given `piton` style (eg. the style `Keyword`) may be semi-global declarations (such as `\bfseries` or `\slshape`) or LaTeX macros with an argument (such as `\fbox` or `\colorbox{yellow}`). In order to deal with both syntaxes, we have used two pairs of braces: `{\\PitonStyle{Keyword}{text to format}}`.

```

1003 local function WithStyle(style,pattern)
1004     return
1005         Ct ( Cc "Open" * Cc ( "{\\PitonStyle{" .. style .. "}" ) * Cc "}" )
1006         * pattern
1007         * Ct ( Cc "Close" )
1008 end

```

The following LPEG catches the Python chunks which are in LaTeX escapes (and that chunks will be considered as normal LaTeX constructions). We recall that `piton.begin_escape` and `piton.end_escape` are Lua strings corresponding to the key `escape-inside`²². Since the elements that will be caught must be sent to LaTeX with standard LaTeX catcodes, we put the capture (done by the function `C`) in a table (by using `Ct`, which is an alias for `lpeg.Ct`) without number of catcode table at the first component of the table.

```

1009 local Escape =
1010     P(piton_begin_escape)
1011     * L ( ( 1 - P(piton_end_escape) ) ^ 1 )
1012     * P(piton_end_escape)

```

The following line is mandatory.

```

1013 lpeg.locale(lpeg)

```

The basic syntactic LPEG

```

1014 local alpha, digit = lpeg.alpha, lpeg.digit
1015 local space = P " "

```

Remember that, for LPEG, the Unicode characters such as `à`, `â`, `ç`, etc. are in fact strings of length 2 (2 bytes) because `lpeg` is not Unicode-aware.

```

1016 local letter = alpha + P "_"
1017 + P "à" + P "â" + P "ç" + P "é" + P "è" + P "ê" + P "ë" + P "ï" + P "î"
1018 + P "ô" + P "û" + P "ü" + P "À" + P "Â" + P "Ç" + P "È" + P "Ê" + P "Ë"

```

²²The `piton` key `escape-inside` is available at load-time only.

```

1019 + P "Ē" + P "İ" + P "Ĭ" + P "Ū" + P "Ū" + P "Ū"
1020
1021 local alphanum = letter + digit

```

The following LPEG `identifier` is a mere pattern (that is to say more or less a regular expression) which matches the Python identifiers (hence the name).

```

1022 local identifier = letter * alphanum ^ 0

```

On the other hand, the LPEG `Identifier` (with a capital) also returns a *capture*.

```

1023 local Identifier = K ( 'Identifier' , identifier)

```

By convention, we will use names with an initial capital for LPEG which return captures.

Here is the first use of our function `K`. That function will be used to construct LPEG which capture Python chunks for which we have a dedicated `piton` style. For example, for the numbers, `piton` provides a style which is called `Number`. The name of the style is provided as a Lua string in the second argument of the function `K`. By convention, we use single quotes for delimiting the Lua strings which are names of `piton` styles (but this is only a convention).

```

1024 local Number =
1025   K ( 'Number' ,
1026     ( digit^1 * P "." * digit^0 + digit^0 * P "." * digit^1 + digit^1 )
1027     * ( S "eE" * S "+-" ^ -1 * digit^1 ) ^ -1
1028     + digit^1
1029   )

```

We recall that `piton.begin_escape` and `piton.end_escape` are Lua strings corresponding to the key `escape-inside`²³. Of course, if the final user has not used the key `escape-inside`, these strings are empty.

```

1030 local Word
1031 if piton_begin_escape ~= ''
1032 then Word = Q ( ( ( 1 - space - P(piton_begin_escape) - P(piton_end_escape) )
1033   - S "\"\r[()]" - digit ) ^ 1 )
1034 else Word = Q ( ( ( 1 - space ) - S "\"\r[()]" - digit ) ^ 1 )
1035 end

1036 local Space = ( Q " " ) ^ 1
1037
1038 local SkipSpace = ( Q " " ) ^ 0
1039
1040 local Punct = Q ( S ".,:;! " )
1041
1042 local Tab = P "\t" * Lc ( '\\l_@@_tab_t1' )

1043 local SpaceIndentation = Lc ( '\\l_@@_an_indentation_space:' ) * ( Q " " )

1044 local Delim = Q ( S "[()]" )

```

The following LPEG catches a space (U+0020) and replace it by `\\l_@@_space_t1`. It will be used in the strings. Usually, `\\l_@@_space_t1` will contain a space and therefore there won't be difference. However, when the key `show-spaces-in-strings` is in force, `\\l_@@_space_t1` will contain `□` (U+2423) in order to visualize the spaces.

```

1045 local VisualSpace = space * Lc "\\l_@@_space_t1"

```

²³The `piton` key `escape-inside` is available at load-time only.

6.3.2 The LPEG python

Some strings of length 2 are explicit because we want the corresponding ligatures available in some fonts such as *Fira Code* to be active.

```
1046 local Operator =
1047   K ( 'Operator' ,
1048       P "!=" + P "<>" + P "==" + P "<<" + P ">>" + P "<=" + P ">=" + P "!="
1049       + P "/" + P "*" + S "--+/*%=<>&.@|"
1050   )
1051
1052 local OperatorWord =
1053   K ( 'Operator.Word' , P "in" + P "is" + P "and" + P "or" + P "not" )
1054
1055 local Keyword =
1056   K ( 'Keyword' ,
1057       P "as" + P "assert" + P "break" + P "case" + P "class" + P "continue"
1058       + P "def" + P "del" + P "elif" + P "else" + P "except" + P "exec"
1059       + P "finally" + P "for" + P "from" + P "global" + P "if" + P "import"
1060       + P "lambda" + P "non local" + P "pass" + P "return" + P "try"
1061       + P "while" + P "with" + P "yield" + P "yield from" )
1062   + K ( 'Keyword.Constant' , P "True" + P "False" + P "None" )
1063
1064 local Builtin =
1065   K ( 'Name.Builtin' ,
1066       P "__import__" + P "abs" + P "all" + P "any" + P "bin" + P "bool"
1067       + P "bytearray" + P "bytes" + P "chr" + P "classmethod" + P "compile"
1068       + P "complex" + P "delattr" + P "dict" + P "dir" + P "divmod"
1069       + P "enumerate" + P "eval" + P "filter" + P "float" + P "format"
1070       + P "frozenset" + P "getattr" + P "globals" + P "hasattr" + P "hash"
1071       + P "hex" + P "id" + P "input" + P "int" + P "isinstance" + P "issubclass"
1072       + P "iter" + P "len" + P "list" + P "locals" + P "map" + P "max"
1073       + P "memoryview" + P "min" + P "next" + P "object" + P "oct" + P "open"
1074       + P "ord" + P "pow" + P "print" + P "property" + P "range" + P "repr"
1075       + P "reversed" + P "round" + P "set" + P "setattr" + P "slice" + P "sorted"
1076       + P "staticmethod" + P "str" + P "sum" + P "super" + P "tuple" + P "type"
1077       + P "vars" + P "zip" )
1078
1079
1080 local Exception =
1081   K ( 'Exception' ,
1082       P "ArithmeticError" + P "AssertionError" + P "AttributeError"
1083       + P "BaseException" + P "BufferError" + P "BytesWarning" + P "DeprecationWarning"
1084       + P "EOFError" + P "EnvironmentError" + P "Exception" + P "FloatingPointError"
1085       + P "FutureWarning" + P "GeneratorExit" + P "IOError" + P "ImportError"
1086       + P "ImportWarning" + P "IndentationError" + P "IndexError" + P "KeyError"
1087       + P "KeyboardInterrupt" + P "LookupError" + P "MemoryError" + P "NameError"
1088       + P "NotImplementedError" + P "OSError" + P "OverflowError"
1089       + P "PendingDeprecationWarning" + P "ReferenceError" + P "ResourceWarning"
1090       + P "RuntimeError" + P "RuntimeWarning" + P "StopIteration"
1091       + P "SyntaxError" + P "SyntaxWarning" + P "SystemError" + P "SystemExit"
1092       + P "TabError" + P "TypeError" + P "UnboundLocalError" + P "UnicodeDecodeError"
1093       + P "UnicodeEncodeError" + P "UnicodeError" + P "UnicodeTranslateError"
1094       + P "UnicodeWarning" + P "UserWarning" + P "ValueError" + P "VMSError"
1095       + P "Warning" + P "WindowsError" + P "ZeroDivisionError"
1096       + P "BlockingIOError" + P "ChildProcessError" + P "ConnectionError"
1097       + P "BrokenPipeError" + P "ConnectionAbortedError" + P "ConnectionRefusedError"
1098       + P "ConnectionResetError" + P "FileExistsError" + P "FileNotFoundError"
1099       + P "InterruptedError" + P "IsADirectoryError" + P "NotADirectoryError"
1100       + P "PermissionError" + P "ProcessLookupError" + P "TimeoutError"
1101       + P "StopAsyncIteration" + P "ModuleNotFoundError" + P "RecursionError" )
1102
1103
1104 local RaiseException = K ( 'Keyword' , P "raise" ) * SkipSpace * Exception * Q ( P "(" )
```

In Python, a “decorator” is a statement whose begins by @ which patches the function defined in the following statement.

```
1106 local Decorator = K ( 'Name.Decorator' , P "@" * letter1 )
```

The following LPEG DefClass will be used to detect the definition of a new class (the name of that new class will be formatted with the piton style Name.Class).

Example: `class myclass:`

```
1107 local DefClass =
1108   K ( 'Keyword' , P "class" ) * Space * K ( 'Name.Class' , identifier )
```

If the word `class` is not followed by a identifier, it will be caught as keyword by the LPEG Keyword (useful if we want to type a list of keywords).

The following LPEG ImportAs is used for the lines beginning by `import`. We have to detect the potential keyword `as` because both the name of the module and its alias must be formatted with the piton style Name.Namespace.

Example: `import numpy as np`

Moreover, after the keyword `import`, it’s possible to have a comma-separated list of modules (if the keyword `as` is not used).

Example: `import math, numpy`

```
1109 local ImportAs =
1110   K ( 'Keyword' , P "import" )
1111   * Space
1112   * K ( 'Name.Namespace' ,
1113       identifier * ( P "." * identifier )0 )
1114   * (
1115       ( Space * K ( 'Keyword' , P "as" ) * Space
1116         * K ( 'Name.Namespace' , identifier ) )
1117       +
1118       ( SkipSpace * Q ( P "," ) * SkipSpace
1119         * K ( 'Name.Namespace' , identifier ) )0
1120   )
```

Be careful: there is no commutativity of + in the previous expression.

The LPEG FromImport is used for the lines beginning by `from`. We need a special treatment because the identifier following the keyword `from` must be formatted with the piton style Name.Namespace and the following keyword `import` must be formatted with the piton style Keyword and must *not* be caught by the LPEG ImportAs.

Example: `from math import pi`

```
1121 local FromImport =
1122   K ( 'Keyword' , P "from" )
1123   * Space * K ( 'Name.Namespace' , identifier )
1124   * Space * K ( 'Keyword' , P "import" )
```

The strings of Python For the strings in Python, there are four categories of delimiters (without counting the prefixes for f-strings and raw strings). We will use, in the names of our LPEG, prefixes to distinguish the LPEG dealing with that categories of strings, as presented in the following tabular.

	Single	Double
Short	'text'	"text"
Long	'''test'''	"""test"""

We have also to deal with the interpolations in the f-strings. Here is an example of a f-string with an interpolation and a format instruction²⁴ in that interpolation:

```
f'Total price: {total+1:.2f} €'
```

The interpolations beginning by % (even though there is more modern technics now in Python).

```
1125 local PercentInterpol =
1126   K ( 'String.Interpol' ,
1127     P "%"
1128     * ( P "(" * alphanum ^ 1 * P ")" ) ^ -1
1129     * ( S "-#0 +" ) ^ 0
1130     * ( digit ^ 1 + P "*" ) ^ -1
1131     * ( P "." * ( digit ^ 1 + P "*" ) ) ^ -1
1132     * ( S "HLL" ) ^ -1
1133     * S "sdfFeExXorgiGauc%"
1134   )
```

We can now define the LPEG for the four kinds of strings. It's not possible to use our function K because of the interpolations which must be formatted with another piton style that the rest of the string.²⁵

```
1135 local SingleShortString =
1136   WithStyle ( 'String.Short' ,
```

First, we deal with the f-strings of Python, which are prefixed by f or F.

```
1137   Q ( P "f" + P "F" )
1138   * (
1139     K ( 'String.Interpol' , P "{" )
1140     * K ( 'Interpol.Inside' , ( 1 - S "}'" ) ^ 0 )
1141     * Q ( P ":" * ( 1 - S "}'" ) ^ 0 ) ^ -1
1142     * K ( 'String.Interpol' , P "}" )
1143     +
1144     VisualSpace
1145     +
1146     Q ( ( P "\\'" + P "{" + P "}" + 1 - S " {}" ) ^ 1 )
1147   ) ^ 0
1148   * Q ( P "'" )
1149   +
```

Now, we deal with the standard strings of Python, but also the “raw strings”.

```
1150   Q ( P '"' + P "r'" + P "R'" )
1151   * ( Q ( ( P "\\'" + 1 - S " \'r%" ) ^ 1 )
1152     + VisualSpace
1153     + PercentInterpol
1154     + Q ( P "%" )
1155   ) ^ 0
1156   * Q ( P "'" ) )
1157
1158
1159 local DoubleShortString =
1160   WithStyle ( 'String.Short' ,
1161     Q ( P "f\\"" + P "F\\"" )
1162     * (
1163       K ( 'String.Interpol' , P "{" )
1164       * Q ( ( 1 - S "}'" ) ^ 0 , 'Interpol.Inside' )
1165       * ( K ( 'String.Interpol' , P ":" ) * Q ( ( 1 - S "}'" ) ^ 0 ) ) ^ -1
1166       * K ( 'String.Interpol' , P "}" )
1167     )
1168     +
1169     VisualSpace
```

²⁴There is no special piton style for the formatting instruction (after the colon): the style which will be applied will be the style of the encompassing string, that is to say `String.Short` or `String.Long`.

²⁵The interpolations are formatted with the piton style `Interpol.Inside`. The initial value of that style is `@@@_piton:n` wich means that the interpolations are parsed once again by piton.

```

1169         +
1170         Q ( ( P "\\\" + P "{" + P "}" + 1 - S " {}\" ) ^ 1 )
1171     ) ^ 0
1172 * Q ( P "\" )
1173 +
1174 Q ( P "\" + P "r\" + P "R\" )
1175 * ( Q ( ( P "\\\" + 1 - S "\"r%" ) ^ 1 )
1176     + VisualSpace
1177     + PercentInterpol
1178     + Q ( P "%" )
1179     ) ^ 0
1180 * Q ( P "\" )
1181
1182 local ShortString = SingleShortString + DoubleShortString

```

Beamer The following LPEG `BalancedBraces` will be used for the (mandatory) argument of the commands `\only` and *al.* of Beamer. It's necessary to use a *grammar* because that pattern mainly checks the correct nesting of the delimiters (and it's known in the theory of formal languages that this can't be done with regular expressions *stricto sensu* only).

```

1183 local BalancedBraces =
1184   P { "E" ,
1185     E =
1186     (
1187       P "{" * V "E" * P "}"
1188       +
1189       ShortString
1190       +
1191       ( 1 - S "{}" )
1192     ) ^ 0
1193   }

```

If Beamer is used (or if the key `beamer` is used at load-time), the following LPEG will be redefined.

```

1194 local Beamer = P ( false )
1195 local BeamerBeginEnvironments = P ( true )
1196 local BeamerEndEnvironments = P ( true )
1197 local BeamerNamesEnvironments =
1198   P "uncoverenv" + P "onlyenv" + P "visibleenv" + P "invisibleenv"
1199   + P "alertenv" + P "actionenv"
1200
1201 UserCommands =
1202   Ct ( Cc "Open" * C ( "\\emph{" ) * Cc "}" )
1203   * ( C ( BalancedBraces ) / (function (s) return MainLoopPython:match(s) end ) )
1204   * P "}" * Ct ( Cc "Close" )
1205
1206 function OneBeamerEnvironment(name)
1207   return
1208     Ct ( Cc "Open"
1209       * C (
1210         P ( "\\begin{" .. name .. "}" )
1211         * ( P "<" * (1 - P ">") ^ 0 * P ">" ) ^ -1
1212       )
1213       * Cc ( "\\end{" .. name .. "}" )
1214     )
1215     * (
1216       C ( ( 1 - P ( "\\end{" .. name .. "}" ) ) ^ 0 )
1217       / (function (s) return MainLoopPython:match(s) end )
1218     )
1219     * P ( "\\end{" .. name .. "}" ) * Ct ( Cc "Close" )
1220 end

```

```

1220 if piton_beamer
1221 then
1222   Beamer =
1223     L ( P "\\pause" * ( P "[" * (1 - P "]" ) ^ 0 * P "]" ) ^ -1 )
1224   +
1225     Ct ( Cc "Open"
1226         * C (
1227             (
1228               P "\\uncover" + P "\\only" + P "\\alert" + P "\\visible"
1229               + P "\\invisible" + P "\\action"
1230             )
1231             * ( P "<" * (1 - P ">") ^ 0 * P ">" ) ^ -1
1232             * P "{"
1233           )
1234         * Cc "}"
1235       )
1236     * ( C ( BalancedBraces ) / (function (s) return MainLoopPython:match(s) end ) )
1237     * P "]" * Ct ( Cc "Close" )
1238   +
1239     OneBeamerEnvironment "uncoverenv"
1240   + OneBeamerEnvironment "onlyenv"
1241   + OneBeamerEnvironment "visibleenv"
1242   + OneBeamerEnvironment "invisibleenv"
1243   + OneBeamerEnvironment "alertenv"
1244   + OneBeamerEnvironment "actionenv"
1245   +
1246     L (

```

For `\\alt`, the specification of the overlays (between angular brackets) is mandatory.

```

1247     ( P "\\alt" )
1248     * P "<" * (1 - P ">") ^ 0 * P ">"
1249     * P "{"
1250   )
1251   * K ( 'ParseAgain.noCR' , BalancedBraces )
1252   * L ( P "}" )
1253   * K ( 'ParseAgain.noCR' , BalancedBraces )
1254   * L ( P "}" )
1255   +
1256   L (

```

For `\\alt`, the specification of the overlays (between angular brackets) is mandatory.

```

1257     ( P "\\temporal" )
1258     * P "<" * (1 - P ">") ^ 0 * P ">"
1259     * P "{"
1260   )
1261   * K ( 'ParseAgain.noCR' , BalancedBraces )
1262   * L ( P "}" )
1263   * K ( 'ParseAgain.noCR' , BalancedBraces )
1264   * L ( P "}" )
1265   * K ( 'ParseAgain.noCR' , BalancedBraces )
1266   * L ( P "}" )

```

Now for the environemnts.

```

1267 BeamerBeginEnvironments =
1268   ( space ^ 0 *
1269     L
1270     (
1271       P "\\begin{" * BeamerNamesEnvironments * "}"
1272       * ( P "<" * (1 - P ">") ^ 0 * P ">" ) ^ -1
1273     )
1274     * P "\r"
1275   ) ^ 0
1276 BeamerEndEnvironments =
1277   ( space ^ 0 *
1278     L ( P "\\end{" * BeamerNamesEnvironments * P "}" )

```



```

1279     * P "\r"
1280   ) ^ 0
1281 end

```

EOL The following LPEG will detect the Python prompts when the user is typesetting an interactive session of Python (directly or through `{pyconsole}` of `pyluatex`). We have to detect that prompt twice. The first detection (called *hasty detection*) will be before the `\@@_begin_line:` because you want to trigger a special background color for that row (and, after the `\@@_begin_line:`, it's too late to change de background).

```

1282 local PromptHastyDetection = ( # ( P ">>>" + P "..." ) * Lc ( '\\@@_prompt:' ) ) ^ -1

```

We remind that the marker `#` of LPEG specifies that the pattern will be detected but won't consume any character.

With the following LPEG, a style will actually be applied to the prompt (for instance, it's possible to decide to discard these prompts).

```

1283 local Prompt = K ( 'Prompt' , ( ( P ">>>" + P "..." ) * P " " ^ -1 ) ^ -1 )

```

The following LPEG EOL is for the end of lines.

```

1284 local EOL =
1285   P "\r"
1286   *
1287   (
1288     ( space^0 * -1 )
1289     +

```

We recall that each line in the Python code we have to parse will be sent back to LaTeX between a pair `\@@_begin_line: - \@@_end_line:`²⁶.

```

1290   Ct (
1291     Cc "EOL"
1292     *
1293     Ct (
1294       Lc "\\@@_end_line:"
1295       * BeamerEndEnvironments
1296       * BeamerBeginEnvironments
1297       * PromptHastyDetection
1298       * Lc "\\@@_newline: \\@@_begin_line:"
1299       * Prompt
1300     )
1301   )
1302 )
1303 *
1304 SpaceIndentation ^ 0

```

The long strings

```

1305 local SingleLongString =
1306   WithStyle ( 'String.Long' ,
1307     ( Q ( S "fF" * P "'''" )
1308       * (
1309         K ( 'String.Interpol' , P "{" )
1310         * K ( 'Interpol.Outside' , ( 1 - S "}:\" - P "'''" ) ^ 0 )
1311         * Q ( P ":" * ( 1 - S "}:\" - P "'''" ) ^ 0 ) ^ -1
1312         * K ( 'String.Interpol' , P "}" )
1313       +
1314       Q ( ( 1 - P "'''" - S "{}\" ) ^ 1 )

```

²⁶Remember that the `\@@_end_line:` must be explicit because it will be used as marker in order to delimit the argument of the command `\@@_begin_line:`

```

1315         +
1316         EOL
1317     ) ^ 0
1318 +
1319     Q ( ( S "rR" ) ^ -1 * P "'''" )
1320     * (
1321         Q ( ( 1 - P "'''" - S "\r%" ) ^ 1 )
1322         +
1323         PercentInterpol
1324         +
1325         P "%"
1326         +
1327         EOL
1328     ) ^ 0
1329 )
1330 * Q ( P "'''" ) )
1331
1332
1333 local DoubleLongString =
1334     WithStyle ( 'String.Long' ,
1335     (
1336         Q ( S "fF" * P "\"\"" )
1337         * (
1338             K ( 'String.Interpol', P "{" )
1339             * K ( 'Interpol.Inside' , ( 1 - S "}:\"r" - P "\"\"" ) ^ 0 )
1340             * Q ( P ":" * ( 1 - S "}:\"r" - P "\"\"" ) ^ 0 ) ^ -1
1341             * K ( 'String.Interpol' , P "}" )
1342             +
1343             Q ( ( 1 - P "\"\"" - S "{}\"r" ) ^ 1 )
1344             +
1345             EOL
1346         ) ^ 0
1347     +
1348     Q ( ( S "rR" ) ^ -1 * P "\"\"" )
1349     * (
1350         Q ( ( 1 - P "\"\"" - S "%\r" ) ^ 1 )
1351         +
1352         PercentInterpol
1353         +
1354         P "%"
1355         +
1356         EOL
1357     ) ^ 0
1358 )
1359 * Q ( P "\"\"" )
1360 )
1361 local LongString = SingleLongString + DoubleLongString

```

We have a LPEG for the Python docstrings. That LPEG will be used in the LPEG `DefFunction` which deals with the whole preamble of a function definition (which begins with `def`).

```

1362 local StringDoc =
1363     K ( 'String.Doc' , P "\"\"" )
1364     * ( K ( 'String.Doc' , ( 1 - P "\"\"" - P "\r" ) ^ 0 ) * EOL
1365     * Tab ^ 0
1366     ) ^ 0
1367     * K ( 'String.Doc' , ( 1 - P "\"\"" - P "\r" ) ^ 0 * P "\"\"" )

```

The comments in the Python listings We define different LPEG dealing with comments in the Python listings.

```

1368 local CommentMath =

```

```

1369 P "$" * K ( 'Comment.Math' , ( 1 - S "$\r" ) ^ 1 ) * P "$"
1370
1371 local Comment =
1372   WithStyle ( 'Comment' ,
1373     Q ( P "#" )
1374     * ( CommentMath + Q ( ( 1 - S "$\r" ) ^ 1 ) ) ^ 0 )
1375     * ( EOL + -1 )

```

The following LPEG `CommentLaTeX` is for what is called in that document the “LaTeX comments”. Since the elements that will be caught must be sent to LaTeX with standard LaTeX catcodes, we put the capture (done by the function `C`) in a table (by using `Ct`, which is an alias for `lpeg.Ct`).

```

1376 local CommentLaTeX =
1377   P(piton.comment_latex)
1378   * Lc "{\\PitonStyle{Comment.LaTeX}{\\ignorespaces}"
1379   * L ( ( 1 - P "\r" ) ^ 0 )
1380   * Lc "}"
1381   * ( EOL + -1 ) -- you could put EOL instead of EOL

```

DefFunction The following LPEG Expression will be used for the parameters in the *argspec* of a Python function. It’s necessary to use a *grammar* because that pattern mainly checks the correct nesting of the delimiters (and it’s known in the theory of formal languages that this can’t be done with regular expressions *stricto sensu* only).

```

1382 local Expression =
1383   P { "E" ,
1384     E = ( 1 - S "{}() []\r," ) ^ 0
1385     * (
1386       ( P "{" * V "F" * P "}"
1387         + P "(" * V "F" * P ")"
1388         + P "[" * V "F" * P "]" ) * ( 1 - S "{}() []\r," ) ^ 0
1389       ) ^ 0 ,
1390     F = ( 1 - S "{}() []\r\"" ) ^ 0
1391     * ( (
1392       P "\"" * (P "\\\"" + 1 - S "\\r" ) ^ 0 * P "\""
1393       + P "\"\" * (P "\\\"\" + 1 - S "\"\r" ) ^ 0 * P "\"\"
1394       + P "{" * V "F" * P "}"
1395       + P "(" * V "F" * P ")"
1396       + P "[" * V "F" * P "]"
1397     ) * ( 1 - S "{}() []\r\"" ) ^ 0 ) ^ 0 ,
1398   }

```

We will now define a LPEG `Params` that will catch the list of parameters (that is to say the *argspec*) in the definition of a Python function. For example, in the line of code

```
def MyFunction(a,b,x=10,n:int): return n
```

the LPEG `Params` will be used to catch the chunk `a,b,x=10,n:int`.

Or course, a `Params` is simply a comma-separated list of `Param`, and that’s why we define first the LPEG `Param`.

```

1399 local Param =
1400   SkipSpace * Identifier * SkipSpace
1401   * (
1402     K ( 'InitialValues' , P "=" * Expression )
1403     + Q ( P ":" ) * SkipSpace * K ( 'Name.Type' , letter^1 )
1404   ) ^ -1
1405
1406 local Params = ( Param * ( Q "," * Param ) ^ 0 ) ^ -1

```

The following LPEG `DefFunction` catches a keyword `def` and the following name of function *but also everything else until a potential docstring*. That's why this definition of LPEG must occur (in the file `piton.sty`) after the definition of several other LPEG such as `Comment`, `CommentLaTeX`, `Params`, `StringDoc`...

```

1406 local DefFunction =
1407   K ( 'Keyword' , P "def" )
1408   * Space
1409   * K ( 'Name.Function.Internal' , identifier )
1410   * SkipSpace
1411   * Q ( P "(" ) * Params * Q ( P ")" )
1412   * SkipSpace
1413   * ( Q ( P "->" ) * SkipSpace * K ( 'Name.Type' , identifier ) ) ^ -1

```

Here, we need a `piton` style `ParseAgain` which will be linked to `\@@_piton:n` (that means that the capture will be parsed once again by `piton`). We could avoid that kind of trick by using a non-terminal of a grammar but we have probably here a better legibility.

```

1414   * K ( 'ParseAgain' , ( 1 - S ":\r" ) ^ 0 )
1415   * Q ( P ":" )
1416   * ( SkipSpace
1417       * ( EOL + CommentLaTeX + Comment ) -- in all cases, that contains an EOL
1418       * Tab ^ 0
1419       * SkipSpace
1420       * StringDoc ^ 0 -- there may be additionnal docstrings
1421   ) ^ -1

```

Remark that, in the previous code, `CommentLaTeX` *must* appear before `Comment`: there is no commutativity of the addition for the *parsing expression grammars* (PEG).

If the word `def` is not followed by an identifier and parenthesis, it will be caught as keyword by the LPEG `Keyword` (useful if, for example, the final user wants to speak of the keyword `def`).

The dictionaries of Python We have LPEG dealing with dictionaries of Python because, in typesettings of explicit Python dictionaries, one may prefer to have all the values formatted in black (in order to see more clearly the keys which are usually Python strings). That's why we have a `piton` style `Dict.Value`.

The initial value of that `piton` style is `\@@_piton:n`, which means that the value of the entry of the dictionary is parsed once again by `piton` (and nothing special is done for the dictionary). In the following example, we have set the `piton` style `Dict.Value` to `\color{black}`:

```
mydict = { 'name' : 'Paul', 'sex' : 'male', 'age' : 31 }
```

At this time, this mechanism works only for explicit dictionaries on a single line!

```

1422 local ItemDict =
1423   ShortString * SkipSpace * Q ( P ":" ) * K ( 'Dict.Value' , Expression )
1424
1425 local ItemOfSet = SkipSpace * ( ItemDict + ShortString ) * SkipSpace
1426
1427 local Set =
1428   Q ( P "{" )
1429   * ItemOfSet * ( Q ( P "," ) * ItemOfSet ) ^ 0
1430   * Q ( P "}" )

```

Miscellaneous

```

1431 local ExceptionInConsole = Exception * Q ( ( 1 - P "\r" ) ^ 0 ) * EOL

```

The main LPEG First, the main loop :

```

1432 MainLoopPython =
1433   ( ( space1 * -1 )
1434     + EOL
1435     + Space
1436     + Tab
1437     + Escape
1438     + CommentLaTeX
1439     + Beamer
1440     + UserCommands
1441     + LongString
1442     + Comment
1443     + ExceptionInConsole
1444     + Set
1445     + Delim

Operator must be before Punct.

1446     + Operator
1447     + ShortString
1448     + Punct
1449     + FromImport
1450     + RaiseException
1451     + DefFunction
1452     + DefClass
1453     + Keyword * ( Space + Punct + Delim + EOL+ -1 )
1454     + Decorator
1455     + OperatorWord * ( Space + Punct + Delim + EOL+ -1 )
1456     + Builtin * ( Space + Punct + Delim + EOL+ -1 )
1457     + Identifier
1458     + Number
1459     + Word
1460   ) ^ 0

```

We recall that each line in the Python code to parse will be sent back to LaTeX between a pair `\@@_begin_line: - \@@_end_line:`²⁷.

```

1461 local python = P ( true )
1462
1463 python =
1464   Ct (
1465     ( ( space - P "\r" ) ^0 * P "\r" ) ^ -1
1466     * BeamerBeginEnvironments
1467     * PromptHastyDetection
1468     * Lc '\@@_begin_line:'
1469     * Prompt
1470     * SpaceIndentation ^ 0
1471     * MainLoopPython
1472     * -1
1473     * Lc '\@@_end_line:'
1474   )
1475
1475 local languages = { }
1476 languages['python'] = python

```

6.3.3 The LPEG ocaml

```

1477 local Delim = Q ( P "[" + P "]" + S "[]" )
1478 local Punct = Q ( S ",:!" )

```

²⁷Remember that the `\@@_end_line:` must be explicit because it will be used as marker in order to delimit the argument of the command `\@@_begin_line:`

```

1479 local identifier =
1480   ( R "az" + R "AZ" + P "_" ) * ( R "az" + R "AZ" + S "_" + digit ) ^ 0
1481
1482 local Identifier = K ( 'Identifier' , identifier )
1483
1484 local Operator =
1485   K ( 'Operator' ,
1486     P "!=" + P "<>" + P "==" + P "<<" + P ">>" + P "<=" + P ">=" + P "!="
1487     + P "||" + P "&&" + P "/" + P "*" + P ";" + P ":" + P "->"
1488     + P "+" + P "-" + P "." + P "/"
1489     + S "~+/*%=<>&@|"
1490   )
1491
1492 local OperatorWord =
1493   K ( 'Operator.Word' ,
1494     P "and" + P "asr" + P "land" + P "lor" + P "lsl" + P "lxor"
1495     + P "mod" + P "or" )
1496
1497 local Keyword =
1498   K ( 'Keyword' ,
1499     P "as" + P "assert" + P "begin" + P "class" + P "constraint" + P "done"
1500     + P "do" + P "downto" + P "else" + P "end" + P "exception" + P "external"
1501     + P "false" + P "for" + P "function" + P "fun" + P "functor" + P "if"
1502     + P "in" + P "include" + P "inherit" + P "initializer" + P "lazy" + P "let"
1503     + P "match" + P "method" + P "module" + P "mutable" + P "new" + P "object"
1504     + P "of" + P "open" + P "private" + P "raise" + P "rec" + P "sig"
1505     + P "struct" + P "then" + P "to" + P "true" + P "try" + P "type"
1506     + P "value" + P "val" + P "virtual" + P "when" + P "while" + P "with" )
1507   + K ( 'Keyword.Constant' , P "true" + P "false" )
1508
1509
1510 local Builtin =
1511   K ( 'Name.Builtin' ,
1512     P "not" + P "incr" + P "decr" + P "fst" + P "snd"
1513     + P "String.length"
1514     + P "List.tl" + P "List.hd" + P "List.mem" + P "List.exists"
1515     + P "List.for_all" + P "List.filter" + P "List.length" + P "List.map"
1516     + P "List.iter"
1517     + P "Array.length" + P "Array.make" + P "Array.make_matrix"
1518     + P "Array.init" + P "Array.copy" + P "Array.copy" + P "Array.mem"
1519     + P "Array.exists" + P "Array.for_all" + P "Array.map" + P "Array.iter"
1520     + P "Queue.create" + P "Queue.is_empty" + P "Queue.push" + P "Queue.pop"
1521     + P "Stack.create" + P "Stack.is_empty" + P "Stack.push" + P "Stack.pop"
1522     + P "Hashtbl.create" + P "Hashtbl.add" + P "Hashtbl.remove"
1523     + P "Hashtbl.mem" + P "Hashtbl.find" + P "Hashtbl.find_opt"
1524     + P "Hashtbl.iter" )

```

The following exceptions are exceptions in the standard library of OCaml (Stdlib).

```

1525 local Exception =
1526   K ( 'Exception' ,
1527     P "Division_by_zero" + P "End_of_File" + P "Failure"
1528     + P "Invalid_argument" + P "Match_failure" + P "Not_found"
1529     + P "Out_of_memory" + P "Stack_overflow" + P "Sys_blocked_io"
1530     + P "Sys_error" + P "Undefined_recursive_module" )

```

The characters in OCaml

```

1531 local Char =
1532   K ( 'String.Short' , P "'" * ( ( 1 - P "'" ) ^ 0 + P "\\'" ) * P "'" )

```

Beamer

```

1533 local BalancedBraces =
1534   P { "E" ,
1535       E =
1536         (
1537           P "{" * V "E" * P "}"
1538         +
1539           P "\" * ( 1 - S "\" ) ^ 0 * P "\" -- OCaml strings
1540         +
1541           ( 1 - S "{" )
1542         ) ^ 0
1543   }

1544 if piton_beamer
1545 then
1546   Beamer =
1547     L ( P "\\pause" * ( P "[" * (1 - P "]" ) ^ 0 * P "]" ) ^ -1 )
1548   +
1549     ( P "\\uncover" * Lc ( '\\@@_beamer_command:n{uncover}' )
1550   + P "\\only" * Lc ( '\\@@_beamer_command:n{only}' )
1551   + P "\\alert" * Lc ( '\\@@_beamer_command:n{alert}' )
1552   + P "\\visible" * Lc ( '\\@@_beamer_command:n{visible}' )
1553   + P "\\invisible" * Lc ( '\\@@_beamer_command:n{invisible}' )
1554   + P "\\action" * Lc ( '\\@@_beamer_command:n{action}' )
1555   )
1556   *
1557   L ( ( P "<" * (1 - P ">") ^ 0 * P ">" ) ^ -1 * P "{" )
1558   * K ( 'ParseAgain.noCR' , BalancedBraces )
1559   * L ( P "}" )
1560   +
1561   L (
1562     ( P "\\alt" )
1563     * P "<" * (1 - P ">") ^ 0 * P ">"
1564     * P "{"
1565   )
1566   * K ( 'ParseAgain.noCR' , BalancedBraces )
1567   * L ( P "}" )
1568   * K ( 'ParseAgain.noCR' , BalancedBraces )
1569   * L ( P "}" )
1570   +
1571   L (
1572     ( P "\\temporal" )
1573     * P "<" * (1 - P ">") ^ 0 * P ">"
1574     * P "{"
1575   )
1576   * K ( 'ParseAgain.noCR' , BalancedBraces )
1577   * L ( P "}" )
1578   * K ( 'ParseAgain.noCR' , BalancedBraces )
1579   * L ( P "}" )
1580   * K ( 'ParseAgain.noCR' , BalancedBraces )
1581   * L ( P "}" )
1582   BeamerBeginEnvironments =
1583     ( space ^ 0 *
1584       L (
1585         (
1586           P "\\begin{" * BeamerNamesEnvironments * "}"
1587           * ( P "<" * ( 1 - P ">") ^ 0 * P ">" ) ^ -1
1588         )
1589         * P "\r"
1590       ) ^ 0
1591     BeamerEndEnvironments =
1592       ( space ^ 0 *
1593         L ( P "\\end{" * BeamerNamesEnvironments * P "}" )
1594         * P "\r"

```

```

1595     ) ^ 0
1596 end

```

```

EOL local EOL = P "*" ( ( space0 * -1) + Ct(Cc"EOL" * Ct(Lc"
@@_endline : "*BeamerEndEnvironments*BeamerBeginEnvironments*PromptHastyDetection*
Lc"
@@_newline :
@@_beginline : " * Prompt))) * SpaceIndentation0

1597 %
1598 % \paragraph{The strings}
1599 %
1600 % We need a pattern |string| without captures because it will be used within the
1601 % comments of OCaml.
1602 % \begin{macrocode}
1603 local string =
1604     Q ( P "\" )
1605     * (
1606         VisualSpace
1607         +
1608         Q ( ( 1 - S " \"r" ) ^ 1 )
1609         +
1610         EOL
1611     ) ^ 0
1612     * Q ( P "\" )
1613 local String = WithStyle ( 'String.Long' , string )

```

Now, the “quoted strings” of OCaml (for example {ext|Essai|ext}).

For those strings, we will do two consecutive analysis. First an analysis to determine the whole string and, then, an analysis for the potential visual spaces and the EOL in the string.

The first analysis require a match-time capture. For explanations about that programmation, see the paragraphe *Lua’s long strings* in www.inf.puc-rio.br/~roberto/lpeg.

```

1614 local ext = ( R "az" + P "_" ) ^ 0
1615 local open = "{" * Cg(ext, 'init') * "|"
1616 local close = "|" * C(ext) * "}"
1617 local closeeq =
1618     Cmt ( close * Cb('init'),
1619         function (s, i, a, b) return a==b end )

```

The LPEG QuotedStringBis will do the second analysis.

```

1620 local QuotedStringBis =
1621     WithStyle ( 'String.Long' ,
1622     (
1623         VisualSpace
1624         +
1625         Q ( ( 1 - S " r" ) ^ 1 )
1626         +
1627         EOL
1628     ) ^ 0 )
1629

```

We use a “function capture” (as called in the official documentation of the LPEG) in order to do the second analysis on the result of the first one.

```

1630 local QuotedString =
1631     C ( open * ( 1 - closeeq ) ^ 0 * close ) /
1632     ( function (s) return QuotedStringBis : match(s) end )

```


The comments in the OCaml listings In OCaml, the delimiters for the comments are (***** and *****). There are unsymmetrical and, therefore, the comments may be nested. That's why we need a grammar.

In these comments, we embed the math comments (between **\$** and **\$**) and we embed also a treatment for the end of lines (since the comments may be multi-lines).

```

1633 local Comment =
1634   WithStyle ( 'Comment' ,
1635     P {
1636       "A" ,
1637       A = Q "(" *
1638         ( V "A"
1639           + Q ( ( 1 - P "(" - P ")" ) - S "\r$\\" ) ^ 1 ) -- $
1640           + string
1641           + P "$" * K ( 'Comment.Math' , ( 1 - S "$\r" ) ^ 1 ) * P "$" -- $
1642           + EOL
1643         ) ^ 0
1644       * Q ")"
1645     } )

```

The DefFunction

```

1646 local DefFunction =
1647   K ( 'Keyword' , P "let rec" + P "let" + P "and" )
1648   * Space
1649   * K ( 'Name.Function.Internal' , identifier )
1650   * Space
1651   * # ( P "=" * space * P "function" + ( 1 - P "=" ) )

```

The parameters of the types

```

1652 local TypeParameter = K ( 'TypeParameter' , P "'" * alpha * # ( 1 - P "'" ) )

```

The main LPEG First, the main loop :

```

1653 MainLoopOCaml =
1654   ( ( space^1 * -1 )
1655     + EOL
1656     + Space
1657     + Tab
1658     + Escape
1659     + Beamer
1660     + TypeParameter
1661     + String + QuotedString + Char
1662     + Comment
1663     + Delim
1664     + Operator
1665     + Punct
1666     + FromImport
1667     + ImportAs
1668     + Exception
1669     + DefFunction
1670     + Keyword * ( Space + Punct + Delim + EOL + -1 )
1671     + OperatorWord * ( Space + Punct + Delim + EOL + -1 )
1672     + Builtin * ( Space + Punct + Delim + EOL + -1 )
1673     + Identifier
1674     + Number
1675     + Word
1676   ) ^ 0

```

We recall that each line in the Python code to parse will be sent back to LaTeX between a pair `\@@_begin_line: - \@@_end_line:`²⁸.

```

1677 local ocaml = P ( true )
1678
1679 ocaml =
1680   Ct (
1681     ( ( space - P "\r" ) ^0 * P "\r" ) ^ -1
1682     * BeamerBeginEnvironments
1683     * Lc ( '\\@@_begin_line:' )
1684     * SpaceIndentation ^ 0
1685     * MainLoopOCaml
1686     * -1
1687     * Lc ( '\\@@_end_line:' )
1688   )
1689 languages['ocaml'] = ocaml

```

6.3.4 The function Parse

The function `Parse` is the main function of the package `piton`. It parses its argument and sends back to LaTeX the code with interlaced formatting LaTeX instructions. In fact, everything is done by the LPEG `python` which returns as capture a Lua table containing data to send to LaTeX.

```

1690 function piton.Parse(language,code)
1691   local t = languages[language] : match ( code )
1692   local left_stack = {}
1693   local right_stack = {}
1694   for _ , one_item in ipairs(t)
1695   do
1696     if one_item[1] == "EOL"
1697     then
1698       for _ , s in ipairs(right_stack)
1699       do tex.sprint( s )
1700       end
1701       for _ , s in ipairs(one_item[2])
1702       do tex.tprint(s)
1703       end
1704       for _ , s in ipairs(left_stack)
1705       do tex.sprint( s )
1706       end
1707     else
1708       if one_item[1] == "Open"
1709       then
1710         tex.sprint( one_item[2] )
1711         table.insert(left_stack,one_item[2])
1712         table.insert(right_stack,one_item[3])
1713       else
1714         if one_item[1] == "Close"
1715         then
1716           tex.sprint( right_stack[#right_stack] )
1717           left_stack[#left_stack] = nil
1718           right_stack[#right_stack] = nil
1719         else
1720           tex.tprint(one_item)
1721         end
1722       end
1723     end
1724   end
1725 end

```

²⁸Remember that the `\@@_end_line:` must be explicit because it will be used as marker in order to delimit the argument of the command `\@@_begin_line:`

The function `ParseFile` will be used by the LaTeX command `\PitonInputFile`. That function merely reads the whole file (that is to say all its lines) and then apply the function `Parse` to the resulting Lua string.

```

1726 function piton.ParseFile(language,name,first_line,last_line)
1727   s = ''
1728   local i = 0
1729   for line in io.lines(name)
1730   do i = i + 1
1731     if i >= first_line
1732     then s = s .. '\r' .. line
1733     end
1734     if i >= last_line then break end
1735   end
1736   piton.Parse(language,s)
1737 end

```

6.3.5 Two variants of the function `Parse` with integrated preprocessors

The following command will be used by the user command `\piton`. For that command, we have to undo the duplication of the symbols `#`.

```

1738 function piton.ParseBis(language,code)
1739   local s = ( Cs ( ( P '##' / '#' + 1 ) ^ 0 ) ) : match ( code )
1740   return piton.Parse(language,s)
1741 end

```

The following command will be used when we have to parse some small chunks of code that have yet been parsed. They are re-scanned by LaTeX because it has been required by `\@@_piton:n` in the `piton` style of the syntactic element. In that case, you have to remove the potential `\@@_breakable_space:` that have been inserted when the key `break-lines` is in force.

```

1742 function piton.ParseTer(language,code)
1743   local s = ( Cs ( ( P '\\\@@_breakable_space:' / ' ' + 1 ) ^ 0 ) )
1744             : match ( code )
1745   return piton.Parse(language,s)
1746 end

```

6.3.6 Preprocessors of the function `Parse` for gobble

We deal now with preprocessors of the function `Parse` which are needed when the “gobble mechanism” is used.

The function `gobble` gobbles n characters on the left of the code. It uses a LPEG that we have to compute dynamically because it depends on the value of n .

```

1747 local function gobble(n,code)
1748   function concat(acc,new_value)
1749     return acc .. new_value
1750   end
1751   if n==0
1752   then return code
1753   else
1754     return Cf (
1755       Cc ( "" ) *
1756       ( 1 - P "\r" ) ^ (-n) * C ( ( 1 - P "\r" ) ^ 0 )
1757       * ( C ( P "\r" )
1758         * ( 1 - P "\r" ) ^ (-n)
1759         * C ( ( 1 - P "\r" ) ^ 0 )
1760       ) ^ 0 ,
1761       concat
1762     ) : match ( code )
1763   end
1764 end

```

The following function `add` will be used in the following `LPEG AutoGobbleLPEG`, `TabsAutoGobbleLPEG` and `EnvGobbleLPEG`.

```
1765 local function add(acc,new_value)
1766     return acc + new_value
1767 end
```

The following LPEG returns as capture the minimal number of spaces at the beginning of the lines of code. The main work is done by two *fold captures* (`lpeg.Cf`), one using `add` and the other (encompassing the previous one) using `math.min` as folding operator.

```
1768 local AutoGobbleLPEG =
1769     ( space ^ 0 * P "\r" ) ^ -1
1770     * Cf (
1771         (
1772             ( P " " ) ^ 0 * P "\r"
1773             +
1774             Cf ( Cc(0) * ( P " " * Cc(1) ) ^ 0 , add )
1775             * ( 1 - P " " ) * ( 1 - P "\r" ) ^ 0 * P "\r"
1776         ) ^ 0
```

We don't take into account the empty lines (with only spaces).

Now for the last line of the Python code...

```
1777     *
1778     ( Cf ( Cc(0) * ( P " " * Cc(1) ) ^ 0 , add )
1779     * ( 1 - P " " ) * ( 1 - P "\r" ) ^ 0 ) ^ -1 ,
1780     math.min
1781 )
```

The following LPEG is similar but works with the indentations.

```
1782 local TabsAutoGobbleLPEG =
1783     ( space ^ 0 * P "\r" ) ^ -1
1784     * Cf (
1785         (
1786             ( P "\t" ) ^ 0 * P "\r"
1787             +
1788             Cf ( Cc(0) * ( P "\t" * Cc(1) ) ^ 0 , add )
1789             * ( 1 - P "\t" ) * ( 1 - P "\r" ) ^ 0 * P "\r"
1790         ) ^ 0
1791         *
1792         ( Cf ( Cc(0) * ( P "\t" * Cc(1) ) ^ 0 , add )
1793         * ( 1 - P "\t" ) * ( 1 - P "\r" ) ^ 0 ) ^ -1 ,
1794         math.min
1795     )
```

The following LPEG returns as capture the number of spaces at the last line, that is to say before the `\end{Piton}` (and usually it's also the number of spaces before the corresponding `\begin{Piton}` because that's the traditionnal way to indent in LaTeX). The main work is done by a *fold capture* (`lpeg.Cf`) using the function `add` as folding operator.

```
1796 local EnvGobbleLPEG =
1797     ( ( 1 - P "\r" ) ^ 0 * P "\r" ) ^ 0
1798     * Cf ( Cc(0) * ( P " " * Cc(1) ) ^ 0 , add ) * -1
```

```
1799 function piton.GobbleParse(language,n,code)
1800     if n==1
1801     then n = AutoGobbleLPEG : match(code)
1802     else if n==2
1803     then n = EnvGobbleLPEG : match(code)
1804     else if n==3
1805     then n = TabsAutoGobbleLPEG : match(code)
1806     end
1807 end
```

```

1808 end
1809 piton.Parse(language,gobble(n,code))
1810 end

```

6.3.7 To count the number of lines

```

1811 function piton.CountLines(code)
1812   local count = 0
1813   for i in code : gmatch ( "\r" ) do count = count + 1 end
1814   tex.sprint(
1815     luatexbase.catcodetables.expl ,
1816     '\\int_set:Nn \\l_@@_nb_lines_int {' .. count .. '}' )
1817 end

1818 function piton.CountNonEmptyLines(code)
1819   local count = 0
1820   count =
1821   ( Cf ( Cc(0) *
1822     (
1823       ( P " " ) ^ 0 * P "\r"
1824       + ( 1 - P "\r" ) ^ 0 * P "\r" * Cc(1)
1825     ) ^ 0
1826     * (1 - P "\r" ) ^ 0 ,
1827     add
1828     ) * -1 ) : match (code)
1829   tex.sprint(
1830     luatexbase.catcodetables.expl ,
1831     '\\int_set:Nn \\l_@@_nb_non_empty_lines_int {' .. count .. '}' )
1832 end

1833 function piton.CountLinesFile(name)
1834   local count = 0
1835   for line in io.lines(name) do count = count + 1 end
1836   tex.sprint(
1837     luatexbase.catcodetables.expl ,
1838     '\\int_set:Nn \\l_@@_nb_lines_int {' .. count .. '}' )
1839 end

1840 function piton.CountNonEmptyLinesFile(name)
1841   local count = 0
1842   for line in io.lines(name)
1843   do if not ( ( P " " ) ^ 0 * -1 ) : match ( line ) )
1844     then count = count + 1
1845     end
1846   end
1847   tex.sprint(
1848     luatexbase.catcodetables.expl ,
1849     '\\int_set:Nn \\l_@@_nb_non_empty_lines_int {' .. count .. '}' )
1850 end
1851 \end{luacode*}

```

7 History

Changes between versions 1.3 and 1.4

New key identifiers in `\PitonOptions`.

New command `\PitonStyle`.

`background-color` now accepts as value a *list* of colors.

Changes between versions 1.2 and 1.3

When the class Beamer is used, the environment `{Piton}` and the command `\PitonInputFile` are “overlay-aware” (that is to say, they accept a specification of overlays between angular brackets).

New key `prompt-background-color`

It’s now possible to use the command `\label` to reference a line of code in an environment `{Piton}`.

A new command `_` is available in the argument of the command `\piton{...}` to insert a space (otherwise, several spaces are replaced by a single space).

Changes between versions 1.1 and 1.2

New keys `break-lines-in-piton` and `break-lines-in-Piton`.

New key `show-spaces-in-string` and modification of the key `show-spaces`.

When the class beamer is used, the environments `{uncoverenv}`, `{onlyenv}`, `{visibleenv}` and `{invisibleenv}`

Changes between versions 1.0 and 1.1

The extension `piton` detects the class `beamer` and activates the commands `\action`, `\alert`, `\invisible`, `\only`, `\uncover` and `\visible` in the environments `{Piton}` when the class `beamer` is used.

Changes between versions 0.99 and 1.0

New key `tabs-auto-gobble`.

Changes between versions 0.95 and 0.99

New key `break-lines` to allow breaks of the lines of code (and other keys to customize the appearance).

Changes between versions 0.9 and 0.95

New key `show-spaces`.

The key `left-margin` now accepts the special value `auto`.

New key `latex-comment` at load-time and replacement of `##` by `#>`

New key `math-comments` at load-time.

New keys `first-line` and `last-line` for the command `\InputPitonFile`.

Changes between versions 0.8 and 0.9

New key `tab-size`.

Integer value for the key `splittable`.

Changes between versions 0.7 and 0.8

New keys `footnote` and `footnotehyper` at load-time.

New key `left-margin`.

Changes between versions 0.6 and 0.7

New keys `resume`, `splittable` and `background-color` in `\PitonOptions`.

The file `piton.lua` has been embedded in the file `piton.sty`. That means that the extension `piton` is now entirely contained in the file `piton.sty`.

Contents

1 Presentation

1

2	Use of the package	2
2.1	Loading the package	2
2.2	The tools provided to the user	2
2.3	The syntax of the command <code>\piton</code>	2
3	Customization	3
3.1	The command <code>\PitonOptions</code>	3
3.2	The styles	5
3.3	Creation of new environments	6
4	Advanced features	6
4.1	Highlighting some identifiers	6
4.2	Mechanisms to escape to LaTeX	8
4.2.1	The “LaTeX comments”	8
4.2.2	The key “math-comments”	8
4.2.3	The mechanism “escape-inside”	9
4.3	Behaviour in the class Beamer	10
4.3.1	<code>{Piton}</code> et <code>\PitonInputFile</code> are “overlay-aware”	10
4.3.2	Commands of Beamer allowed in <code>{Piton}</code> and <code>\PitonInputFile</code>	10
4.3.3	Environments of Beamer allowed in <code>{Piton}</code> and <code>\PitonInputFile</code>	11
4.4	Page breaks and line breaks	12
4.4.1	Page breaks	12
4.4.2	Line breaks	12
4.5	Footnotes in the environments of <code>piton</code>	13
4.6	Tabulations	13
5	Examples	13
5.1	Line numbering	13
5.2	Formatting of the LaTeX comments	14
5.3	Notes in the listings	15
5.4	An example of tuning of the styles	16
5.5	Use with <code>pyluatex</code>	17
6	Implementation	20
6.1	Introduction	20
6.2	The L3 part of the implementation	21
6.2.1	Declaration of the package	21
6.2.2	Parameters and technical definitions	23
6.2.3	Treatment of a line of code	25
6.2.4	<code>PitonOptions</code>	28
6.2.5	The numbers of the lines	29
6.2.6	The command to write on the aux file	30
6.2.7	The main commands and environments for the final user	30
6.2.8	The styles	35
6.2.9	The initial style	37
6.2.10	Highlighting some identifiers	38
6.2.11	Security	38
6.2.12	The error messages of the package	38
6.3	The Lua part of the implementation	40
6.3.1	Special functions dealing with LPEG	40
6.3.2	The LPEG python	42
6.3.3	The LPEG ocaml	52
6.3.4	The function <code>Parse</code>	57
6.3.5	Two variants of the function <code>Parse</code> with integrated preprocessors	58
6.3.6	Preprocessors of the function <code>Parse</code> for gobble	58
6.3.7	To count the number of lines	59
7	History	60