

6



B



D

- ## NOTES

- ## NOTES (continued)

- ## SOURCES

- ### FIELD OF VIEW, deg, EVERY FIGURE

	FIGURE		H	V	DIAG	
65	Raspberry Pi	DECL	53.50	41.41	--	USED
	Arducam B0033	DECL	54	41	--	margin
	3.60 mm on the active array	DERI	53.50	41.41	64.42	agrees
AF	Arducam B0176	DECL	54	44	--	margin
	Arducam B0121	DECL	54	41	--	USED
	3.67 mm, from the 35 mm equivalent	DERI	52.62	40.70	63.44	margin
120	Arducam B006604 page	DECL	--	--	120	
	Arducam catalogue, B006604	DECL	120	90	--	REJECTED
	Arducam catalogue, B006604N	DECL	96	72	--	USED
	120 diagonal, equidistant	DERI	96	72	120	agrees
	120 diagonal, rectilinear	DERI	108.36	92.20	120	margin
	120 diagonal, equisolid	DERI	94.31	69.83	120	margin
	Commonlands CIL282, 2.2 mm	DECL	96	72	122	agrees
	YXFF4Y001A1, scaled to 120	DERI	94.43	70.82	120	margin
	YXFF4Y001A1, 1.79 mm	DECL, relabelled	92.40	73.90	119.90	margin

B

	f mm	F	FOCUS	RANGE, mm	HYPER m	NEAR m
65	3.60 DECL	F2.9 DECL	Fixed	1000 to inf	1.60 / 3.20	0.80 / 1.60
AF	3.67 DERI	F2.9 ASSU	Motorized	80 to inf	1.66 / 3.32	0.83 / 1.66
120	2.17 DERI	F2.4 ASSU	Fixed	1000 to inf	0.70 / 1.40	0.35 / 0.70
WS G	3.15 DECL	F2.35 DECL	Adjustable	100 to inf	--	--

C

Z	NEAR	FAR	DEPTH
80	76.5	83.9	7.4
100	94.5	106.2	11.7
150	137.8	164.5	26.7

- The 65 deg lens: rays, and its picture on the board
- - - The 120 deg lens: rays, and its picture on the board
- - - The rectangle the 120 deg lens's angles give
- Camera Module v1.3
- ▶ Dimension, extension and leader

D

DRAWN generated		VERSION v0.0-352-g967eb38	UNITS mm	SCALE 1:2.5
SIZE A3	SHEET 1 OF 1	DRAWING NO RPICAM-LENS		REV A
SUBJECT OV5647 lenses		GENERAL TOLERANCE angles as declared, DERI and ASSU as flagged		PROJECTION 