




NOTES

- 1. All dimensions in millimetres. The datum symbol marks the origin: the lower-left corner of the board outline, X right, Y up, viewed from the component side.
- 2. Geometry is design nominal, read from the KiCad board file.
- 3. Hole IDs are the board's own reference designators, taken from the KiCad file, not assigned by this drawing. They are not in any particular positional order.
- 4. Geometrically identical to revision v1.2.3: the outline, mounting holes, Pmod hosts and every feature on this sheet are in the same place. Only the electrical design and the shuttle differ.
- 5. Pmod host headers are on a 22.86 mm (0.9 in) pitch, per the Digilent Pmod Interface Specification 1.2.0.
- 6. The Pmod host headers along the lower edge are what a mounting plate has to register against. Their 22.86 mm pitch is identical on every Tiny Tapeout demo board revision, but their distance from the lower board edge and their absolute position along it are not.

NOTES (continued)

- 7. The chain-double-dot rectangle around each Pmod host pin field is the connector body, drawn where it overhangs the board edge. It is not a board feature; it is what a mating peripheral and any bracket have to clear.
- 8. Pmod host coordinates are tabulated to three decimals, unlike everything else on this sheet. That is not a claim to micrometre accuracy: rounded to two, two adjacent hosts print 22.85 apart and contradict the 22.86 pitch the specification mandates and this drawing dimensions.
- 9. Pmod host ports are lettered JA, JB, JC on the Pmod HAT Adapter and on the Raspberry Pi sheets, after Digilent's own labelling; named by signal direction on the Tiny Tapeout demo boards, after the silkscreen; and numbered PMOD 1 to 3 on the mounting plate sheets, which number positions rather than ports. The fitting guide TT-MP-02 maps a board's first host to a plate position.

HOLE SCHEDULE

ID	X mm	Y mm	DIA mm	KEEPOUT mm
MT1	3.75	3.75	3.20	6.40
MT2	100.75	3.75	3.20	6.40
MT3	3.75	77.25	3.20	6.40
MT4	100.75	77.25	3.20	6.40

PMOD HOST HEADERS

PORT	REF	EDGE	CX mm	CY mm	PIN1 X mm	PIN1 Y mm
INPUT	J3	bottom	27.695	4.275	34.045	5.545
BIDIR	J5	bottom	50.555	4.275	56.905	5.545
OUTPUT	J6	bottom	73.415	4.275	79.765	5.545

FEATURE SCHEDULE

#	FEATURE	X EXTENT mm	Y EXTENT mm
1	USB-C power / control	21.88 to 34.62	73.05 to 81.35
2	7-segment display	86.05 to 94.05	17.00 to 29.00
3	LED D1	100.07 to 101.53	69.52 to 72.48
4	LED D2	95.07 to 96.53	69.52 to 72.48
5	LED D3	90.97 to 92.43	69.52 to 72.48
6	LED D4	91.02 to 93.98	62.77 to 64.23
7	Side Pmod J12 (not fitted)	-8.55 to 6.30	9.83 to 26.08
8	Side Pmod J13 (not fitted)	-8.55 to 6.30	32.69 to 48.94
9	Side Pmod J14 (not fitted)	-8.55 to 6.30	55.55 to 71.80

NOTES (continued)

- 10. Board thickness is 1.6 mm nominal. The KiCad file states 1.56252 mm, which is the sum of its stackup layers rather than a specified finished thickness, so it is not quoted as one.
- 11. Upper edge carries a shallow recess for the USB-C shell, contributed by the connector footprint's own edge cuts (fillet radii 0.136 mm, 0.303 mm, 0.364 mm, 0.4 mm).

SOURCES

- 1. KiCad board file: <https://github.com/TinyTapeout/tt-demo-pcb> tinytapeout-demo.kicad_pcb @ cffd80d7b - title block: TinyTapeout 4+ Demoboard rev 1.2.2, dated 2024-04-26
- 2. Shuttle mapping: <https://github.com/TinyTapeout/tt-demo-pcb/blob/main/doc/historic/README.md> - used by: TT04

TINY TAPEOUT 4+ DEMO BOARD

tinytapeout-demo rev 1.2.2

DRAWN	DATE	UNITS	SCALE
generated	2026-09-10	mm	1:1
SIZE	SHEET	DRAWING NO	REV
A3	1 OF 1	TT-DB-02	A
MATERIAL		GENERAL TOLERANCE	
PCB, 1.6 nominal		edge +/-0.20 hole pos +/-0.10 hole dia +/-0.08	