




NOTES

1. Viewed from the component side.
2. All three models share this outline exactly: 85.00 x 56.00 mm, R3.00 corners and the same four mounting hole centres. Only the hole diameter and the keep-out differ.
3. The 40-pin GPIO header is in the same place on all three because the Raspberry Pi HAT specification fixes it; the three drawings were read separately and required to agree.
4. The Ethernet jack and the USB type A ports swap places between the Pi 3 and the Pi 4. On the Pi 3B/3B+ and on the Pi 5 the RJ45 sits in the lower right corner with the USB ports above it; on the Pi 4B the RJ45 is in the upper right corner with the USB ports below. A chassis cut for one will not take the other.
5. The Pi 5 adds AUX1 and AUX2, two 3.00 mm holes on the mounting hole axes. Power input is micro-USB on the Pi 3B/3B+ and USB-C on the Pi 4B and the Pi 5.
6. The three power inputs very nearly coincide: their nearest faces are 0.025 mm apart, so at 1:1 the three outlines print as one line and that corner cannot be read as three. The feature schedule gives each model's extents.
7. Assembled envelope, every model taken together and connector overhang included: 88.00 x 57.32 mm. Each model's own is on its own sheet.
8. A balloon number means the same part on every Raspberry Pi sheet. Each leader goes to one place and carries a balloon for each model, left to right Pi 3B/3B+, Pi 4B, Pi 5, the ring in that model's own line type and colour, so a row reads which part each model puts there. The 40-pin header, the same part on all three, has one plain balloon.

NOTES (continued)

9. Design keep-outs to 6.2 mm diameter around every mounting hole, per the Raspberry Pi HAT specification. The phantom circles are that figure; KEEPOUT gives what each model's own drawing shows.
10. The Diligent Pmod HAT Adapter is not drawn. It is the same on all three, and its phantom pin fields would lie across the lower edge and the right-hand connectors, which are what this sheet exists to show; RPI-3B, RPI-4B, RPI-5 and ACC-HAT-PMOD carry it.
11. HDMI, micro-HDMI and the 3.5 mm audio jack are deliberately not drawn on any sheet of this family.
12. SOURCES lists the drawings only; what was read from each, and the drawing notes quoted from it, are on that model's own sheet.

SOURCES

1. Pi 3B/3B+, Mechanical drawing: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-mechanical-drawing.dxf>
2. Pi 3B/3B+, Mechanical drawing: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-plus-mechanical-drawing.dxf>
3. Pi 3B/3B+, Mounting holes: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-mechanical-drawing.pdf>
4. Pi 4B, Mechanical drawing and mounting holes: <https://datasheets.raspberrypi.com/rpi4/raspberry-pi-4-mechanical-drawing.dxf>

FEATURE SCHEDULE

#	ON	FEATURE	X EXTENT mm	Y EXTENT mm
1	all three	40-pin GPIO header	7.10 to 57.90	50.00 to 55.00
2	Pi 3B/3B+	micro-USB power input	6.85 to 14.35	-0.60 to 4.71
2	Pi 4B	USB-C power input	6.88 to 15.53	-1.25 to 6.15
2	Pi 5	USB-C power input	7.84 to 14.52	-1.32 to 6.00
3	Pi 3B/3B+	Ethernet RJ45	65.65 to 87.00	2.50 to 18.00
3	Pi 4B	Ethernet RJ45	66.65 to 88.00	37.99 to 53.51
3	Pi 5	Ethernet RJ45	66.72 to 87.96	2.21 to 18.19
4	Pi 3B/3B+	USB 2.0 type A (upper pair)	69.30 to 87.00	39.65 to 53.57
4	Pi 4B	USB 3.0 type A (upper pair)	70.50 to 88.00	20.43 to 34.25
4	Pi 5	USB 3.0 type A (upper pair)	70.92 to 87.24	40.84 to 53.15
5	Pi 3B/3B+	USB 2.0 type A (lower pair)	69.30 to 87.00	21.65 to 35.57
5	Pi 4B	USB 2.0 type A (lower pair)	70.30 to 88.00	1.65 to 15.57
5	Pi 5	USB 3.0 type A (lower pair)	70.92 to 87.24	22.92 to 35.16

HOLE SCHEDULE

ID	X mm	Y mm	ON	DIA mm 3B / 4B / 5	KEEPOUT mm 3B / 4B / 5
MT1	3.50	3.50	all three	2.75 +/-0.05 / 2.70 / 2.70	not given / 6.00 / 5.80
MT2	61.50	3.50	all three	2.75 +/-0.05 / 2.70 / 2.70	not given / 6.00 / 5.80
MT3	3.50	52.50	all three	2.75 +/-0.05 / 2.70 / 2.70	not given / 6.00 / 5.80
MT4	61.50	52.50	all three	2.75 +/-0.05 / 2.70 / 2.70	not given / 6.00 / 5.80
AUX1	3.50	9.50	Pi 5	- / - / 3.00	- / - / not given
AUX2	61.50	46.50	Pi 5	- / - / 3.00	- / - / not given

LEGEND

- Outline, mounting holes and 40-pin GPIO header: identical on all three models
- Mounting hole keep-out, 6.2 dia, per the HAT specification
- Pi 3B/3B+: power input, Ethernet and USB
- Pi 4B: power input, Ethernet and USB
- Pi 5: power, Ethernet, USB and its two extra holes
- Balloons on one leader: one per model, Pi 3B/3B+, Pi 4B, Pi 5, left to right
- Dimension, extension and callout leader

SOURCES (continued)

5. Pi 5, Mechanical drawing and mounting holes: <https://datasheets.raspberrypi.com/rpi5/raspberry-pi-5-mechanical-drawing.pdf>

RASPBERRY PI 3B/3B+, 4B AND 5 COMPARED

One 85 x 56 outline: what is shared and what moves

DRAWN	VERSION	UNITS	SCALE
generated	v0.0-428-ge99aeaa	mm	1:1
SIZE	SHEET	DRAWING NO	REV
A3	1 OF 1	RPI-ALL	A
MATERIAL	GENERAL TOLERANCE		
- not a made part	reference only - governed by RPI-3B, RPI-4B and RPI-5		