




NOTES

1. Viewed from the component side.
2. Phantom outline is the Digilent Pmod HAT Adapter fitted on the 40-pin GPIO header; its mounting holes coincide with this board's.
3. Hole IDs are assigned by this drawing and mean the same hole on every Raspberry Pi sheet.
4. The Raspberry Pi 3 Model B and Raspberry Pi 3 Model B+ drawings agree on every hole and connector position, so one sheet covers both.
5. The 40-pin GPIO header position is fixed by the Raspberry Pi HAT specification, so it is the same on every Raspberry Pi sheet.
6. Design keep-outs to 6.2 mm diameter around every mounting hole, per the Raspberry Pi HAT specification; KEEPOUT gives what this model's own drawing shows.
7. Pmod host JC overhangs the lower edge, over the HDMI and power connectors. Fit the two standoffs opposite the 40-pin header, as Digilent's manual warns, so JC's pins cannot touch the HDMI shell. HDMI connectors are not drawn.

NOTES (continued)

8. Pmod HAT Adapter host positions are DERIVED, good to about +/-0.75 mm; drawing ACC-PMOD-HAT has the derivation.
9. Assembled envelope, connector overhang included: 87.00 x 56.60 mm.

SOURCES

1. Mechanical drawing: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-mechanical-drawing.dxf> - Raspberry Pi Ltd
2. Mechanical drawing: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-plus-mechanical-drawing.dxf> - Raspberry Pi Ltd, Raspberry Pi 3 Model B+
3. Mounting holes: <https://datasheets.raspberrypi.com/rpi3/raspberry-pi-3-b-mechanical-drawing.pdf> - Drawing note on the Model B drawing, quoted: 4x M2.5 MOUNTING HOLES DRILLED TO 2.75 +/- 0.05mm. The B+ drawing gives no hole size, but its geometry is identical.

HOLE SCHEDULE

ID	X mm	Y mm	DIA mm	KEEPOUT mm
MT1	3.50	3.50	2.75 +/-0.05	not given
MT2	61.50	3.50	2.75 +/-0.05	not given
MT3	3.50	52.50	2.75 +/-0.05	not given
MT4	61.50	52.50	2.75 +/-0.05	not given

FEATURE SCHEDULE

#	FEATURE	X EXTENT mm	Y EXTENT mm
1	40-pin GPIO header	7.10 to 57.90	50.00 to 55.00
2	micro-USB power input	6.85 to 14.35	-0.60 to 4.71
3	Ethernet RJ45	65.65 to 87.00	2.50 to 18.00
4	USB 2.0 type A (upper pair)	69.30 to 87.00	39.65 to 53.57
5	USB 2.0 type A (lower pair)	69.30 to 87.00	21.65 to 35.57

PMOD HAT ADAPTER HOSTS

PORT	EDGE	CX mm	CY mm	PIN1 X mm	PIN1 Y mm
JA	left edge	9.400	39.290	8.130	45.640
JB	left edge	9.400	16.430	8.130	22.780
JC	bottom edge	27.600	9.400	21.250	8.130


LEGEND

- Board outline
- Component body, scheduled
- Adjacent part
- Dimension, extension and leader

RASPBERRY PI 3 MODEL B AND B+

85 x 56 mm, both models

DRAWN generated		VERSION v0.0-171-g3d6831c	UNITS mm	SCALE 1:1	
SIZE A3	SHEET 1 OF 1	DRAWING NO RPI-3B			REV A
MATERIAL PCB, thickness not stated		GENERAL TOLERANCE edge +/-0.20 hole pos +/-0.10 hole dia per schedule			



HOLE SCHEDULE

ID	X mm	Y mm	DIA mm	KEEPOUT mm
MT1	3.50	3.50	2.70	6.00
MT2	61.50	3.50	2.70	6.00
MT3	3.50	52.50	2.70	6.00
MT4	61.50	52.50	2.70	6.00

FEATURE SCHEDULE

#	FEATURE	X EXTENT mm	Y EXTENT mm
1	40-pin GPIO header	7.10 to 57.90	50.00 to 55.00
2	USB-C power input	6.88 to 15.53	-1.25 to 6.15
3	Ethernet RJ45	66.65 to 88.00	37.99 to 53.51
4	USB 3.0 type A (upper pair)	70.50 to 88.00	20.43 to 34.25
5	USB 2.0 type A (lower pair)	70.30 to 88.00	1.65 to 15.57

PMOD HAT ADAPTER HOSTS


PORT	EDGE	CX mm	CY mm	PIN1 X mm	PIN1 Y mm
JA	left edge	9.400	39.290	8.130	45.640
JB	left edge	9.400	16.430	8.130	22.780
JC	bottom edge	27.600	9.400	21.250	8.130

LEGEND

- Board outline
- Component body, scheduled
- - - Adjacent part, hole keep-out
- Dimension, extension and leader

RASPBERRY PI 4 MODEL B

85 x 56 mm			
DRAWN generated		VERSION v0.0-171-g3d6831c	
UNITS mm		SCALE 1:1	
SIZE A3	SHEET 1 OF 1	DRAWING NO RPI-4B	
MATERIAL PCB, thickness not stated		GENERAL TOLERANCE edge +/-0.20 hole pos +/-0.10 hole dia +/-0.08	



NOTES

- Viewed from the component side.
- Phantom outline is the Digilent Pmod HAT Adapter fitted on the 40-pin GPIO header; its mounting holes coincide with this board's.
- Hole IDs are assigned by this drawing and mean the same hole on every Raspberry Pi sheet.
- The 40-pin GPIO header position is fixed by the Raspberry Pi HAT specification, so it is the same on every Raspberry Pi sheet.
- Design keep-outs to 6.2 mm diameter around every mounting hole, per the Raspberry Pi HAT specification; KEEPOUT gives what this model's own drawing shows.
- Pmod host JC overhangs the lower edge, over the HDMI and power connectors. Fit the two standoffs opposite the 40-pin header, as Digilent's manual warns, so JC's pins cannot touch the HDMI shell. HDMI connectors are not drawn.
- Pmod HAT Adapter host positions are DERIVED, good to about +/-0.75 mm; drawing ACC-PMOD-HAT has the derivation.

NOTES (continued)

- Assembled envelope, connector overhang included: 87.96 x 57.32 mm.

SOURCES

- Mechanical drawing: <https://datasheets.raspberrypi.com/rpi5/raspberry-pi-5-mechanical-drawing.pdf> - Raspberry Pi Ltd
- Mounting holes: <https://datasheets.raspberrypi.com/rpi5/raspberry-pi-5-mechanical-drawing.pdf> - Hole diameter dimensioned on the drawing as $\varnothing 2.7$ mm; the keep-out circle is drawn and measures 5.80 mm.

HOLE SCHEDULE

ID	X mm	Y mm	DIA mm	KEEPOUT mm
MT1	3.50	3.50	2.70	5.80
MT2	61.50	3.50	2.70	5.80
MT3	3.50	52.50	2.70	5.80
MT4	61.50	52.50	2.70	5.80
AUX1	3.50	9.50	3.00	not given
AUX2	61.50	46.50	3.00	not given

FEATURE SCHEDULE

#	FEATURE	X EXTENT mm	Y EXTENT mm
1	40-pin GPIO header	7.10 to 57.90	50.00 to 55.00
2	USB-C power input	7.84 to 14.52	-1.32 to 6.00
3	Ethernet RJ45	66.72 to 87.96	2.21 to 18.19
4	USB 3.0 type A (upper pair)	70.92 to 87.24	40.84 to 53.15
5	USB 3.0 type A (lower pair)	70.92 to 87.24	22.92 to 35.16

PMOD HAT ADAPTER HOSTS

PORT	EDGE	CX mm	CY mm	PIN1 X mm	PIN1 Y mm
JA	left edge	9.400	39.290	8.130	45.640
JB	left edge	9.400	16.430	8.130	22.780
JC	bottom edge	27.600	9.400	21.250	8.130

LEGEND

- Board outline
- Component body, scheduled
- Adjacent part, hole keep-out
- Dimension, extension and leader

RASPBERRY PI 5

85 x 56 mm

DRAWN generated		VERSION v0.0-171-g3d6831c		UNITS mm		SCALE 1:1	
SIZE A3	SHEET 1 OF 1		DRAWING NO RPI-5				REV A
MATERIAL PCB, thickness not stated			GENERAL TOLERANCE edge +/-0.20 hole pos +/-0.10 hole dia +/-0.08				