

The Embedded-Chain RGA

A tombstone-free replicated list whose sort keys are the birth chains,
entropy-optimally encoded — design, proofs, validation, and related work

Sal / FP Launchpad — KC + Claude

working names in the artifact: `embed-tree` (unary), `embed-code` (delta-coded)

2026-07-14; revised 2026-07-15 (the datatype separated from its encoding)

Abstract

The embedded-chain RGA is a replicated list (a sequence MRDT for three-way merges with an LCA) built from one idea: an element’s sort key is its *birth chain* — the sequence of timestamps from the root of the birth tree down to the element, dead ancestors included — written at birth and never edited. Display order is lexicographic order on birth chains (per level: newest first, RGA’s rule); deletion removes the element’s record and nothing else; the merge is OR-set survival over event sets, contains no repair, and never decides an order. Timestamps are unique, so *ties cannot exist*; chains travel with the insert events, so the state is a canonical function of the event set. The whole state is the live nodes — no tombstones, no ledger, no event log: the dead persist only as entries inside their descendants’ sort keys. On top of this sits a separable *representation* layer: chains are carried as parent-relative dyadic intervals through an order-preserving prefix-free code of the timestamp *differentials*, which realizes chain concatenation as affine composition, turns deletion into an exact isometric fold, and prices a dead ancestor at $\Theta(\log \delta)$ coordinate bits — the entropy of the race that created it, the information-theoretic minimum, paid only at genuine races. The design is machine-validated: clean on the L1–L25 anomaly battery (except backward-run interleaving L19, the published RGA’s own anomaly) and on 420+ randomized version-DAG executions, and **lockstep read-equal with the published tombstoned RGA at every step of 120 randomized executions**. Insert operations carry the anchor’s birth chain — consulted by no reachable execution, kept because the proof of `rc` = Either commutation requires totality of reordered application; the prefix is ghost state in the strict, machine-checkable sense. We give the datatype and its one-line metatheory, the encoding and its faithfulness theorem, the validation record, a detailed comparison with Eg-walker, related work, and the Lean mechanization plan on the proved RGA scaffolding.

1 The datatype: sort keys are birth chains

Timestamps $t \in \mathbb{N}^+$ are Lamport stamps, globally unique, and double as element identities. Causality gives: the anchor of every insert carries a smaller timestamp than the insert itself.

The birth tree. Every insert names an anchor. The event set therefore induces a tree: the root is the front sentinel 0; the *birth parent* of each element is its anchor. The tree is append-only and never edited — an element’s place in it is fixed at birth.

Birth chains. The *birth chain* of u is the sequence of timestamps from the root down to u (sentinel elided): $\text{chain}(u) = \text{chain}(a) \cdot u$ when u was inserted after anchor a , and $\text{chain}(u) = \langle u \rangle$ at the front. Dead ancestors are *not* elided: their timestamps remain in their descendants’ chains. The

chain is the sort key, and everything in this section is stated in terms of it; nothing here depends on how chains are stored (§2).

Type. A state is a finite map over *live nodes only*:

$$\sigma : u \mapsto (\text{chain}(u), \text{char}_u).$$

init. $\sigma_0 = \emptyset$.

do (the operations). Two operations, with $\text{rc} = \text{Either}$ everywhere (§3):

- $\text{ins}(x \leftarrow a, c, \pi)$ — insert element x (its timestamp) with character c after anchor a ($a = 0$ for the front). The payload $\pi = \text{chain}(a)$ is the anchor’s birth chain, carried *for the proof alone* (§3). Application on a state where a is live (every reachable application, by honesty):

$$\sigma[x] := (\text{chain}_\sigma(a) \cdot x, c), \quad \pi \text{ unread.}$$

No head-tracking, no reading of siblings.

- $\text{del}(d)$ — remove d ’s record. Nothing else changes: survivors’ chains are untouched — in particular, d ’s descendants still carry d ’s timestamp in their sort keys. If d is absent, no-op (concurrent double delete).

read. Sort survivors by *chain-lex*: compare chains timestamp-by-timestamp with *larger first*; a proper prefix precedes its extensions (a live ancestor displays immediately before its descendants). Among same-parent siblings this is exactly RGA’s newest-first rule; equivalently, the canonical order is the RGA traversal of the birth tree restricted to survivors.

merge. $\text{merge}(L, A, B)$, L the LCA: *survival* (OR-set) — live iff in all three, or born in exactly one branch. There is no second step at this layer: survivors’ chains come with their insert events, so every input that holds a survivor agrees on its chain. The merge never compares timestamps and never decides an order.

Inv / applicable / honesty. The honesty contract is the proved RGA’s: an insert is *generated* at a replica where its anchor is live (you insert after a character you can see), and ins/del are *applied* on states where they are applicable (anchor live; delete of a live or already-dead node). On every reachable state, application never consults π . Canonicity (Theorem 1) doubles as Inv; at the representation layer, Theorem 2(iii) is its stored form.

$\approx$. Equality. The state is a canonical function of the event set (Theorem 1), so no quotient is needed — convergence is literal state equality.

The metatheory, which is nearly definitional. At this layer the design’s theorems all but evaporate; we record them because they are the specification the representation must meet (§2).

Theorem 1 (chain-level metatheory). *In every reachable state:*

- (i) *Canonicity:* $\sigma = \{u \mapsto (\text{chain}(u), \text{char}_u)\}$ over survivors u — the state is a function of the event set.

(ii) *Birth constancy*: $\text{chain}(u)$ is fixed at u 's insert and never edited by any later transition.

(iii) *Totality — no ties*: *chain-lex* is a total order on every state's survivors.

Proof. (i) Survivorship is OR-set — a function of the event set — and a survivor's chain is determined by its insert event alone: by induction, ins writes $\text{chain}_\sigma(a) \cdot x = \text{chain}(a) \cdot x$ (the anchor is live at application, by honesty, and its stored chain is canonical), while del and the merge only delete or select records, never rewrite them. (ii) is (i) read off per node: no transition writes to an existing record. (iii) Distinct elements' chains are distinct (they end in distinct timestamps); if neither is a prefix of the other, the first difference compares two distinct timestamps in $\mathbb{N}$ — uniqueness of Lamport stamps is the no-tie property; prefix pairs are ancestor/descendant, ordered by the prefix rule. $\square$

The one-line separation, and the conservation law. The repo's *proved* flat tombstone-free RGA fails the L1 delete-reorder litmus (the $[b, a, c] \rightarrow [c, b]$ anomaly) because its climb re-sorts a rehomed node by its own timestamp: *its sort key is the birth chain truncated at each rehoming*. This design keeps the chain whole. That is the entire difference between the two datatypes, and it is the crisp form of the campaign's conservation law: *the sort key must retain dead ancestors' timestamps* — every design that forgets them has a named machine-checked countermodel (§6). What is negotiable is only how many bits the retained timestamps cost; that is the subject of §2, and the answer is: the entropy of the races, and nothing else.

Worked example. 6 and 10 concurrently insert at the front: chains $\langle 6 \rangle$ and $\langle 10 \rangle$ — display $[10, 6]$, no arbitration, at every replica and merge order. Type 22, 16 under 6: chains $\langle 6, 22 \rangle$, $\langle 6, 16 \rangle$. Delete 6: the records of 22 and 16 are untouched and still carry 6's timestamp. A third party concurrently inserts 8 at the front: $\langle 8 \rangle$ sorts below $\langle 10 \rangle$ and above $\langle 6, 22 \rangle$ — display $[10, 8, 22, 16]$ whether 8 arrives before or after 6's death (machine-checked as the *credential countermodel*, the shape that kills every timestamp-oblivious variant, §4).

2 The representation: chains as entropy-coded coordinates

Everything above is the datatype; everything below is bits. A naive carrier would store a full timestamp at every chain level and compare whole chains at every read. The representation compresses the chains without disturbing their order — two independent codings, then a coordinate realization whose maintenance is purely local. What this section owes §1 is a single obligation, *faithfulness* (Theorem 2): the coordinate order must be exactly chain-lex, in every reachable state, forever. Correctness lives upstairs; this layer is an implementation that must not lie.

Step 1: differential coding. By causality $\delta = x - a \geq 1$. A chain-lex first difference always compares two entries with the *same* anchor (the shared prefix), and for a fixed anchor, ordering by x and by δ coincide — so each chain level may store the differential instead of the timestamp. This is where *pay for concurrency* enters: sequential typing has $\delta = 1$ at every level regardless of how long the document has lived, while a genuine race with timestamp gap g costs $\log_2 g$ bits. The differential is an encoding choice, not semantics — the mathematical object remains the timestamp.

Step 2: entropy coding. For $\delta \geq 1$ let L be the bit-length of δ and

$$C(\delta) = \underbrace{1 \cdots 1}_{L-1} 0 \text{ } (\delta \text{ with its leading bit removed}) \quad (|C(\delta)| = 2L - 1),$$

an order-preserving prefix-free code. *Any* order-preserving prefix-free code works here, and the artifact exists twice to prove it: **embed-tree** carries unary codes, **embed-code** the delta code above — two encodings of one datatype. The delta code is the entropy-optimal choice: $2\lceil \log_2 \delta \rceil + 1$ bits, Elias- γ -style.

The mint. Writing $b = 1 \cdot C(\delta)$ (a leading 1 keeps coordinates positive) and $w = 2^{-|b|-2}$, the mint is the second quarter of b 's dyadic cell:

$$M(\delta) = (0.b + w, 0.b + 2w) \subset [0.b, 0.b + 4w).$$

The quarter placement leaves a gap below and headroom above inside the cell, and the open space $(0.b + 2w, 0.b + 4w)$ is never minted — it exists so that the interval has room to *contain* the node's own subtree without touching the next cell.



Figure 1: Mints $M(\delta)$ for $\delta = 1..4$ inside the parent's unit interval (cell boundaries dotted). Larger deltas sit strictly higher; distinct deltas are disjoint with gaps; each mint is a quarter of its cell, leaving room for the node's own subtree.

The stored state. The carrier stores each live node parent-relatively:

$$\sigma : t \mapsto (\text{par} \in \mathbb{N}, (lo, hi) \subset (0, 1), \text{char}),$$

where (lo, hi) is a dyadic-rational interval *relative to the parent's interval*, and $\text{par} = 0$ denotes the root sentinel (which owns $(0, 1)$ and is never stored). A node's *absolute* interval is the affine composition of the intervals along its parent chain; write

$$\alpha(u) = \varphi_{c_1} \circ \dots \circ \varphi_{c_k}(M(\delta_u))$$

for the composition of the mints along u 's birth chain $c_1 \dots c_k u$ (where φ_v maps $(0, 1)$ onto v 's mint interval, order-preservingly, and δ_v is v 's delta to its birth parent): $\alpha(u)$ is the *encoding of chain*(u). Semantically the coordinates are rationals; the natural carrier is a bit string per node (below).

Maintenance. How the stored form tracks the datatype:

- **ins**($x \leftarrow a$) mints $M(x - a)$ relative to a : the new record depends only on the two timestamps.
- **del**(d) *isometrically folds* d into its children: each child c is re-parented to d 's parent with d 's interval composed in, $c.\text{frac} := d.\text{frac} \circ c.\text{frac}$ — an exact affine substitution. Note what this is: upstairs, deletion changes nobody's sort key (§1); the fold is the parent-relative storage scheme *re-normalizing* while every absolute interval stays fixed. Representation maintenance, not datatype semantics.
- The merge *refolds*: for each survivor, compute its absolute interval by folding its record to the root inside the input that holds it (a record's stored parent is always live in its own input, so the chain stays in one input; by Theorem 2(iii) the choice of input cannot matter — asserted at runtime, never fired); re-parent to the nearest *surviving* ancestor; re-relativize.
- The read is depth-first from the root, children in descending order of lo . No tie rule is needed (Corollary 1).

The one obligation. The four theorems of the earlier drafts collapse into a single statement about the encoding.

Theorem 2 (encoding faithfulness). *(i) Order-embedding at one level: for $\delta \neq \delta'$, $M(\delta)$ and $M(\delta')$ are disjoint with a gap; $\delta < \delta' \Rightarrow M(\delta)$ lies entirely below $M(\delta')$.*

(ii) Homomorphism: α realizes chain concatenation as affine composition and embeds chain-lex in the interval order: for distinct u, v , if $\text{chain}(u)$ is a proper prefix of $\text{chain}(v)$ then $\alpha(v) \subset \alpha(u)$ (and, if both are live, the two are never read-time siblings); otherwise $\alpha(u) \cap \alpha(v) = \emptyset$, with the chain-lex-greater element's interval strictly higher.

(iii) Exact maintenance: in every reachable state, every live node's stored records compose to exactly $\alpha(u)$.

Proof. (i) C is prefix-free: codes of lengths $2L-1 < 2M-1$ differ at position L (the shorter's header terminator 0 against the longer's header 1); equal-length codes differ in the payload. Prefix-free codes have pairwise-disjoint dyadic cells. C is monotone as a binary fraction: within a length class the payload is δ 's low bits in order; across classes the position- L bit decides in favor of the longer code. Disjoint cells ordered by their codes, and mints interior quarters of their cells, give both claims. (ii) If neither chain is a prefix of the other, they first differ on distinct deltas relative to the *same* birth ancestor (§2, step 1); (i) separates them there, and affine images of disjoint intervals are disjoint and order-preserved (each φ is increasing). If $\text{chain}(u)$ prefixes $\text{chain}(v)$, then $\alpha(v) \subseteq \varphi_{c_1} \circ \dots \circ \varphi_{c_k}(\varphi_u((0, 1))) = \alpha(u)$ by construction; and if both are live, v 's nearest live ancestor is u or deeper — so they never share a current parent, and sibling groups are pairwise disjoint. (iii) By induction over transitions. *ins* establishes it by definition. *del*'s fold replaces (par, frac) pairs by their exact composition — α is unchanged. The merge recomputes precisely $\alpha(u)$ (folding a record chain to the root) and re-relativizes against another α ; ties cannot exist by (i) and (ii), so no step of any transition ever rewrites an interval by anything but exact composition. $\square$

Corollary 1 (display $\equiv$ chain-lex; no tie rule). *The read (DFS by descending lo) enumerates survivors in exactly chain-lex order — per level, larger delta first: among same-parent siblings, exactly newest first; survivors rank by their own timestamps, folded heirs by their dead founder's. Sibling lo-values never tie; the read's id tiebreak is dead code. Machine checks: pairwise sibling disjointness asserted at every read of 320 randomized executions — clean; over 19,531 multi-member sibling groups, own-timestamp order violated 3,481 times (exactly the post-fold heir groups — forcing own-ts there is the refuted dissolution behavior), **chain-lex violated 0 times**.*

The entropy law. A coordinate is the concatenation of the codes along the birth chain: $\Theta(\sum_i \log \delta_i)$ bits — the entropy of the chain. Sequential typing ($\delta = 1$ at every level) costs ~ 4 bits per level; a race with timestamp gap g costs $2 \log_2 g + O(1)$ bits. *The state pays for the magnitude of actual concurrency, and for nothing else.* Measured (1000 elements):

scenario	unary mint	delta-coded mint	quarter carve (ts-oblivious, refuted)
chain then delete-all ($\delta=1$)	2^{502501} (~ 61 KB)	2^{4001} (~ 0.5 KB)	2^{2001}
1000 root siblings ($\delta=t$)	max 2^{1003} , 125 KB total	max 2^{23} , 5 KB total	— (ties)

The carrier. The natural representation is a **parent-relative bit string per node**: the fold is concatenation, comparison is lexicographic — $O(1)$ -ish with structure sharing; the rationals are the semantics of the strings, kept for the proofs. IEEE 754 binary64 is machine-refuted as the carrier — a faithfulness failure, not a design failure: mints degenerate at $t = 52$, depths underflow at 44, and rounding voids Theorem 2(iii) (6/120 PBT executions die). The obstruction is a pigeonhole — chains carry $\Theta(\sum \log \delta)$ bits, a fixed-width word holds 64 — but binary64 is sound as a *comparison cache* with exact fallback on float equality.

What remains open. Dead chain entries concatenated into survivors’ strings are the conservation law’s irreducible content (§1); reclaiming them under *causal stability* (renumber once every replica has seen the delete — the only condition under which rewriting geometry is safe, since no verdict involving the dead can be contested again) is the one open cost item, and it is orthogonal to correctness.

3 The insert prefix: for the proof, and the proof alone

The proved tombstone-free RGA’s *why-the-path-matters* analysis applies verbatim, and this design inherits its discipline.

Why rc must be Either. In the Sal framework, any oriented conflict-resolution entry for an insert/delete pair awakens the machine-refuted `cond_comm_base` obligation: ordering $\text{ins}(x \leftarrow a)$ against $\text{del}(a)$ (in either direction) is undischargable as a conflict entry, because rehoming is non-transitive across chains of deletions. So `rc` = `Either`: the proof must show the two *commute*, in both orders, on all applicable states.

The commutation, and where the prefix earns its keep. Order 1: $\text{ins}(x \leftarrow a)$ then $\text{del}(a)$ — x is born with chain $\pi \cdot x$, and the delete touches no chain (downstairs: the fold re-homes x ’s record with composed coordinates; by exactness $\alpha(x) = \alpha(a) \circ M(x - a)$). Order 2: $\text{del}(a)$ then $\text{ins}(x \leftarrow a)$ — a is gone; application must still be *total* and land x on the same sort key. This is what the carried prefix $\pi = \text{chain}(a)$ (equivalently, the anchor’s coordinate — its chain of codes) provides: apply sets $\text{chain}(x) = \pi \cdot x$ (downstairs: $\alpha(x) = \pi \circ M(x - a)$, attached to the nearest live ancestor). The two orders produce *equal* states — commutation to equality, not merely up to $\approx$, courtesy of canonicity (Theorem 1).

Ghost, in the strict sense. On every reachable state the anchor is live at application (honesty), and the application reads only the state and the two timestamps: π is never consulted. The Lean artifact carries this as `ins_prefix_ghost` (`Sal/MRDTs/RGA_Embed/RGA_Embed_MRDT.lean`): on accurate ops the *always- π* transition and the state-reading transition are literally the same function — the two conventions of this section coincide on every honest state. An implementation may therefore drop π from the wire entirely; the *proof* may not, because the verification conditions quantify over reorderings that visit unreachable states, and there application without π is partial. The prefix costs $O(\sum \log \delta)$ bits — the same entropy as the coordinate itself — and exists at the proof layer alone.

4 Validation

All numbers reproduce from `whiteboard/litmus/` (`embed_tree.py`; harnesses `litmus.py`, `pbt.py`).

check	verdict
litmus battery L1–L25 (incl. every countermodel that killed 16 prior designs: ceiling escapes, tie inheritance, three-branch topology, frame mixing, fold-verdict inheritance)	clean, except one-sided L19 (backward-run interleaving — the published RGA’s own anomaly)
credential countermodel (tie heirs vs mid-ts third party, death-before vs death-after topologies)	converges, no flips — = RGA _† ’s reads
subordination-escape and retroactive-subordination CEs	survive
randomized version-DAG PBT (FLIP / CONV / LIVE / DUP)	120/120 and 300/300 clean
per-read sibling-disjointness assertion sweep	320/320 clean
chain-lex instrumentation (19,531 sibling groups)	0 violations
lockstep vs the published tombstoned RGA	read-equal at every apply/merge/read, 120/120
L1 delete-reorder vs the proved flat tombstone-free RGA	embed [2, 3] ✓ vs flat [3, 2] ×

The lockstep row is the identification: *the embedded-chain RGA is observationally the published tombstoned RGA with the tombstone set compressed into coordinate entropy* — machine-checked on 120 executions; the read-for-read theorem is the mechanization target, not yet a theorem. The L1 row is the separation from the repo’s *proved* flat tombstone-free RGA, and it is exactly the one-line difference of §1: that design’s climb re-sorts a rehomed node by its own timestamp (the $[b, a, c] \rightarrow [c, b]$ anomaly), i.e. its sort key is the birth chain *truncated at each rehoming*; this design keeps the chain whole.

5 Comparison with Eg-walker

Eg-walker (Gentle & Kleppmann, EuroSys 2025) is the closest system in spirit, and the two designs can be read as the *operational* and *denotational* realizations of the same thesis — **pay for concurrency, not for history**:

	Eg-walker	embedded-chain RGA
model	op-based; replicas exchange events	MRDT: three-way merge with an LCA
durable state	full event graph on disk , deletes included, retained while concurrent ops may arrive; document state metadata-free	live nodes only ; no event log anywhere; dead survive as $\Theta(\log \delta)$ bits inside live coordinates
merge mechanism	<i>replay</i> : walk the event graph, rebuild a transient CRDT structure (tombstones reappear transiently), discard at causally-linear points	<i>refold</i> : $O(\text{survivors})$ coordinate recomputation; no replay, no transient structure, no order decisions
sequential-editing cost	$\approx$ zero (plain edits; no metadata)	$\approx$ zero order metadata (~ 4 bits/level; plain append-like behavior)
concurrency cost	replay time proportional to the concurrent region, at every affected merge	coordinate bits proportional to $\log(\text{ts gap})$, once, in space
ordering semantics	Yjs-variant (FugueMax-adjacent); maximal non-interleaving <i>conjectured</i> , not proved; two-sided (no L19 analogue)	$\equiv$ published RGA (machine lockstep); one-sided — L19 backward-run interleaving inherited, two-sided extension future work
correctness artifact	informal proof (Appendix C) + property testing	L1–L25 battery + DAG PBT + lockstep vs RGA ₊ ; Lean mechanization as the deliverable — the design was chosen so the merge proves itself (no order decisions to verify)
op payload	integer origin positions (compact, human-meaningful)	two timestamps + ghost prefix (droppable on the wire; §3)

Three sentences of honest positioning. *(i)* Eg-walker achieves its clean document state by keeping the entire history and re-deriving order on demand; the embedded-chain RGA achieves it by making order derivation unnecessary — the sort keys are written at birth and never edited, and the coordinates are their encoding (§2), precomputed at mint time and exact forever. *(ii)* Eg-walker’s ordering target is stronger where L19 is concerned (Fugue-style two-sidedness removes backward interleaving; this design inherits RGA’s one-sided anomaly — by construction, since it is read-equal to RGA). *(iii)* The verification gap runs the other way: Eg-walker’s replay-transform-clear loop is algorithmically sophisticated and only informally proved; here the merge performs no arbitration at all, the metatheory is one-line at the chain layer plus a single faithfulness theorem at the encoding layer, and the mechanization inherits a proved scaffolding (§7). In the MRDT setting there is also a model fit: Eg-walker must reconstruct merge context by replay because the op-based model gives it none; the MRDT model hands the merge its LCA, which is exactly the context replay rebuilds.

6 Related work

The verified landscape sweep lives in `whiteboard/litmus/related-work.md` (per-claim verdicts, primary sources); this section positions the datatype.

Retention taxonomy. What nearby systems keep for the dead: tombstone records (RGA with cemetery under causal stability; WOOT; Yjs’s per-deletion GC structs, kept forever; Fugue —

“we cannot remove a deleted element’s node entirely”; Peritext — “the positions must be remembered”); the full history (Eg-walker’s event graph, Chronofold/causal trees where the log *is* the text); consensus-gated compaction (Treedoc’s flatten requires Paxos-commit); or **dead identifiers inside live position keys** (Logoot/LSEQ, Weidner’s position-strings/list-positions — the Fugue id space). The embedded-chain RGA is in the last class *by information content* — dead ancestors’ timestamps persist inside survivors’ sort keys, at live-reachable scope — but with three deltas to its classmates: the retention is *entropy-optimal and delta-coded* (a sequential history costs a constant per element where Logoot-family keys grow with allocation policy), the *birth tree kept whole* gives forward non-interleaving and delete-order preservation (position-key designs interleave — the Pa-PoC’19 anomaly — and Figma-style fractional indexing is unsound under concurrency by its own account), and the semantics is pinned to the best-studied sequence CRDT by a machine-checked lockstep rather than being a new point in anomaly space.

The impossibility backdrop. Attiya et al. (PODC 2016) prove $\Omega(D)$ metadata for push-based protocols meeting even the weak list spec — the published form of “ordering requires remembering the dead.” This design does not escape the bound; it *relocates and minimizes* the memory: $\Theta(\log \delta)$ bits per dead-chain element inside live coordinates (plus the MRDT version store, which the model provides). The campaign’s sharper, machine- witnessed form is the *conservation law* (§1): the sort key must retain dead ancestors’ timestamps — the verdict information survives every encoding change (stamp, spine, tombstone, or denominator bits) — and ties force separate *metadata* only under timestamp-oblivious minting; the timestamp-faithful mint carries the same bits inside the coordinate. Eight timestamp-oblivious mutation variants each have a named machine-checked countermodel (fold-verdict erasure; repair non-locality); the credential countermodel separates this design from all of them.

Verified datatypes. Isabelle RGA (Gomes et al. OOPSLA’17, op-based convergence), OpSets (list semantics specified by a total order of identified ops — arbitration-by-identity as specification), VeriFx (SMT, convergence properties), MET (TLA+, list CRDT bugs). In the MRDT line (Kaki et al. OOPSLA’19; Peepul PLDI’22; RA-lin OOPSLA’25 — this framework), no verified sequence with sequence-CRDT-grade ordering guarantees exists; the proved flat tombstone-free RGA in this repo is own-fold RA-linearizable but fails the sequential delete-order spec (the spec-limit lesson). The embedded-chain RGA delivers the first part of the missing artifact — RA-linearizability is now a kernel-checked Lean theorem (§7) and delete-order preservation, display stability and forward non-interleaving are proved at the model layer — with the RGA read-equivalence (the remaining intent theorem) still owed.

Treedoc’s lesson, inverted. Treedoc re-balances geometry and must pay consensus for it; the delta-tree arc’s principle (*reprojection without consensus is safe iff geometry has been demoted to a rendering*) is here taken to its fixed point: geometry is never reprojected at all — it is immutable, so it may safely be the only thing.

7 Mechanization status

The capstone is proved (2026-07-15, kernel-clean on {propext, Classical.choice, Quot.sound}):

$$\text{embed_ra_linearizable3} : \text{EReach } \Gamma \ C \rightarrow \text{IsRALinearizable3 } C$$

— RA-linearizability per version at every honestly reachable configuration, *parametric in the code* Γ (both the entropy-optimal binary delta code and the unary code are proved `OrderedPrefixCode` instances). The factoring is exactly this note’s design–encoding split, which is itself evidence for the split:

1. **Model layer** (`Sal/MRDTs/RGA_Embed/`, four files, 0 sorry): the code-parametric kernel; commutations *to state equality* under `rc = Either (rc_non_comm')`; `ins_prefix_ghost`; coherence and chain-generation closures; display stability — step stability (S2, delete-order preservation at its ‘del’ instance) proved *without any axioms*, merge pairwise stability (S4, the adopted contract); unique decodability (`coordOf_inj`); **the chain-lex theorem** (`display_iff_chainBefore = Corollary 1`); non-interleaving as subtree convexity (`subtree_convex`); Theorem 2(i) for both codes (`binEnc_mono/binEnc_prefixFree`, cross-validated against the Python C by kernel `decide`); `native_decide` SPOTs where the flat RGA’s delete-reorder witness gets the opposite verdict.
2. **Conditioned instance** (`Sal/ConditionedMRDTs/MRDT_Instances/EmbedRGA/`, one file, seven sections, 0 sorry) — via the *mergeable-queue route* (`JoinLemma3At` + the `HonestReach` metatheorem), not the rehoming RGA’s 55-file conditioned chain: the route requires canonical states unique per event set, which is Theorem 1(i). Landed: the canonical sorted-list state; strictly-sorted extensionality (`esorted_ext` — sorted lists with the same members are equal, replacing any canonical-list formula); **fold-canonicity** (`e_fold_canon`: well-formed enumerations of one event set fold to the *same* state — Theorem 1(i) mechanized); the honesty core and its bridge to well-formedness; the merge membership characterization (`e_mergeL_mem`, OR-set survival with honesty closing the cross-branch-delete corner); the Join (`e_join_at` — the merge is its own linearization witness); and the capstone.

Still owed: the ‘applicable’-discharges-honesty layer (the generation discipline, mirroring the queue’s §8); intent theorems transported to the instance; and the equivalence target `read ◦ embed = read ◦ RGA†` on honest executions, stated at the chain layer (both sides are functions of the event set), which converts the design into a theorem *about* the published RGA: it admits a strictly-live compaction preserving every read. Until that lands, the lockstep identification of §4 remains machine-checked on the stated executions, not proved.

Provenance. `whiteboard/litmus/embed_tree.py` (the design, the timestamp-oblivious control, the credential countermodel, the IEEE 754 measurements; `python3 embed_tree.py / fp / code`); `litmus.py`, `pbt.py` (battery and DAG harness); `contest_tree.py` (lockstep harness, CE regressions); `whiteboard/retention-countermodel.pdf` (the retention arc that forced this design); `whiteboard/delta-tree-design.pdf` (the ledger-based sibling design and the invariants I1–I3); `whiteboard/litmus/related-work.md` (verified source list: Roh et al. JPDC’11; Attiya et al. PODC’16; Kleppmann et al. PaPoC’19; Weidner & Kleppmann TPDS’25 (Fugue); Gentle & Kleppmann EuroSys’25 (Eg-walker, arXiv:2409.14252); Pregoça et al. ICDCS’09 (Treedoc); Grishchenko & Patrakeev PaPoC’20 (Chronofold); Litt et al. CSCW’22 (Peritext); Gomes et al. OOPSLA’17; OpSets 2018; Kaki et al. OOPSLA’19; Peepul PLDI’22; RA-lin OOPSLA’25; VeriFy ECOOP’23; Figma/Wallace fractional indexing; Weidner position-strings).