

MatchMind — Watch to Web App

Supabase Sync Issues & Fixes (v1.3.7–v1.3.10)

Context

The MatchMind Garmin app records match data on-watch and POSTs it to Supabase after each match. The Training Hub web app will read that data to display a Tennis tab. The following issues were discovered and fixed while getting the data pipeline reliable.

1. Wrong Supabase API Key Format

(Fixed in v1.3.9)

Problem:

The anon key in Secrets.mc used the new sb_publishable_... format (Supabase SDK style). The Garmin app calls Supabase via raw REST (no SDK), which requires the JWT eyJ... token. All upload attempts silently failed — Supabase API logs showed zero requests to /rest/v1/matches.

Fix:

Updated SUPABASE_ANON_KEY in Secrets.mc to the correct JWT format (same key confirmed working in Training Hub).

2. HTTP Request Fired Too Early

(Fixed in v1.3.10)

Problem:

The startup retry called makeWebRequest() inside getInitialView(). This fires before the Garmin Communications layer is ready — in the simulator it returned -200; on a real watch it silently dropped the request. The supabase_payload key was never cleared, so every app launch attempted and failed the retry forever.

Fix:

Moved the retry from getInitialView() to onStart(), deferred by a 2-second Timer so the Communications layer is fully initialised before the request fires.

3. Garbage Collector Killed the Callback

(Fixed in v1.3.10)

Problem:

Even when the POST reached Supabase, the Monkey C garbage collector could destroy the SupabaseSync object before onResponse() fired. The upload succeeded on Supabase's side but the app never received the confirmation and never cleared the pending flag.

Fix:

Added a _matchSync field to TennisApp to anchor the SupabaseSync instance. Released to null inside onResponse() only after a confirmed 200/201/204 success.

4. Pending Upload Lost After Normal Match End

(Fixed in v1.3.8)

Problem:

The retry logic used the match resume state key (`tennis_match_state`) to reconstruct the engine on next launch. But `finishAndExit()` calls `clearState()`, which deletes that key. After a normal match end, the state was gone before the next launch — silent failure, no retry.

Fix:

The Supabase payload is now saved to a separate storage key (`supabase_payload`) at the moment the upload is attempted. This key is never touched by `clearState()` and is only cleared when `onResponse()` receives a 200 success.

Next Step

The data pipeline from watch to Supabase is now reliable. The next step is to build the Tennis tab in the Training Hub web app, reading match data from the Supabase matches table using the Supabase JS SDK.