Moon Mission Plant and Flight Software: Mathematics

1 Conventions

SI units throughout: meters, seconds, kilograms, radians. Frame: origin at Earth's center, z along Earth's rotation axis, x toward the vernal equinox, axes fixed relative to the stars (Earth-centered equatorial). Source: `workloads/moon/common/`.

2 Vectors

For $\mathbf{a}, \mathbf{b} \in \mathbb{R}^3$ and scalar s:

$$\mathbf{a} \cdot \mathbf{b} = a_x b_x + a_y b_y + a_z b_z \tag{1}$$

$$\mathbf{a} \times \mathbf{b} = (a_y b_z - a_z b_y,\ a_z b_x - a_x b_z,\ a_x b_y - a_y b_x) \tag{2}$$

$$\|\mathbf{a}\| = \sqrt{\mathbf{a} \cdot \mathbf{a}} \tag{3}$$

The cross product follows the right-hand rule: $\hat{x} \times \hat{y} = \hat{z}$. Code: `vec3.hpp`. Tests: `test_vec3.cpp`.

3 Constants

Symbol	Value	Unit	Source
μ_E	$3.986004418 \times 10^{14}$	$\mathrm{m}^3/\mathrm{s}^2$	IERS Conventions 2010
μ_M	$4.902800066 \times 10^{12}$	$\mathrm{m}^3/\mathrm{s}^2$	JPL DE430
R_E	6 378 137	m	equatorial radius
R_M	1 737 400	m	mean radius
ω_E	7.292115×10^{-5}	rad/s	sidereal rotation
a_M	3.844×10^{8}	m	mean Earth–Moon distance
ε	23.439°		obliquity of the ecliptic
i_M	5.145°		lunar orbit inclination to the ecliptic
ϕ_L	28.573°		launch latitude, Kennedy LC-39A
g_0	9.80665	m/s^2	standard gravity

Code: `constants.hpp`.

4 Time

Mission time t is seconds since the epoch $\mathrm{JD}_0 = 2\,434\,743.5$ (1954-01-01 00:00 UTC; Bart Howard's original "Fly Me to the Moon" sheet music was published in 1954). Julian centuries from J2000:

$$T = \frac{\mathrm{JD}_0 + t/86400 - 2\,451\,545.0}{36\,525} \tag{4}$$

5 Moon ephemeris

Circular orbit of radius a_M. Mean elements, Meeus, *Astronomical Algorithms*, ch. 47, linear terms (higher-order terms change the result by about 0.0003° at the epoch):

$$L' = 218.3164477^\circ + 481\,267.88123421^\circ\, T \qquad \text{mean longitude} \tag{5}$$

$$\Omega = 125.0445479^\circ - 1934.1362891^\circ\, T \qquad \text{ascending node} \tag{6}$$

$$u = L' - \Omega \qquad \text{argument of latitude} \tag{7}$$

Position in the ecliptic frame:

$$\mathbf{r}_{\text{ecl}} = a_M \begin{pmatrix} \cos\Omega\cos u - \sin\Omega\sin u\cos i_M \\ \sin\Omega\cos u + \cos\Omega\sin u\cos i_M \\ \sin u\,\sin i_M \end{pmatrix} \tag{8}$$

Rotation into the Earth-equatorial frame about x by ε:

$$\mathbf{r}_M = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos\varepsilon & -\sin\varepsilon \\ 0 & \sin\varepsilon & \cos\varepsilon \end{pmatrix} \mathbf{r}_{\text{ecl}} \tag{9}$$

The orbit's tilt I to Earth's equator follows from

$$\cos I = \cos\varepsilon\cos i_M - \sin\varepsilon\sin i_M\cos\Omega \tag{10}$$

At the epoch, $I = 25.988^\circ$, within the real range 18.3°–28.6° over the 18.6-year nodal cycle.

Limitations. The real orbit is eccentric ($e \approx 0.055$), so the modeled position differs from the true one by up to about 6° in longitude and 20 000 km in distance. $u = L' - \Omega$ is the standard approximation. Code: `moon_ephemeris.hpp`. Tests: `test_moon_ephemeris.cpp`.

6 Gravity

With $\mathbf{r}$ the spacecraft position, $\mathbf{r}_M$ the Moon position, and $r = \|\mathbf{r}\|$, $r_M = \|\mathbf{r}_M\|$:

$$\mathbf{g} = -\mu_E\frac{\mathbf{r}}{r^3} + \mu_M\left(\frac{\mathbf{r}_M - \mathbf{r}}{\|\mathbf{r}_M - \mathbf{r}\|^3} - \frac{\mathbf{r}_M}{r_M^3}\right) \tag{11}$$

The first term is Earth's pull. The Moon contribution is the third-body perturbation: the Moon's pull on the spacecraft minus the Moon's pull on Earth. The subtracted part, the indirect term, is required because the frame is centered on Earth, which itself accelerates toward the Moon. Near Earth the two Moon terms nearly cancel; near the Moon the first dominates. Code: `dynamics.cpp`. Tests: `test_dynamics.cpp`.

7 Engine and actuator limits

The flight software commands a throttle τ and a direction $\mathbf{d}$. The plant applies the limits of a real engine:

$$\tau' = \begin{cases} 1 & \tau > 1 \\ \tau & 0 < \tau \le 1 \\ 0 & \text{otherwise (including NaN)} \end{cases} \tag{12}$$

The engine is off ($\tau' = 0$) when $\|\mathbf{d}\|$ is zero, infinite, or NaN, or when the mass has reached the dry mass m_{dry}. Otherwise:

$$F = \tau' F_{\max} \tag{13}$$

$$\mathbf{a}_T = \frac{F}{m} \frac{\mathbf{d}}{\|\mathbf{d}\|} \tag{14}$$

$$\dot{m} = -\frac{F}{I_{sp}\, g_0} \tag{15}$$

The direction is normalized, so a corrupted command can point the engine anywhere but cannot push harder than full thrust. These limits are physics of the plant, not a flight software defense.

8 Equations of motion

$$\dot{\mathbf{r}} = \mathbf{v} \tag{16}$$

$$\dot{\mathbf{v}} = \mathbf{g}(\mathbf{r}, t) + \mathbf{a}_T \tag{17}$$

$$\dot{m} = -\frac{F}{I_{sp}\, g_0} \tag{18}$$

Code: `dynamics.cpp`, function `derivative`.