

Interactive Visualization of Time-Dependent Bipartite Graphs

Yahya Jabary*

Manuela Waldner†

Vienna University of Technology

Index Terms: Interactive Visualization, Temporal Graphs, Bipartite Graphs, Transparency Database

1 INTRODUCTION

Effective visualization of temporal graphs can reveal valuable insights such as patterns, trends, and anomalies that might otherwise remain hidden in raw data. This allows researchers, analysts, and decision-makers to quickly grasp evolving relationships, identify critical points of change, and make data-driven decisions.

In the context of global warming, multi-temporal scale visualizations of carbon emissions data can provide valuable insights for decision-makers, as demonstrated by Ma et al. [4]. In logistics, these visualizations can help optimize supply chain operations and identify inefficiencies [7] [5]. For social networks, they can illuminate user interactions and information spread. In public policy, temporal graph visualizations can aid in tracking disease spread, monitoring resource allocation and analyzing policy impacts [1]. These examples demonstrate how temporal graph visualizations compress temporal network data into intuitive representations. And as the volume and complexity of temporal data continue to grow across various domains, the development and application of effective visualization techniques for temporal graphs will likely become increasingly important.

As a practical example this paper explores various techniques for interactive visualization of time-dependent and bipartite graphs, using the “Media Transparency Database Austria” [3].

Time-dependent graphs or temporal graphs are structures that evolve over time, with nodes and edges changing as time progresses. These graphs are crucial for representing dynamic systems and processes that unfold chronologically. They allow us to observe patterns, trends, and changes in relationships between entities over different time periods [6]. One specific type of temporal graph that has gained prominence is the bipartite graph. **Bipartite** graphs or bigraphs consist of two distinct sets of nodes, with connections only existing between nodes from different sets, but not within the same set. If the two subsets have equal cardinality (balanced bigraph) and each node in one subset is connected to every node in the other subset, the graph is called a complete bigraph [2]. These graphs are particularly useful for modeling relationships between two different types of entities, such as public authorities and their advertising expenditures. Due to their scale and complexity, time-dependent and bipartite graphs can be challenging to visualize effectively. To make sense of the Media Transparency Database Austria, which contains thousands of entries over multiple years, we need to design scalable and **interactive visualizations** that allow users to explore the data, for example, by filtering, zooming, and selecting specific time periods or entities.

The “Media Transparency Database Austria” [3] is a public repository that records the advertising expenses of public authorities in Austria. This database serves as a tool for transparency (based on the Austrian § 34 Transparenzdatenbankgesetz 2012 TDBG), allowing citizens and researchers to track how public funds are spent on advertising across various media outlets. It provides a rich dataset that can be represented as both a time-dependent and

bipartite graph structure. By visualizing this data – although not the focus of this paper – we can gain insights into how public authorities allocate advertising budgets, which media outlets receive the most funding, and how these relationships evolve over time and across different entities.

akslndnakjsdnaklndkjsndaksjnd

By applying time-dependent and bipartite graph visualizations to the Media Transparency Database, we can uncover valuable insights. For instance, we can observe how advertising spending patterns change over time, which public authorities are the biggest advertisers, and which media outlets receive the most funding.

This survey paper aims to explore various techniques and approaches for designing interactive visualizations of time-dependent and bipartite graphs. We will examine different methods for representing temporal data, strategies for laying out bipartite relationships, and ways to combine these approaches effectively.

Throughout this paper, we will focus on creating clear, uncluttered overviews while maximizing information content[3]. We will also discuss techniques for handling large-scale data, as the Media Transparency Database likely contains thousands of entries over multiple years.

By the end of this survey, readers will have a comprehensive understanding of how to design effective interactive visualizations for time-dependent and bipartite graphs, using the Media Transparency Database Austria as a practical and relevant example.

Existing visualization methods often struggle with large-scale, temporal bipartite data. Our research aims to address these limitations through:

1. Scalable visualization techniques for large datasets
2. Hierarchical aggregation and clustering methods
3. Intuitive user interface design
4. Integration of time series visualization

The goal is to create accessible, insightful visualizations for both experts and non-experts. Our findings will contribute to information visualization research and provide tools for analyzing public spending on advertising in Austria.

2 RELATED WORK

3 VISUAL ENCODING AND INTERACTION DESIGN

4 IMPLEMENTATION

5 EVALUATION

REFERENCES

- [1] W. Chung and V. S. Lai. A temporal graph framework for intelligence extraction in social media networks. *Information & Management*, 60(4):103773, 2023. 1
- [2] R. Diestel. *Graph theory: Springer graduate text gtm 173*, vol. 173. Reinhard Diestel, 2012. 1
- [3] R. . KommAustria. Media Transparency Database Austria. https://www.rtr.at/medien/was_wir_tun/medientransparenz/VeroeffentlichteDaten/veroeffentlichungen.de.html, 2024. [Online; accessed 01-July-2024]. 1
- [4] M. Ma, P. Xie, F. Teng, B. Wang, S. Ji, J. Zhang, and T. Li. Hst-gnn: Hierarchical spatio-temporal graph neural network for weather forecasting. *Information Sciences*, 648:119580, 2023. 1
- [5] R. Tamilmani and E. Stefanakis. Modelling and analysis of semantically enriched simplified trajectories using graph databases. *Advances in Cartography and GIScience of the ICA*, 2019. 1

*e-mail:yahya.jabary@tuwien.ac.at

†e-mail:manuela.waldner@tuwien.ac.at

- [6] M. Waldner, D. Steinböck, and E. Gröller. Interactive exploration of large time-dependent bipartite graphs. *J. Comput. Lang.*, 57:100959, 2020. [1](#)
- [7] H. Yang, F. Zhou, G. Lin, M. Lin, and S. Lin. Animated mesh simplification based on motion features in visual sensor networks. *International Journal of Distributed Sensor Networks*, 15, 2019. [1](#)