

UNIT 42  
BY PALO ALTO NETWORKS

Threat Research Center > Threat Research > Malware

MALWARE

Unit 42 Technical Analysis: Seaduke

🕒 6 min read

👤 By: Josh Grunzweig

📅 Published: July 14, 2015

🏷️ Categories: Malware , Threat Research

🏷️ Tags: Duke malware , Forkmeiamfamous , Seaduke , Symantec , Trojan

📄

🖨️

Share ▾

Earlier this week **Symantec released a blog post** detailing a new Trojan used by the ‘Duke’ family of malware. Within this blog post, a payload containing a function named ‘forkmeiamfamous’ was mentioned. While performing some research online, Unit 42 was able to identify the following **sample**, which is being labeled as ‘Trojan.Win32.Seadask’ by a number of anti-virus companies.

MD5	A25EC7749B2DE12C2A86167AFA88A4DD
SHA1	BB71254FBD41855E8E70F05231CE77FEE6F00388
SHA256	3EB86B7B067C296EF53E4857A74E09F12C2B84B666FC130D1F58AEC18BC74B0D
Compile Timestamp	2013-03-23 22:26:55
File type	PE32 executable (GUI) Intel 80386, for MS Windows, UPX compressed

Our analysis has turned up more technical details and indicators on the malware itself that aren’t mentioned in Symantec’s post. Here are some of our observations:

### First Layer of Obfuscation

Once the UPX packer is removed from the malware sample, it becomes quickly apparent that we’re dealing with a sample compiled using **PyInstaller**. This program allows an individual to write a program using the Python scripting language and convert it into an executable for the Microsoft Windows, Linux, Mac OSX, Solaris, or AIX platform. The following subset of strings that were found within the UPX-unpacked binary confirms our suspicions.

- `sys.path.append(r"%s")`
- `del sys.path[:]`
- `import sys`
- `PYTHONHOME`
- `PYTHONPATH`

### RELATED ARTICLES

From DarkGate to AsyncRAT: Malware Detected and Shared As Unit 42 Timely Threat Intelligence

Blocking Dedicated Attacking Hosts Is Not Enough: In-Depth Analysis of a Worldwide Linux XorDDoS Campaign

Targeted Attack Campaign Against ManageEngine ADSelfService Plus Delivers Godzilla Webshells, NGLite Trojan and KdcSponge Stealer

- Error creating child process!
- Cannot GetProcAddress for PySys\_SetObject
- PySys\_SetObject

Because the sample was written in Python originally, we’re able to extract the underlying code. A tool such as ‘**PyInstaller Extractor**’ can be used to extract the underlying pyc files present within the binary.



Figure 1. Extracted Python files from Seaduke

We can then use a tool such as **uncompyle2** to convert the Python byte-code into the original source code. Once this process is completed, we quickly realize that the underlying Python code has been obfuscated.



Figure 2. Obfuscated Python code

## Second Layer of Obfuscation

Tracing through the obfuscated code, we identify an ‘exec(ZxkBDKLakV)’ statement, which will presumably execute some Python code. Tracing further, we discover that this string is generated via appending a number of strings to the ‘ZxkBDKLakV’ variable. Finally, we find that after this string is created, it is base64-decoded and subsequently decompressed using the ZLIB library.



Figure 3. Second layer of obfuscation identified

The following simple Python code can be used to circumvent this layer of obfuscation:

This site uses cookies essential to its operation, for analytics, and for personalized content and ads. Please read our privacy statement for more information. [Privacy statement](#)

```
12 variable = "ZxkBDKLakV"
13
14 regex = "%s \+= ([a-zA-Z0-9])\n" % variable
15 out = ""
16 for x in re.findall(regex, fdata):
17     regex2 = "%s = \"([a-zA-Z0-9\+\\+])\\"" % x
18     for x1 in re.findall(regex2, fdata):
19         out += x1
20
21 o = base64.b64decode(out)
22 print zlib.decompress(o)
```

The remaining Python code still appears to be obfuscated, however, overall functionality can be identified.

## Final Payload

As we can see below, almost all variable names and class names have been obfuscated using long unique strings.



Figure 4. Obfuscation discovered in final payload

Using a little brainpower and search/replace, we can begin identifying and renaming functionality within the malware. A cleaned up copy of this code can be found on [GitHub](#). One of the first things we notice is a large blob of base64-encoded data, which is additionally decompressed using ZLIB. Once we decode and decompress this data, we are rewarded with a JSON object containing configuration data for this malware:



Figure 5. Base64-encoded / ZLIB compressed data

```
1 {
2   "first_run_delay": 0,
3   "keys": {
4     "aes": "KIjbzZ/ZxdESKD2XosXqIbEdrCxy3mqDSSLWJ7BFk3o=",
5     "aes_iv": "cleUKIi+mAVSKL2704J/UQ=="
6   },
7   "autoload_settings": {
8     "exe_name": "LogonUI.exe",
9     "app_name": "LogonUI.exe",
10    "delete_after": false
11  },
12  "host_scripts": ["http://monitor.syn[.]cn/rss.php"],
13  "referer": "https://www.facebook.com/",
14  "user_agent": "SiteBar/3.3.8 (Bookmark Server; http://sitebar.org/)",
15  "key_id": "P4BNZR0",
16  "enable_autoload": false
17 }
```

This configuration object provides a number of clues and indicators about the malware itself. After this data is identified, we begin tracing execution of the malware from the beginning. When the malware is initially run, it will determine on which operating system it is running. Should it be running on a non-Windows system, we see a call to the infamous 'forkmeiamfamous' method. This method is responsible for configuring a number of Unix-specific settings, and forking the process.



Figure 6. Main execution of malware

Continuing along, we discover that this malware has the ability to persist using one of the following techniques:



Figure 7. Persistence techniques

After the malware installs itself, it begins making network requests. All network communications are performed over HTTP for this particular sample; however, it appears to support HTTPS as well. When the malware makes the initial outbound connection, a specific Cookie value is used.



Figure 8. Initial HTTP request made

In actuality, this Cookie value contains encrypted data. The base64-encoded data is parsed from the Cookie value (padding is added as necessary).

EBJhZTIKIqN8nYWejKh7UpDycPlcrGMEcTE=

The resulting decoded data is shown below.

\x10\x12ae9J\x8a\xa3|\x9d\x85\x9e\x8c\xa8{R\x90\xf2p\xf9\\\xacc\x04q1

The underlying data has the following characteristics.



Figure 9. Cookie data structure

XORing the first single character against the second character identifies the length of the random string. Using the above example, we get the following.

First Character : '\x10'  
Second Character : '\x12'  
String Length (16 ^ 18) : 2  
Random String : 'ae'  
Encrypted Data : '9J\x8a\xa3|\x9d\x85\x9e\x8c\xa8{R\x90\xf2p\xf9\\\xacc\x04q1'

Finally, the encrypted data is encrypted using the RC4 algorithm. The key is generated by concatenating the previously used random string with the new one, and taking the SHA1 hash of this data.



This same key is used to decrypt any response data provided by the server. The server attempts to mimic a HTML page and provides base64-encoded data within the response, as shown below.



ensured that no individual HTTP session can be decrypted without seeing the previous session. If the decrypted data does not produce proper JSON data, Seaduke will discard it and enter a sleep cycle.

Otherwise, this JSON data will be parsed for commands. The following commands have been identified in Seaduke.

Command	Description
cd	Change working directory to one specified
pwd	Return present working directory
cdt	Change working directory to %TEMP%
autoload	Install malware in specified location
migrate	Migrate processes
clone_time	Clone file timestamp information
download	Download file
execw	Execute command
get	Get information about a file
upload	Upload file to specified URL
b64encode	Base64-encode file data and return result
eval	Execute Python code
set_update_interval	Update sleep timer between main network requests
self_exit	Terminate malware
seppuku	Terminate and uninstall malware

In order for the ‘self\_exit’ or ‘seppuku’ commands to properly execute, the attackers must supply a secondary argument of ‘YESIAMSURE’.

## Conclusion

Overall, Seaduke is quite sophisticated. While written in Python, the malware employs a number of interesting techniques for encrypting data over the network and persisting on the victim machine. WildFire customers are protected against this threat. Additionally, Palo Alto Networks properly categorizes the URL used by Seaduke as malicious.

Back to top

### TAGS

- Duke malware
- Forkmeiamfamous
- Seaduke
- Symantec
- Trojan

Threat Research Center

Next: APT Group UPS Targets US Government with Hacking Team Flash Exploit

### Related Malware Resources

UNIT 42

THREAT RESEARCH

IC

November 1, 2024

TA Phone Home: EDR Evasion Testing Reveals Extortion Actor's Toolkit

Extortion

Data exfiltration

Read now →

UNIT 42

THREAT RESEARCH

IC

October 9, 2024

Contagious Interview: DPRK Threat Actors Lure Tech Industry Job Seekers to Inst...

North Korea

Social engineering

Python

UNIT 42

THREAT RESEARCH

IC

October 1, 2024

Detecting Vulnerability Scanning Traffic From Underground Tools Using...

Machine Learning

Read now →

UNIT 42

THREAT ACTOR GROUPS

IC

September 26, 2024

Unraveling Sparkling Pisces's Tool Set: KLogEXE and FPSpy

MITRE

Keylogger

North Korea

Read now →



UNIT 42

Get updates from Unit 42

Subscribe

Small

Log

Peace of mind comes from staying ahead of threats. Contact us today.

Your Email

Subscribe for email updates to all Unit 42 threat research. By submitting this form, you agree to our [Terms of Use](#) and acknowledge our [Privacy Statement](#).

Subscribe

Right Arrow

Products and services	Company	Popular links
<div>Network Security Platform</div> <div>CLOUD DELIVERED SECURITY SERVICES</div> <div>Advanced Threat Prevention</div> <div>DNS Security</div> <div>Data Loss Prevention</div> <div>IoT Security</div> <div>Next-Generation Firewalls</div> <div>Hardware Firewalls</div> <div>Strata Cloud Manager</div>	<div>Code to Cloud Platform</div> <div>Prisma Cloud</div> <div>Cloud-Native Application Protection Platform</div>	<div>Blog</div> <div>Communities</div> <div>Content Library</div> <div>Cyberpedia</div> <div>Event Center</div> <div>Manage Email Preferences</div> <div>Products A-Z</div> <div>Product Certifications</div> <div>Report a Vulnerability</div> <div>Sitemap</div>

Autonomous Digital Experience Management	
Cloud Access Security Broker	
Zero Trust Network Access	
AI-Driven Security Operations Platform	Threat Intel and Incident Response Services
Cortex XDR	Proactive Assessments
Cortex XSOAR	Incident Response
Cortex Xpanse	Transform Your Security Strategy
Cortex XSIAM	Discover Threat Intelligence
External Attack Surface Protection	
Security Automation	
Threat Prevention, Detection & Response	