



Threat Hunter Playbook

Search this book...

KNOWLEDGE LIBRARY

Windows

PRE-HUNT ACTIVITIES

Data Management

GUIDED HUNTS

Windows

LSASS Memory Read Access

DLL Process Injection via CreateRemoteThread and LoadLibrary

Active Directory Object Access via Replication Services

Active Directory Root Domain Modification for Replication Services

Registry Modification to Enable Remote Desktop Conections

Local PowerShell Execution

WDigest Downgrade

PowerShell Remote Session

Alternate PowerShell Hosts

Domain DPAPI Backup Key Extraction

SysKey Registry Keys Access

SAM Registry Hive Handle Request

WMI Win32_Process Class and Create Method for Remote Execution

WMI Eventing

WMI Module Load

Local Service Installation

Remote Service creation

Remote Service Control Manager Handle

Remote Interactive Task Manager

LSASS Dump

Registry Modification for Extended

Domain DPAPI Backup Key Extraction

Hypothesis

Adversaries might be extracting the DPAPI domain backup key from my DC to be able to decrypt any domain user master key files.

Technical Context

Starting with Microsoft® Windows® 2000, the operating system began to provide a data protection application-programming interface (API). This Data Protection API (DPAPI) is a pair of function calls (CryptProtectData / CryptUnprotectData) that provide operating system-level data protection services to user and system processes. DPAPI initially generates a strong key called a MasterKey, which is protected by the user’s password. DPAPI uses a standard cryptographic process called Password-Based Key Derivation to generate a key from the password. This password-derived key is then used with Triple-DES to encrypt the MasterKey, which is finally stored in the user’s profile directory.

When a computer is a member of a domain, DPAPI has a backup mechanism to allow unprotection of the data. When a MasterKey is generated, DPAPI talks to a Domain Controller. Domain Controllers have a domain-wide public/private key pair, associated solely with DPAPI. The local DPAPI client gets the Domain Controller public key from a Domain Controller by using a mutually authenticated and privacy protected RPC call. The client encrypts the MasterKey with the Domain Controller public key. It then stores this backup MasterKey along with the MasterKey protected by the user’s password.

Offensive Tradecraft

If an adversary obtains domain admin (or equivalent) privileges, the domain backup key can be stolen and used to decrypt any domain user master key. Tools such as Mimikatz with the method/module lsadump::backupkeys can be used to extract the domain backup key. It uses the LsaOpenPolicy/LsaRetrievePrivateData API calls (instead of MS-BKRP) to retrieve the value for the G BCKUPKEY_P LSA secrets.

Additional reading

- https://github.com/OTRF/ThreatHunter-Playbook/tree/master/docs/library/windows/data_protection_api.md
- https://github.com/OTRF/ThreatHunter-Playbook/tree/master/docs/library/windows/lsa_policy_objects.md

Pre-Recorded Security Datasets

Metadata	Value
docs	https://securitydatasets.com/notebooks/atomic/windows/credential_access/SDWIN-190518235535.html

Contents

Hypothesis

Technical Context

Offensive Tradecraft

Pre-Recorded Security Datasets

Analytics

Known Bypasses

False Positives

Hunter Notes

Hunt Output

References

link https://raw.githubusercontent.com/OTRF/Security-Datasets/master/datasets/atomic/windows/credential_access/host/empire_mimikatz_backupkeys_dcerpc_smb_lsarpc.zip

Download Dataset

```
import requests
from zipfile import ZipFile
from io import BytesIO

url = 'https://raw.githubusercontent.com/OTRF/Security-Datasets/master/datasets/atomic/windows/credential_access/host/empire_mimikatz_backupkeys_dcerpc_smb_lsarpc.zip'
zipFileRequest = requests.get(url)
zipFile = ZipFile(BytesIO(zipFileRequest.content))
datasetJSONPath = zipFile.extract(zipFile.namelist()[0])
```

Read Dataset

```
import pandas as pd
from pandas.io import json

df = json.read_json(path_or_buf=datasetJSONPath, lines=True)
```

Analytics

A few initial ideas to explore your data and validate your detection logic:

Analytic I

Monitor for any SecretObject with the string BCKUPKEY in the ObjectName.

Data source	Event Provider	Relationship	Event
Windows active directory	Microsoft-Windows-Security-Auditing	User accessed AD Object	4662

Logic

```
SELECT `@timestamp`, Hostname, ObjectServer, ObjectType, ObjectName
FROM dataTable
WHERE LOWER(Channel) = "security"
      AND EventID = 4662
      AND AccessMask = "0x2"
      AND lower(ObjectName) LIKE "%bckupkey%"
```

Pandas Query

```
(
df[['@timestamp', 'Hostname', 'ObjectServer', 'ObjectType', 'ObjectName']]
[(df['Channel'].str.lower() == 'security')
 & (df['EventID'] == 4662)
 & (df['AccessMask'] == '0x2')
 & (df['Message'].str.lower().str.contains('.*bckupkey.*', regex=True))]
].head()
)
```

Analytic II

We can get the user logon id of the user that accessed the *bckupkey* object and JOIN it with a successful logon event (4624) user logon id to find the source IP.

Data source	Event Provider	Relationship	Event
Authentication log	Microsoft-Windows-Security-Auditing	User authenticated Host	4624
Windows active directory	Microsoft-Windows-Security-Auditing	User accessed AD Object	4662

Logic

```
SELECT o.`@timestamp`, o.Hostname, o.ObjectName, a.IpAddress
FROM dataTable o
INNER JOIN (
    SELECT Hostname, TargetUserName, TargetLogonId, IpAddress
    FROM dataTable
    WHERE LOWER(Channel) = "security"
        AND EventID = 4624
        AND LogonType = 3
        AND NOT TargetUserName LIKE "%$"
) a
ON o.SubjectLogonId = a.TargetLogonId
WHERE LOWER(Channel) = "security"
    AND o.EventID = 4662
    AND o.AccessMask = "0x2"
    AND lower(o.ObjectName) LIKE "%bckupkey%"
    AND o.Hostname = a.Hostname
```

Pandas Query

```
backupKeyDf = (
df[['@timestamp', 'Hostname', 'ObjectName', 'IpAddress', 'SubjectLogonId']]

[(df['Channel'].str.lower() == 'security')
 & (df['EventID'] == 4662)
 & (df['AccessMask'] == '0x2')
 & (df['ObjectName'].str.lower().str.contains('.*bckupkey.*', regex=True))]
).head()
)

networkLogonDf = (
df[['@timestamp', 'Hostname', 'TargetUserName', 'TargetLogonId', 'IpAddress']]

[(df['Channel'].str.lower() == 'security')
 & (df['EventID'] == 4624)
 & (df['LogonType'] == 3)
 & (~df['SubjectUserName'].str.endswith('.*$', na=False))]
).head()
)

(
pd.merge(backupKeyDf, networkLogonDf,
    left_on = ['SubjectLogonId', 'Hostname'], right_on = ['TargetLogonId', 'Hostr
```

Analytic III

Monitoring for access to the protected_storage named pipe via SMB is very interesting to identify potential DPAPI activity over the network. Mimikatz uses the Lsarpc named pipe now.

Data source	Event Provider	Relationship	Event
File	Microsoft-Windows-Security-Auditing	User accessed File	5145

Logic

```
SELECT `@timestamp`, Hostname, SubjectUserName, ShareName, RelativeTargetName,
FROM dataTable
WHERE LOWER(Channel) = "security"
      AND EventID = 5145
      AND ShareName LIKE "%IPC%"
      AND RelativeTargetName = "protected_storage"
```

Pandas Query

```
(
df[['@timestamp', 'Hostname', 'SubjectUserName', 'ShareName', 'RelativeTargetName']]
[(df['Channel'].str.lower() == 'security')
 & (df['EventID'] == 5145)
 & (df['RelativeTargetName'].str.lower() == 'protected_storage')
 & (df['ShareName'].str.contains('.*IPC.*', regex=True))]
)
```

Analytic IV

This event generates every time that a backup is attempted for the DPAPI Master Key. When a computer is a member of a domain, DPAPI has a backup mechanism to allow unprotection of the data. When a Master Key is generated, DPAPI communicates with a domain controller. It might be already created and this event might not trigger.

Data source	Event Provider	Relationship	Event
File	Microsoft-Windows-Security-Auditing	User requested access File	4692

Logic

```
SELECT `@timestamp`, Hostname, SubjectUserName
FROM dataTable
WHERE LOWER(Channel) = "security"
      AND EventID = 4692
```

Pandas Query

```
(
df[['@timestamp', 'Hostname', 'SubjectUserName']]
[(df['Channel'].str.lower() == 'security')
 & (df['EventID'] == 4692)]
)
```

Known Bypasses

False Positives

Hunter Notes

- Backup key can be displayed as base64 blob or exported as a .pvk file on disk (Mimikatz-like)
- Windows security event 4692 (Backup of data protection master key was attempted) also generates every time a new DPAPI Master Key is generated
- When a computer is a member of a domain, DPAPI has a backup mechanism to allow unprotection of the data. When a Master Key is generated, DPAPI communicates with a domain controller.

Hunt Output

Type	Link
Sigma Rule	https://github.com/SigmaHQ/sigma/blob/master/rules/windows/builtin/security/win_dpapi_domain_backupkey_extraction.yml
Sigma Rule	https://github.com/SigmaHQ/sigma/blob/master/rules/windows/builtin/security/win_protected_storage_service_access.yml
Sigma Rule	https://github.com/SigmaHQ/sigma/blob/master/rules/windows/builtin/security/win_dpapi_domain_masterkey_backup_at.yml

References

- <https://www.harmj0y.net/blog/redteaming/operational-guidance-for-offensive-user-dpapi-abuse/>
- https://digital-forensics.sans.org/summit-archives/dfirprague14/Give_Me_the_Password_and_III_Rule_the_World_Francesco_Picasso.pdf
- <https://docs.microsoft.com/en-us/windows/desktop/devnotes/pstore>
- https://github.com/gentilkiwi/mimikatz/blob/641a3b29acd326d07269300d94dceafea041f760/mimikatz/modules/kuhl_m_IsaduL1926
- <https://github.com/GhostPack/SharpDPAPI/blob/6388040a92e59fc0d5a82b4ec31599aa6778fd3b/SharpDPAPI/lib/Backup.cs#L4>
- https://github.com/gentilkiwi/mimikatz/blob/641a3b29acd326d07269300d94dceafea041f760/mimikatz/modules/kuhl_m_IsaduL1926
- https://github.com/gentilkiwi/mimikatz/blob/641a3b29acd326d07269300d94dceafea041f760/mimikatz/modules/kuhl_m_IsaduL1926
- https://docs.microsoft.com/en-us/openspecs/windows_protocols/ms-lsad/88c6bd18-6c40-4a82-ae19-fe7bfec5108b

Previous
Alternate PowerShell Hosts

Next
SysKey Registry Keys Access