



Search 

# Active Directory Security

Active Directory & Enterprise Security, Methods to Secure Active Directory, Attack Methods & Effective Defenses, PowerShell, Tech Notes, & Geek Trivia...

Home

About

AD Resources

Attack Defense & Detection

Contact

Mimikatz

Presentations


Schema Versions

Security Resources

SPNs

Top Posts

 [Detecting Kerberoasting Activity](#)

[Sp4rkCon \(2017\) Talk Slides Posted – Active Directory Security: The Good, the Bad, & the UGLY](#) 

FEB  
08  
2017

## Detecting Kerberoasting Activity Part 2 – Creating a Kerberoast Service Account Honeypot

By [Sean Metcalf](#) in [ActiveDirectorySecurity](#), [Microsoft Security](#), [Technical Reference](#)

In my previous post, “[Detecting Kerberoasting Activity](#)” I explain how [Kerberoasting works](#) and describe how to [detect potential Kerberoasting activity](#). The trick to this is understanding what activity is normal in order to filter out the noise and increase the fidelity of the alert.

This post describes how to filter from millions of events to a single one to detect Kerberoasting activity.

### Detecting Kerberoasting Activity

As I noted in the [previous post](#), looking for TGS service tickets with RC4 encryption was a good method to discover Kerberoasting activity.

*Windows added Kerberos AES (128 & 256) encryption starting with Windows Server 2008 and Windows Vista which means that*

*most Kerberos requests will be AES encrypted with any modern Windows OS. Any Kerberos RC4 tickets requested should be the exception. There are systems that only support Kerberos RC4 by default ([NetApp](#)). Inter-forest Kerberos tickets also use RC4 unless [configured for AES](#) – ensure your forest trusts support AES and then enable AES over the trust.*

*Once all Domain Controllers are configured to log 4769 events, these events need to be filtered before sending the data into a SIEM/Splunk. Since we are only really interested in Kerberos TGS service tickets with RC4 encryption, it's possible to filter the events. As shown above, Kerberos events with AES encryption has Ticket Encryption Type set to 0x12. Kerberos RC4 encrypted tickets have Ticket Encryption Type set to 0x17.*

*These events can be filtered using the following which greatly reduces the amount of events flowing into the SIEM/Splunk:*

- Ticket Options: 0x40810000
- Ticket Encryption: 0x17


*With this information, we can start investigating potential Kerberoasting activity and reduce the number of 4769 events.*

*We can further reduce the number of 4769 events that flow into SIEM/Splunk:*

- Filter out requests from service accounts (ads45service@lab.adsecurity.org)
- Filter on Audit Success
- Filter out requests for service names with a “\$” which are typically for computer accounts (or trusts or Managed Service Accounts, all accounts where Windows automatically generates a long, complex password).

*In limited testing, I’ve seen 4769 event totals reduced from millions to thousands and hundreds using these filtering techniques.*

***Here’s a 4769 event that may potentially be from Kerberoasting activity:***



Following this line of thought, we can look at TGS ticket requests with specific ticket encryption & ticket options to identify potential Kerberoast activity.

*Using the information regarding ticket encryption type and ticket options, we can use PowerShell to parse the DC's event log looking for 4769 events with this info.*

EventID	Date	AccountName	ServiceName
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	svc-VDIPVS01
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	Svc-BizTalk01
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	SVC-BOADS-01
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	SVC-AGPM-01
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	svc-adsMSSQL10
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	svc-adsSQLSA
4769	1/25/2017 9:36:07 PM	JoeUser@LAB.ADSECURITY.ORG	svc-adsMSSQL11
4769	1/25/2017 9:36:06 PM	JoeUser@LAB.ADSECURITY.ORG	SQL-ADSD0B317-SVC

*That looks really odd. Why would any account request several different service names (Citrix PVS, BizTalk, Business Objects, AGPM GPO management, and several SQL service accounts) within a second or two of each other?*

*That stands out and looks really suspicious and is very likely Kerberoasting activity. This provides great information on what users could be compromised and what activity on which computers should be scrutinized.*

*A single user requesting RC4 encrypted TGS tickets for several services, such as lots of SQL service principal names is suspicious and it's worth investigating the IP (client address) the requests came from. The same thing is true for multiple RC4 encrypted TGS requests over time for lots of service principal names. A pattern does emerge when there's one or two accounts that request a variety of RC4 TGS tickets.*

Read the entire [post](#) for more information on how Kerberoasting works, etc.

### Filtering the Noise to Find Malicious Activity

I note in that post that 4769 events on Domain Controllers are extremely numerous, some of the most numerous events on a network.

*But, what if we only cared about 1 event?*

That would reduce the number of 4769 events down to a single event that only occurs when something malicious is happening?

This post describes how to further narrow down to best detect Kerberoasting activity on a network: Creating a Service Account Honeypot to detect Kerberoasting.


Note: I still recommend [filtering 4769 event IDs on Domain Controllers](#) and flowing them into SIEM/Splunk since this will provide information on resources users are accessing as well as help flag when a single user is requesting multiple service principal names (which is suspicious).

### Creating a Kerberoast Service Account Honeypot

In order to create a Kerberoast Service Account Honeypot, we need to create a user account in AD and give it a fake service principal name (SPN). It has to be fake so we know that when it's requested, this request is not valid and therefore is malicious. It's also important to make this account look attractive by setting the "AdminCount" attribute to 1 as this flags the account as [potentially having elevated AD rights](#). Adding this account to a bunch of fake groups made to look like it's providing additional elevated rights helps to add to the illusion.

Step 1: Create a new AD user account.

Step 2: Set the "AdminCount" attribute to 1.



Step 2: Add a Service Principal Name (SPN) to the account. This SPN needs to be unique, so it should not simply be copied from another system. SQL service accounts are pretty common, so that's not a bad one to use (MSSQLSvc/sql01.lab.adsecurity.org). Just don't reuse one that already exists.

The following example is a bit less... subtle. 😊

Step 3: It may also be useful to add the honeypot account to a fake group that looks like it might have admin rights.

**Note:**

To make things interesting, you could give this account an easy password that could be guessed, something like “Password1234” (or a keyboard combination). This way we can monitor if someone logs on with this account. However, the Kerberos TGS service ticket request is enough to know that Kerberoasting activity is occurring and we know from which computer it’s being done thanks to the event information (“Client Address”).

## **Detecting Kerberoast Service Account Honeypot “Access”**

Once the honeypot account is created with a service principal name that doesn't do anything and therefore should never be requested or used. The reason this service principal name should never be requested is that we made it up and it isn't linked to any real application that would be requesting it. There is no reason for anyone to every request a Kerberos TGS service ticket for this since there is no actual associated service running for it. Therefore, if we see that someone requested a Kerberos TGS ticket, they are very likely attempting to Kerberoast this account.

An attacker gains access to the internal network and searches for accounts with service principal names and have admincount set to 1.

This shows our new honeypot account to the attacker who is now interested in this account and requests an RC4 encrypted Kerberos TGS ticket for the SPN. A klist shows the attacker got the TGS ticket in memory.

By looking for 4769 events on Domain Controllers with the ticket encryption option 0x12 (along with other filters I describe in the [Kerberoast detection post](#)), we can see that Joe User requested a Kerberos ticket for a SPN that doesn't exist and should never be requested!

The Account Name shows which account was used and Client Address provides the computer IP from where the attacker requested the honeypot Kerberos service account.



When we use our Kerberoast discovery PowerShell script against the Domain Controller event logs, we find that Joe User has requested a lot of Kerberos service tickets, including the one for our Honeypot (which again should never be requested since it doesn't exist).

Using a service account honeypot, this changes this detection from “potential” Kerberoasting activity, to definite Kerberoasting activity.

Note that we can also configure an IDS rule that looks at TGS-REQ packets with the service name “KerberoastHoneyPot” (again, or something more boring and subtle).

## Conclusion

Kerberoasting requires requesting Kerberos TGS service tickets with RC4 encryption which shouldn't be regular activity on a network. Logging 4769 events on Domain Controllers, filtering these events by ticket encryption type (0x17), known service accounts (Account Name field) & computers (Service Name field) greatly reduces the number of events forwarded to the central logging and alerting system. Gathering and monitoring this data also creates a good baseline of what's “normal” in order to more easily detect anomalous activity.

Detecting Kerberoasting activity is possible by logging the correct activity on Domain Controllers. Determining if this activity is malicious is not requires in-depth knowledge of how RC4 TGS tickets are used in the environment. Creating a service account honeypot with a SPN that doesn't do anything, provides another data point. Any Kerberos ticket request involving the honeypot service account should be seen as malicious.

## Kerberoasting References

- [Detecting Kerberoasting Activity](#) (part 1)
- [Cracking Kerberos TGS Tickets Using Kerberoast – Exploiting Kerberos to Compromise the Active Directory Domain](#)

- [Attack Methods for Gaining Domain Admin Rights in Active Directory](#)
- [Sneaky Persistence Active Directory Trick #18: Dropping SPNs on Admin Accounts for Later Kerberoasting](#)
- [Targeted Kerberoasting \(Harmj0y\)](#)
- [Kerberoasting without Mimikatz \(Harmj0y\)](#)
- [Roasting AS REPs \(Harmj0y\)](#)
- [Sean Metcalf's Presentations on Active Directory Security](#)
- [Kerberoast \(GitHub\)](#)
- [Tim Medin's DerbyCon "Attacking Microsoft Kerberos Kicking the Guard Dog of Hades" presentation in 2014 \(slides & video\).](#)

(Visited 53,832 times, 2 visits today)

□ [AP-REQ](#), [Audit Kerberos Service Ticket Operations](#), [Detect Kerberoast Activity](#), [Detecting Kerberoast activity](#), [Event ID 4769](#), [Kerberoast honeypot](#), [Kerberoasting activity](#), [Kerberos RC4 Encryption](#), [Kerberos Service Ticket](#), [Kerberos TGS](#), [Kerberos TGS Ticket](#), [NTLM Password](#), [RC4\\_HMAC\\_MD5](#), [service account honeypot](#), [TGS-REP](#), [TGS-REQ](#)



## Sean Metcalf

I improve security for enterprises around the world working for TrimarcSecurity.com

Read the About page (top left) for information about me. :)

[https://adsecurity.org/?page\\_id=8](https://adsecurity.org/?page_id=8)



### RECENT POSTS

## [BSides Dublin – The Current State of Microsoft Identity Security: Common Security Issues and Misconfigurations – Sean Metcalf](#)

---

## [DEFCON 2017: Transcript – Hacking the Cloud](#)

---

## [Detecting the Elusive: Active Directory Threat Hunting](#)

---

## [Detecting Kerberoasting Activity](#)

---

## [Detecting Password Spraying with Security Event Auditing](#)

---

---

### TRIMARC ACTIVE DIRECTORY SECURITY SERVICES

Have concerns about your Active Directory environment? Trimarc helps enterprises improve their security posture.

[Find out how...](#) [TrimarcSecurity.com](https://TrimarcSecurity.com)

---

### POPULAR POSTS

[PowerShell Encoding & Decoding \(Base64\)](#)

---

[Attack Methods for Gaining Domain Admin Rights in...](#)

---

[Kerberos & KRBTGT: Active Directory's...](#)

---

[Finding Passwords in SYSVOL & Exploiting Group...](#)

---

[Securing Domain Controllers to Improve Active...](#)

---

[Securing Windows Workstations: Developing a Secure Baseline](#)

---

[Detecting Kerberoasting Activity](#)

---

[Mimikatz DCSync Usage, Exploitation, and Detection](#)

---

[Scanning for Active Directory Privileges &...](#)

---

[Microsoft LAPS Security & Active Directory LAPS...](#)

---

CATEGORIES

[ActiveDirectorySecurity](#)

[Apple Security](#)

[Cloud Security](#)

[Continuing Education](#)

[Entertainment](#)

[Exploit](#)

[Hacking](#)

[Hardware Security](#)

[Hypervisor Security](#)

[Linux/Unix Security](#)

[Malware](#)

[Microsoft Security](#)

[Mitigation](#)

[Network/System Security](#)

[PowerShell](#)

[RealWorld](#)

[Security](#)

[Security Conference Presentation/Video](#)

[Security Recommendation](#)

[Technical Article](#)

[Technical Reading](#)

[Technical Reference](#)

TheCloud

Vulnerability

## TAGS

ActiveDirectory Active Directory Active Directory Security ActiveDirectorySecurity  
ADReading AD Security ADSecurity Azure AzureAD DCSync DomainController GoldenTicket GroupPolicy  
HyperV Invoke-Mimikatz KB3011780 KDC Kerberos KerberosHacking KRBTGT LAPS LSASS MCM  
MicrosoftEMET MicrosoftWindows mimikatz MS14068 PassTheHash PowerShell  
PowerShellCode PowerShellHacking PowerShellv5 PowerSploit Presentation Security SilverTicket  
SneakyADPersistence SPN TGS TGT Window s7 Windows10 WindowsServer2008R2 WindowsServer2012  
WindowsServer2012R2



## RECENT POSTS

**BSides Dublin – The Current State of Microsoft Identity Security: Common Security Issues and Misconfigurations – Sean Metcalf**

**DEFCON 2017: Transcript – Hacking the Cloud**

**Detecting the Elusive: Active Directory Threat Hunting**

**Detecting Kerberoasting Activity**

**Detecting Password Spraying with Security Event Auditing**

## RECENT COMMENTS

**Derek** on [Attacking Read-Only Domain Controllers \(RODCs\) to Own Active Directory](#)

**Sean Metcalf** on [Securing Microsoft Active Directory Federation Server \(ADFS\)](#)

---

**Brad** on [Securing Microsoft Active Directory Federation Server \(ADFS\)](#)

---

**Joonas** on [Gathering AD Data with the Active Directory PowerShell Module](#)

---

**Sean Metcalf** on [Gathering AD Data with the Active Directory PowerShell Module](#)

---

---

## ARCHIVES

[June 2024](#)

---

[May 2024](#)

---

[May 2020](#)

---

[January 2020](#)

---

[August 2019](#)

---

[March 2019](#)

---

[February 2019](#)

---

[October 2018](#)

---

[August 2018](#)

---

[May 2018](#)

---

[January 2018](#)

---

[November 2017](#)

---

[August 2017](#)

---

[June 2017](#)

---

[May 2017](#)

---

[February 2017](#)

---

[January 2017](#)

---

November 2016

October 2016

September 2016

August 2016

July 2016

June 2016

April 2016

March 2016

February 2016

January 2016

December 2015

November 2015

October 2015

September 2015

August 2015

July 2015

June 2015

May 2015

April 2015

March 2015

February 2015

January 2015

December 2014

November 2014



[October 2014](#)

[September 2014](#)

[August 2014](#)

[July 2014](#)

[June 2014](#)

[May 2014](#)

[April 2014](#)

[March 2014](#)

[February 2014](#)

[July 2013](#)

[November 2012](#)

[March 2012](#)

[February 2012](#)

CATEGORIES

[ActiveDirectorySecurity](#)

[Apple Security](#)

[Cloud Security](#)

[Continuing Education](#)

[Entertainment](#)

[Exploit](#)

[Hacking](#)

[Hardware Security](#)

[Hypervisor Security](#)

---

[Linux/Unix Security](#)

---

[Malware](#)

---

[Microsoft Security](#)

---

[Mitigation](#)

---

[Network/System Security](#)

---

[PowerShell](#)

---

[RealWorld](#)

---

[Security](#)

---

[Security Conference Presentation/Video](#)

---

[Security Recommendation](#)

---

[Technical Article](#)

---

[Technical Reading](#)

---

[Technical Reference](#)

---

[TheCloud](#)

---

[Vulnerability](#)

---

---

**META**

[Log in](#)

---

[Entries feed](#)

---

[Comments feed](#)


---

[WordPress.org](#)

---

## COPYRIGHT

Content Disclaimer: This blog and its contents are provided "AS IS" with no warranties, and they confer no rights. Script samples are provided for informational purposes only and no guarantee is provided as to functionality or suitability. The views shared on this blog reflect those of the authors and do not represent the views of any companies mentioned. Content Ownership: All content posted here is intellectual work and under the current law, the poster owns the copyright of the article. Terms of Use Copyright © 2011 - 2020.

Content Disclaimer: This blog and its contents are provided "AS IS" with no warranties, and they confer no rights. Script samples are provided for informational purposes only and no guarantee is provided as to functionality or suitability. The views shared on this blog reflect those of the authors and do not represent the views of any companies mentioned. Made with  by Graphene Themes.