We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. Privacy Statement Third-Party Cookies

Accept

Reject

Manage cookies

Microsoft Ignite

Nov 19-22, 2024

Register now >



Learn

Product documentation ∨ Development languages ∨

Q

Sign in

Windows Server

Get started Failover clustering Management Identity and access Networking Troubleshooting

Related products ~

📆 Filter by title

schtasks

· วนาเสวหว

schtasks-change

schtasks-create

schtasks-delete

schtasks-end

schtasks-query

schtasks-run

> scwcmd

> secedit

serverceipoptin

servermanagercmd

serverweroptin

Services for Network File System (NFS)

command reference

set environmental variables

setlocal

setx

sfc

shadow

shift

showmount

shutdown

simulate restore

sort

start

subst

sxstrace sysocmgr

systeminfo

takeown

> tapicfg

taskkill

tasklist

tcmsetup

Learn / Windows Server /

schtasks commands

Article • 02/03/2023 • 13 contributors •

Server 2016, ✓ Windows 11, ✓ Windows 10, ✓ Azure Stack HCI, versions 23H2 and 22H2

Applies Windows Server 2025, Windows Server 2022, Windows Server 2019, Windows

Feedback

In this article

Required permissions

Syntax

Related links

Schedules commands and programs to run periodically or at a specific time, adds and removes tasks from the schedule, starts and stops tasks on demand, and displays and changes scheduled tasks.



The schtasks.exe tool performs the same operations as Scheduled Tasks in Control **Panel**. You can use these tools together and interchangeably.

Required permissions

- To schedule, view, and change all tasks on the local computer, you must be a member of the Administrators group.
- To schedule, view, and change all tasks on the remote computer, you must be a member of the Administrators group on the remote computer, or you must use the /u parameter to provide the credentials of an Administrator of the remote computer.
- You can use the /u parameter in a /create or /change operation if the local and remote computers are in the same domain, or if the local computer is in a domain that the remote computer domain trusts. Otherwise, the remote computer can't authenticate the user account specified, and it can't verify that the account is a member of the Administrators group.
- The task you plan to run must have the appropriate permission; these permissions vary by task. By default, tasks run with the permissions of the current user of the local computer, or with the permissions of the user specified by the /u parameter, if one is

□ Download PDF

included. To run a task with permissions of a different user account or with system permissions, use the /ru parameter.

Syntax



Parameters

Expand table

Parameter	Description
schtasks change	 Changes one or more of the following properties of a task: The program that the task runs (/tr) The user account under which the task runs (/ru) The password for the user account (/rp) Adds the interactive-only property to the task (/it)
schtasks create	Schedules a new task.
schtasks delete	Deletes a scheduled task.
schtasks end	Stops a program started by a task.
schtasks query	Displays tasks scheduled to run on the computer.
schtasks run	Starts a scheduled task immediately. The run operation ignores the schedule, but uses the program file location, user account, and password saved in the task to run the task immediately.

Related links

• Command-Line Syntax Key

Feedback

⑤ English (United States)
✓× Your Privacy Choices
★ Theme ✓
Manage cookies Previous Versions Blog ☑ Contribute Privacy ☑ Terms of Use Trademarks ☑ ⑥ Microsoft 2024