 We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking “Manage Cookies” at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept


Reject

Manage cookies


# Microsoft Ignite

Nov 19–22, 2024

Register now >

 | **Learn** [Discover](#) [Product documentation](#) [Development languages](#) [Topics](#)

 [Sign in](#)

 We're no longer updating this content regularly. Check the [Microsoft Product Lifecycle](#) for information about how this product, service, technology, or API is supported.

Recommended Version

 Filter by title

[...](#) / [Management and Tools](#) / [Command-Line Reference](#) /

## Ldifde

Article • 08/31/2016

### In this article

- [Syntax](#)
- [Parameters](#)
- [Remarks](#)
- [Examples](#)
- [Additional references](#)

Applies To: Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2003 with SP1, Windows 8

Creates, modifies, and deletes directory objects. You can also use **ldifde** to extend the schema, export Active Directory user and group information to other applications or services, and populate Active Directory Domain Services (AD DS) with data from other directory services.

**Ldifde** is a command-line tool that is built into Windows Server 2008. It is available if you have the AD DS or Active Directory Lightweight Directory Services (AD LDS) server role installed. To use **ldifde**, you must run the **ldifde** command from an elevated command prompt. To open an elevated command prompt, click **Start**, right-click **Command Prompt**, and then click **Run as administrator**.


For examples of how to use this command, see [Examples](#).

## Syntax

 Copy

```
Ldifde [-i] [-f <FileName>] [-s <ServerName>] [-c <String1> <String2>] [-v] [-j]
```

## Parameters

 Expand table

Net use

Net user

Net view

Parameter	Description
-i	Specifies to use the import mode. The default mode is export.
-f <FileName>	Identifies the import or export file name.
-s <ServerName>	Specifies the domain controller to perform the import or export operation. By default, <b>Ldifde</b> runs on the domain controller on which <b>Ldifde</b> is installed.
-c <String1> <String2>	Replaces all occurrences of <String1> with <String2>. Generally, you use this parameter when you import data from one domain to another and you must replace the distinguished name of the export domain (<String1>) with the distinguished name of the import domain (<String2>).
-v	Sets verbose mode.
-j <Path>	Sets the log file location. The default location is the current path.
-t <PortNumber>	Specifies a Lightweight Directory Access Protocol (LDAP) port number. The default LDAP port number is 389. The global catalog port number is 3268.
-d <BaseDN>	Sets the distinguished name of the search base for data export.
-r <LDAPFilter>	Creates an LDAP search filter for data export. For example, to export all users with a surname that you specify, you can use the following filter:  -r (and(objectClass=User)(sn=Surname))
-p <Scope>	Sets the search scope. The search scope options are <b>Base</b> , <b>OneLevel</b> , or <b>SubTree</b> .
-l <LDAPAttributeList>	Sets the list of attributes to return in the results of an export query. If you do not specify this parameter, the search returns all attributes.
-o <LDAPAttributeList>	Sets the list of attributes to omit from the results of an export query. This is typically used when exporting objects from AD DS and then importing them into another LDAP-compliant directory. If attributes are not supported by another directory, you can omit the attributes from the result set using this option.
-g	Omits paged searches.
-m	Omits attributes that apply only to Active Directory objects, such as the <b>ObjectGUID</b> , <b>objectSID</b> , <b>pwdLastSet</b> and <b>samAccountType</b> attributes.
-n	Omits the export of binary values.
-k	Ignores errors during an import operation and continues processing. This parameter ignores all of the following errors: <ul style="list-style-type: none"><li>• The object is already a member of the group</li><li>• The operation has an object class violation</li></ul> <p>This violation means that the specified object class does not exist, if the object being imported has no other attributes.</p> <ul style="list-style-type: none"><li>• The object already exists</li><li>• The operation has a constraint violation</li><li>• The attribute or value already exists</li><li>• The operation found no such object</li></ul>
-a <UserDistinguishedName> <Password>	Sets the command to run using the distinguished name (<UserDistinguishedName>) and password (<Password>) that you supply. By default, the command uses the credentials of the user who is currently logged on to the network.
-b <UserName> <Domain> <Password>	Sets the command to run using the supplied <UserName> <Domain> <Password>. By default, the command will run using the credentials of the user currently logged on to the network.
/?	Displays help at the command menu.


## Remarks

- When you create the import file to use with the **ldifde** command, use a **changeType** value to define the type of changes that the import file will contain. The following table shows the **changeType** values that you can use.

 Expand table

Value	Description
add	Specifies that new content is contained in the import file.
modify	Specifies that existing content has been modified in the import file.
delete	Specifies that content has been deleted in the import file.


The following example shows an LDAP Data Interchange Format (LDIF) import file format that uses the **add** value.

 Copy

```
DN: CN=SampleUser,DC=DomainName
changetype: add
CN: SampleUser
description: DescriptionOfFile
objectClass: User
sAMAccountName: SampleUser
```


## Examples

To retrieve only the distinguished name, common name, first name, surname, and telephone number for user objects in the fabrikam.com domain to a file named ldifde.txt in the c:\ldifde folder, run the following command:

 Copy

```
Ldifde -d dc=fabrikam,dc=com -r (objectClass=User) -l distinguishedname,cn,giver
```

To selectively omit the object creation date and time and the object globally unique identifier (GUID), run the following command:

 Copy

```
Ldifde -d dc=fabrikam,dc=com -r (objectClass=User) -o whenCreated,objectGUID -f
```

### Tip

For more examples, see the following resources: [Article 237677](#)  (<https://go.microsoft.com/fwlink/?LinkID=87487> ) in the Microsoft Knowledge Base [Article 555636](#)  (<https://go.microsoft.com/fwlink/?LinkId=187670> ) in Microsoft Knowledge Base




## Additional references

[Command-Line Syntax Key](#)

[LDIFDE](#) 

[Import or Export Directory Objects Using Ldifde](#) 

 English (United States)  Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#)  [Contribute](#) [Privacy](#)  [Terms of Use](#) [Trademarks](#)  [© Microsoft 2024](#)