






Product 

Solutions 

Resources 

Open Source 

Enterprise 



Sign in

Sign up

 redcanaryco / atomic-red-team

Public

 Notifications

 Fork 2.8k

 Star 9.7k

 Code

 Issues 6

 Pull requests 5

 Actions

 Wiki

 Security

 Insights

 Files

 f339e7d



 Go to file

>  .github

>  atomic_red_team

>  atomics

>  Indexes

>  T1003.001

>  T1003.002

>  T1003.003

>  T1003.004

>  T1003.005

>  T1003.006

>  T1003.007

>  T1003.008

>  T1003

>  T1006

>  T1007

>  T1010

>  T1012

>  T1014

>  T1016

>  T1018

>  T1020

>  T1021.001

>  T1021.002

>  T1021.003

>  T1021.006

>  T1027.001

>  T1027.002

>  T1027.004

>  T1027

>  T1030

>  T1033

>  T1036.003

>  T1036.004

>  T1036.005

>  T1036.006

>  T1036

atomic-red-team / atomics / T1552.003 / T1552.003.md 

 Atomic Red Team doc generat... Generated docs from job=generate-d... 819934c · 2 years ago  History

PreviewCodeBlame44 lines (21 loc) · 1.7 KB

Raw

T1552.003 - Bash History

Description from ATT&CK

Adversaries may search the bash command history on compromised systems for insecurely stored credentials. Bash keeps track of the commands users type on the command-line with the "history" utility. Once a user logs out, the history is flushed to the user's `.bash_history` file. For each user, this file resides at the same location: `~/.bash_history` . Typically, this file keeps track of the user's last 500 commands. Users often type usernames and passwords on the command-line as parameters to programs, which then get saved to this file when they log out. Adversaries can abuse this by looking through the file for potential credentials. (Citation: External to DA, the OS X Way)

Atomic Tests

- [Atomic Test #1 - Search Through Bash History](#)

Atomic Test #1 - Search Through Bash History

Search through bash history for specifice commands we want to capture

Supported Platforms: Linux, macOS

auto_generated_guid: 3cfde62b-7c33-4b26-a61e-755d6131c8ce







Inputs:

Name	Description	Type	Default Value
output_file	Path where captured results will be placed	Path	~/loot.txt
bash_history_grep_args	grep arguments that filter out specific commands we want to capture	Path	-e '-p' -e 'pass' -e 'ssh'
bash_history_filename	Path of the bash history file to capture	Path	~/.bash_history

Attack Commands: Run with `sh` !

```
cat #{bash_history_filename} | grep #{bash_history_grep_args} > #{output_file}
```



- >  T1037.001
- >  T1037.002
- >  T1037.004
- >  T1037.005
- >  T1039
- >  T1040

