

CiscoUmbrella
 CommonSecurityLog
 DeviceEvents
 DeviceFileEvents
 DeviceNetworkEvents

DeviceProcessEvents

```
54 lines (53 loc) ⋅ 2.37 KB ⋅ ①
                                                                                Raw 📮 🕹
Code
        Blame
          id: 23de46ea-c425-4a77-b456-511ae4855d69
   1
   2
          name: Rare subscription-level operations in Azure
   3
          description: |
            'This query looks for a few sensitive subscription-level events based on Azure Activi
             For example this monitors for the operation name 'Create or Update Snapshot' which i
   6
             to dump hashes or extract sensitive information from the disk.'
   7
          severity: Low
          requiredDataConnectors:
   8
   9
            - connectorId: AzureActivity
  10
              dataTypes:
  11
                - AzureActivity
  12
          queryFrequency: 1d
  13
          queryPeriod: 14d
  14
          triggerOperator: gt
  15
          triggerThreshold: 0
  16
          tactics:
  17
            - CredentialAccess
  18
            - Persistence
  19
          relevantTechniques:
  20
            - T1003
  21
            - T1098
  22
          query:
  23
  24
            let starttime = 14d;
            let endtime = 1d;
  25
            // The number of operations below which an IP address is considered an unusual source
  26
  27
            let alertOperationThreshold = 5;
  28
            let SensitiveOperationList = dynamic(["microsoft.compute/snapshots/write", "microsof
  29
            let SensitiveActivity = AzureActivity
   30
            | where OperationNameValue in~ (SensitiveOperationList) or OperationNameValue hassuff
            | where ActivityStatusValue =~ "Success";
  31
   32
            SensitiveActivity
  33
            | where TimeGenerated between (ago(starttime) .. ago(endtime))
   34
            | summarize count() by CallerIpAddress, Caller, OperationNameValue
  35
            | where count_ >= alertOperationThreshold
   36
            | join kind = rightanti (
  37
            SensitiveActivity
   38
            | where TimeGenerated >= ago(endtime)
  39
            | summarize StartTimeUtc = min(TimeGenerated), EndTimeUtc = max(TimeGenerated), Activ
  40
            OperationIds = makelist(OperationId), CorrelationIds = makelist(CorrelationId), Resou
  41
            by CallerIpAddress, Caller, OperationNameValue
  42
            ) on CallerIpAddress, Caller, OperationNameValue
  43
            | extend timestamp = StartTimeUtc, AccountCustomEntity = Caller, IPCustomEntity = Cal
  44
          entityMappings:
  45
            - entityType: Account
              fieldMappings:
  46
  47
                - identifier: FullName
                  columnName: AccountCustomEntity
  48
  49
            - entityType: IP
  50
              fieldMappings:
  51
                - identifier: Address
                  columnName: IPCustomEntity
   52
          version: 1.1.1
          kind: Scheduled
```