

Filter by title

gpnxup

**gpresult**

gpupdate

graftabl

help

helpctr

hostname

icads

if

ipconfig

ipxroute

irftp

jetpack

klist

> ksetup

ktmutil

ktpass

label

lodctr

> logman

logoff

lpq

lpr

macfile

makecab

> manage bde

mapadmin

md

mkdir

mklink

mmc

mode

more

mount

mountvol

move

mqbkup

mqsvc

mqtgsvc

msdt

msg

msiexec

msinfo32





 Download PDF

Learn / Windows Server /

# gpresult

Article • 11/01/2024 • 14 contributors •

Applies  Windows Server 2025,  Windows Server 2022,  Windows Server 2019,  Windows to: Server 2016,  Windows 11,  Windows 10,  Azure Stack HCI, versions 23H2 and 22H2

 Feedback

## In this article

- Syntax
- Related links

Displays the Resultant Set of Policy (RSoP) information for a remote user and computer. To use RSoP reporting for remotely targeted computers through the firewall, you must have firewall rules that enable inbound network traffic on the ports.

## Syntax


Copy

```
gpresult [/s <system> [/u <username> [/p [<password>]]]] [/user [<targetdomain>\<targetuser>]]
```

### Note

Except when using */?*, you must include an output option, */r*, */v*, */z*, */x*, or */h*.

## Parameters

 Expand table

Parameter	Description
<i>/s</i> <code>&lt;system&gt;</code>	Specifies the name or IP address of a remote computer. Don't use backslashes. The default is the local computer.
<i>/u</i> <code>&lt;username&gt;</code>	Uses the credentials of the specified user to run the command. The default user is the user who is signed in to the computer that issues the command.
<i>/p</i> <code>[&lt;password&gt;]</code>	Specifies the password of the user account that is provided in the <i>/u</i> parameter. If <i>/p</i> is omitted, <b>gpresult</b> prompts for the password. The <i>/p</i> parameter can't be used with <i>/x</i> or <i>/h</i> .
<i>/user</i> <code>[&lt;targetdomain&gt;\&lt;targetuser&gt;]</code>	Specifies the remote user whose RSoP data is to be displayed.
<i>/scope</i> <code>{user   computer}</code>	Displays RSoP data for either the user or the computer. If <i>/scope</i> is omitted, <b>gpresult</b> displays RSoP data for both the user and the computer.
<code>[/x   /h] &lt;filename&gt;</code>	Saves the report in either XML ( <i>/x</i> ) or HTML ( <i>/h</i> ) format at the location and with the file name that is specified by the <i>filename</i> parameter. Can't be used with <i>/u</i> , <i>/p</i> , <i>/r</i> , <i>/v</i> , or <i>/z</i> .

/f	Forces <b>gpresult</b> to overwrite the file name that is specified in the /x or /h option.
/r	Displays RSoP summary data.
/v	Displays verbose policy information. This includes detailed settings that were applied with a precedence of 1.
/z	Displays all available information about Group Policy. This includes detailed settings that were applied with a precedence of 1 and higher.
/?	Displays help at the command prompt.

## Remarks

- Group Policy is the primary administrative tool for defining and controlling how programs, network resources, and the operating system operate for users and computers in an organization. In an active directory environment, Group Policy is applied to users or computers based on their membership in sites, domains, or organizational units.
- Because you can apply overlapping policy settings to any computer or user, the Group Policy feature generates a resulting set of policy settings when the user signs in. The **gpresult** command displays the resulting set of policy settings that were enforced on the computer for the specified user when the user signed in.
- Because /v and /z produce much information, it's useful to redirect output to a text file (for example, `gpresult/z >policy.txt`).
- On ARM64 versions of Windows, only the `gpresult` in SysWow64 works with the `/h` parameter.

## Examples

To retrieve RSoP data for only the remote user *maindom\targetuser*, on the computer *srvmain*, enter:

Copy

```
gpresult /s srvmain /user maindom\targetuser /scope user /r
```

To save all available information about Group Policy to a file named *policy.txt* for only the remote user *maindom\targetuser*, on the computer *srvmain*, enter:

Copy

```
gpresult /s srvmain /user maindom\targetuser /z > policy.txt
```

To display RSoP data for the signed-in user, *maindom\hiropln* with the password *p@ssW23*, for the computer *srvmain*, enter:

Copy

```
gpresult /s srvmain /u maindom\hiropln /p p@ssW23 /r
```

## Related links




- [Command-Line Syntax Key](#)



## Feedback

Was this page helpful?

 Yes

 No

 English (United States)   Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#)  [Contribute](#) [Privacy](#)  [Terms of Use](#) [Trademarks](#)  [© Microsoft 2024](#)