



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies



regini

Article • 02/03/2023 • 9 contributors

Feedback

In this article

[Syntax](#)

[Related links](#)

Modifies the registry from the command line or a script, and applies changes that were preset in one or more text files. You can create, modify, or delete registry keys, in addition to modifying the permissions on the registry keys.

For details on the format and content of the text script file that regini.exe uses to make changes to the registry, see [How to change registry values or permissions from a command line or a script](#).

Syntax

```
regini [-m \\machinename | -h hivefile hiveroot][-i n] [-o c
```

Parameters

 Expand table

Parameter	Description
-m <\\computername>	Specifies the remote computer name with a registry that is to be modified. Use the format \\ComputerName .
-h <hivefile hiveroot>	Specifies the local registry hive to modify. You must specify the name of the hive file and the root of the hive in the format hivefile hiveroot .
-i <n>	Specifies the level of indentation to use to indicate the tree structure of registry keys in the command output. The regdmp.exe tool (which gets a registry key's current permissions in binary format) uses indentation in multiples of four, so the default value is 4 .
-o <outputwidth>	Specifies the width of the command output, in characters. If the output will appear in the command window, the default value is the width of the window. If the output is directed to a file, the default value is 240 characters.
-b	Specifies that regini.exe output is backward compatible with previous versions of regini.exe .
textfiles	Specifies the name of one or more text files that contain registry data. Any number of ANSI or Unicode text files can be listed.

Remarks

The following guidelines apply primarily to the content of the text files that contain registry data that you apply by using **regini.exe**.

- Use the semicolon as an end-of-line comment character. It must be the first non-blank character in a line.
- Use the backslash to indicate continuation of a line. The command will ignore all characters from the backslash up to (but not including) the first non-blank character of the next line. If you include more than one space before the backslash, it is replaced by a single space.
- Use hard-tab characters to control indentation. This indentation indicates the tree structure of the registry keys; however, these characters are converted to a single space regardless of their position.

Related links


- [Command-Line Syntax Key](#)

Feedback

Was this page helpful?

 Yes

 No

 English (United States)

 Your Privacy Choices


 Theme 

[Manage cookies](#)


[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024