

Product ▾Solutions ▾Resources ▾Open Source ▾Enterprise ▾Pricing

🔍

Sign in

Sign up

vysecurity / Aggressor-VYSECPublic

🔔Notifications

Fork60

Star207

<>Code

🕒Issues2

🔗Pull requests

🎬Actions

📁Projects

🛡️Security

📊Insights

📁Files

🔑0d61c80

🔍

🔍Go to file

.gitignore

Blacklist.cna

HAMMERTHROW.cna

Invoke-CredLeak.ps1

Invoke-Vnc.ps1

README.md

auto-keylog-consent.cna

auto-prepenv.cna

credleak.cna

http.cna

mimikatz_addons.cna

ping.cna

portfwd.cna

pushover-ng.cna

pushover.cna

test.cna

virustotal-ng.cna

vnc-psh.cna

Aggressor-VYSEC / ping.cna📄

⋮

vysecurityHTTP

f8eb941 · 6 years ago🕒History

CodeBlame57 lines (47 loc) · 1.48 KB

Raw📄📥🔗

```
1      # A script to allow you to ping an IP address and it will convert to Hex equivalent
2      # Concept of IR looking for IP regex in logs by @Nebulator inspired me to write this.
3      #
4      # Author: @vysecurity
5
6      alias ping {
7          # $1 - Self
8          # $2 - IP
9
10         if ($2){
11             $ip = $2;
12             ($p1,$p2,$p3,$p4) = split("\\.", $ip);
13
14             if ((int($p1) >= 0) && (int($p1) <= 255) && (int($p2) >= 0) && (int($p2) <= 255) && (int($p3) >= 0) && (int($p3) <= 255) && (int($p4) >= 0) && (int($p4) <= 255)) {
15                 # Correct IP at this bit
16
17                 $p1h = formatNumber($p1, 10, 16);
18                 $p2h = formatNumber($p2, 10, 16);
19                 $p3h = formatNumber($p3, 10, 16);
20                 $p4h = formatNumber($p4, 10, 16);
21
22                 $p1hs = "$p1h";
23                 $p2hs = "$p2h";
24                 $p3hs = "$p3h";
25                 $p4hs = "$p4h";
26
27                 if (strlen($p1hs) == 1){
28                     $p1hs = "0 $+ $p1hs";
29                 }
30                 if (strlen($p2hs) == 1){
31                     $p2hs = "0 $+ $p2hs";
32                 }
33                 if (strlen($p3hs) == 1){
34                     $p3hs = "0 $+ $p3hs";
35                 }
36                 if (strlen($p4hs) == 1){
37                     $p4hs = "0 $+ $p4hs";
38                 }
39
40                 $final = "0x $+ $p1hs $+ $p2hs $+ $p3hs $+ $p4hs";
41
42                 btask($1, "ping $ip $+ : $+ $final");
43                 bshell($1, "ping $final");
44             }
45             else{
46                 berror($1, "Invalid IP address");
47             }
48         }
49         else{
50             berror($1, "You must specify an IP address");
51         }
52     }
53
54     beacon_command_register("ping", "Issues Ping on the target after converting it to hex format to
55     "Syntax: ping [IP address]\n" .
56     "Issues a ping on the IP address specified after converting it to hex format to
57     "
```

Page 1 of 2

51