



redcanaryco / atomic-red-team Public

Notifications Fork 2.8k Star 9.7k

<> Code Issues 6 Pull requests 4 Actions Wiki Security Insights

atomic-red-team / atomics / T1036.006 / T1036.006.md

...

CircleCI Atomic Red Team doc... Generate docs from job=generate\_and\_commit\_gui... 37ea965 · 3 years ago

80 lines (37 loc) · 2.4 KB

Preview Code Blame

Raw Copy Download Menu

# T1036.006 - Space after Filename

## Description from ATT&CK

Adversaries can hide a program's true filetype by changing the extension of a file. With certain file types (specifically this does not work with .app extensions), appending a space to the end of a filename will change how the file is processed by the operating system.

For example, if there is a Mach-O executable file called `evil.bin`, when it is double clicked by a user, it will launch Terminal.app and execute. If this file is renamed to `evil.txt`, then when double clicked by a user, it will launch with the default text editing application (not executing the binary). However, if the file is renamed to `evil.txt`  (note the space at the end), then when double clicked by a user, the true file type is determined by the OS and handled appropriately and the binary will be executed (Citation: Mac Backdoors are back).

Adversaries can use this feature to trick users into double clicking benign-looking files of any format and ultimately executing something malicious.

## Atomic Tests

- [Atomic Test #1 - Space After Filename \(Manual\)](#)
- [Atomic Test #2 - Space After Filename](#)

## Atomic Test #1 - Space After Filename (Manual)

---

Space After Filename

**Supported Platforms:** macOS

**auto\_generated\_guid:** 89a7dd26-e510-4c9f-9b15-f3bae333360f

**Run it with these steps!**

1. `echo '#!/bin/bash\nnecho "print \"hello, world!\"\" | /usr/bin/python\nexit' > execute.txt && chmod +x execute.txt`
2. `mv execute.txt "execute.txt "`
3. `./execute.txt\`

## Atomic Test #2 - Space After Filename

---

Space after filename.

**Supported Platforms:** macOS, Linux

**auto\_generated\_guid:** b95ce2eb-a093-4cd8-938d-5258cef656ea

**Attack Commands:** Run with **bash** !

```
mkdir -p /tmp/atomic-test-T1036.006
cd /tmp/atomic-test-T1036.006
mkdir -p 'testdirwithspaceend '
/usr/bin/echo -e "%d\n\n#!/usr/bin/perl\nprint \"running T1035.006 with space aft
```



```
chmod +x 'testdirwithspaceend /init '  
'./testdirwithspaceend /init '
```

### Cleanup Commands:

```
rm -rf /tmp/atomic-test-T1036.006
```

