We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. Privacy Statement Third-Party Cookies

| Accept | Reject | Manage cookies |

ⓘ We're no longer updating this content regularly. Check the **Microsoft Product Lifecycle** for information about how this product, service, technology, or API is supported.

Recommended Version

✕

⊕   ⋮

Sc stop

Article • 08/31/2016

In this article

Syntax

Parameters

Remarks

Examples

Additional references

Applies To: Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2003 with SP2, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012, Windows Server 2003 with SP1, Windows 8

Sends a STOP control request to a service.

> ⚠ **Warning**
>
> Incorrectly editing the registry may severely damage your system. Before making changes to the registry, you should back up any valued data on the computer.

For examples of how to use this command, see Examples.

Syntax

```
sc [<ServerName>] stop <ServiceName>
```

Parameters

⌞⌝ Expand table

Parameter	Description
<ServerName>	Specifies the name of the remote server on which the service is located. The name must use the Universal Naming Convention (UNC) format (for example, \\myserver). To run SC.exe locally, omit this parameter.
<ServiceName>	Specifies the service name returned by the **getkeyname** operation.
/?	Displays help at the command prompt.

Remarks

Not all services can be stopped.

Examples

To stop the TAPISRV service, type:

```
sc stop tapisrv
```

Additional references

Command-Line Syntax Key