
 Atomic Red Team doc generat... Generated docs from job=generate-docs branch=master ... 819934c · 2 years ago 

136 lines (72 loc) · 4.08 KB

# T1053.003 - Cron

## Description from ATT&CK

Adversaries may abuse the `cron` utility to perform task scheduling for initial or recurring execution of malicious code.(Citation: 20 macOS Common Tools and Techniques) The `cron` utility is a time-based job scheduler for Unix-like operating systems. The `crontab` file contains the schedule of cron entries to be run and the specified times for execution. Any `crontab` files are stored in operating system-specific file paths.

An adversary may use `cron` in Linux or Unix environments to execute programs at system startup or on a scheduled basis for [Persistence](#).

## Atomic Tests

- [Atomic Test #1 - Cron - Replace crontab with referenced file](#)
- [Atomic Test #2 - Cron - Add script to all cron subfolders](#)
- [Atomic Test #3 - Cron - Add script to /var/spool/cron/crontabs/ folder](#)

# Atomic Test #1 - Cron - Replace crontab with referenced file

This test replaces the current user's crontab file with the contents of the referenced file. This technique was used by numerous IoT automated exploitation attacks.

**Supported Platforms:** macOS, Linux

**auto\_generated\_guid:** 435057fb-74b1-410e-9403-d81baf194f75

**Inputs:**

Name	Description	Type	Default Value
command	Command to execute	String	/tmp/evil.sh
tmp_cron	Temporary reference file to hold evil cron schedule	Path	/tmp/persistevil

**Attack Commands:** Run with `bash` !

```
crontab -l > /tmp/notevil
echo "* * * * * #{command}" > #{tmp_cron} && crontab #{tmp_cron}
```

**Cleanup Commands:**

```
crontab /tmp/notevil
```

# Atomic Test #2 - Cron - Add script to all cron subfolders

This test adds a script to /etc/cron.hourly, /etc/cron.daily, /etc/cron.monthly and /etc/cron.weekly folders configured to execute on a schedule. This technique was used by the threat actor Rocke during the exploitation of Linux web servers.

**Supported Platforms:** macOS, Linux

auto\_generated\_guid: b7d42afa-9086-4c8a-b7b0-8ea3faa6ebb0

Inputs:

Name	Description	Type	Default Value
command	Command to execute	String	echo 'Hello from Atomic Red Team' > /tmp/atomic.log
cron_script_name	Name of file to store in cron folder	String	persistevil

Attack Commands: Run with `bash` ! Elevation Required (e.g. root or admin)

```
echo "#{command}" > /etc/cron.daily/#{cron_script_name}
echo "#{command}" > /etc/cron.hourly/#{cron_script_name}
echo "#{command}" > /etc/cron.monthly/#{cron_script_name}
echo "#{command}" > /etc/cron.weekly/#{cron_script_name}
```

Cleanup Commands:

```
rm /etc/cron.daily/#{cron_script_name}
rm /etc/cron.hourly/#{cron_script_name}
rm /etc/cron.monthly/#{cron_script_name}
rm /etc/cron.weekly/#{cron_script_name}
```

# Atomic Test #3 - Cron - Add script to /var/spool/cron/crontabs/ folder

This test adds a script to a /var/spool/cron/crontabs folder configured to execute on a schedule. This technique was used by the threat actor Rocke during the exploitation of Linux web servers.

Supported Platforms: Linux

auto\_generated\_guid: 2d943c18-e74a-44bf-936f-25ade6cccab4

Inputs:

Name	Description	Type	Default Value
command	Command to execute	String	echo 'Hello from Atomic Red Team' > /tmp/atomic.log
cron_script_name	Name of file to store in /var/spool/cron/crontabs folder	String	persistevil

Attack Commands: Run with `bash` ! Elevation Required (e.g. root or admin)

```
echo "#{command}" >> /var/spool/cron/crontabs/#{cron_script_name}
```

Cleanup Commands:

```
rm /var/spool/cron/crontabs/#{cron_script_name}
```