



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking “Manage Cookies” at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies

Microsoft Ignite

Nov 19–22, 2024

Register now >



Learn

Discover

Product documentation

Development languages

Topics



Sign in

ⓘ We're no longer updating this content regularly. Check the [Microsoft Product Lifecycle](#) for information about how this product, service, technology, or API is supported.

Return to main site



Filter by title

TechNet Wiki Archive

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

Q

R

S

T

U

V

W

X

Y

Z

Non-Alphabetic

Learn / TechNet Wiki Archive /



AdFind command examples

Article • 01/17/2024

AdFind created by [Joe Richards](#) . He is great Active Directory MVP and created more Free Tools [here](#) .

Here is [AdFind Usage](#) and examples.

Query the schema version

AdFind -schema -s base objectVersion

Query wellKnownObjects

AdFind -default -s base wellknownObjects

List deleted objects

AdFind -default -rb "CN=Deleted Objects" -showdel

List conflict objects

AdFind -b -gc -f "(Name=*\0ACNF:*)" -dn

Retrieve all Attributes

AdFind.exe -schema -f “objectClass=attributeSchema” cn IDAPDisplayName -nodn -csv >Attributes.txt

Retrieve all Classes

AdFind.exe -schema -f “objectclass=classSchema” cn IDAPDisplayName -nodn -csv >Classes.txt

Find Domain Functional level (for example Domain=Contoso.com)

AdFind -s Base -b "DC=Contoso,DC=com" msDS-Behavior-Version

List Subnets

AdFind -subnets -f (objectCategory=subnet)

List UPN Suffixes

AdFind -partitions -s base uPNSuffixes

List Password Policy

AdFind -default -s base lockoutduration lockoutthreshold lockoutobservationwindow maxpwdage minpwdage minpwdlength pwdhistorylength pwdproperties

Check Tombstone Lifetime

AdFind -config -f objectclass=ntdsservice tombstoneLifetime

Query AD for all Groups and Users that have adminCount = 1 (adminSDholder)

AdFind -default -f "(&(|(&(objectCategory=person)(objectClass=user)) (objectCategory=group)))(adminCount=1))" -dn

List all objects in an OU (for example OU=NewYork, Domain=Contoso.com)

AdFind -b "OU=NewYork,DC=Contoso,DC=com" -s one -dn

List all OUs in Domain

AdFind -default -f "objectcategory=organizationalUnit" -dn

Find disabled accounts

AdFind -default -bit -f userAccountControl:AND:=2

OR

AdFind -s subtree -b DC=Contoso,DC=com -f userAccountControl:1.2.840.113556.1.4.803:=2 -dn

List Users with expired password

AdFind -s subtree -b ,DC=Contoso,DC=com -f userAccountControl:1.2.840.113556.1.4.803:=8388608 -dn

List Users Display Name in domain

AdFind -b DC=Contoso,DC=com -f "objectcategory=person" displayName -sl

Find User SID History (for example User=Ed.Price)

AdFind -default -f name=Ed.Price sIDHistory

List Users with Dial-in configuration that have **Allow** access in OU (for exampleOU=IT, Domain=Contoso.com)

AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&(objectCategory=person) (objectClass=user)(msNPAllowDialin=TRUE))" distinguishedName sAMAccountName

List Users with Dial-in configuration that have **Deny** access in OU (for exampleOU=IT, Domain=Contoso.com)

AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&(objectCategory=person) (objectClass=user)(msNPAllowDialin=FALSE))" distinguishedName sAMAccountName

List Users with Dial-in configuration that have **Control** access through Remote Access Policy in OU (for exampleOU=IT, Domain=Contoso.com)

AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&(objectCategory=person) (objectClass=user)(!(msNPAllowDialin=*)))" distinguishedName sAMAccountName

List member of a Group (for example Group=IT_Support)

AdFind -b "CN=IT_Support,CN=Users,DC=Contoso,DC=com" member

Count the number of members of a Group (for example Group=IT_Support)

AdFind -f "sAMAccountName=IT_Support" member -list | AdFind -c

List Nested Group members (for example Group=Support, OU=IT, Domain=Contoso.com)

```
AdFind -default -bit -f
"memberof:1.2.840.113556.1.4.1941:=CN=Support,OU=IT,DC=Contos,DC=com"
sAMAccountName -nodn
```

List all Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "(objectcategory=group)"
```

List all Universal Distribution Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&
(objectcategory=group)(sAMAccountType=268435457)(grouptype:OR:=8))" 1.1
```

List all Universal Security Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&
(objectcategory=group)(grouptype:AND:=-2147483640))" 1.1
```

List all Universal Groups (Distribution & Security) in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&
(objectcategory=group)(grouptype:OR:=8))" 1.1
```

List all Global Groups (Distribution & Security) in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)
(grouptype:OR:=2))" 1.1
```

List all Global Security Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)
(grouptype:AND:=-2147483646))" 1.1
```

List all Global Distribution Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)
(sAMAccountType=268435457)(grouptype:OR:=2))" 1.1
```

List all Domain Local Groups (Distribution & Security) in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)
(grouptype:OR:=4))" 1.1
```

List all Domain Local Security Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "(&(objectcategory=group)
(sAMAccountType=536870912))" 1.1
```

List all Domain Local Distribution Groups in OU (for exampleOU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "(&(objectcategory=group)
(sAMAccountType=536870913))" 1.1
```

Find all Computer objects in domain and displays cn & createTimeStamp

```
AdFind -b dc=Contoso,dc=com -f "objectcategory=computer" cn createTimeStamp
```

